AUTHENTICATED
U.S. GOVERNMENT
INFORMATION
GPO

TABLE E–6—MAXIMUM ERP (WATTS) FOR CONTROL TRANSMITTERS (HAAT MORE THAN 152 METERS)—Continued

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)					
	152 (500)	305 (1000)	457 (1500)	610 (2000)	762 (2500)	914 (3000)
193 (120)	50	19	9	5	3	2

See § 22.627(b)(1)(iii). This table is for antenna heights of more than 152 meters (500 feet) above average terrain. For intermediate values of height and/or distance, use linear interpolation to obtain the maximum permitted ERP.

TABLE E–7—MAXIMUM ERP (WATTS) FOR CONTROL TRANSMITTERS

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)								
	30 (100)	46 (150)	61 (200)	76 (250)	91 (300)	107 (350)	122 (400)	137 (450)	152 (500)
108 (67)	1000	1000	1000	1000	1000	1000	1000	1000	1000
106 (66)	1000	1000	1000	1000	1000	1000	1000	1000	750
105 (65)	1000	1000	1000	1000	1000	1000	825	650	600
103 (64)	1000	1000	1000	1000	1000	775	625	500	400
101 (63)	1000	1000	1000	1000	440	400	350	320	300
100 (62)	1000	1000	1000	525	375	250	200	150	125
98 (61)	1000	700	450	250	200	125	100	75	50
97 (60)	1000	425	225	125	100	75	50	.....	.....

See § 22.627(b)(2). This table applies to control transmitters in the Boston, Chicago, Cleveland, Detroit, Los Angeles, New York-Northeastern New Jersey, Philadelphia, Pittsburgh and Washington, DC urban areas. This table is for antenna heights of 152 meters (500 feet) or less above average terrain. For antenna heights between those in the table, use the next higher antenna height. For distances between those in the table, use the next lower distance.

[59 FR 59507, Nov. 17, 1994; 60 FR 9890, Feb. 22, 1995; as amended at 63 FR 68946, Dec. 14, 1998]

470–512 MHz TRUNKED MOBILE OPERATION

§ 22.651 470–512 MHz channels for trunked mobile operation.

The following channels are allocated for assignment to transmitters providing trunked public mobile service within the specified urban areas. All channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

Houston

488.0125	491.0125	488.0875	491.0875
488.0375	491.0375	488.1125	491.1125
488.0625	491.0625	488.1375	491.1375

New York-Northern New Jersey

473.0125	479.0125	473.1625	479.1625
473.0375	479.0375	473.1875	479.1875
473.0625	479.0625	473.2125	479.2125
473.0875	479.0875	473.2375	479.2375
473.1125	479.1125	473.2625	479.2625
473.1375	479.1375	473.2875	479.2875

[59 FR 59507, Nov. 17, 1994; 60 FR 9891, Feb. 22, 1995]

§ 22.653 Eligibility.

Only licensees already authorized to provide trunked mobile service or their successors in interest are eligible to apply for additional use of these channels for trunked mobile service, and then only in the urban areas already authorized.

§ 22.657 Transmitter locations.

The purpose of the rules in paragraphs (a) and (b) of this section is to define the areas in which the 470–512 MHz channels are allocated for public mobile use. The purpose of the rules in paragraphs (c) through (f) of this section is to reduce the likelihood that interference to television reception from public mobile operations on these channels will occur. The protected TV station locations specified in paragraphs (d), (e)(1) and (f) of this section are the locations of record as of September 1974, and these do not change even though the TV stations may have been subsequently relocated.

(a) *Base transmitter locations.* Base transmitter locations must be within 80 kilometers (50 miles) of the designated locations in this paragraph. Mobile transmitters must not be operated at locations more than 129 kilometers (80 miles) from the designated locations in this paragraph. Note: All coordinates are referenced to North American Datum 1983 (NAD83).

Urban area	N. latitude	W. longitude
Houston, TX	29°45′26.8″	95°21′37.8″
New York, NY-NE NJ	40°45′06.4″	73°59′37.5″

(b) *Mobile area of operation.* Mobile transmitters must not be operated at locations more than 48 kilometers (30 miles) from all associated base stations.

(c) *Protection from intermodulation interference.* Base transmitter locations must be at least 1.6 kilometers (1 mile) from the current main transmitter locations of all TV stations transmitting on TV channels separated by 2, 3, 4, 5, 7, or 8 TV channels from the TV channel containing the frequencies on which the base station will transmit. This requirement is intended to reduce the likelihood of intermodulation interference.

(d) Adjacent channel protection from mobile transmitters. Base transmitter locations must be at least 145 kilometers (90 miles) from the applicable protected TV station locations specified in this paragraph. This requirement is intended to provide a 0 dB minimum desired to undesired signal strength ratio at the Grade B contour of an adjacent channel TV station. Note: All coordinates are referenced to North American Datum 1983 (NAD83).

Control transmitter frequency range	Protected TV station location	TV channel
470–476 MHz.	Lancaster, PA, 40°15′45.3″ N. Lat. 76°27′47.9″ W. Long..	(15)
476–482 MHz.	Scranton, PA, 41°10′58.3″ N. Lat. 75°52′19.7″ W. Long..	(16)

(e) *Co-channel protection from mobile transmitters.* Base transmitter locations must be at least the distance specified in paragraph (e)(2) of this section from the applicable protected TV station locations specified in paragraph (e)(1) of this section. This requirement is intended to provide a 40 dB minimum desired to undesired signal strength ratio at the Grade B contour of a co-channel TV station.

(1) The protected TV station locations are as follows (all coordinates are referenced to North American Datum 1983 (NAD83)):

Control transmitter frequency range	Protected TV station location
470–476 MHz.	Washington, DC, 38°57′17.4″ N. Lat. 77°00′15.9″ W. Long.
476–482 MHz.	Lancaster, PA, 40°15′45.3″ N. Lat. 76°27′47.9″ W. Long.

(2) The required minimum distance depends upon the effective radiated power (ERP) of the most powerful mobile transmitter(s) in the system:

Mobile unit ERP (watts)	Minimum distance	
	Kilometers	Miles
60	193	(120)
50	185	(115)
25	177	(110)
10	169	(105)
5	161	(100)

(f) *Co-channel protection from base transmitters with high antennas.* This paragraph applies only to base transmitter locations in the New York-Northeastern New Jersey urban area that utilize an antenna height of more than 152 meters (500 feet) above average terrain. The distance between the location of such a base transmitter and the applicable protected TV station location specified in this paragraph must equal or exceed the sum of the distance from the base transmitter location to the radio horizon in the direction of the specified location and 89 kilometers (55 miles—representing the distance from the main transmitter location of the TV station to its Grade B contour in the direction of the base transmitter). The distance to the radio horizon is calculated as follows:

$$d = \sqrt{17 \times h}$$

Where d is the distance to the radio horizon in kilometers h is the height of the antenna center of radiation above ground level in meters

NOTE: All coordinates are referenced to North American Datum 1983 (NAD83)):

Control transmitter frequency range	Protected TV station location
470–476 MHz.	Washington, DC, 38°57′17.4″ N. Lat. 77°00′15.9″ W. Long.
476–482 MHz.	Lancaster, PA, 40°15′45.3″ N. Lat. 76°27′47.9″ W. Long.

(g) The FCC may waive specific distance separation requirements of paragraphs (d) through (f) of this section if the applicant submits an engineering analysis which demonstrates that terrain effects and/or operation with less effective radiated power would satisfy the applicable minimum desired to undesired signal strength ratios at the Grade B contours of the protected TV stations. For this purpose, the Grade B contour of a TV station is deemed to be a circle with a 89 kilometer (55 mile) radius, centered on the protected TV station location, and along which the median TV signal field strength is 64 dBμV/m. In any showing intended to demonstrate compliance with the minimum desired to undesired signal ratio requirements of this section, all predicted field strengths must have been determined using the UHF TV propagation curves contained in part 73 of this chapter.

[59 FR 59507, Nov. 17, 1994, as amended at 63 FR 68947, Dec. 14, 1998]

§ 22.659 Effective radiated power limits.

The purpose of the rules in this section, which limit effective radiated power (ERP), is to reduce the likelihood that interference to television reception from public mobile operations on these channels will occur. The protected TV station locations specified in this section are the locations of record as of September 1974, and these do not change even though the TV stations may have been subsequently relocated.

(a) *Maximum ERP.* The ERP of base transmitters must not exceed 100 Watts under any circumstances. The ERP of mobile transmitters must not exceed 60 Watts under any circumstances.

(b) *Co-channel protection from base transmitters.* The ERP of base transmitters in the New York-Northeastern New Jersey urban area must not exceed the limits in the tables referenced in paragraphs (b)(2) and (b)(3) of this section. The limits depend upon the height above average terrain of the base transmitter antenna and the distance between the base transmitter and the nearest protected TV station location in paragraph (b)(1) of this section.

(1) The protected TV station locations are as follows (all coordinates are referenced to North American Datum 1983 (NAD83)):

Control transmitter frequency range	Protected TV station location
470–476 MHz.	Washington, DC, 38°57′17.4″ N. Lat. 77°00′15.9″ W. Long.
476–482 MHz.	Lancaster, PA, 40°15′45.3″ N. Lat. 76°27′47.9″ W. Long.

(2) Tables E–8 and E–9 of this section apply to base transmitters in the New York-Northeastern New Jersey urban area that transmit on channels in the 476–482 MHz range.

(3) Tables E–10 and E–11 of this section apply to base transmitters in the New York-Northeastern New Jersey urban area that transmit on channels in the 470–476 MHz range.

(c) *Adjacent channel protection from base transmitters.* The ERP of base transmitters must not exceed the limits in Table E–12 of this section. The limits depend upon the height above average terrain of the base transmitter antenna and the distance between the base transmitter and the nearest protected TV station location specified in paragraph (c)(1) of this section.

(1) The protected TV station locations are as follows (all coordinates are referenced to North American Datum 1983 (NAD83)):

Control transmitter frequency range	Protected TV station location	TV channel
470–476 MHz	Hanover, NH, 43°42′30.3″ N. Lat. 72°09′14.3″ W. Long	(15)
476–482 MHz	Lancaster, PA, 40°15′45.3″ N. Lat. 76°27′47.9″ W. Long	(15)
482–488 MHz	Scranton, PA, 41°10′58.3″ N. Lat. 75°52′19.7″ W. Long	(16)
	Hanover, NH, 43°42′30.3″ N. Lat. 72°09′14.3″ W. Long	(15)

NOTE: Coordinates are referenced to North American Datum 1983 (NAD83).

(2) Table E–12 of this section applies to base transmitters in the New York-Northeastern New Jersey urban area.

TABLE E–8—MAXIMUM ERP (WATTS) FOR BASE TRANSMITTERS (HAAT 152 METERS OR LESS)

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)									
	15 (50)	30 (100)	46 (150)	61 (200)	76 (250)	91 (300)	107 (350)	122 (400)	137 (450)	152 (500)
209 (130)	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000
201 (125)	1000	1000	1000	1000	1000	1000	1000	850	750	725
193 (120)	1000	1000	1000	1000	900	750	675	600	550	500
185 (115)	1000	1000	800	725	600	525	475	425	375	350
177 (110)	850	700	600	500	425	375	325	300	275	225
169 (105)	600	475	400	325	275	250	225	200	175	150
161 (100)	400	325	275	225	175	150	140	125	110	100
153 (95)	275	225	175	125	110	95	80	70	60	50
145 (90)	175	125	100	75	50	.....	.....	.....	.....	.....

See § 22.659(b)(2). This table is for antenna heights of 152 meters (500 feet) or less above average terrain. For antenna heights between those in the table, use the next higher antenna height. For distances between those in the table, use the next lower distance.

TABLE E–9—MAXIMUM ERP (WATTS) FOR BASE TRANSMITTERS (HAAT MORE THAN 152 METERS)

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)					
	152 (500)	305 (1000)	457 (1500)	610 (2000)	762 (2500)	914 (3000)
209 (130)	1000	447	219	117	71	46
193 (120)	500	209	95	50	30	19
177 (110)	225	91	35	19	11	8
161 (100)	100	30	10	5	3	2
153 (95)	50	13	5	3	2	1

See § 22.659(b)(2). This table is for antenna heights of more than 152 meters (500 feet) above average terrain. For intermediate values of height and/or distance, use linear interpolation to obtain the maximum permitted ERP.

TABLE E–10—MAXIMUM ERP (WATTS) FOR BASE TRANSMITTERS (HAAT 152 METERS OR LESS)

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)									
	15 (50)	30 (100)	46 (150)	61 (200)	76 (250)	91 (300)	107 (350)	122 (400)	137 (450)	152 (500)
261 (162)	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000
257 (160)	1000	1000	1000	1000	1000	1000	1000	1000	1000	800
249 (155)	1000	1000	1000	1000	1000	875	775	700	625	575
241 (150)	1000	1000	950	775	725	625	550	500	450	400
233 (145)	850	750	650	575	500	440	400	350	320	300
225 (140)	600	575	465	400	350	300	275	250	230	225
217 (135)	450	400	335	300	255	240	200	185	165	150
209 (130)	350	300	245	200	185	160	145	125	120	100
201 (125)	225	200	170	150	125	110	100	90	80	75
193 (120)	175	150	125	105	90	80	70	60	55	50

See § 22.659(b)(3). This table applies for antenna heights of 152 meters (500 feet) or less above average terrain. For antenna heights between those in the table, use the next higher antenna height. For distances between those in the table, use the next lower distance.

TABLE E–11—MAXIMUM ERP (WATTS) FOR BASE TRANSMITTERS (HAAT MORE THAN 152 METERS)

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)					
	152 (500)	305 (1000)	457 (1500)	610 (2000)	762 (2500)	914 (3000)
261 (162)	1000	501	282	170	110	71
241 (150)	400	209	110	60	36	23
225 (140)	225	102	50	28	16	10
209 (130)	100	48	21	11	7	5
193 (120)	50	19	9	5	3	2

See § 22.659(b)(3). This table is for antenna heights of more than 152 meters (500 feet) above average terrain. For intermediate values of height and/or distance, use linear interpolation to obtain the maximum permitted ERP.

TABLE E–12—MAXIMUM ERP (WATTS) FOR BASE TRANSMITTERS

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)								
	30 (100)	46 (150)	61 (200)	76 (250)	91 (300)	107 (350)	122 (400)	137 (450)	152 (500)
108 (67)	1000	1000	1000	1000	1000	1000	1000	1000	1000
106 (66)	1000	1000	1000	1000	1000	1000	1000	1000	750
105 (65)	1000	1000	1000	1000	1000	1000	825	650	600
103 (64)	1000	1000	1000	1000	1000	775	625	500	400
101 (63)	1000	1000	1000	1000	440	400	350	320	300
100 (62)	1000	1000	1000	525	375	250	200	150	125
98 (61)	1000	700	450	250	200	125	100	75	50
97 (60)	1000	425	225	125	100	75	50	.....	.....

See §22.659(c)(2). This table applies to base transmitters in the New York-Northeastern New Jersey urban areas. This table is for antenna heights of 152 meters (500 feet) or less above average terrain. For antenna heights between those in the table, use the next higher antenna height. For distances between those in the table, use the next lower distance.

[59 FR 59507, Nov. 17, 1994, as amended at 63 FR 68947, Dec. 14, 1998]

Subpart F—Rural Radiotelephone Service

§ 22.701 Scope.

The rules in this subpart govern the licensing and operation of stations and systems in the Rural Radiotelephone Service. The licensing and operation of these stations and systems is also subject to rules elsewhere in this part that apply generally to the Public Mobile Services. In case of conflict, however, the rules in this subpart govern.

§ 22.702 Eligibility.

Existing and proposed communications common carriers are eligible to hold authorizations to operate conventional central office, interoffice and rural stations in the Rural Radiotelephone Service. Subscribers are also eligible to hold authorizations to operate rural subscriber stations in the Rural Radiotelephone Service.

[69 FR 75170, Dec. 15, 2004]

§ 22.703 Separate rural subscriber station authorization not required.

A separate authorization is not required for rural subscriber stations for which the effective radiated power does not exceed 60 Watts and for which FAA notification of construction or alteration of the antenna structure is not required (see criteria in §17.7 of this chapter). Authority to operate such rural subscriber stations is conferred by the authorization of the central office or base station from which they receive service.

§ 22.705 Rural radiotelephone system configuration.

Stations in the Rural Radiotelephone Service are authorized to communicate as follows:

(a) Rural subscriber stations are authorized to communicate with and through the central office station(s) with which they are associated. However, where the establishment of a central office station in this service is not feasible, rural subscriber stations may be authorized to communicate with and through a base station in the Paging and Radiotelephone Service.

(b) Central office stations may communicate only with rural subscriber stations.

(c) Interoffice stations may communicate only with other interoffice stations.

§ 22.709 Rural radiotelephone service application requirements.

In addition to information required by Subparts B and D of this part, FCC Form 601 applications for authorization to operate a station in the Rural Radiotelephone Service must contain the applicable supplementary information described in this section.

(a) *Interoffice stations.* Applications for authority to operate a new interoffice station or to add transmitters or points of communications to an existing interoffice station must contain an exhibit demonstrating that the requested facilities would be used only