

the control of the reaction rate in a nuclear reactor, including the neutron absorbing part and the support or suspension structures therefor;

(4) Reactor primary coolant pumps, *i.e.*, pumps especially designed or prepared for circulating the primary coolant in a nuclear reactor.

(5) Reactor pressure tubes, *i.e.*, tubes especially designed or prepared to contain fuel elements and the primary coolant in a nuclear reactor at an operating pressure in excess of 50 atmospheres.

(6) Zirconium tubes, *i.e.*, zirconium metal and alloys in the form of tubes or assemblies of tubes especially designed or prepared for use in a nuclear reactor.

(7) Reactor internals, *e.g.*, core support structures, control and rod guide tubes, thermal shields, baffles, core grid plates and diffuser plates especially designed or prepared for use in a nuclear reactor.

(8) Reactor control rod drive mechanisms, including detection and measuring equipment to determine flux levels.

(9) Any other components especially designed or prepared for use in a nuclear reactor or in any of the components described in this appendix.

[55 FR 30450, July 26, 1990, as amended at 55 FR 34519, Aug. 23, 1990; 58 FR 13004, Mar. 9, 1993; 61 FR 35602, July 8, 1996; 65 FR 70291, Nov. 22, 2000]

APPENDIX B TO PART 110—ILLUSTRATIVE LIST OF GAS CENTRIFUGE ENRICHMENT PLANT COMPONENTS UNDER NRC'S EXPORT LICENSING AUTHORITY

1. *Assemblies and components especially designed or prepared for use in gas centrifuges.*

NOTE: The gas centrifuge normally consists of a thin-walled cylinder(s) of between 75mm (3 ins.) and 400 mm (16 ins.) diameter contained in a vacuum environment and spun at high peripheral speed (of the order of 300 m/ per second and more) with the central axis vertical. In order to achieve high speed, the materials of construction for the rotating rotor assembly, and hence its individual components, have to be manufactured to very close tolerances in order to minimize the unbalance. In contrast to other centrifuges, the gas centrifuge for uranium enrichment is characterized by having within the rotor chamber a rotating disc-shaped baffle(s) and a stationary tube arrangement for feeding and extracting UF₆ gas and featuring at least 3 separate channels of which 2 are connected to scoops extending from the rotor axis towards the periphery of the rotor chamber. Also contained within the vacuum environment are a number of critical items which do not rotate and which, although they are especially designed, are not difficult

to fabricate nor are they fabricated out of unique materials. A centrifuge facility, however, requires a large number of these components so that quantities can provide an important indication of end use.

1.1 *Rotating Components.*

(a) Complete Rotor Assemblies: Thin-walled cylinders, or a number of interconnected thin-walled cylinders, manufactured from one of the high strength-to-density ratio materials described in the Footnote to this Section.

If interconnected, the cylinders are joined together by flexible bellows or rings as described in §1.1(c). The rotor is fitted with an internal baffle(s) and end caps, as described in §1.1 (d) and (e), if in final form. However, the complete assembly may be delivered only partly assembled.

(b) Rotor Tubes: Especially designed or prepared thin-walled cylinders with thickness of 12mm (.50 in.) or less, a diameter of between 75mm (3 ins.) and 400mm (16 ins.), and manufactured from one of the high strength-to-density ratio materials described in the Footnote to this Section.

(c) Rings or Bellows: Components especially designed or prepared to give localized support to the rotor tube or to join together a number of rotor tubes. The bellows in a short cylinder of wall thickness 3mm (.125 in.) or less, a diameter of between 75mm (3 ins.) and 400mm (16 ins.), having a convolute, and manufactured from one of the high strength-to-density ratio materials described in the footnote to this section.

(d) Baffles: Disc shaped components of between 75mm (3 ins.) and 400mm (16 ins.) diameter especially designed or prepared to be mounted inside the centrifuge rotor tube, in order to isolate the take-off chamber from the main separation chamber and, in some cases, to assist the UF₆ gas circulation within the main separation chamber of the rotor tube, and manufactured from one of the high strength-to-density ratio materials described in the Footnote to this Section.

(e) Top Caps/Bottom Caps: Disc shaped components of between 75mm (3 ins.) and 400mm (16 ins.) diameter especially designed or prepared to fit to the ends of the rotor tube, and so contain the UF₆ within the rotor tube, and in some cases to support, retain or contain as an integrated part, an element of the upper bearing (top cap) or to carry the rotating elements of the motor and lower bearing (bottom cap), and manufactured from one of the high strength-to-density ratio materials described in the Footnote to this Section.

FOOTNOTE

The materials used for centrifuge rotating components are:

(a) Maraging steel capable of an ultimate tensile strength of 2.050×10^9 N/m² (300,000 lb/in.²) or more.

(b) Aluminium alloys capable of an ultimate tensile strength of 0.460×10^9 N/m² (67,000 lb/in.²) or more.

(c) Filamentary materials suitable for use in composite structures and having a specific modulus of 3.18×10^6 m or greater and a specific ultimate tensile strength of 7.62×10^4 m or greater.

("Specific Modulus" is the Young's modulus in N/m² divided by the specific weight in N/m³ when measured at a temperature of 23±20C and a relative humidity of 50±5%. "Specific tensile strength" is the ultimate tensile strength in N/m² divided by the specific weight in N/m³ when measured at a temperature of 23±20C and a relative humidity of 50±5%.)

1.2 Static Components.

(a) Magnetic Suspension Bearings: Especially designed or prepared bearing assemblies consisting of an annular magnet suspended within a housing containing a damping medium. The housing will be manufactured from a UF₆ resistant material (see footnote to section 2). The magnet couples with a pole piece or a second magnet fitted to the top cap described in Section 1.1(e). The magnet may be ring-shaped with a relation between outer and inner diameter smaller or equal to 1.6:1. The magnet may be in a form having an initial permeability of 0.15 Henry/meter (120,000 in CGS units) or more, or a remanence of 98.5 percent or more, or an energy product of greater than 80,000 joules/m³ (10×10^6 gauss-oersteds.) In addition to the usual material properties, it is a prerequisite that the deviation of the magnetic axes from the geometrical axes is limited to very small tolerances (lower than 0.1mm) or that homogeneity of the material of the magnet is specially called for.

(b) Bearings/Dampers: Especially designed or prepared bearings comprising a pivot/cup assembly mounted on a damper. The pivot is normally a hardened steel shaft polished into a hemisphere at one end with a means of attachment to the bottom cap described in Section 1.1(e) at the other. The shaft may, however, have a hydrodynamic bearing attached. The cup is pellet-shaped with hemispherical indentation in one surface. These components are often supplied separately to the damper.

(c) Molecular Pumps: Especially designed or prepared cylinders having internally machined or extruded helical grooves and internally machined bores. Typical dimensions are as follows: 7mm (0.3 ins.) to 400mm (16 ins.) internal diameter, 10mm (0.4 ins.) or more wall thickness, 1 to 1 length to diameter ratio. The grooves are typically rectangular in cross-section and 2mm (0.08 in.) or more in depth.

(d) Motor Stators: Especially designed or prepared ring shaped stators for high speed multi-phase AC hysteresis (or reluctance) motors for synchronous operation within a vacuum in the frequency range of 600-2000 Hz and a power range of 50-1000 volts amps. The stators consist of multi-phase windings on a laminated low loss iron core comprised of thin layers typically 2.0mm (0.08 in.) thick or less.

(e) Centrifuge housing/recipients: Components especially designed or prepared to contain the rotor tube assembly of a gas centrifuge. The housing consists of a rigid cylinder of wall thickness up to 30 mm (1.2in) with precision machined ends to locate the bearings and with one or more flanges for mounting. The machined ends are parallel to each other and perpendicular to the cylinder's longitudinal axis to within 0.05 degrees or less. The housing may also be a honeycomb type structure to accommodate several rotor tubes. The housings are made of or protected by materials resistant to corrosion by UF₆.

(f) Scoops: Especially designed or prepared tubes of up to 12 mm (0.5in) internal diameter for the extraction of UF₆ gas from within the rotor tube by a Pitot tube action (that is, with an aperture facing into the circumferential gas flow within the rotor tube, for example by bending the end of a radially disposed tube) and capable of being fixed to the central gas extraction system. The tubes are made of or protected by materials resistant to corrosion by UF₆.

2. Especially designed or prepared auxiliary systems, equipment and components for gas centrifuge enrichment plants.

NOTE: The auxiliary systems, equipment and components for a gas centrifuge enrichment plant are the systems of the plant needed to feed UF₆ to the centrifuges to link the individual centrifuges to each other to form cascades (or stages) to allow for progressively higher enrichments and to extract the product and tails of UF₆ from the centrifuges, together with the equipment required to drive the centrifuges or to control the plant.

Normally UF₆ is evaporated from the solid using heated autoclaves and is distributed in gaseous form to the centrifuges by way of cascade header pipework. The "product" and "tails" of UF₆ gaseous streams flowing from the centrifuges are also passed by way of cascade header pipework to cold traps (operating at about -70 °C) where they are condensed prior to onward transfer into suitable containers for transportation or storage. Because an enrichment plant consists of many thousands of centrifuges arranged in cascades, there are many kilometers of cascade header pipework incorporating thousands of welds with a substantial amount of repetition of layout. The equipment, component

Pt. 110, App. C

10 CFR Ch. I (1-1-10 Edition)

and piping systems are fabricated to very high vacuum and cleanliness standards.

The following items either come into direct contact with UF₆ process gas or directly control the centrifuge and the passage of the gas from centrifuge to centrifuge and cascade to cascade.

(a) Feed Systems/Product and Tails Withdrawal Systems:

Especially designed or prepared process systems including:

1. Feed autoclaves (or stations), used for passing UF₆ to the centrifuge cascades at up to 100 KN/m² (15 psi) and at a rate of 1 kg/h or more.
2. Desublimers (or cold traps) used to remove UF₆ from the cascades at up to 3 kN/m² (0.5 lb/in²) pressure. The desublimers are capable of being chilled to -70 °C and heated to 70 °C.
3. Product and tails stations used for trapping UF₆ into containers.

This plant equipment and pipework are wholly made of or lined with UF₆ resistant materials (see Footnote to this Section) and are fabricated to very high vacuum and cleanliness standards.

(b) Machine Header Piping Systems:

Especially designed or prepared piping systems and header systems for handling UF₆ within the centrifuge cascades.

This piping network is normally of the "triple" header system with each centrifuge connected to each of the headers. There is thus a substantial amount of repetition in its form. It is wholly made of UF₆ resistant materials (see Note to this Section) and is fabricated to very high vacuum and cleanliness standards.

(c) UF₆ Mass Spectrometers/Ion Sources: Especially designed or prepared magnetic or quadrupole mass spectrometers capable of taking "on-line" sample of feed, product or tails from UF₆ gas streams and having all of the following characteristics:

1. Unit resolution for mass greater than 320.
2. Ion sources constructed of or lined with nichrome, monel or nickel-plate.
3. Electron bombardment ionization sources.
4. Having a collector system suitable for isotope analysis.

(d) Frequency Changers: Frequency changers (also known as converters or invertors) especially designed or prepared to supply motor stators as defined under Section 1.2(d), or parts, components and subassemblies of such frequency changers having all of the following characteristics:

1. A multiphase output of 600 Hz to 2000Hz.
2. High stability (with frequency control better than 0.1%).
3. Low harmonic distortion (less than 2%).
4. An efficiency of greater than 80%.

FOOTNOTE

Materials resistant to corrosion by UF₆ include stainless steel, aluminum, aluminum alloys, nickel or alloys containing 60% or more nickel.

[49 FR 47203, Dec. 3, 1984. Redesignated at 55 FR 30450, July 26, 1990; 58 FR 13005, Mar. 9, 1993; 61 FR 35602, July 8, 1996; 65 FR 70291, Nov. 22, 2000]

APPENDIX C TO PART 110—ILLUSTRATIVE LIST OF GASEOUS DIFFUSION ENRICHMENT PLANT ASSEMBLIES AND COMPONENTS UNDER NRC EXPORT LICENSING AUTHORITY

NOTE—In the gaseous diffusion method of uranium isotope separation, the main technological assembly is a special porous gaseous diffusion barrier, heat exchanger for cooling the gas (which is heated by the process of compression), seal valves and control valves, and pipelines. Inasmuch as gaseous diffusion technology uses uranium hexafluoride (UF₆), all equipment, pipeline and instrumentation surfaces (that come in contact with the gas) must be made of materials that remain stable in contact with UF₆. A gaseous diffusion facility requires a number of these assemblies, so that quantities can provide an important indication of end use.

The auxiliary systems, equipment and components for gaseous diffusion enrichment plants are the systems of plant needed to feed UF₆ to the gaseous diffusion assembly to link the individual assemblies to each other to form cascades (or stages) to allow for progressively higher enrichments and to extract the "product" and "tails" UF₆ from the diffusion cascades. Because of the high inertial properties of diffusion cascades, any interruption in their operation, and especially their shut-down, leads to serious consequences. Therefore, a strict and constant maintenance of vacuum in all technological systems, automatic protection for accidents, and precise automated regulation of the gas flow is of importance in a gaseous diffusion plant. All this leads to a need to equip the plant with a large number of special measuring, regulating, and controlling systems.

Normally UF₆ is evaporated from cylinders placed within autoclaves and is distributed in gaseous form to the entry point by way of cascade header pipework. The "product" and "tails" UF₆ gaseous streams flowing from exit points are passed by way of cascade header pipework to either cold traps or to compression stations where the UF₆ gas is liquified prior to onward transfer into suitable containers for transportation or storage. Because a gaseous diffusion enrichment plant consists of a large number of gaseous diffusion assemblies arranged in cascades,