

§ 1915.171

accessories, the employer shall ensure that the following steps are taken:

(1) The devil claws (also known as chain stoppers) shall be made fast to the anchor chains.

(2) The riding pawls shall be in the engaged position.

(3) In the absence of devil claws and riding pawls, the anchor chains shall be secured to a suitable fixed structure of the vessel.

[47 FR 16986, Apr. 20, 1982, as amended at 67 FR 44545, July 3, 2002]

Subpart K—Portable, Unfired Pressure Vessels, Drums and Containers, Other Than Ship's Equipment

§ 1915.171 Scope and application of subpart.

The standards contained in this subpart shall apply to ship repairing and shipbuilding and shall not apply to shipbreaking.

§ 1915.172 Portable air receivers and other unfired pressure vessels.

(a) Portable, unfired pressure vessels, built after the effective date of this regulation, shall be marked and reported indicating that they have been designed and constructed to meet the standards of the American Society of Mechanical Engineers Boiler and Pressure Vessel Code, Section VIII, Rules for Construction of Unfired Pressure Vessels, 1963. They shall be subjected to a hydrostatic pressure test of one and one-half times the working pressure of the vessels.

(b) Portable, unfired pressure vessels, not built to the code requirements of paragraph (a) of this section, and built prior to the effective date of this regulation, shall be examined quarterly by a competent person. They shall be subjected yearly to a hydrostatic pressure test of one and one-half times the working pressure of the vessels.

(c) The relief valves on the portable, unfired pressure vessels in paragraphs (a) and (b) of this section shall be set to the safe working pressure of the vessels, or set to the lowest safe working pressure of the systems, whichever is lower.

29 CFR Ch. XVII (7–1–10 Edition)

(d) A certification record of such examinations and tests made in compliance with the requirements of paragraphs (a) and (b) of this section shall be maintained. The certification record shall include the date of examinations and tests, the signature of the person who performed the examinations or tests and the serial number, or other identifier, of the equipment examined and tested.

[47 FR 16986, Apr. 20, 1982, as amended at 51 FR 34562, Sept. 29, 1986; 67 FR 44545, July 3, 2002]

§ 1915.173 Drums and containers.

(a) Shipping drums and containers shall not be pressurized to remove their contents.

(b) A temporarily assembled pressurized piping system conveying hazardous liquids or gases shall be provided with a relief valve and by-pass to prevent rupture of the system and the escape of such hazardous liquids or gases.

(c) Pressure vessels, drums and containers containing toxic or flammable liquids or gases shall not be stored or used where they are subject to open flame, hot metal, or other sources of artificial heat.

(d) Unless pressure vessels, drums and containers of 30 gallon capacity or over containing flammable or toxic liquids or gases are placed in an out-of-the-way area where they will not be subject to physical injury from an outside source, barriers or guards shall be erected to protect them from such physical injury.

(e) Containers of 55 gallons or more capacity containing flammable or toxic liquid shall be surrounded by dikes or pans which enclose a volume equal to at least 35 percent of the total volume of the containers.

(f) Fire extinguishers adequate in number and suitable for the hazard shall be provided. These extinguishers shall be located in the immediate area where pressure vessels, drums and containers containing flammable liquids or gases are stored or in use. Such extinguishers shall be ready for use at all times.