

## § 250.505

well as the appropriate requirements of this subpart.

[53 FR 10690, Apr. 1, 1988. Redesignated and amended at 63 FR 29479, 29485, May 29, 1998; 68 FR 8434, Feb. 20, 2003]

### § 250.505 Subsea completions.

No subsea well completion shall be commenced until the lessee obtains written approval from the District Manager in accordance with § 250.513 of this part. That approval shall be based upon a case-by-case determination that the proposed equipment and procedures will adequately control the well and permit safe production operations.

[53 FR 10690, Apr. 1, 1988. Redesignated and amended at 63 FR 29479, 29485, May 29, 1998]

### § 250.506 Crew instructions.

Prior to engaging in well-completion operations, crew members shall be instructed in the safety requirements of the operations to be performed, possible hazards to be encountered, and general safety considerations to protect personnel, equipment, and the environment. Date and time of safety meetings shall be recorded and available at the facility for review by MMS representatives.

### §§ 250.507–250.508 [Reserved]

### § 250.509 Well-completion structures on fixed platforms.

Derricks, masts, substructures, and related equipment shall be selected, designed, installed, used, and maintained so as to be adequate for the potential loads and conditions of loading that may be encountered during the proposed operations. Prior to moving a well-completion rig or equipment onto a platform, the lessee shall determine the structural capability of the platform to safely support the equipment and proposed operations, taking into consideration the corrosion protection, age of platform, and previous stresses to the platform.

[53 FR 10690, Apr. 1, 1988, as amended at 54 FR 50616, Dec. 8, 1989. Redesignated at 63 FR 29479, May 29, 1998]

### § 250.510 Diesel engine air intakes.

Diesel engine air intakes must be equipped with a device to shut down

## 30 CFR Ch. II (7–1–10 Edition)

the diesel engine in the event of runaway. Diesel engines that are continuously attended must be equipped with either remote operated manual or automatic-shutdown devices. Diesel engines that are not continuously attended must be equipped with automatic-shutdown devices.

[74 FR 46908, Sept. 14, 2009]

### § 250.511 Traveling-block safety device.

All units being used for well-completion operations that have both a traveling block and a crown block must be equipped with a safety device that is designed to prevent the traveling block from striking the crown block. The device must be checked for proper operation weekly and after each drill-line slipping operation. The results of the operational check must be entered in the operations log.

[74 FR 46908, Sept. 14, 2009]

### § 250.512 Field well-completion rules.

When geological and engineering information available in a field enables the District Manager to determine specific operating requirements, field well-completion rules may be established on the District Manager's initiative or in response to a request from a lessee. Such rules may modify the specific requirements of this subpart. After field well-completion rules have been established, well-completion operations in the field shall be conducted in accordance with such rules and other requirements of this subpart. Field well-completion rules may be amended or canceled for cause at any time upon the initiative of the District Manager or upon the request of a lessee.

### § 250.513 Approval and reporting of well-completion operations.

(a) No well-completion operation may begin until the lessee receives written approval from the District Manager. If completion is planned and the data are available at the time you submit the Application for Permit to Drill and Supplemental APD Information Sheet (Forms MMS-123 and MMS-123S), you may request approval for a well-completion on those forms (see §§ 250.410 through 250.418 of this part). If