

Environmental Protection Agency

§ 63.1349

from the clinker cooler any gases which:

(1) Contain particulate matter in excess of 0.050 kg per Mg (0.10 lb per ton) of feed (dry basis) to the kiln.

(2) Exhibit opacity greater than ten percent.

(b) [Reserved]

§ 63.1346 Standards for new or reconstructed raw material dryers.

(a) New or reconstructed raw material dryers located at facilities that are major sources can not discharge to the atmosphere any gases which:

(1) Exhibit opacity greater than ten percent, or

(2) Contain THC in excess of 20 ppmv, on a dry basis as propane corrected to 7 percent oxygen if the source commenced construction after December 2, 2005. As an alternative to the 20 ppmv standard, you may demonstrate a 98 percent reduction in THC emissions from the exit of the raw materials dryer to discharge to the atmosphere. If the source is a greenfield dryer constructed on or prior to December 2, 2005, then the THC limit is 50 ppmv, on a dry basis corrected to 7 percent oxygen.

(b) New or reconstructed raw materials dryers located at a facility that is an area source cannot discharge to the atmosphere any gases which contain THC in excess of 20 ppmv, on a dry basis as propane corrected to 7 percent oxygen if the source commenced construction after December 2, 2005. As an alternative to the 20 ppmv standard, you may demonstrate a 98 percent reduction in THC emissions from the exit of the raw materials dryer to discharge to the atmosphere. If the source is a greenfield dryer constructed on or prior to December 2, 2005, then the THC limit is 50 ppmv, on a dry basis corrected to 7 percent oxygen.

[71 FR 76551, Dec. 20, 2006]

§ 63.1347 Standards for raw and finish mills.

The owner or operator of each new or existing raw mill or finish mill at a facility which is a major source subject to the provisions of this subpart shall not cause to be discharged from the mill sweep or air separator air pollution control devices of these affected

sources any gases which exhibit opacity in excess of ten percent.

§ 63.1348 Standards for affected sources other than kilns; in-line kiln/raw mills; clinker coolers; new and reconstructed raw material dryers; and raw and finish mills.

The owner or operator of each new or existing raw material, clinker, or finished product storage bin; conveying system transfer point; bagging system; and bulk loading or unloading system; and each existing raw material dryer, at a facility which is a major source subject to the provisions of this subpart shall not cause to be discharged any gases from these affected sources which exhibit opacity in excess of ten percent.

MONITORING AND COMPLIANCE PROVISIONS

§ 63.1349 Performance testing requirements.

(a) The owner or operator of an affected source subject to this subpart shall demonstrate initial compliance with the emission limits of § 63.1343 and §§ 63.1345 through 63.1348 using the test methods and procedures in paragraph (b) of this section and § 63.7. Performance test results shall be documented in complete test reports that contain the information required by paragraphs (a)(1) through (a)(10) of this section, as well as all other relevant information. The plan to be followed during testing shall be made available to the Administrator prior to testing, if requested.

(1) A brief description of the process and the air pollution control system;

(2) Sampling location description(s);

(3) A description of sampling and analytical procedures and any modifications to standard procedures;

(4) Test results;

(5) Quality assurance procedures and results;

(6) Records of operating conditions during the test, preparation of standards, and calibration procedures;

(7) Raw data sheets for field sampling and field and laboratory analyses;

(8) Documentation of calculations;

(9) All data recorded and used to establish parameters for compliance monitoring; and