

Pt. 63, Subpt. VVVVVV, Table 4

40 CFR Ch. I (7–1–10 Edition)

TABLE 4 TO SUBPART VVVVVV OF PART 63—EMISSION LIMITS AND COMPLIANCE REQUIREMENTS FOR METAL HAP PROCESS VENTS

process vents as shown in the following table.

As required in §63.11496(f), you must comply with the requirements for metal HAP

| For * * * | You must * * * | Except * * * |
|--|--|-----------------|
| Each CMPU with total metal HAP emissions ≥400 lb/yr. | Reduce collective uncontrolled emissions of total metal HAP emissions by ≥95 percent by weight by routing emissions from a sufficient number of the metal process vents through a closed-vent system to any combination of control devices, according to the requirements of §63.11496(f)(3), (4), or (5). | Not applicable. |

TABLE 5 TO SUBPART VVVVVV OF PART 63—EMISSION LIMITS AND COMPLIANCE REQUIREMENTS FOR STORAGE TANKS

As required in §63.11497, you must comply with the requirements for storage tanks as shown in the following table.

| For each * * * | You must * * * | Except * * * |
|---|---|--|
| 1. Storage tank with a design capacity ≥40,000 gallons, storing liquid that contains organic HAP listed in Table 1 to this subpart, and for which the maximum true vapor pressure (MTVP) of total organic HAP at the storage temperature is ≥5.2 kPa and <76.6 kPa. | <p>a. Comply with the requirements of subpart WW of this part;</p> <p>b. Reduce total organic HAP emissions by ≥95 percent by weight by operating and maintaining a closed-vent system and control device (other than a flare) in accordance with § 63.982(c)(1); or</p> <p>c. Reduce total HAP emissions by operating and maintaining a closed-vent system and a flare in accordance with §63.982(b); or</p> <p>d. Vapor balance in accordance with §63.2470(e); or</p> <p>e. Route emissions to a fuel gas system or process in accordance with the requirements in §63.982(d) and the requirements referenced therein.</p> | <p>i. All required seals must be installed by the compliance date in §63.11494.</p> <p>ii. Compliance may be based on either total organic HAP or TOC;</p> <p>iii. Comply with the management practice inspection requirements in §63.11495 for the closed-vent system;</p> <p>iv. When the term storage vessel is used in subpart SS of this part, the term storage tank, surge control vessel, or bottoms receiver, as defined in §63.11502 of this subpart, applies; and</p> <p>v. The requirements do not apply during periods of planned routine maintenance of the control device, as specified in §63.11497(b).</p> <p>w. The requirements do not apply during periods of planned routine maintenance of the flare, as specified in §63.11497(b); and</p> <p>x. When the term storage vessel is used in subpart SS of this part, it means storage tank, surge control vessel, or bottoms receiver, as defined in §63.11502 of this subpart.</p> <p>y. Not applicable.</p> <p>z. When the term storage vessel is used in subpart SS of this part, it means storage tank, surge control vessel, or bottoms receiver, as defined in §63.11502.</p> |