

**§ 414.46**

**§ 414.46 Pretreatment standards for new sources (PSNS).**

Except as provided in 40 CFR 403.7 any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve discharges in accordance with § 414.111.

[58 FR 36892, July 9, 1993]

**Subpart E—Thermosetting Resins**

**§ 414.50 Applicability; description of the thermosetting resins subcategory.**

The provisions of this subpart are applicable to the process wastewater discharges resulting from the manufacture of the products classified under SIC 28214 thermosetting resins including those resins and resin groups listed below. Product groups are indicated with an asterisk (\*).

- \*Alkyd Resins
- Dicyanodiamide Resin
- \*Epoxy Resins
- \*Fumaric Acid Polyesters
- \*Furan Resins
- Glyoxal-Urea Formaldehyde Textile Resin
- \*Ketone-Formaldehyde Resins
- \*Melamine Resins
- \*Phenolic Resins
- \*Polyacetal Resins
- Polyacrylamide
- \*Polyurethane Prepolymers
- \*Polyurethane Resins
- \*Urea Formaldehyde Resins
- \*Urea Resins

[52 FR 42568, Nov. 5, 1987, as amended at 57 FR 41844, Sept. 11, 1992]

**§ 414.51 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).**

Except as provided in 40 CFR 125.30 through 125.32, and in 40 CFR 414.11(i) for point sources with production in two or more subcategories, any existing point source subject to this subpart must achieve discharges not exceeding the quantity (mass) determined by multiplying the process wastewater flow subject to this subpart times the concentration listed in the following table.

**40 CFR Ch. I (7-1-09 Edition)**

Effluent characteristics	BPT effluent limitations <sup>1</sup>	
	Maximum for any one day	Maximum for monthly average
BOD5 .....	163	61
TSS .....	216	67
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> All units except pH are milligrams per liter.  
<sup>2</sup> Within the range of 6.0 to 9.0 at all times.

[52 FR 42568, Nov. 5, 1987, as amended at 57 FR 41844, Sept. 11, 1992]

**§ 414.52 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]**

**§ 414.53 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).**

(a) The Agency has determined that for existing point sources whose total OCPSF production defined by § 414.11 is less than or equal to five (5) million pounds of OCPSF products per year, the BPT level of treatment is the best available technology economically achievable. Accordingly, the Agency is not promulgating more stringent BAT limitations for these point sources.

(b) Except as provided in paragraph (a) of this section and in 40 CFR 125.30 through 125.32, any existing point source that uses end-of-pipe biological treatment and is subject to this subpart must achieve discharges in accordance with § 414.91 of this part.

(c) Except as provided in paragraph (a) of this section and in 40 CFR 125.30 through 125.32, any existing point source that does not use end-of-pipe biological treatment and is subject to this subpart must achieve discharges in accordance with § 414.101 of this part.

**§ 414.54 New source performance standards (NSPS).**

(a) Any new source that uses end-of-pipe biological treatment and is subject to this subpart must achieve discharges in accordance with § 414.91 of