## **Environmental Protection Agency**

SUBPART AU-NICKEL CARBONATE

	PSES effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Milligrams per liter (mg/l)	
Copper(T) Nickel(T)	1.1 1.1	0.36 0.36

In cases where POTWs find it necessary to impose mass limitations, the following equivalent mass limitations are provided as an alternate: The limitations for copper (T) and nickel (T) are the same as specified in §415.473(b).

## §415.475 New source performance standards (NSPS).

(a) Any new source subject to this subpart and producing nickel sulfate, nickel chloride, nickel fluorobate or nickel nitrate must achieve the following new source performance standards (NSPS):

SUBPART AU—NICKEL SULFATE, NICKEL CHLORIDE, NICKEL NITRATE, AND NICKEL FLUOBORATE

	NSPS effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (or pounds per 1,000 lb) of product	
TSS Copper Nickel	0.096 0.00074 0.00074	0.032 0.00024 0.00024
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range 6.0 to 9.0

(b) Any new source subject to this subpart and producing nickel carbonate must achieve the following new source performance standards (NSPS):

SUBPART AU-NICKEL CARBONATE

	NSPS effluent limitations		
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days	
	Kg/kkg (or pounds per/1,000 lb) or product		
TSS Copper Nickel	17. 0.13 0.13	5.6 0.042 0.042	

SUBPART AU—NICKEL CARBONATE—Continued

	NSPS effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range 6.0 to 9.0.

## § 415.476 Pretreatment standards for new sources (PSNS).

(a) Except as provided in 40 CFR 403.7, any new source subject to this subpart and producing nickel sulfate, nickel chloride, nickel fluoborate or nickel nitrate which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): The limitations for copper (T) and nickel (T) are the same as specified in §415.474(a).

(b) Except as provided in 40 CFR 403.7, any new source subject to this subpart and producing nickel carbonate which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): The limitations for copper (T) and nickel (T) are the same as specified in §415.474(b).

## §415.477 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

(a) Except as provided in 40 CFR 125.30 through 125.32 any existing point source subject to this subpart and producing nickel sulfate, nickel chloride, nickel fluoborate or nickel nitrate must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations are the same for TSS and pH as specified in §415.472(a).

(b) Except as provided in 40 CFR 125.30 through 125.32 any existing point source subject to this subpart and producing nickel carbonate must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of