

**§ 417.30**

treatment works must comply with 40 CFR part 403.

[60 FR 33952, June 29, 1995]

**Subpart C—Soap Manufacturing by Fatty Acid Neutralization Subcategory**

**§ 417.30 Applicability; description of the soap manufacturing by fatty acid neutralization subcategory.**

The provisions of this subpart are applicable to discharges resulting from the manufacturing of neat soap by neutralizing refined fatty acids with an alkaline material in approximately stoichiometric amounts in batch or continuous operations.

**§ 417.31 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *anhydrous product* shall mean the theoretical product that would result if all water were removed from the actual product.

(c) The term *neat soap* shall mean the solution of completely saponified and purified soap containing about 20-30 percent water which is ready for final formulation into a finished product.

**§ 417.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kilograms per 1,000 kg of anhydrous product)	
BOD5 .....	0.03	0.01
COD .....	0.15	.05

**40 CFR Ch. I (7-1-09 Edition)**

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	English units (pounds per 1,000 lb of anhydrous product)	
TSS .....	0.06	.02
Oil and grease .....	0.03	.01
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
BOD5 .....	0.03	0.01
COD .....	0.15	.05
TSS .....	0.06	.02
Oil and grease .....	0.03	.01
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 13372, Apr. 12, 1974; 39 FR 17841, May 21, 1974, as amended at 60 FR 33952, June 29, 1995]

**§ 417.33 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.**

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kilograms per 1,000 kg of anhydrous product)	
BOD5 .....	0.02	0.01
COD .....	0.10	.05
TSS .....	0.04	.02
Oil and grease .....	0.02	.01
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
BOD5 .....	0.02	0.01
COD .....	0.10	.05
TSS .....	0.04	.02
Oil and grease .....	0.02	.01
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.