

§ 425.32

| Pollutant or pollutant property | BPT limitations | |
|---------------------------------|--|-----------------------------|
| | Maximum for any 1 day | Maximum for monthly average |
| | Kg/kg (or pounds per 1,000 pounds) of raw material | |
| BOD ₅ | 6.7 | 3.0 |
| TSS | 9.7 | 4.4 |
| Oil & Grease | 2.8 | 1.3 |
| Total Chromium | 0.17 | 0.06 |
| pH | (¹) | (¹) |

¹ Within the range of 6.0 to 9.0

[47 FR 52870, Nov. 23, 1982, as amended at 53 FR 9182, Mar. 21, 1988]

§ 425.32 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The effluent limitations are those for BOD₅, TSS, Oil and Grease, and pH contained in § 425.31.

§ 425.33 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT): The effluent limitations are those for Total Chromium contained in § 425.31.

§ 425.34 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

40 CFR Ch. I (7-1-10 Edition)

| Pollutant or pollutant property | NSPS | |
|---------------------------------|---|-----------------------------|
| | Maximum for any 1 day | Maximum for monthly average |
| | Kg/kg (or pound per 1,000 lb) of raw material | |
| BOD ₅ | 5.9 | 2.7 |
| TSS | 8.5 | 3.9 |
| Oil and grease | 2.4 | 1.1 |
| Total chromium | 0.15 | 0.06 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

§ 425.35 Pretreatment standards for existing sources (PSES).

(a) Except as provided in § 425.04 and 40 CFR 403.7 and § 403.13, any existing sources subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403, and achieve the following pretreatment standards:

| Pollutant or pollutant property | PSES limitations | |
|---------------------------------|-----------------------------|-----------------------------|
| | Maximum for any 1 day | Maximum for monthly average |
| | Milligrams per liter (mg/l) | |
| Sulfide | 24 | -- |
| Total Chromium | 12 | 8 |
| pH | (¹) | (¹) |

¹ Not less than 7.0.

(b) Any existing source subject to this subpart which processes less than 350 hides/day shall comply with § 425.35(a), except that the Total Chromium limitations contained in § 425.35(a) do not apply.

[47 FR 52870, Nov. 23, 1982; 48 FR 36116, June 30, 1983, as amended at 53 FR 9182, Mar. 21, 1988]

§ 425.36 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7 and § 425.04, any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403, and achieve the pretreatment standards contained in § 425.35.