

**Environmental Protection Agency**

**§ 426.115**

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT). (The fluoride and lead limitations are applicable to the abrasive polishing and acid polishing waste water streams while the TSS, oil, and pH limitations are applicable to the entire process waste water stream):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (g/kg of furnace pull)	
Oil .....	260.0	130.0
TSS .....	300.0	150.0
Fluoride .....	140.0	70.0
Lead .....	39.0	4.5
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (lb/1,000 lb of furnace pull)	
Oil .....	0.26	0.13
TSS .....	0.30	0.15
Fluoride .....	0.14	0.07
Lead .....	0.009	0.0045
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 2957, Jan. 16, 1975, as amended at 60 FR 33959, June 29, 1995]

**§ 426.113 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.**

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable. These limitations are applicable to the abrasive polishing and acid polishing waste water streams.

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (g/kg of furnace pull)	
Fluoride .....	120.0	60.0
Lead .....	0.9	0.45
	English units (lb/1,000 lb of furnace pull)	
Fluoride .....	0.12	0.06
Lead .....	0.0009	0.00045

[44 FR 50747, Aug. 29, 1979]

**§ 426.114 [Reserved]**

**§ 426.115 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart (the fluoride and lead limitations are applicable to the abrasive polishing and acid polishing waste water streams while the TSS, oil, and pH limitations are applicable to the entire process waste water stream):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (g/kg of furnace pull)	
Oil .....	260.0	130.0
TSS .....	260.0	130.0
Fluoride .....	120.0	60.0
Lead .....	30.9	0.45
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (lb/1,000 lb of furnace pull)	
Oil .....	0.26	0.13
TSS .....	0.26	0.13
Fluoride .....	0.12	0.06
Lead .....	0.0009	0.00045
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.