

SUBPART E

*Cleaning or Etching Bath*

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	0.067	0.027
Cyanide .....	0.036	0.015
Zinc .....	0.183	0.075
TTO .....	0.124	.....
Oil and grease (alternate monitoring parameter) .....	1.79	1.79

SUBPART E

*Cleaning or Etching Rinse*

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	0.52	0.21
Cyanide .....	0.28	0.11
Zinc .....	1.42	0.59
TTO .....	0.96	.....
Oil and grease (alternate monitoring parameter) .....	13.91	13.91

SUBPART E

*Cleaning or Etching Scrubber Liquor*

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	0.72	0.29
Cyanide .....	0.39	0.16
Zinc .....	1.97	0.812
TTO .....	1.34	.....
Oil and grease (alternate monitoring parameter) .....	19.33	19.33

[48 FR 49149, Oct. 24, 1983; 49 FR 11632, 11633, and 11635, Mar. 27, 1984]

§ 467.57 **Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.** [Reserved]

**Subpart F—Drawing With Emulsions or Soaps Subcategory**

§ 467.60 **Applicability; description of the drawing with emulsions or soaps subcategory.**

This subpart applies to discharges of pollutants to waters of the United States and introduction of pollutants into publicly owned treatment works from the core and the ancillary operations of the drawing with emulsions or soaps subcategory.

§ 467.61 **Specialized definitions.**

For the purpose of this subpart:

(a) The “core” of the drawing with emulsions or soaps subcategory shall include drawing using emulsions or soaps, stationary casting, artificial aging, annealing, degreasing, sawing, and swaging.

(b) The term “ancillary operation” shall mean any operation not previously included in the core, performed on-site, following or preceding the drawing operation. The ancillary operations shall include continuous rod casting, solution heat treatment and cleaning or etching.

§ 467.62 **Effluent limitations representing the degree of effluent reduction attainable by the application of best practicable control technology currently available.**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available: