

§ 471.73

40 CFR Ch. I (7-1-10 Edition)

SUBPART G—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of sawed or ground uranium rinse	
Cadmium .....	0.001	0.0004
Chromium .....	0.002	0.0007
Copper .....	0.006	0.003
Lead .....	0.002	0.0006
Nickel .....	0.003	0.002
Fluoride .....	0.277	0.123
Molybdenum .....	0.024	0.011

(k) *Area cleaning rinse.*

SUBPART G—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium formed	
Cadmium .....	0.009	0.004
Chromium .....	0.016	0.007
Copper .....	0.055	0.026
Lead .....	0.012	0.006
Nickel .....	0.024	0.016
Fluoride .....	2.56	1.14
Molybdenum .....	0.216	0.096

(l) *Drum, washwater.*

SUBPART G—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium formed	
Cadmium .....	0.009	0.004
Chromium .....	0.017	0.007
Copper .....	0.057	0.027
Lead .....	0.013	0.006
Nickel .....	0.025	0.017
Fluoride .....	2.64	1.17
Molybdenum .....	0.223	0.099

(m) *Laundry washwater.*

SUBPART G—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/employee—day	
Cadmium .....	5.24	2.10
Chromium .....	9.70	3.93
Copper .....	33.6	16.0
Lead .....	7.34	3.41
Nickel .....	14.4	9.70
Fluoride .....	1.560	692
Molybdenum .....	132	58.4

(n) *Degreasing spent solvents—Subpart G—BAT.* There shall be no discharge of process wastewater pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2888, Jan. 22, 1986]

§ 471.73 **New source performance standards (NSPS).**

Any new source subject to this subpart must achieve the following new source performance standards (NSPS). The mass of pollutants in the uranium forming process wastewater shall not exceed the following values:

(a) *Extrusion spent lubricants—Subpart G—NSPS.* There shall be no discharge of process wastewater pollutants.

(b) *Extrusion tool contact cooling water.*

SUBPART G—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium extruded	
Cadmium .....	0.007	0.003
Chromium .....	0.013	0.005
Copper .....	0.044	0.021
Lead .....	0.010	0.005
Nickel .....	0.019	0.013
Fluoride .....	2.05	0.908
Molybdenum .....	0.173	0.077
Oil and grease .....	0.344	0.344
TSS .....	0.516	0.413
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(c) *Heat treatment contact cooling water.*

SUBPART G—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of extruded or forged uranium heat treated	
Cadmium .....	0.006	0.003
Chromium .....	0.012	0.005
Copper .....	0.040	0.019
Lead .....	0.009	0.004
Nickel .....	0.017	0.012
Fluoride .....	1.86	0.827
Molybdenum .....	0.158	0.070
Oil and grease .....	0.313	0.313
TSS .....	0.470	0.376
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

**Environmental Protection Agency**

**§ 471.73**

(d) *Forging spent lubricants—Subpart G—NSPS.* There shall be no discharge of process wastewater pollutants.

(e) *Surface treatment spent baths.*

**SUBPART G—NSPS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium surface treated	
Cadmium .....	0.006	0.002
Chromium .....	0.010	0.004
Copper .....	0.035	0.017
Lead .....	0.008	0.004
Nickel .....	0.015	0.010
Fluoride .....	1.62	0.718
Molybdenum .....	0.137	0.061
Oil and grease .....	0.272	0.272
TSS .....	0.408	0.327
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(f) *Surface treatment rinse.*

**SUBPART G—NSPS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium surface treated	
Cadmium .....	0.068	0.027
Chromium .....	0.125	0.051
Copper .....	0.432	0.206
Lead .....	0.095	0.044
Nickel .....	0.186	0.125
Fluoride .....	20.1	8.90
Molybdenum .....	1.70	0.752
Oil and grease .....	3.37	3.37
TSS .....	5.06	4.05
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(g) *Wet air pollution control scrubber blowdown.*

**SUBPART G—NSPS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium surface treated	
Cadmium .....	0.0007	0.0003
Chromium .....	0.001	0.0005
Copper .....	0.005	0.002
Lead .....	0.001	0.0005
Nickel .....	0.002	0.001
Fluoride .....	0.208	0.092
Molybdenum .....	0.018	0.008
Oil and grease .....	0.035	0.035
TSS .....	0.053	0.042
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(h) *Sawing or grinding spent emulsions.*

**SUBPART G—NSPS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium sawed or ground with emulsions	
Cadmium .....	0.001	0.0005
Chromium .....	0.002	0.0009
Copper .....	0.007	0.004
Lead .....	0.002	0.0008
Nickel .....	0.003	0.002
Fluoride .....	0.338	0.150
Molybdenum .....	0.029	0.013
Oil and grease .....	0.057	0.057
TSS .....	0.085	0.068
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(i) *Sawing or grinding contact cooling water.*

**SUBPART G—NSPS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium sawed or ground with contact cooling water	
Cadmium .....	0.033	0.013
Chromium .....	0.061	0.025
Copper .....	0.211	0.101
Lead .....	0.046	0.022
Nickel .....	0.091	0.061
Fluoride .....	9.82	4.36
Molybdenum .....	0.830	0.368
Oil and grease .....	1.65	1.65
TSS .....	2.48	1.98
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(j) *Sawing or grinding rinse.*

§ 471.74

40 CFR Ch. I (7-1-10 Edition)

SUBPART G—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of sawed or ground uranium rinsed	
Cadmium .....	0.001	0.0004
Chromium .....	0.002	0.0007
Copper .....	0.006	0.003
Lead .....	0.002	0.0006
Nickel .....	0.003	0.002
Fluoride .....	0.277	0.123
Molybdenum .....	0.024	0.011
Oil and grease .....	0.047	0.047
TSS .....	0.070	0.056
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(k) *Area cleaning rinse.*

SUBPART G—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium formed	
Cadmium .....	0.009	0.004
Chromium .....	0.016	0.007
Copper .....	0.055	0.026
Lead .....	0.012	0.006
Nickel .....	0.024	0.016
Fluoride .....	2.56	1.14
Molybdenum .....	0.216	0.096
Oil and grease .....	0.429	0.429
TSS .....	0.644	0.515
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(l) *Drum washwater.*

SUBPART G—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium formed	
Cadmium .....	0.009	0.004
Chromium .....	0.017	0.007
Copper .....	0.057	0.027
Lead .....	0.013	0.006
Nickel .....	0.025	0.017
Fluoride .....	2.64	1.17
Molybdenum .....	0.223	0.099
Oil and grease .....	0.443	0.443
TSS .....	0.665	0.532
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(m) *Laundry washwater.*

SUBPART G—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/employee—day	
Cadmium .....	5.24	2.10
Chromium .....	9.70	3.93
Copper .....	33.6	16.0
Lead .....	7.34	3.41
Nickel .....	14.4	9.70
Fluoride .....	1,560	692
Molybdenum .....	132	58.4
Oil and grease .....	262	262
TSS .....	393	315
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(n) *Degreasing spent solvents—Subpart G—NSPS.* There shall be no discharge of process waster pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2888, Jan. 22, 1986]

§ 471.74 Pretreatment standards for existing sources (PSES). [Reserved]

§ 471.75 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS). The mass of wastewater pollutants in uranium forming process wastewater introduced into a POTW shall not exceed the following values:

(a) *Extrusion spent lubricants—Subpart G—PSNS.* There shall be no discharge of process wastewater pollutants.

(b) *Extrusion tool contact cooling water.*

SUBPART G—PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium extruded	
Cadmium .....	0.007	0.003
Chromium .....	0.013	0.005
Copper .....	0.044	0.021
Lead .....	0.010	0.005
Nickel .....	0.019	0.013
Fluoride .....	2.05	0.908
Molybdenum .....	0.173	0.077

(c) *Heat treatment contact cooling water.*