

Environmental Protection Agency

§ 57.502

(2) Each NSO shall require the submission of a final report, within 6 months of the required date for completion of the measures specified in the approved plan evaluating the performance and adequacy of the SCS developed pursuant to the approved plan. The report shall include:

(i) A detailed description of how the criteria that form the basis for particular curtailment decisions were derived;

(ii) A complete description of each SCS element listed in § 57.402 (a) through (d) (covering monitoring, meteorology, and the DLA), and an explanation of why the elements fulfill the requirements of those sections;

(iii) A reliability study demonstrating that the SCS will prevent violations of the NAAQS in the smelter's DLA at all times. The reliability study shall include a comprehensive analysis of the system's operation during one or more three-month seasonal periods when meteorological conditions creating the most serious risk of NAAQS violations are likely to occur. Where it is impossible, because of time restraints, to include in such a study and analysis of the three month seasonal period with meteorological conditions creating the most serious risk of NAAQS violations, the study shall analyze the system's operation on the basis of all available information. The NSO shall provide that in such case, a supplemental reliability study shall be submitted after the end of the worst case three-month period as a part of the next semi-annual report required under § 57.402(f).

(iv) A copy of the current SCS operational manual.

(c) *Amendment of the NSO.* Each NSO shall be amended, if necessary, within 3 months of completion of the measures required under the SCS development plan and also, if necessary, within three months of submission of the final report or any supplement to the final report required under paragraph (b)(2) of this section, to reflect the most current approved elements of the SCS and, as appropriate, to fulfill all other requirements of this subpart. Each NSO shall also be subsequently amended (as provided in § 57.104) whenever necessary as a result of the program required by

§ 57.402(f) or to reflect improved SCS operating procedures or other system requirements.

Subpart E—Fugitive Emission Evaluation and Control

§ 57.501 General requirements.

(a) Each NSO shall require the smelter owner to use such control measures as may be necessary to ensure that the smelter's fugitive emissions do not result in violations of the NAAQS for SO₂ in the smelter's DLA.

(b) A smelter which is operating under an NSO containing a SIP compliance schedule established in accordance with § 57.705 is required to be making progress toward compliance with any fugitive control requirements contained in its respective SIP and need not meet the other requirements contained in this subpart.

(c) A smelter which is subject to an NSO which does not contain a SIP compliance schedule must meet the provisions of §§ 57.502 and 57.503.

§ 57.502 Evaluation.

(a) *Evaluation at the time of application.* Any smelter owner may demonstrate at the time of application for an NSO that the smelter's SO₂ fugitive emissions will not cause or significant contribute to violations of the NAAQS in the smelter's DLA. If such demonstration is not made, the smelter owner shall submit the design and workplan for a study adequate to assess the sources of significant fugitive emissions from the smelter and their effects upon ambient air quality.

(b) Evaluation during the first 6 months of the NSO. The design and workplan of the study shall be approved, if adequate, by the issuing agency and included in the NSO. The study shall commence no later than the date when the NSO becomes effective and an analysis of its results shall be submitted to the issuing agency within 6 months of the effective date of the NSO. The study shall include an appropriate period during which the ambient air shall be monitored to determine the impact of fugitive emissions of sulfur dioxide, arsenic (at copper smelters only), lead (at lead and

§ 57.503

40 CFR Ch. I (7–1–10 Edition)

zinc smelters only), and total suspended particulates on the ambient air quality in the smelter's DLA.

§ 57.503 Control measures.

The NSO of any smelter subject to the requirements of § 57.502(b) shall be amended, if necessary, within 6 months of EPA's receipt of the analysis specified in § 57.502(b), as provided in § 57.704(c) to implement the requirement of § 57.501. Measures required to be implemented may include:

(a) *Additional supplementary control.* The use of the supplementary control system, if the additional use of the system does not interfere with the smelter owner's ability to meet the requirements of subpart D; and

(b) *Engineering and maintenance techniques.* The use of engineering and maintenance techniques to detect and prevent leaks and capture and vent fugitive emissions through appropriate stacks. These techniques include but are not limited to:

(1) For reactors, installation and proper operation of primary hoods;

(2) For roasters, installation and proper operation of primary hoods on all hot calcine transfer points;

(3) For furnaces, installation and proper operation of primary hoods on all active matte tap holes, matte launders, slag skim bays, and transfer points;

(4) For converters, installation and proper operation of primary hoods for blowing operations, and where appropriate, secondary hoods for charging and pouring operations;

(5) For sintering machines, installation and proper operation of primary hoods on the sinter bed, all hot sinter ignition points, all concentrate laydown points, and all hot sinter transfer points;

(6) For blast furnaces, installation and proper operation of primary hoods on all active slag and lead bullion furnace tap holes and transfer points;

(7) For dross reverberatory furnaces, installation and proper operation of primary hoods on all active charging and discharging points;

(8) Maintenance of all ducts, flues and stacks in a leak-free condition to the maximum extent possible;

(9) Maintenance of all process equipment under normal operating conditions in such a fashion that out-leakage of fugitive gases will be prevented to the maximum extent possible;

(10) Secondary or tertiary hooding on process equipment where necessary; and

(11) Partial or complete building evacuation as appropriate.

§ 57.504 Continuing evaluation of fugitive emission control measures.

Each NSO shall require the smelter owner to conduct an active program to continuously review the effectiveness of the fugitive emission control measures implemented pursuant to § 57.503 in maintaining the NAAQS and, if such measures are not sufficiently effective, to evaluate what additional measures should be taken to assure that the NAAQS will be maintained with a reasonable degree of reliability. The NSO shall also require submission of a semi-annual report to the issuing Agency detailing the results of this review and evaluation. Such a report may be submitted as part of the report required under § 57.402(f).

§ 57.505 Amendments of the NSO.

An NSO shall be amended within three months of submission of any report required under § 57.504 so as to require additional fugitive emission control measures if such report establishes that such additional measures are necessary to assure that the NAAQS will be maintained with a reasonable degree of reliability.

Subpart F—Research and Development Requirements

§ 57.601 General requirements.

(a) This subpart is not applicable to NSOs which contain a SIP compliance schedule in accordance with § 57.705.

(b) The requirements of this subpart may be waived with respect to a smelter if the owner of that smelter submits with its NSO application a written certification by a corporate official authorized to make such a certification that the smelter will either comply with its SO₂ SIP limits by January 2, 1988 or close after January 1, 1988 until it can comply with such limits.