#### EMISSION LIMITS

- 60.4315 What pollutants are regulated by this subpart?
- 60.4320 What emission limits must I meet for nitrogen oxides  $(NO_X)$ ?
- 60.4325 What emission limits must I meet for  $NO_X$  if my turbine burns both natural gas and distillate oil (or some other combination of fuels)?
- 60.4330 What emission limits must I meet for sulfur dioxide (SO<sub>2</sub>)?

#### GENERAL COMPLIANCE REQUIREMENTS

60.4333 What are my general requirements for complying with this subpart?

#### MONITORING

- 60.4335 How do I demonstrate compliance for  $NO_X$  if I use water or steam injection?
- 60.4340 How do I demonstrate continuous compliance for  $NO_X$  if I do not use water or steam injection?
- 60.4345 What are the requirements for the continuous emission monitoring system equipment, if I choose to use this option?
- 60.4350 How do I use data from the continuous emission monitoring equipment to identify excess emissions?
- 60.4355 How do I establish and document a proper parameter monitoring plan?
- 60.4360 How do I determine the total sulfur content of the turbine's combustion fuel?
- 60.4365 How can I be exempted from monitoring the total sulfur content of the fuel?
- 60.4370 How often must I determine the sulfur content of the fuel?

#### REPORTING

- 60.4375 What reports must I submit?
- 60.4380 How are excess emissions and monitor downtime defined for  $NO_X$ ?
- 60.4385 How are excess emissions and monitoring downtime defined for SO<sub>2</sub>?
- 60.4390 What are my reporting requirements if I operate an emergency combustion turbine or a research and development turbine?
- 60.4395 When must I submit my reports?

## PERFORMANCE TESTS

- 60.4400 How do I conduct the initial and subsequent performance tests, regarding  $NO_X$ ?
- 60.4405 How do I perform the initial performance test if I have chosen to install a  $NO_X$ -diluent CEMS?
- 60.4410 How do I establish a valid parameter range if I have chosen to continuously monitor parameters?
- 60.4415 How do I conduct the initial and subsequent performance tests for sulfur?

#### DEFINITIONS

- 60.4420 What definitions apply to this subpart?
- TABLE 1 TO SUBPART KKKK OF PART 60-NI-TROGEN OXIDE EMISSION LIMITS FOR NEW STATIONARY COMBUSTION TURBINES

AUTHORITY: 42 U.S.C. 7401 et seq.

Source: 36 FR 24877, Dec. 23, 1971, unless otherwise noted.

## **Subpart A—General Provisions**

### § 60.1 Applicability.

- (a) Except as provided in subparts B and C, the provisions of this part apply to the owner or operator of any stationary source which contains an affected facility, the construction or modification of which is commenced after the date of publication in this part of any standard (or, if earlier, the date of publication of any proposed standard) applicable to that facility.
- (b) Any new or revised standard of performance promulgated pursuant to section 111(b) of the Act shall apply to the owner or operator of any stationary source which contains an affected facility, the construction or modification of which is commenced after the date of publication in this part of such new or revised standard (or, if earlier, the date of publication of any proposed standard) applicable to that facility.
- (c) In addition to complying with the provisions of this part, the owner or operator of an affected facility may be required to obtain an operating permit issued to stationary sources by an authorized State air pollution control agency or by the Administrator of the U.S. Environmental Protection Agency (EPA) pursuant to Title V of the Clean Air Act (Act) as amended November 15, 1990 (42 U.S.C. 7661). For more information about obtaining an operating permit see part 70 of this chapter.
- (d) Site-specific standard for Merck & Co., Inc.'s Stonewall Plant in Elkton, Virginia. (1) This paragraph applies only to the pharmaceutical manufacturing facility, commonly referred to as the Stonewall Plant, located at Route 340 South, in Elkton, Virginia ("site").
- (2) Except for compliance with 40 CFR 60.49b(u), the site shall have the option of either complying directly

with the requirements of this part, or reducing the site-wide emissions caps in accordance with the procedures set forth in a permit issued pursuant to 40 CFR 52.2454. If the site chooses the option of reducing the site-wide emissions caps in accordance with the procedures set forth in such permit, the requirements of such permit shall apply in lieu of the otherwise applicable requirements of this part.

(3) Notwithstanding the provisions of paragraph (d)(2) of this section, for any provisions of this part except for Subpart Kb, the owner/operator of the site shall comply with the applicable provisions of this part if the Administrator determines that compliance with the provisions of this part is necessary for achieving the objectives of the regulation and the Administrator notifies the site in accordance with the provisions of the permit issued pursuant to 40 CFR 52.2454.

[40 FR 53346, Nov. 17, 1975, as amended at 55 FR 51382, Dec. 13, 1990; 59 FR 12427, Mar. 16, 1994; 62 FR 52641, Oct. 8, 1997]

#### § 60.2 Definitions.

The terms used in this part are defined in the Act or in this section as follows:

Act means the Clean Air Act (42 U.S.C. 7401 et seq.)

Administrator means the Administrator of the Environmental Protection Agency or his authorized representative.

Affected facility means, with reference to a stationary source, any apparatus to which a standard is applicable.

Alternative method means any method of sampling and analyzing for an air pollutant which is not a reference or equivalent method but which has been demonstrated to the Administrator's satisfaction to, in specific cases, produce results adequate for his determination of compliance.

Approved permit program means a State permit program approved by the Administrator as meeting the requirements of part 70 of this chapter or a Federal permit program established in this chapter pursuant to Title V of the Act (42 U.S.C. 7661).

Capital expenditure means an expenditure for a physical or operational change to an existing facility which ex-

ceeds the product of the applicable "annual asset guideline repair allowance percentage" specified in the latest edition of Internal Revenue Service (IRS) Publication 534 and the existing facility's basis, as defined by section 1012 of the Internal Revenue Code. However, the total expenditure for a physical or operational change to an existing facility must not be reduced by any "excluded additions" as defined in IRS Publication 534, as would be done for tax purposes.

Clean coal technology demonstration project means a project using funds appropriated under the heading 'Department of Energy-Clean Coal Technology', up to a total amount of \$2,500,000,000 for commercial demonstrations of clean coal technology, or similar projects funded through appropriations for the Environmental Protection Agency.

Commenced means, with respect to the definition of new source in section 111(a)(2) of the Act, that an owner or operator has undertaken a continuous program of construction or modification or that an owner or operator has entered into a contractual obligation to undertake and complete, within a reasonable time, a continuous program of construction or modification.

Construction means fabrication, erection, or installation of an affected facility.

Continuous monitoring system means the total equipment, required under the emission monitoring sections in applicable subparts, used to sample and condition (if applicable), to analyze, and to provide a permanent record of emissions or process parameters.

Electric utility steam generating unit means any steam electric generating unit that is constructed for the purpose of supplying more than one-third of its potential electric output capacity and more than 25 MW electrical output to any utility power distribution system for sale. Any steam supplied to a steam distribution system for the purpose of providing steam to a steam-electric generator that would produce electrical energy for sale is also considered in determining the electrical energy output capacity of the affected facility.

Equivalent method means any method of sampling and analyzing for an air

pollutant which has been demonstrated to the Administrator's satisfaction to have a consistent and quantitatively known relationship to the reference method, under specified conditions.

Excess Emissions and Monitoring Systems Performance Report is a report that must be submitted periodically by a source in order to provide data on its compliance with stated emission limits and operating parameters, and on the performance of its monitoring systems.

Existing facility means, with reference to a stationary source, any apparatus of the type for which a standard is promulgated in this part, and the construction or modification of which was commenced before the date of proposal of that standard; or any apparatus which could be altered in such a way as to be of that type.

Force majeure means, for purposes of §60.8, an event that will be or has been caused by circumstances beyond the control of the affected facility, its contractors, or any entity controlled by the affected facility that prevents the owner or operator from complying with the regulatory requirement to conduct performance tests within the specified timeframe despite the affected facility's best efforts to fulfill the obligation. Examples of such events are acts of nature, acts of war or terrorism, or equipment failure or safety hazard beyond the control of the affected facilitv.

Isokinetic sampling means sampling in which the linear velocity of the gas entering the sampling nozzle is equal to that of the undisturbed gas stream at the sample point.

Issuance of a part 70 permit will occur, if the State is the permitting authority, in accordance with the requirements of part 70 of this chapter and the applicable, approved State permit program. When the EPA is the permitting authority, issuance of a Title V permit occurs immediately after the EPA takes final action on the final permit.

Malfunction means any sudden, infrequent, and not reasonably preventable failure of air pollution control equipment, process equipment, or a process to operate in a normal or usual manner. Failures that are caused in part by

poor maintenance or careless operation are not malfunctions.

Modification means any physical change in, or change in the method of operation of, an existing facility which increases the amount of any air pollutant (to which a standard applies) emitted into the atmosphere by that facility or which results in the emission of any air pollutant (to which a standard applies) into the atmosphere not previously emitted.

Monitoring device means the total equipment, required under the monitoring of operations sections in applicable subparts, used to measure and record (if applicable) process parameters.

Nitrogen oxides means all oxides of nitrogen except nitrous oxide, as measured by test methods set forth in this part.

One-hour period means any 60-minute period commencing on the hour.

Opacity means the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Owner or operator means any person who owns, leases, operates, controls, or supervises an affected facility or a stationary source of which an affected facility is a part.

Part 70 permit means any permit issued, renewed, or revised pursuant to part 70 of this chapter.

Particulate matter means any finely divided solid or liquid material, other than uncombined water, as measured by the reference methods specified under each applicable subpart, or an equivalent or alternative method.

Permit program means a comprehensive State operating permit system established pursuant to title V of the Act (42 U.S.C. 7661) and regulations codified in part 70 of this chapter and applicable State regulations, or a comprehensive Federal operating permit system established pursuant to title V of the Act and regulations codified in this chapter.

Permitting authority means:

(1) The State air pollution control agency, local agency, other State agency, or other agency authorized by the Administrator to carry out a permit program under part 70 of this chapter; or

(2) The Administrator, in the case of EPA-implemented permit programs under title V of the Act (42 U.S.C. 7661).

Proportional sampling means sampling at a rate that produces a constant ratio of sampling rate to stack gas flow rate.

Reactivation of a very clean coal-fired electric utility steam generating unit means any physical change or change in the method of operation associated with the commencement of commercial operations by a coal-fired utility unit after a period of discontinued operation where the unit:

- (1) Has not been in operation for the two-year period prior to the enactment of the Clean Air Act Amendments of 1990, and the emissions from such unit continue to be carried in the permitting authority's emissions inventory at the time of enactment;
- (2) Was equipped prior to shut-down with a continuous system of emissions control that achieves a removal efficiency for sulfur dioxide of no less than 85 percent and a removal efficiency for particulates of no less than 98 percent:
- (3) Is equipped with low- $NO_X$  burners prior to the time of commencement of operations following reactivation; and
- (4) Is otherwise in compliance with the requirements of the Clean Air Act.

  Reference method, means any method

Reference method means any method of sampling and analyzing for an air pollutant as specified in the applicable subpart.

Repowering means replacement of an existing coal-fired boiler with one of the following clean coal technologies: atmospheric or pressurized fluidized bed combustion, integrated gasification combined cycle, magnetohydrodynamics, direct and indirect coal-fired turbines, integrated gasification fuel cells, or as determined by the Administrator, in consultation with the Secretary of Energy, a derivative of one or more of these technologies, and any other technology capable of controlling multiple combustion emissions simultaneously with improved boiler or generation efficiency and with significantly greater waste reduction relative to the performance of technology in widespread commercial use as of November 15, 1990. Repowering shall also include any oil and/or gas-fired unit which has been awarded clean coal technology demonstration funding as

of January 1, 1991, by the Department of Energy.

Run means the net period of time during which an emission sample is collected. Unless otherwise specified, a run may be either intermittent or continuous within the limits of good engineering practice.

Shutdown means the cessation of operation of an affected facility for any purpose.

Six-minute period means any one of the 10 equal parts of a one-hour period. Standard means a standard of performance proposed or promulgated under this part.

Standard conditions means a temperature of 293 K (68F) and a pressure of 101.3 kilopascals (29.92 in Hg).

Startup means the setting in operation of an affected facility for any purpose.

State means all non-Federal authorities, including local agencies, interstate associations, and State-wide programs, that have delegated authority to implement: (1) The provisions of this part; and/or (2) the permit program established under part 70 of this chapter. The term State shall have its conventional meaning where clear from the context.

Stationary source means any building, structure, facility, or installation which emits or may emit any air pollutant.

Title V permit means any permit issued, renewed, or revised pursuant to Federal or State regulations established to implement title V of the Act (42 U.S.C. 7661). A title V permit issued by a State permitting authority is called a part 70 permit in this part.

Volatile Organic Compound means any organic compound which participates in atmospheric photochemical reactions; or which is measured by a reference method, an equivalent method, an alternative method, or which is determined by procedures specified under any subpart.

[44 FR 55173, Sept. 25, 1979, as amended at 45 FR 5617, Jan. 23, 1980; 45 FR 85415, Dec. 24, 1980; 54 FR 6662, Feb. 14, 1989; 55 FR 51382, Dec. 13, 1990; 57 FR 32338, July 21, 1992; 59 FR 12427, Mar. 16, 1994; 72 FR 27442, May 16, 2007]

## **Environmental Protection Agency**

### § 60.3 Units and abbreviations.

Used in this part are abbreviations and symbols of units of measure. These are defined as follows:

(a) System International (SI) units of measure:

A-ampere g—gram Hz-hertz J—joule K-degree Kelvin kg-kilogram m-meter  $m^3$ —cubic meter mg—milligram— $10^{-3}$  gram mm—millimeter—10 <sup>-3</sup> meter  $Mg-megagram-10^6~gram$ mol-mole N-newton ng—nanogram— $10^{-9}$  gram nm—nanometer—10 -9 meter Pa-pascal s-second V—volt W-watt  $\Omega$ —ohm  $\mu g\text{--microgram}\text{--}10^{\,-6}\;gram$ 

# (b) Other units of measure:

Btu—British thermal unit °C—degree Celsius (centigrade) cal—calorie cfm-cubic feet per minute cu ft-cubic feet dcf-dry cubic feet dcm-dry cubic meter dscf—dry cubic feet at standard conditions dscm-dry cubic meter at standard conditions eq—equivalent °F—degree Fahrenheit  $ft\\-\!\!-\!feet$ gal-gallon gr—grain g-eq—gram equivalent hr-hour in-inch k-1.000l—liter lpm-liter per minute lb-pound meq-milliequivalent min-minute ml-milliliter mol. wt.—molecular weight ppb—parts per billion ppm—parts per million psia—pounds per square inch absolute psig—pounds per square inch gage °R—degree Rankine scf—cubic feet at standard conditions scfh-cubic feet per hour at standard conditions

scm-cubic meter at standard conditions

sec-second

sa ft—square feet std—at standard conditions

#### (c) Chemical nomenclature:

CdS-cadmium sulfide CO-carbon monoxide CO<sub>2</sub>—carbon dioxide HCl—hydrochloric acid Hg-mercury H<sub>2</sub>O—water  $\overline{H_2}S$ —hydrogen sulfide H<sub>2</sub>SO<sub>4</sub>—sulfuric acid  $N_2$ —nitrogen NO-nitric oxide NO<sub>2</sub>—nitrogen dioxide NO<sub>x</sub>-nitrogen oxides O<sub>2</sub>—oxygen SO<sub>2</sub>—sulfur dioxide SO<sub>3</sub>—sulfur trioxide SO<sub>x</sub>—sulfur oxides

#### (d) Miscellaneous:

A.S.T.M.—American Society for Testing and Materials

[42 FR 37000, July 19, 1977; 42 FR 38178, July 27, 1977]

#### § 60.4 Address.

(a) All requests, reports, applications, submittals, and other communications to the Administrator pursuant to this part shall be submitted in duplicate to the appropriate Regional Office of the U.S. Environmental Protection Agency to the attention of the Director of the Division indicated in the following list of EPA Regional Offices.

Region I (Connecticut, Maine, Massachusetts, New Hampshire, Rhode Island, Vermont), Director, Air Management Division, U.S. Environmental Protection Agency, John F. Kennedy Federal Building, Boston, MA 02203.

Region II (New Jersey, New York, Puerto Rico, Virgin Islands), Director, Air and Waste Management Division, U.S. Environmental Protection Agency, Federal Office Building, 26 Federal Plaza (Foley Square), New York, NY 10278.

Region III (Delaware, District of Columbia, Maryland, Pennsylvania, Virginia, West Virginia), Director, Air Protection Divi-sion, Mail Code 3AP00, 1650 Arch Street, Philadelphia, PA 19103-2029.

Region IV (Alabama, Florida, Georgia, Kentucky, Mississippi, North Carolina, South Carolina, Tennessee), Director, Air and Waste Management Division, U.S. Environmental Protection Agency, 345 Courtland Street, NE., Atlanta, GA 30365.

Region V (Illinois, Indiana, Michigan, Minnesota, Ohio, Wisconsin), Director, Air and Radiation Division, U.S. Environmental

- Protection Agency, 77 West Jackson Boulevard, Chicago, IL 60604–3590.
- Region VI (Arkansas, Louisiana, New Mexico, Oklahoma, Texas); Director; Air, Pesticides, and Toxics Division; U.S. Environmental Protection Agency, 1445 Ross Avenue, Dallas, TX 75202.
- Region VII (Iowa, Kansas, Missouri, Nebraska), Director, Air, RCRA, and Toxics Division, U.S. Environmental Protection Agency, 901 N. 5th Street, Kansas City, KS 66101.
- Region VIII (Colorado, Montana, North Dakota, South Dakota, Utah, Wyoming) Director, Air and Toxics Technical Enforcement Program, Office of Enforcement, Compliance and Environmental Justice, Mail Code 8ENF-AT, 1595 Wynkoop Street, Denver, CO 80202-1129.
- Region IX (American Samoa, Arizona, California, Guam, Hawaii, Nevada, Northern Mariana Islands), Director, Air Division, U.S. Environmental Protection Agency, 75 Hawthorne Street, San Francisco, CA 94105.
- Region X (Alaska, Oregon, Idaho, Washington), Director, Air and Waste Management Division, U.S. Environmental Protection Agency, 1200 Sixth Avenue, Seattle, WA 98101.
- (b) Section 111(c) directs the Administrator to delegate to each State, when appropriate, the authority to implement and enforce standards of performance for new stationary sources located in such State. All information required to be submitted to EPA under paragraph (a) of this section, must also be submitted to the appropriate State Agency of any State to which this authority has been delegated (provided, that each specific delegation may except sources from a certain Federal or State reporting requirement). The appropriate mailing address for those States whose delegation request has been approved is as follows:
  - (A) [Reserved]
- (B) State of Alabama: Alabama Department of Environmental Management, P.O. Box 301463, Montgomery, Alabama 36130–1463.
  (C) State of Alaska, Department of Envi-
- ronmental Conservation, Pouch O, Juneau, AK 99811.
  - (D) Arizona:
- Arizona Department of Environmental Quality, Office of Air Quality, P.O. Box 600, Phoenix, AZ 85001-0600.
- Maricopa County Air Pollution Control, 2406 S. 24th Street, Suite E-214, Phoenix, AZ 85034.
- Pima County Department of Environmental Quality, 130 West Congress Street, 3rd Floor, Tucson, AZ 85701-1317.

- Pinal County Air Quality Control District, Building F, 31 North Pinal Street, Florence, AZ 85232.
- NOTE: For tables listing the delegation status of agencies in Region IX, see paragraph (d) of this section.
- (E) State of Arkansas: Chief, Division of Air Pollution Control, Arkansas Department of Pollution Control and Ecology, 8001 National Drive, P.O. Box 9583, Little Rock, AR 72209.
  - (F) California:
- Amador County Air Pollution Control District, 500 Argonaut Lane, Jackson, CA 95642
- Antelope Valley Air Pollution Control District, 43301 Division Street, Suite 206, P.O. Box 4409, Lancaster, CA 93539-4409.
- Bay Area Air Quality Management District, 939 Ellis Street, San Francisco, CA 94109.
- Butte County Air Pollution Control District, 2525 Dominic Drive, Suite J, Chico, CA 95928-7184.
- Calaveras County Air Pollution Control District, 891 Mountain Ranch Rd., San Andreas, CA 95249.
- Colusa County Air Pollution Control District, 100 Sunrise Blvd., Suite F, Colusa, CA 95932-3246.
- El Dorado County Air Pollution Control District, 2850 Fairlane Court, Bldg. C, Placerville, CA 95667-4100.
- Feather River Air Quality Management District, 938 14th Street, Marysville, CA 95901–4149.
- Glenn County Air Pollution Control District, 720 N. Colusa Street, P.O. Box 351, Willows, CA 95988-0351.
- Great Basin Unified Air Pollution Control District, 157 Short Street, Suite 6, Bishop, CA 93514-3537.
- Imperial County Air Pollution Control District, 150 South Ninth Street, El Centro, CA 92243-2801.
- Kern County Air Pollution Control District (Southeast Desert), 2700 M. Street, Suite 302, Bakersfield, CA 93301-2370.
- Lake County Air Quality Management District, 885 Lakeport Blvd., Lakeport, CA 95453-5405.
- Lassen County Air Pollution Control District, 175 Russell Avenue, Susanville, CA 96130–4215.
- Mariposa County Air Pollution Control District, P.O. Box 5, Mariposa, CA 95338.
- Mendocino County Air Pollution Control District, 306 E. Gobbi Street, Ukiah, CA 95482-5511.
- Modoc County Air Pollution Control District, 202 W. 4th Street, Alturas, CA 96101–3915.
- Mojave Desert Air Quality Management District, 14306 Part Avenue, Victorville, CA 92392-2310.

- Monterey Bay Unified Air Pollution Control District, 24580 Silver Cloud Ct., Monterey, CA 93940-6536
- North Coast Unified Air Pollution Control District, 2300 Myrtle Avenue, Eureka, CA 95501-3327.
- Northern Sierra Air Quality Management District, 200 Litton Drive, P.O. Box 2509, Grass Valley, CA 95945-2509.
- Northern Sonoma County Air Pollution Control District, 150 Matheson Street, Healdsburg, CA 95448-4908.
- Placer County Air Pollution Control District, DeWitt Center, 11464 "B" Avenue, Auburn, CA 95603-2603.
- Sacramento Metropolitan Air Quality Management District, 777 12th Street, Third Floor, Sacramento, CA 95814-1908.
- San Diego County Air Pollution Control District, 9150 Chesapeake Drive, San Diego, CA 92123–1096.
- San Joaquin Valley Unified Air Pollution Control District, 1999 Tuolumne Street, 1990 E. Gettysburg, Fresno, CA 93726.
- San Luis Obispo County Air Pollution Control District, 3433 Roberto Court, San Luis Obispo, CA 93401-7126.
- Santa Barbara County Air Pollution Control District, 26 Castilian Drive, B-23, Goleta, CA 93117-3027.
- Shasta County Air Quality Management District, 1855 Placer Street, Suite 101, Redding, CA 96001-1759.
- Siskiyou County Air Pollution Control District, 525 So. Foothill Drive, Yreka, CA 96097-3036.
- South Coast Air Quality Management District, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182.
- Tehama County Air Pollution Control District, P.O. Box 38 (1750 Walnut Street), Red Bluff, CA 96080-0038.
- Tuolumne County Air Pollution Control District, 2 South Green Street, Sonora, CA 95370–4618.
- Ventura County Air Pollution Control District, 669 County Square Drive, Ventura, CA 93003-5417.
- Yolo-Solano Air Quality Management District, 1947 Galileo Ct., Suite 103, Davis, CA 95616-4882.
- NOTE: For tables listing the delegation status of agencies in Region IX, see paragraph (d) of this section.
- (G) State of Colorado, Department of Public Health and Environment, 4300 Cherry Creek Drive South, Denver, CO 80222-1530.
- NOTE: For a table listing Region VIII's NSPS delegation status, see paragraph (c) of
- (H) State of Connecticut, Bureau of Air Management, Department of Environmental Protection, State Office Building, 165 Capitol Avenue, Hartford, CT 06106.

- (I) State of Delaware, Department of Natural Resources & Environmental Control, 89 Kings Highway, P.O. Box 1401, Dover, Delaware 19903.
- (J) District of Columbia, Department of Public Health, Air Quality Division, 51 N Street, NE., Washington, DC 20002.
- (K) State of Florida: Florida Department of Environmental Protection, Division of Air Resources Management, 2600 Blair Stone Road, MS 5500, Tallahassee, Florida 32399– 2400
- (L) State of Georgia: Georgia Department of Natural Resources, Environmental Protection Division, 2 Martin Luther King Jr. Drive, SE., Suite 1152 East Floyd Tower, Atlanta, Georgia 30334–9000.
- (M) Hawaii:
- Hawaii State Agency, Clean Air Branch, 919 Ala Moana Blvd., 3rd Floor, Post Office Box 3378, Honolulu, HI 96814.

NOTE: For tables listing the delegation status of agencies in Region IX, see paragraph (d) of this section.

- (N) State of Idaho, Department of Health and Welfare, Statehouse, Boise, ID 83701.
- (O) State of Illinois, Bureau of Air, Division of Air Pollution Control, Illinois Environmental Protection Agency, 2200 Churchill Road, Springfield, IL 62794-9276.
- (P) State of Indiana, Indiana Department of Environmental Management, 100 North Senate Avenue, P.O. Box 6015, Indianapolis, Indiana 46206-6015.
- (Q) State of Iowa: Iowa Department of Natural Resources, Environmental Protection Division, Air Quality Bureau, 7900 Hickman Road, Suite 1, Urbandale, IA 50322.
- (R) State of Kansas: Kansas Department of Health and Environment, Bureau of Air and Radiation, 1000 S.W. Jackson, Suite 310, Topeka, KS 66612-1366.
- (S) Commonwealth of Kentucky: Commonwealth of Kentucky, Energy and Environment Cabinet, Department of Environmental Protection, Division for Air Quality, 200 Fair Oaks Lane, 1st Floor, Frankfort, Kentucky 40610–1403.
- Louisville Metro Air Pollution Control District, 850 Barret Avenue, Louisville, Kentucky 40204.
- (T) State Louisiana: Louisiana Department of Environmental Quality, P.O. Box 4301, Baton Rouge, Louisiana 70821–4301. For a list of delegated standards for Louisiana (excluding Indian country), see paragraph (e)(2) of this section.
- (U) State of Maine, Bureau of Air Quality Control, Department of Environmental Protection, State House, Station No. 17, Augusta, ME 04333.
- (V) State of Maryland, Department of the Environment, 1800 Washington Boulevard, Suite 705, Baltimore, Maryland 21230.
- (W) Commonwealth of Massachusetts, Division of Air Quality Control, Department of

Environmental Protection, One Winter Street, 7th floor, Boston, MA 02108.

(X) State of Michigan, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909.

(Y) Minnesota Pollution Control Agency, Division of Air Quality, 520 Lafayette Road, St. Paul, MN 55155.

(Z) State of Mississippi: Mississippi Department of Environmental Quality, Office of Pollution Control, Air Division, 515 East Amite Street, Jackson, Mississippi 39201.

(AA) State of Missouri: Missouri Department of Natural Resources, Division of Environmental Quality, P.O. Box 176, Jefferson City, MO 65102.

(BB) State of Montana, Department of Environmental Quality, 1520 E. 6th Ave., PO Box 200901, Helena, MT 59620-0901.

NOTE: For a table listing Region VIII's NSPS delegation status, see paragraph (c) of this section.

(CC) State of Nebraska, Nebraska Department of Environmental Control, P.O. Box 94877, State House Station, Lincoln, NE 68509.

Lincoln-Lancaster County Health Department, Division of Environmental Health, 2200 St. Marys Avenue, Lincoln, NE 68502 (DD) Nevada:

Nevada State Agency, Air Pollution Control, Bureau of Air Quality/Division of Environmental Protection, 333 West Nye Lane, Carson City, NV 89710.

Clark County Department of Air Quality Management, 500 S. Grand Central Parkway, First floor, Las Vegas, NV 89155-1776. Washoe County Air Pollution Control, Washoe County District Air Quality Man-

agement, P.O. Box 11130, 1001 E. Ninth Street, Reno, NV 89520. NOTE: For tables listing the delegation status of agencies in Region IX, see paragraph

(d) of this section.

(EE) State of New Hampshire, Air Resources Division, Department of Environmental Services, 64 North Main Street, Caller Box 2033, Concord, NH 03302-2033.

(FF) State of New Jersey: New Jersey Department of Environmental Protection, Division of Environmental Quality, Enforcement Element, John Fitch Plaza, CN-027, Trenton, NJ 08625.

(1) The following table lists the specific source and pollutant categories that have been delegated to the states in Region II. The (X) symbol is used to indicate each category that has been delegated.

			Sta	ite	
	Subpart	New Jersey	New York	Puerto Rico	Virgin Is- lands
D	Fossil-Fuel Fired Steam Generators for Which Construction Commenced After August 17, 1971 (Steam Generators and Lignite Fired Steam Generators).	x	X	x	х
Da	Electric Utility Steam Generating Units for Which Construction Commenced After September 18, 1978.	X		X.	
Db	Industrial-Commercial-Institutional Steam Generating Units	Χ	X	Χ	X
E	Incinerators	X	X	Χ	X
F	Portland Cement Plants	Χ		Χ	X
G	Nitric Acid Plants	Χ	X	Χ	X
Н	Sulfuric Acid Plants	Χ	X	Χ	X
1	Asphalt Concrete Plants	Χ	X	X	X
J	Petroleum Refineries—(All Categories)	Χ	X	Χ	X
K	Storage Vessels for Petroleum Liquids Constructed After June 11, 1973, and prior to May 19, 1978.	Х	X	X	X
Ka	Storage Vessels for Petroleum Liquids Constructed After May 18, 1978.	X	X	Χ.	
L	Secondary Lead Smelters	X	x	x	x
М	Secondary Brass and Bronze Ingot Production Plants	X			x
N	Iron and Steel Plants	Χ	X		X
0	Sewage Treatment Plants	X	X	X	X
P	Primary Copper Smelters	X			x
Q	Primary Zinc Smelters	X			X
R	Primary Lead Smelters	X	X	X	X
S	Primary Aluminum Reduction Plants	Χ	X	X	X
Т	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants.	X	X	X	X
U	Phosphate Fertilizer Industry: Superphosphoric Acid Plants	X	X	X	X
V	Phosphate Fertilizer Industry: Diammonium Phosphate Plants	X	X	X	X
W	Phosphate Fertilizer Industry: Triple Superphosphate Plants	X	X		X
Χ	Phosphate Fertilizer Industry: Granular Triple Superphosphate	Χ	X		X
Υ	Coal Preparation Plants		X	X	X
Z	Ferroally Production Facilities	Χ	X	X	X
AA	Steel Plants: Electric Arc Furnaces				

			Sta	ate	
	Subpart	New Jersey	New York	Puerto Rico	Virgin Is- lands
AAa	Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels in Steel Plants.	x	x	X.	
BB	Kraft Pulp Mills	X	X	X.	
CC	Glass Manufacturing Plants	X	X	X.	
DD	Grain Elevators	x	X	X.	
EE	Surface Coating of Metal Furniture	Χ	X	X.	
GG	Stationary Gas Turbines	X	X	X.	
HH	Lime Plants	x	X	X.	
KK	Lead Acid Battery Manufacturing Plants	X	X.		
LL	Metallic Mineral Processing Plants	X	x	X.	
MM	Automobile and Light-Duty Truck Surface Coating Operations	X	X.		
NN	Phosphate Rock Plants	X	X.		
PP	Ammonium Sulfate Manufacturing Plants	X	X.		
QQ	Graphic Art Industry Publication Rotogravure Printing	X	X	X	X
RR	Pressure Sensitive Tape and Label Surface Coating Operations.	X	X	X.	
SS	Industrial Surface Coating: Large Appliances	Χ	X	X.	
TT	Metal Coil Surface Coating	Χ	x	X.	
UU	Asphalt Processing and Asphalt Roofing Manufacture	X	X	X.	
VV	Equipment Leaks of Volatile Organic Compounds in Synthetic			X.	
	Organic Chemical Manufacturing Industry.				
ww	Beverage Can Surface Coating Industry	X	X	X.	
XX	Bulk Gasoline Terminals	Χ	X	X.	
FFF	Flexible Vinyl and Urethane Coating and Printing	X	X	X.	
GGG	Equipment Leaks of VOC in Petroleum Refineries	X		X.	
HHH	Synthetic Fiber Production Facilities	Χ		X.	
JJJ	Petroleum Dry Clearners	X	X	X.	
KKK	Equipment Leaks of VOC from Onshore Natural Gas Processing Plants.				
LLL	Onshore Natural Gas Processing Plants; SO <sub>2</sub> Emissions		X.		
000	Nonmetallic Mineral Processing Plants		X	X.	
PPP	Wool Fiberglass Insulation Manufacturing Plants		x	X.	

- (GG) State of New Mexico: New Mexico Environment Department, 1190 St. Francis Drive, P.O. Box 26110, Santa Fe, New Mexico 87502. Note: For a list of delegated standards for New Mexico (excluding Bernalillo County and Indian country), see paragraph (e)(1) of this section.
- (i) Albuquerque-Bernalillo County Air Quality Control Board, c/o Environmental Health Department, P.O. Box 1293, Albuquerque, New Mexico 87103.
  - (ii) [Reserved]
- (HH) New York: New York State Department of Environmental Conservation, 50 Wolf Road Albany, New York 12233, attention: Division of Air Resources
- (II) State of North Carolina: North Carolina Department of Environment and Natural Resources, Division of Air Quality, 1641 Mail Service Center, Raleigh, North Carolina 27699–1641.
- Forsyth County Environmental Affairs, 537 North Spruce Street, Winston-Salem, North Carolina 27101.

- Mecklenburg County Air Quality, 700 N. Tryon St., Suite 205, Charlotte, North Carolina 28202–2236.
- Western North Carolina Regional Air Quality Agency, 49 Mount Carmel Road, Asheville, North Carolina
- (JJ) State of North Dakota, Division of Air Quality, North Dakota Department of Health, P.O. Box 5520, Bismarck, ND 58506-5520.

NOTE: For a table listing Region VIII's NSPS delegation status, see paragraph (c) of this section.

## (KK) State of Ohio:

- (i) Medina, Summit and Portage Counties; Director, Akron Regional Air Quality Management District, 177 South Broadway, Akron, OH 44308.
- (ii) Stark County: Air Pollution Control Division, 420 Market Avenue North, Canton, Ohio 44702-3335.
- (iii) Butler, Clermont, Hamilton, and Warren Counties: Air Program Manager, Hamilton County Department of Environmental Services, 1632 Central Parkway, Cincinnati, Ohio 45210.

- (iv) Cuyahoga County: Commissioner, Department of Public Health & Welfare, Division of Air Pollution Control, 1925 Saint Clair, Cleveland, Ohio 44114.
- (v) Belmont, Carroll, Columbiana, Harrison, Jefferson, and Monroe Counties: Director, North Ohio Valley Air Authority (NOVAA), 814 Adams Street, Steubenville, OH 43952.
- (vi) Clark, Darke, Greene, Miami, Montgomery, and Preble Counties: Director, Regional Air Pollution Control Agency (RAPCA) 451 West Third Street, Dayton, Ohio 45402.
- (vii) Lucas County and the City of Rossford (in Wood County): Director, Toledo Environmental Services Agency, 26 Main Street, Toledo, OH 43605.
- (viii) Adams, Brown, Lawrence, and Scioto Counties; Engineer-Director, Air Division, Portsmouth City Health Department, 740 Second Street, Portsmouth, OH 45662.
- (ix) Allen, Ashland, Auglaize, Crawford, Defiance, Erie, Fulton, Hancock, Hardin, Henry, Huron, Marion, Mercer, Ottawa, Paulding, Putnam, Richland, Sandusky, Seneca, Van Wert, Williams, Wood (except City of Rossford), and Wyandot Counties: Ohio Environmental Protection Agency, Northwest District Office, Air Pollution Control, 347 Dunbridge Rd., Bowling Green, Ohio 43402.
- (x) Ashtabula, Holmes, Lorain, and Wayne Counties: Ohio Environmental Protection Agency, Northeast District Office, Air Pollution Unit, 2110 East Aurora Road, Twinsburg, OH 44087.
- (xi) Athens, Coshocton, Gallia, Guernsey, Hocking, Jackson, Meigs, Morgan, Muskingum, Noble, Perry, Pike, Ross, Tuscarawas, Vinton, and Washington Counties: Ohio Environmental Protection Agency, Southeast District Office, Air Pollution Unit, 2195 Front Street, Logan, OH 43138.
- (xii) Champaign, Clinton, Highland, Logan, and Shelby Counties: Ohio Environmental Protection Agency, Southwest District Office, Air Pollution Unit, 401 East Fifth Street, Dayton, Ohio 45402–2911.
- (xiii) Delaware, Fairfield, Fayette, Franklin, Knox, Licking, Madison, Morrow, Pickaway, and Union Counties: Ohio Environmental Protection Agency, Central District Office, Air

- Pollution Control, 3232 Alum Creek Drive, Columbus, Ohio, 43207–3417.
- (xiv) Geauga and Lake Counties: Lake County General Health District, Air Pollution Control, 105 Main Street, Painesville, OH 44077.
- (xv) Mahoning and Trumbull Counties: Mahoning-Trumbull Air Pollution Control Agency, 9 West Front Street, Youngstown, OH 44503.
- (LL) State of Oklahoma, Oklahoma State Department of Health, Air Quality Service, P.O. Box 53551, Oklahoma City, OK 73152.
- (i) Oklahoma City and County: Director, Oklahoma City-County Health Department, 921 Northeast 23rd Street, Oklahoma City, OK 73105.
- (ii) Tulsa County: Tulsa City-County Health Department, 4616 East Fifteenth Street, Tulsa, OK 74112.
- (MM) State of Oregon. (i) Oregon Department of Environmental Quality (ODEQ), 811 SW Sixth Avenue, Portland, OR 97204–1390, http://www.deg.state.or.us.
- (ii) Lane Regional Air Pollution Authority (LRAPA), 1010 Main Street, Springfield, Oregon 97477, http://www.lrapa.org.
- (NN)(i) City of Philadelphia, Department of Public Health, Air Management Services, 321 University Avenue, Philadelphia, Pennsylvania 19104.
- (ii) Commonwealth of Pennsylvania, Department of Environmental Protection, Bureau of Air Quality Control, P.O. Box 8468, 400 Market Street, Harrisburg, Pennsylvania 17105.
- (iii) Allegheny County Health Department, Bureau of Environmental Quality, Division of Air Quality, 301 39th Street, Pittsburgh, Pennsylvania 15201.
- (OO) State of Rhode Island, Division of Air and Hazardous Materials, Department of Environmental Management, 291 Promenade Street, Providence, RI 02908.
- (PP) State of South Carolina: South Carolina Department of Health and Environmental Control, 2600 Bull Street, Columbia, South Carolina 29201.
- (QQ) State of South Dakota, Air Quality Program, Department of Environment and Natural Resources, Joe Foss Building, 523 East Capitol, Pierre, SD 57501–3181.

NOTE: For a table listing Region VIII's NSPS delegation status, see paragragh (c) of this section.

(RR) State of Tennessee: Tennessee Department of Environment and Conservation, Division of Air Pollution Control, 401 Church Street, 9th Floor, L&C Annex, Nashville, Tennessee 37243–1531.

Knox County Air Quality Management—Department of Public Health, 140 Dameron Avenue, Knoxville, TN 37917.

Air Pollution Control Bureau, Metropolitan Health Department, 311 23rd Avenue North, Nashville, TN 37203.

Chattanooga-Hamilton County Air Pollution Control Bureau, 6125 Preservation Drive, Chattanooga, TN 37416.

Memphis-Shelby County Health Department—Air Pollution Control Program, 814 Jefferson Avenue, Memphis, TN 38105.

(SS) State of Texas, Texas Air Control Board, 6330 Highway 290 East, Austin, TX 78723.

(TT) State of Utah, Division of Air Quality, Department of Environmental Quality, P.O. Box 144820, Salt Lake City, UT 84114–4820.

NOTE: For a table listing Region VIII's NSPS delegation status, see paragraph (c) of this section.

(UU) State of Vermont, Air Pollution Control Division, Agency of Natural Resources, Building 3 South, 103 South Main Street, Waterbury, VT 05676.

(VV) Commonwealth of Virginia, Department of Environmental Quality, 629 East Main Street, Richmond, Virginia 23219.

(WW) State of Washington. (i) Washington State Department of Ecology (Ecology), P.O. Box 47600, Olympia, WA 98504–7600, http://www.ecy.wa.gov/

- (ii) Benton Clean Air Authority (BCAA), 650 George Washington Way, Richland, WA 99352–4289, http://www.bcaa.net/
- (iii) Northwest Air Pollution Control Authority (NWAPA), 1600 South Second St., Mount Vernon, WA 98273-5202, http://www.nwair.org/
- (iv) Olympic Regional Clean Air Agency (ORCAA), 909 Sleater-Kinney Road S.E., Suite 1, Lacey, WA 98503– 1128, http://www.orcaa.org/
- (v) Puget Sound Clean Air Agency (PSCAA), 110 Union Street, Suite 500, Seattle, WA 98101-2038, http://www.pscleanair.org/
- (vi) Spokane County Air Pollution Control Authority (SCAPCA), West 1101 College, Suite 403, Spokane, WA 99201, http://www.scapca.org/

(vii) Southwest Clean Air Agency (SWCAA), 1308 NE. 134th St., Vancouver, WA 98685-2747, http://www.swcleanair.org/

(viii) Yakima Regional Clean Air Authority (YRCAA), 6 South 2nd Street, Suite 1016, Yakima, WA 98901, http://co.yakima.wa.us/cleanair/default.htm

(ix) The following table lists the delegation status of the New Source Performance Standards for the State of Washington. An "X" indicates the subpart has been delegated, subject to all the conditions and limitations set forth in Federal law and the letters granting delegation. Some authorities cannot be delegated and are retained by EPA. Refer to the letters granting delegation for a discussion of these retained authorities. The dates noted at the end of the table indicate the effective dates of Federal rules that have been delegated. Authority for implementing and enforcing any amendments made to these rules after these effective dates are not delegated.

NSPS SUBPARTS DELEGATED TO WASHINGTON AIR AGENCIES

-										
Subpart <sup>1</sup>		Washington								
Subpart .	Ecology 2	BCAA <sup>3</sup>	NWAPA 4	ORCAA5	PSCAA6	SCAPCA <sup>7</sup>	SWCAA8	YRCAA 9		
A General Provisions     B Adoption and Submittal of State Plans for Designated Facilities.     C Emission Guidelines and Compliance Times	х	х	х	х	х	х	х	х		

§ 60.4

NSPS SUBPARTS DELEGATED TO WASHINGTON AIR AGENCIES—Continued

Cubmout 1				Washi	ington			
Subpart 1	Ecology <sup>2</sup>	ВСАА 3	NWAPA 4	ORCAA 5	PSCAA6	SCAPCA7	SWCAA 8	YRCAA9
Cb Large Municipal Waste Combustors that are Constructed on or before September 20, 1994 (Emission Guidelines and Compliance Times).  Cc Municipal Solid Waste Landfills (Emission Guidelines and Compliance Times).  Cd Sulfuric Acid Production								
Units (Emission Guidelines and Compliance Times).  Ce Hospital/Medical/Infec-								
tious Waste Incinerators (Emission Guidelines and Compliance Times). D Fossil-Fuel-Fired Steam Generators for which Con-								
struction is Commenced after August 17, 1971 Da Electric Utility Steam Generating Units for which Construction is Com-	х	Х	х	x	x	х	x	х
menced after September 18, 1978  Db Industrial-Commercial-	×	х	x	×	×	×	×	x
Institutional Steam Generating Units  Dc Small Industrial-Commercial-Institutional Steam	×	Х	x	×	×	×	×	х
Generating Units  E Incinerators  Ea Municipal Waste Com-	X X	X X	X X	X X	X X	X X	X X	X X
bustors for which Con- struction is Commenced after December 20, 1989 and on or before Sep-		V						
tember 20, 1994 Eb—Large Municipal Waste Combustors	X	X X	X	X X	X X	X X	X	X
Ec—Hospital/Medical/Infectious Waste Incinerators	X	Х	×	x	x	×		
F Portland Cement Plants G Nitric Acid Plants	X X	X X	X X	X	X X	X	X X	X X
H Sulfuric Acid Plants I Hot Mix Asphalt Facilities	X	X X	X X	X X	X X	X	X X	X X
J Petroleum Refineries K Storage Vessels for Petroleum Liquids for which Construction, Reconstruction, or Modification Commenced after June 11,	x	Ŷ	x	x	x	x	x	x
1973 and prior to May 19, 1978	х	х	х	х	x	x	х	х
1978 and prior to July 23, 1984	x	X	x	X	x	x	x	х
Modification Commenced after July 23, 1984	x	х	x	×	×	x	x	x

**Environmental Protection Agency** 

NSPS SUBPARTS DELEGATED TO WASHINGTON AIR AGENCIES—Continued

NSP5 500	PARIS DI	ELEGATED	TO WASH	Washi		ies—Con	illueu ——	
Subpart 1	Ecology 2	BCAA3	NWAPA 4	ORCAA5	PSCAA6	SCAPCA7	SWCAA8	YRCAA 9
L Secondary Lead Smelt-	,	.,		,	.,	.,	.,	
ers M Secondary Brass and	X	X	X	X	X	X	X	X
Bronze Production Plants	X	Х	Х	X	X	Х	X	X
N Primary Emissions from Basic Oxygen Process								
Furnaces for which Con-								
struction is Commenced after June 11, 1973	x	х	X	×	×	X	x	×
Na Secondary Emissions								
from Basic Oxygen Proc- ess Steel-making Facilities								
for which Construction is								
Commenced after January 20, 1983	x	X	X	×	×	X	×	×
O Sewage Treatment								
Plants P Primary Copper Smelters	X	X X	X	X X	X X	X X	X X	X X
Q Primary Zinc Smelters	x	X	X	x	x	X	x	ı x
R Primary Lead Smelters	X	X	X	X	X	X	X	X
S Primary Aluminum Re-								
duction Plants 10  T Phosphate Fertilizer In-	X							
dustry: Wet Process Phos-								
phoric Acid Plants	X	Х	Х	X	X	Х	X	X
U Phosphate Fertilizer In- dustry: Superphosphoric								
Acid Plants	X	Χ	Х	X	X	Х	X	X
V Phosphate Fertilizer In- dustry: Diammonium								
Phosphate Plants	X	Х	Х	X	X	Х	X	X
W Phosphate Fertilizer In-								
dustry: Triple Superphos- phate Plants	x	Х	х	×	×	X	x	×
X Phosphate Fertilizer In-								
dustry: Granular Triple Superphosphate Storage								
Facilities	X	Х	Х	X	x	Х	X	X
Y Coal Preparation Plants	X	Х	Х	X	X	Х	X	X
Z Ferroalloy Production Fa- cilities	x	X	х	×	×	X	x	×
AA Steel Plants: Electric								
Arc Furnaces Constructed after October 21, 1974								
and on or before August								
17, 1983 Floatric	X	Х	Х	X	X	Х	X	X
AAa Steel Plants: Electric Arc Furnaces and Argon-								
Oxygen Decarburization								
Vessels Constructed after August 7, 1983	x	х	x	×	×	x	×	x
BB Kraft Pulp Mills 11	x	^	^	^	_ ^	_ ^	_ ^	_ ^
CC Glass Manufacturing		v	V	,	,	V	\ \ \	
Plants DD Grain Elevators	X	X X	X	X	X	X	X	X
EE Surface Coating of								
Metal FurnitureGG Stationary Gas Tur-	X	Х	Х	X	X	X	X	X
bines	x	Х	Х	х	x	Х	X	X
HH Lime Manufacturing Plants	×	x	x	×	×	x	×	×
KK Lead-Acid Battery Man-	^	^	^	^	_ ^	_ ^	_ ^	_ ^
ufacturing Plants	X	Х	X	X	X	X	X	X
LL Metallic Mineral Proc- essing Plants	x	X	х	×	×	X	x	x
MM Automobile and Light								
Duty Truck Surface Coat- ing Operations	×	х	x	×	×	x	×	x
NN Phosphate Rock Plants		X	X	X	X	X	X	X

§ 60.4

NSPS SUBPARTS DELEGATED TO WASHINGTON AIR AGENCIES—Continued

NSPS 508	PARIS DI	ELEGATED	TO WASH	Wash		ies—Con	inueu	
Subpart 1	Ecology 2	BCAA <sup>3</sup>	NWAPA 4	ORCAA5	PSCAA6	SCAPCA 7	SWCAA8	YRCAA 9
	Loology	50/01	14474174	0110701	1 00/01	00/11/0/1	0110781	1110701
PP Ammonium Sulfate Manufacture	x	X	х	×	×	x	×	×
QQ Graphic Arts Industry: Publication Rotogravure								
Printing	X	X	Х	x	x	Х	x	×
RR Pressure Sensitive Tape and Label Surface								
Coating StandardsSS Industrial Surface Coat-	X	Х	Х	×	X	X	X	x
ing: Large Appliances	x	X	Х	×	x	X	x	x
TT Metal Coil Surface Coating	x	х	х	x	x	x	x	x
UU Asphalt Processing and Asphalt Roof Manu-								
facture VV Equipment Leaks of	X	Х	Х	X	X	X	X	X
VOC in Synthetic Organic								
Chemical Manufacturing Industry	×	Х	X	×	×	x	×	x
WW Beverage Can Sur-		v	V					
face Coating Industry  XX Bulk Gasoline Termi-	X	X	X	X	X	X	X	X
nalsAAA New Residential	X	Х	Х	X	X	X	X	X
Wood Heaters.								
BBB Rubber Tire Manufac- turing Industry	x	X	х	×	x	x	x	×
DDD VOC Emissions from Polymer Manufacturing In-								
dustry	x	Х	х	x	x	x	x	x
FFF Flexible Vinyl and Ure- thane Coating and Printing	×	х	x	×	×	x	×	x
GGG Equipment Leaks of VOC in Petroleum Refin-								
eries	x	Х	Х	x	x	X	x	x
HHH Synthetic Fiber Pro- duction Facilities	×	x	X	×	×	x	×	×
III VOC Emissions from								
Synthetic Organic Chemical Manufacturing Indus-								
try Air Oxidation Unit Processes	×	x	x	×	×	x	x	×
JJJ Petroleum Dry Clean-								
ers KKK Equipment Leaks of	X	X	X	X	X	X	X	X
VOC from Onshore Nat- ural Gas Processing								
Plants	x	Х	х	x	x	x	x	x
LLL Onshore Natural Gas Processing: SO <sub>2</sub> Emis-								
sions	X	X	Х	X	X	Х	X	X
NNN VOC Emissions from Synthetic Organic Chem-								
ical Manufacturing Indus- try Distillation Operations	×	x	x	×	x	x	x	×
OOO Nonmetallic Mineral								
Processing PlantsPPP Wool Fiberglass Insu-			X		X		X	
lation Manufacturing Plants	×	x	x	×	×	x	x	×
QQQ VOC Emissions from	^	^		^	_ ^		_ ^	_ ^
Petroleum Refinery Wastewater Systems	x	X	х	×	x	x	×	x
RRR VOCs from Synthetic		•						
Organic Chemical Manu- facturing Industry Reactor								
ProcessesSSS Magnetic Tape Coat-	X	Х	Х	X	X	X	X	X
ing Facilities	X	Х	Х	x	l x	X	X	X

NSPS SUBPARTS DELEGATED TO WASHINGTON AIR AGENCIES—Continued

Culpmont 1				Wash	ington			
Subpart 1	Ecology 2	BCAA3	NWAPA 4	ORCAA5	PSCAA6	SCAPCA7	SWCAA8	YRCAA 9
TTT Industrial Surface Coating: Surface Coating of Plastic Parts for Busi-								
ness MachinesUUU Calciners and Dryers	х	x	х	x	×	x	×	х
in Mineral Industries VVV Polymeric Coating of	х	Х	Х	х	x	X	x	×
Supporting Substrates Fa- cilities WWW Municipal Solid	х	Х	Х	х	×	×	×	×
Waste Landfills	x	×	X	×	x	x		x
eration Units for which Construction is Com- menced after November, 30, 1999 or for which Modification or Recon- struction is Commenced on or after June 1, 2001 DDDD Commercial and In- dustrial Solid Waste Incin- eration Units that Com- menced Construction on or before November 30, 1999 (Emission Guidelines and Compliance Times).	x	x		×	x	x		x

(XX) State of West Virginia, Department of Environmental Protection, Division of Air Quality, 601 57th Street, SE., Charleston, West Virginia 25304.

and Compliance Times).

1 Any authority within any subpart of this part that is not delegable, is not delegated. Please refer to Attachment B to the delegation letters for a listing of the NSPS authorities excluded from delegation.

2 Washington State Department of Ecology, for 40 CFR 60.17(h)(1), (h)(2), (h)(3) and 40 CFR part 60, subpart AAAA, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect February 20, 2001.

3 Benton Clean Air Authority, for 40 CFR 60.17(h)(1), (h)(2), (h)(3) and 40 CFR part 60, subpart AAAA, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart AAAA, as in effect on June 6, 2001; for 40 CFR part 60, subpart ACCC, as in effect on June 1, 2001; and 40 CFR part 60, subpart AAAA, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 20

on June 6, 2001; for 40 CFR part 60, subpart CCCC, as in effect on June 1, 2001; and for all other NSPS delegated, as in effect of Subpart S of this part is not delegated to local agencies in Washington because the Washington State Department of Ecology retains sole authority to regulate Primary Aluminum Plants, pursuant to Washington Administrative Code 173–415–010.

11 Subpart BB of this part is not delegated to local agencies in Washington because the Washington State Department of Ecology retains sole authority to regulate Kraft and Sulfite Pulping Mills, pursuant to Washington State Administrative Code 173–405–012 and 173–410–012.

(YY) Wisconsin—Wisconsin Department of Natural Resources, P.O. Box 7921, Madison, WI 53707.

(ZZ) State of Wyoming, Department of Environmental Quality, Air Quality Division, Herschler Building, 122 West 25th Street, Cheyenne, WY 82002.

NOTE: For a table listing Region VIII's NSPS delegation status, see paragraph (c) of this section.

(AAA) Territory of Guam: Guam Environmental Protection Agency, Post Office Box 2999, Agana, Guam 96910.

NOTE: For tables listing the delegation status of agencies in Region IX, see paragraph (d) of this section.

(BBB) Commonwealth of Puerto Rico: Commonwealth of Puerto Rico Environmental Quality Board, P.O. Box 11488, Santurce, PR 00910, Attention: Air Quality Area Director (see table under §60.4(b)(FF)(1)).

(CCC) U.S. Virgin Islands: U.S. Virgin Islands Department of Conservation and Cultural Affairs, P.O. Box 578, Charlotte Amalie, St. Thomas, VI 00801.

(DDD) American Samoa Environmental Protection Agency, Pago Pago, American Samoa 96799.

NOTE: For tables listing the delegation status of agencies in Region IX, see paragraph (d) of this section.

(EEE) Commonwealth of the Northern Mariana Islands, Division of Environmental Quality, P.O. Box 1304, Saipan, MP 96950.

NOTE: For tables listing the delegation status of agencies in Region IX, see paragraph (d) of this section.

(c) The following is a table indicating the delegation status of New Source Performance Standards for Region VIII.

DELEGATION STATUS OF NEW SOURCE PERFORMANCE STANDARDS [(NSPS) for Region VIII]

Subpart	СО	MT	ND	SD	UT	WY
A—General Provisions	(*)	(*)	(*)	(*)	(*)	(*)
D—Fossil Fuel Fired Steam Generators	(*)	(*)	(*)	(*)	(*)	(*)
Da—Electric Utility Steam Generators	(*)	(*)	(*)	(*)	(*)	(*)
Db—Industrial-Commercial—Institutional Steam Gen-						
erators	(*)	(*)	(*)	(*)	(*)	(*)
Dc—Industrial-Commercial-Institutional Steam Gen-			(4)	443		
erators	(*)	(*)	(*)	(*)	(*)	(*)
E—Incinerators	(*)	(*)	(*)	(*)	(*)	(*)
Ea—Municipal Waste Combustors	(*)	(*)	(*)	(*)	(*)	(*)
Eb—Large Municipal Waste Combustors		(*)		(*)	(*)	(*)
Ec—Hospital/Medical/Infectious Waste Incinerators	(*)	(*)	(*)	(*)	(*)	(*)
F—Portland Cement Plants	(*)	(*)	(*)	(*)	(*)	(*)
G—Nitric Acid Plants	(*)	(*)	(*)		(*)	(*)
H—Sulfuric Acid Plants	(*)	(*)	(*)		(*)	(*)
I—Asphalt Concrete Plants	(*)	(*)	(*)	(*)	(*)	(*)
J—Petroleum Refineries	(*)	(*)	(*)		(*)	(*)
K-Petroleum Storage Vessels (after 6/11/73 & prior						
to			(4)	443		443
5/19/78)	(*)	(*)	(*)	(*)	(*)	(*)
Ka—Petroleum Storage Vessels (after 5/18/78 & prior						
to	(4)	(4)	(4)	(+)	(4)	(4)
7/23/84)	(*)	(*)	(*)	(*)	(*)	(*)
Kb—Petroleum Storage Vessels (after 7/23/84)	(*)	(*)	(*)	(*)	(*)	(*)
L—Secondary Lead Smelters	(*)	(*)	(*)	(*)		
M—Secondary Brass and Bronze Production.	(+)	(+)	(+)	(+)		
Plants	(*)	(*)	(*)	(*)		
N—Primary Emissions from Basic Oxygen Process	(*)	(*)	(*)	(*)		
Furnaces (after 6/11/73)	(*)	(*)	(*)	(*)		
ess Furnaces (after 1/20/83)	(*)	(*)	(*)	(*)		
O—Sewage Treatment Plants	(*)	(*)	(*)	(*)	(*)	(*)
P—Primary Copper Smelters	(*)	(*)	(*)	(*)		()
Q—Primary Zinc Smelters	(*)	(*)	(*)	(*)		
R—Primary Lead Smelters	(*)	(*)	(*)	(*)		
S—Primary Aluminum Reduction Plants	(*)	(*)	(*)	(*)		
T—Phosphate Fertilizer Industry: Wet Process Phos-	()	()	( )	()		
phoric Plants	(*)	(*)	(*)		(*)	(*)
U—Phosphate Fertilizer Industry: Superphosphoric	( )	()	()		()	( )
Acid Plants	(*)	(*)	(*)		(*)	(*)
7 Old Fiding	()	()	. ()	i.	( )	()

# DELEGATION STATUS OF NEW SOURCE PERFORMANCE STANDARDS—Continued [(NSPS) for Region VIII]

[(NSPS) for Region VIII]								
Subpart	со	MT	ND	SD	UT	WY		
V—Phosphate Fertilizer Industry: Diammonium Phos-								
phate Plants	(*)	(*)	(*)		(*)	(*)		
phate Plants	(*)	(*)	(*)		(*)	(*)		
X—Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities	(*)	(*)	(*)		(*)	(*)		
Y—Coal Preparation Plants	(*)	(*)	(*)	(*)	(*)	(*)		
Z—Ferroalloy Production Facilities	(*)	(*)	(*)		(*)	(*)		
17/83)	(*)	(*)	(*)		(*)	(*)		
AAa—Steel Plants: Electric Arc Furnaces and Argon- Oxygen Decarburization Vessels (after 8/7/83)	(*\	(*)	(*)		(*)	(*)		
BB—Kraft Pulp Mills	(*) (*)	(*) (*)	(*) (*)	(*)	( )	(*)		
CC—Glass Manufacturing Plants	(*)	(*)	(*)		(*)	(*)		
DD—Grain Elevator  EE—Surface Coating of Metal Furniture	(*) (*)	(*) (*)	(*) (*)	(*)	(*) (*)	(*) (*)		
GG—Stationary Gas Turbines	(*)	(*)	(*)	(*)	(*)	(*) (*)		
HH—Lime Manufacturing PlantsKK—Lead-Acid Battery Manufacturing Plants	(*) (*)	(*) (*)	(*) (*)	(*)	(*) (*)	(*) (*)		
LL—Metallic Mineral Processing Plants	(*)	(*)	(*)	(*)	(*)	(*)		
MM—Automobile & Light Duty Truck Surface Coating Operations	(*)	(*)	(*)		(*)	(*)		
NN—Phosphate Rock Plants	(*)	(*)	(*)		(*)	(*)		
PP—Ammonium Sulfate Manufacturing	(*)	(*)	(*)		(*)	(*)		
QQ—Graphic Arts Industry: Publication Rotogravure Printing	(*)	(*)	(*)	(*)	(*)	(*)		
RR—Pressure Sensitive Tape & Label Surface Coat-	(*)	(*)	(*)	(*)	(*)	(*)		
ing	(*) (*)	(*) (*)	(*) (*)	(*)	(*) (*)	(*) (*)		
TT—Metal Coil Surface Coating	( <del>*</del> )	(*)	(*)		(*)	(*) (*)		
UU—Asphalt Processing & Asphalt Roofing Manufacture	(*)	(*)	(*)		(*)	(*)		
VV—Synthetic Organic Chemicals Manufacturing:				443				
Equipment Leaks of VOC	(*)	(*) (*)	(*) (*)	(*)	(*) (*)	(*) (*)		
XX—Bulk Gasoline Terminals	(*)	(*)	(*)	(*)	(*)	(*)		
AAA—Residential Wood Heaters BBB—Rubber Tires	(*) (*)	(*) (*)	(*)	(*)	(*) (*)	(*) (*)		
DDD—VOC Emissions from Polymer Manufacturing	( )	()	()		()	()		
Industry	(*) (*)	(*)	(*)		(*) (*)	(*) (*)		
FFF—Flexible Vinyl & Urethane Coating & Printing GGG—Equipment Leaks of VOC in Petroleum Refin-	( )	(*)	()		()	()		
eries	(*)	(*)	(*)		(*)	(*)		
HHH—Synthetic Fiber ProductionIII—VOC Emissions from the Synthetic Organic	(*)	(*)	(*)		(*)	(*)		
Chemical Manufacturing Industry Air Oxidation Unit						***		
JJJ—Petroleum Dry Cleaners	(*)	(*) (*)	(*) (*)	(*)	(*) (*)	(*) (*)		
KKK-Equipment Leaks of VOC from Onshore Nat-				( )		,,		
ural Gas Processing Plants LLL—Onshore Natural Gas Processing: SO <sub>2</sub> Emis-	(*)	(*)	(*)		(*)	(*)		
sions	(*)	(*)	(*)		(*)	(*)		
NNN—VOC Emissions from the Synthetic Organic Chemical Manufacturing Industry Distillation Oper-								
ations	(*)	(*)	(*)	(*)	(*)	(*)		
OOO—Nonmetallic Mineral Processing Plants	(*)	(*)	(*)	(*) (*)	(*) (*)	(*) (*)		
PPP—Wool Fiberglass Insulation Manufacturing Plants	(*)	(*)	(*)		(*)	(*)		
QQQ-VOC Emissions from Petroleum Refinery								
Wastewater Systems  RRR—VOC Emissions from Synthetic Organic Chem-	(*)	(*)	(*)		(*)	(*)		
istry Manufacturing Industry (SOCMI) Reactor Proc-								
esses	(*) (*)	(*) (*)	(*) (*)	(*) (*)	(*)	(*) (*)		
TTT—Plastic Parts for Business Machine Coatings	(*) (*)	(*) (*)	(*) (*)		(*) (*)	(*)		
UUU—Calciners and Dryers in Mineral Industries	(*)	(*)	(*)	(*)	(*)	(*)		
VVV—Polymeric Coating of Supporting Substrates WWW—Municipal Solid Waste Landfills	(*) (*)	(*) (*)	(*) (*)	(*)	(*) (*)	(*) (*) (*) (*) (*)		
AAAA-Small Municipal Waste Combustors		(*)	(*)		(*)	(*)		
CCCC-Commercial and Industrial Solid Waste Incineration Units	l	(*)	(*)		(*)	(*)		
		` '	` '		` '	` '		

# DELEGATION STATUS OF NEW SOURCE PERFORMANCE STANDARDS—Continued [(NSPS) for Region VIII]

Subpart	со	MT	ND	SD	UT	WY
EEEE—Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Commenced On or After June 16, 2006						(*)

<sup>(\*)</sup> Indicates approval of State regulation.

(d) The following tables list the specific part 60 standards that have been delegated unchanged to the air pollution control agencies in Region IX. The (X) symbol is used to indicate each standard that has been delegated. The

following provisions of this subpart are not delegated:  $\S 60.4(b)$ , 60.8(b), 60.9, 60.11(b), 60.11(e), 60.13(a), 60.13(d)(2), 60.13(g), 60.13(i).

(1) Arizona. The following table identifies delegations for Arizona:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR ARIZONA

		А	ir Pollution Co	ontrol Agend	у
	Subpart	Arizona DEQ	Maricopa County	Pima County	Pinal County
A	General Provisions	Х	Х	Х	Х
D	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971.	Х	Х	X	X
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.	Х	Х	X	X
Db	Industrial-Commercial-Institutional Steam Generating Units	X	X	X	l x
Dc	Small Industrial Steam Generating Units	X	X	X	x
E	Incinerators	X	X	X	l x
Ea	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.	X	X	X	X
Eb	Municipal Waste Combustors Constructed After September 20, 1994.	X	X	X	
Ec	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.	X	X	X	
F	Portland Cement Plants	Х	X	Х	l x
G	Nitric Acid Plants	x	x	X	l x
H	Sulfuric Acid Plant	X	X	X	X
ï	Hot Mix Asphalt Facilities	x	l $\hat{x}$	x	l x
J	Petroleum Refineries	x	x	x	l x
Ja	Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After May 14, 2007.	^		^	
K	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.	X	Х	Х	X
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.	Х	Х	Х	X
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.	Х	Х	Х	X
L	Secondary Lead Smelters	X	X	X	l x
M	Secondary Brass and Bronze Production Plants	X	X	X	x
N	Primary Emissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.	X	X	X	X
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Fa- cilities for Which Construction is Commenced After January 20, 1983.	Х	Х	Х	X
0	Sewage Treatment Plants	X	X	Х	X
P	Primary Copper Smelters	Х	X	Х	X
Q	Primary Zinc Smelters	X	X	X	X
R	Primary Lead Smelters	Х	X	Х	X
S	Primary Aluminum Reduction Plants	X	X	X	X
Ť	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants	X	X	X	X
Ü	Phosphate Fertilizer Industry: Superphosphoric Acid Plants	X	X	X	X
V	Phosphate Fertilizer Industry: Diammonium Phosphate Plants	X	l â	X	l x
w	Phosphate Fertilizer Industry: Triple Superphosphate Plants	X	l â	X	l x
X	Phosphate Fertilizer Industry: Granular Triple Superphosphate Stor-	x	x	x	l x
	age Facilities.	^	^	^	^

§ 60.4 **Environmental Protection Agency** 

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR ARIZONA—Continued

	Subport	Α	ir Pollution Co	ontroi Ageno	·
	Subpart	Arizona DEQ	Maricopa County	Pima County	Pinal County
Y	Coal Preparation Plants	Х	Х	Х	Х
Z	Ferroalloy Production Facilities	Χ	X	X	X
AA	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.	Χ	х	Х	X
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.	Χ	X	Х	X
BB	Kraft Pulp Mills	X	X	X	X
CC	Glass Manufacturing Plants	X	X	X	X
DD	Grain Elevators	X	X	X	X
EE	Surface Coating of Metal Furniture	X	X	X	X
FF	(Reserved).				
GG	Stationary Gas Turbines	Х	X	X	X
HH	Lime Manufacturing Plants	Х	X	Х	X
KK	Lead-Acid Battery Manufacturing Plants	Х	X	Х	X
LL	Metallic Mineral Processing Plants	Х	X	X	X
MM	Automobile and Light Duty Trucks Surface Coating Operations	X	X	X	X
NN	Phosphate Rock Plants	X	X	X	X
PP	Ammonium Sulfate Manufacture	X	X	X	X
QQ	Graphic Arts Industry: Publication Rotogravure Printing	X	X	X	X
RR	Pressure Sensitive Tape and Label Surface Coating Operations	X X	X X	X	X X
SS	Industrial Surface Coating: Large Appliances			X	X
TT UU	Metal Coil Surface Coating	X X	X X	X X	X
VV	Asphalt Processing and Asphalt Roofing Manufacture	x	x	x	x
VVa	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.	Х			
WW	Beverage Can Surface Coating Industry	X	X	X	X
XX	Bulk Gasoline Terminals	X	X	X	X
AAA	New Residential Wool Heaters	X	X	X	X
BBB CCC	Rubber Tire Manufacturing Industry	X	X	Х	X
DDD	Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry.	Х	Х	Х	x
EEE	(Reserved).	v	V	v	
FFF GGG	Flexible Vinyl and Urethane Coating and Printing	X X	X	X	X
GGGa	Equipment Leaks of VOC in Petroleum Refineries	x	^	^	^
HHH	Synthetic Fiber Production Facilities	X	X	X	X
III	Volatile Organic Compound (VOC) Emissions From the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.	Х	Х	Х	X
JJJ	Petroleum Dry Cleaners	X	X	X	X
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.	Х	X	Х	X
LLL	Onshore Natural Gas Processing: SO <sub>2</sub> Emissions	X	Х	Х	X
MMM NNN	(Reserved).  Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Op-	x	х	x	x
000	erations.  Nonmetallic Mineral Processing Plants	Х	x	X	×
PPP	Wool Fiberglass Insulation Manufacturing Plants	X	x	X	x
QQQ	VOC Emissions From Petroleum Refinery Wastewater Systems	X	X	X	x
RRR	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.	X	Х		
SSS	Magnetic Tape Coating Facilities	X	X	X X	×
UUU	Calciners and Dryers in Mineral Industries	X	X	Х	
VVV	Polymeric Coating of Supporting Substrates Facilities	Χ	X	Χ	X
WWW	Municipal Solid Waste Landfills	Χ	X	Х	
AAAA	Small Municipal Waste Combustion Units for Which Construction is Commenced After August 30, 1999 or for Which Modification or Reconstruction is Commended After June 6, 2001.	Х	X	Х	

§ 60.4

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR ARIZONA—Continued

		Ai	Air Pollution Control Agency				
	Subpart	Arizona DEQ	Maricopa County	Pima County	Pinal County		
cccc	Commercial and Industrial Solid Waste Incineration Units for Which Construction Is Commenced After November 30, 1999 or for Which Modification or Reconstruction Is Commenced on or After June 1, 2001.	х	х	х			
EEEE	Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Commenced on or After June 16, 2006.	X	Х				
IIII JJJJ	Stationary Compression Ignition Internal Combustion Engines Stationary Spark Ignition Internal Combustion Engines.	X					
KKKK GGGG	Stationary Combustion Turbines	X					

(2) California. The following tables identify delegations for each of the local air pollution control agencies of California.

(i) Delegations for Amador County Air Pollution Control District, Antelope Valley Air Pollution Control District, Bay Area Air Quality Management District, and Butte County Air Pollution Control District are shown in the following table:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR AMADOR COUNTY APCD, ANTELOPE VALLEY APCD, BAY AREA AQMD, AND BUTTE COUNTY AQMD

		Air pollution control agency			rol agency	
		Amador County APCD	Antelope Valley APCD	Bay Area AQMD	Butte County APCD	
A D	General Provisions. Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971.			x		
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.			×		
Db Dc E Ea	Industrial-Commercial-Institutional Steam Generating Units Small Industrial Steam Generating Units Incinerators Municipal Waste Combustors Constructed After December 20,			X X X		
Eb	1989 and On or Before September 20, 1994.  Municipal Waste Combustors Constructed After September 20,					
Ec	1994. Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.					
F	Portland Cement Plants	l		X		
G	Nitric Acid Plants			l x		
H	Sulfuric Acid Plants			X		
1	Hot Mix Asphalt Facilities			X		
J	Petroleum Refineries			X		
K	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.			X		
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.			х		
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.			X		
L	Secondary Lead Smelters			X		
M	Secondary Brass and Bronze Production Plants			X		
N	Primary Émissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.			X		
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Fa- cilities for Which Construction is Commenced After January 20, 1983.			х		
0	Sewage Treatment Plants			×		
P	Primary Copper Smelters			X		
Q	Primary Zinc Smelters	l	l	l x		

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR AMADOR COUNTY APCD, ANTELOPE VALLEY APCD, BAY AREA AQMD, AND BUTTE COUNTY AQMD—Continued

		Air pollution control agency			
	Subpart	Amador County APCD	Antelope Valley APCD	Bay Area AQMD	Butte County APCD
R	Primary Lead Smelters			Х	
S	Primary Aluminum Reduction Plants			X	
T	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants.				
J	Phosphate Fertilizer Industry: Superphosphoric Acid Plants			X	
V	Phosphate Fertilizer Industry: Diammonium Phosphate Plants			X	
N	Phosphate Fertilizer Industry: Triple Superphosphate Plants			X	
	Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities.			X	
<u> </u>	Coal Preparation Plants			X	
7	Ferroalloy Production Facilities			X	
AA	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.			X	
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.			X	
3B	Kraft pulp Mills			X	
CC	Glass Manufacturing Plants			X	
DD	Grain Elevators			X	
E	Surface Coating of Metal Furniture			X	
FF	(Reserved).				
GG	Stationary Gas Turbines			X	
HH.	Lime Manufacturing Plants			X	
ΚK	Lead-Acid Battery Manufacturing Plants			X	
L 48.4	Metallic Mineral Processing Plants			X	
MN	Automobile and Light Duty Trucks Surface Coating Operations			X X	
NN PP	Phosphate Rock Plants			X	
QQ	Ammonium Sulfate Manufacture			X	
RR	Graphic Arts Industry: Publication Rotogravure Printing			x	
SS	Industrial Surface Coating: Large Appliances			X	
T	Metal Coil Surface Coating			X	
JU	Asphalt Processing and Asphalt Roofing Manufacture			l $\hat{x}$	
/V	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.			x	
ww	Beverage Can Surface Coating Industry			l x	
XX	Bulk Gasoline Terminals.				
AAA	New Residential Wool Heaters			X	
3BB	Rubber Tire Manufacturing Industry			X	
CCC DDD	(Reserved). Volatile Organic Compounds (VOC) Emissions from the Polymer			х	
	Manufacturing Industry.				
EEE	(Reserved).			, , , , , , , , , , , , , , , , , , ,	
FFF	Flexible Vinyl and Urethane Coating and Printing			X	
GGG HHH	Equipment Leaks of VOC in Petroleum Refineries			X	
II	Synthetic Fiber Production Facilities			^	
	Unit Processes.				
JJJ KKK	Petroleum Dry Cleaners			X	
LL	Plants. Onshore Natural Gas Processing: SO2 Emissions.				
MMM	(Reserved).				
NNN	Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Op-			X	
000	erations.  Nonmetallic Mineral Processing Plants			x	
PPP	Wool Fiberglass Insulation Manufacturing Plants			x	
QQQ	VOC Emissions From Petroleum Refinery Wastewater Systems.			``	
RRR	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.				
SSS	Magnetic Tape Coating Facilities			X	
TTT	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.			X	
UUU	Calciners and Dryers in Mineral Industries			Х	
VVV	Polymeric Coating of Supporting Substrates Facilities			x	
www	Municipal Solid Waste Landfills.	I .	l .	1	

(ii) [Reserved]

(iii) Delegations for Glenn County Air Pollution Control District, Great Basin Unified Air Pollution Control District, Imperial County Air Pollution Control District, and Kern County Air Pollution Control District are shown in the following table:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR GLENN COUNTY APCD, GREAT BASIN UNIFIED APCD, IMPERIAL COUNTY APCD, AND KERN COUNTY APCD

		Air pollution control agency			
	Subpart	Glenn County APCD	Great Basin Unified APCD	Imperial County APCD	Kern County APCD
A	General Provisions		Х		Х
D	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971.		Х		Х
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.		Х		Χ
Db	Industrial-Commercial-Institutional Steam Generating Units		X		X
Dc	Small Industrial Steam Generating Units		X		X
Ē	Incinerators		X		X
Ea	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.		X		**
Eb	Municipal Waste Combustors Constructed After September 20, 1994.				
Ec	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20. 1996.				
F	Portland Cement Plants		Х		Х
G	Nitric Acid Plants		x		X
H	Sulfuric Acid Plants		x		^
i'	Hot Mix Asphalt Facilities		x	l	Χ
j	Petroleum Refineries		X		X
K	Storage Vessels for Petroleum Liquids for Which Construction, Re-		x		x
K	construction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.		^		^
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.		Х		Х
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or		Х		Х
	Modification Commenced After July 23, 1984.				
L	Secondary Lead Smelters		X		Х
М	Secondary Brass and Bronze Production Plants		X		X
N	Primary Emissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.		Х		Х
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Fa- cilities for Which Construction is Commenced After January 20, 1983.		Х		Х
0	Sewage Treatment Plants		X		Х
Р	Primary Copper Smelters		X		X
Q	Primary Zinc Smelters		X		X
R	Primary Lead Smelters		Х		X
S	Primary Aluminum Reduction Plants		X		Х
Ť	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants		X		X
Ù	Phosphate Fertilizer Industry: Superphosphoric Acid Plants		X		X
V	Phosphate Fertilizer Industry: Diammonium Phosphate Plants		X		X
w	Phosphate Fertilizer Industry: Triple Superphosphate Plants		x		X
X	Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities.		X		X
Υ	Coal Preparation Plants		Х	ll	Х
ż	Ferroalloy Production Facilities		X		X
ĀA	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.		X		X
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.		Х		X
BB	Kraft pulp Mills		X		Х
CC	Glass Manufacturing Plants		X		Χ
DD	Grain Elevators		X		Χ
EE	Surface Coating of Metal Furniture		X		X
FF	(Reserved).				
GG	Stationary Gas Turbines		X		Х
HH	Lime Manufacturing Plants		X		X
KK	Lead-Acid Battery Manufacturing Plants		X		X
LL	Metallic Mineral Processing Plants				
			- •		

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR GLENN COUNTY APCD, GREAT BASIN UNIFIED APCD, IMPERIAL COUNTY APCD, AND KERN COUNTY APCD—Continued

		Air pollution control agency				
	Subpart	Glenn County APCD	Great Basin Unified APCD	Imperial County APCD	Kern County APCD	
MM	Automobile and Light Duty Trucks Surface Coating Operations		Х		Х	
NN	Phosphate Rock Plants		X		X	
PP	Ammonium Sulfate Manufacture		X		Х	
QQ	Graphic Arts Industry: Publication Rotogravure Printing		X		X	
RR	Pressure Sensitive Tape and Label Surface Coating Operations		X		X	
SS	Industrial Surface Coating: Large Appliances		X		X	
TT	Metal Coil Surface Coating		X	l	X	
UU	Asphalt Processing and Asphalt Roofing Manufacture		X	l	X	
VV	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.		Х		Х	
WW XX	Beverage Čan Surface Coating Industry		Х		Х	
AAA	New Residential Wool Heaters		X	l	X	
BBB	Rubber Tire Manufacturing Industry		X	l	X	
CCC	(Reserved).					
DDD	Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry.		Х		Х	
EEE	(Reserved).					
FFF	Flexible Vinyl and Urethane Coating and Printing		Х	l	Х	
GGG	Equipment Leaks of VOC in Petroleum Refineries		X		X	
HHH	Synthetic Fiber Production Facilities		X	l	Х	
III	Volatile Organic Compound (VOC) Emissions From the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.		X		X	
JJJ	Petroleum Dry Cleaners		X		X	
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.		X		Х	
LLL MMM	Onshore Natural Gas Processing: SO2 Emissions				Х	
NNN	Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Operations.		X		Х	
000	Nonmetallic Mineral Processing Plants		X		Х	
PPP	Wool Fiberglass Insulation Manufacturing Plants		X		Х	
QQQ	VOC Emissions From Petroleum Refinery Wastewater Systems		X		Х	
RRR	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.				х	
SSS	Magnetic Tape Coating Facilities		X		Х	
TTT	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.		Х	х		
UUU	Calciners and Dryers in Mineral Industries		X		Х	
VVV	Polymeric Coating of Supporting Substrates Facilities		X	l	Х	

(iv) Delegations for Lake County Air Quality Management District, Lassen County Air Pollution Control District, Mariposa County Air Pollution Control District, and Mendocino County Air Pollution Control District are shown in the following table:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR LAKE COUNTY AIR QUALITY MANAGEMENT DISTRICT, LASSEN COUNTY AIR POLLUTION CONTROL DISTRICT, AND MENDOCINO COUNTY AIR POLLUTION CONTROL DISTRICT

		Air pollution control agency			
	Subpart	Lake County AQMD	Lassen County APCD	Mariposa County AQMD	Mendocino County AQMD
A D	General Provisions	X X			X X

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR LAKE COUNTY AIR QUALITY MANAGEMENT DISTRICT, LASSEN COUNTY AIR POLLUTION CONTROL DISTRICT, MARIPOSA COUNTY AIR POLLUTION CONTROL DISTRICT—Continued

		A	Air pollution c	ontrol agend	y
	Subpart	Lake County AQMD	Lassen County APCD	Mariposa County AQMD	Mendocino County AQMD
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.	Х			Х
Db	Industrial-Commercial-Institutional Steam Generating Units	X			
Dc	Small Industrial Steam Generating Units	X			X
E	Incinerators	Х			X
Ea	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.	Х			X
Eb	Municipal Waste Combustors Constructed After September 20, 1994.				
Ec F	Hospital/Medical/Infectious Waste Incinerators for Which Construc- tion is Commenced After June 20, 1996. Portland Cement Plants	X			x
G	Nitric Acid Plants	x			
Н	Sulfuric Acid Plants	X			X
i'	Hot Mix Asphalt Facilities	X			l $\hat{x}$
J	Petroleum Refineries	X			X
K	Storage Vessels for Petroleum Liquids for Which Construction,	X			X
	Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.				
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.	Х			X
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liq- uid Storage Vessels) for Which Construction, Reconstruction, or	Х			x
	Modification Commenced After July 23, 1984.	v			
L M	Secondary Lead Smelters	X			X
N	Secondary Brass and Bronze Production Plants Primary Emissions from Basic Oxygen Process Furnaces for	X			X
14	Which Construction is Commenced After June 11, 1973.	^			_ ^
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Facilities for Which Construction is Commenced After January 20, 1983.	Х			×
0	Sewage Treatment Plants	Х		l	×
P	Primary Copper Smelters	X			x
Q	Primary Zinc Smelters	X			X
R	Primary Lead Smelters	X			X
S	Primary Aluminum Reduction Plants	X			X
T	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants	X X			X X
U V	Phosphate Fertilizer Industry: Superphosphoric Acid Plants	X			X
w	Phosphate Fertilizer Industry: Triple Superphosphate Plants	X			x x
X	Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities.	X			x
Υ	Coal Preparation Plants	X			X
Z	Ferroalloy Production Facilities	X			X
AA	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.	X			X
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.	X			X
BB CC	Kraft Pulp Mills	X X			X X
DD	Grain Elevators	X			l ŝ
EE	Surface Coating of Metal Furniture	X			X
FF	(Reserved).				
GG	Stationary Gas Turbines	X			X
HH	Lime Manufacturing Plants	Х			X
KK	Lead-Acid Battery Manufacturing Plants	X			X
LL	Metallic Mineral Processing Plants	X			X X X X
MM NN	Automobile and Light Duty Trucks Surface Coating Operations	X X			×
NN PP	Phosphate Rock Plants	X			
QQ	Graphic Arts Industry: Publication Rotogravure Printing	x			l â
RR	Pressure Sensitive Tape and Label Surface Coating Operations	X			x
SS	Industrial Surface Coating: Large Appliances	X			x x
TT	Metal Coil Surface Coating				X
		-			

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR LAKE COUNTY AIR QUALITY MANAGEMENT DISTRICT, LASSEN COUNTY AIR POLLUTION CONTROL DISTRICT, MARIPOSA COUNTY AIR POLLUTION CONTROL DISTRICT—Continued

		Air pollution control agency				
		Lake County AQMD	Lassen County APCD	Mariposa County AQMD	Mendocino County AQMD	
UU	Asphalt Processing and Asphalt Roofing Manufacture	Х			х	
VV	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.	×			×	
WW	Beverage Can Surface Coating Industry	X			X	
XX	Bulk Gasoline Terminals.					
AAA	New Residential Wool Heaters	X			X	
BBB	Rubber Tire Manufacturing Industry	X			X	
CCC	(Reserved).					
DDD EEE	Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry. (Reserved).	X			X	
FFF	Flexible Vinyl and Urethane Coating and Printing	x			x	
GGG	Equipment Leaks of VOC in Petroleum Refineries	x			x	
HHH	Synthetic Fiber Production Facilities	l â			l â	
III	Volatile Organic Compound (VOC) Emissions From the Synthetic	x			x	
	Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.		•••••		^	
JJJ	Petroleum Dry Cleaners	X			X	
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.	X			×	
LLL	Onshore Natural Gas Processing: SO2 Emissions	X			X	
MMM	(Reserved)					
NNN	Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Operations.	X			X	
000	Nonmetallic Mineral Processing Plants	X			X	
PPP	Wool Fiberglass Insulation Manufacturing Plants	X			X	
QQQ	VOC Emissions From Petroleum Refinery Wastewater Systems	X			X	
RRR	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.	X				
SSS	Magnetic Tape Coating Facilities	X			X	
TTT	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.					
UUU	Calciners and Dryers in Mineral Industries	X			X	
VVV	Polymeric Coating of Supporting Substrates Facilities	X			X	
WWW	Municipal Solid Waste Landfills	X				

(v) Delegations for Modoc County Air Pollution Control District, Mojave Desert Air Quality Management District, Monterey Bay Unified Air Pollution Control District, and North Coast Unified Air Pollution Control District are shown in the following table:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR MODOC COUNTY AIR POL-LUTION CONTROL DISTRICT, MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT, MONTEREY BAY UNIFIED AIR POLLUTION CONTROL DISTRICT, AND NORTH COAST UNIFIED AIR POLLUTION CONTROL DISTRICT

		Air pollution control agency			
	Subpart	Modoc County APCD	Mojave Desert AQMD	Monterey Bay Uni- fied APCD	North Coast Unified AQMD
Α	General Provisions	х		х	Х
D	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971.	X	Х	X	Х
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.	X		X	Х
Db	Industrial-Commercial-Institutional Steam Generating Units	X		X	Х
Dc	Small Industrial Steam Generating Units	l		X	

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR MODOC COUNTY AIR POLLUTION CONTROL DISTRICT, MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT, MONTEREY BAY UNIFIED AIR POLLUTION CONTROL DISTRICT, AND NORTH COAST UNIFIED AIR POLLUTION CONTROL DISTRICT—Continued

		Air pollution control agency				
	Subpart	Modoc County APCD	Mojave Desert AQMD	Monterey Bay Uni- fied APCD	North Coast Unified AQMD	
E Ea	Incinerators	Х	Х	х	Х	
Eb	Municipal Waste Combustors Constructed After September 20, 1994.					
Ec	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.					
F	Portland Cement Plants	X	X	X	X	
G	Nitric Acid Plants	X	X	X	X	
4	Sulfuric Acid Plants	X	X	X	X	
	Hot Mix Asphalt Facilities	Х	X	X	Х	
J	Petroleum Refineries	X	X	X	Х	
K	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.	Х	X	X	Х	
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.	Х		X	Х	
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.	Х		X	Х	
L	Secondary Lead Smelters	Х	×	x	Х	
M	Secondary Brass and Bronze Production Plants	X	X	l x l	X	
N	Primary Emissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.	x	x	x	x	
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Fa- cilities for Which Construction is Commenced After January 20, 1983.	Х		X	Х	
0	Sewage Treatment Plants	X	X	X	X	
Р	Primary Copper Smelters	X		X	X	
Q	Primary Zinc Smelters	X		X	X	
R	Primary Lead Smelters	X		X	Х	
S	Primary Aluminum Reduction Plants	Х		X	X	
T	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants	X	X	X	Х	
U	Phosphate Fertilizer Industry: Superphosphoric Acid Plants	X	X	X	X	
V	Phosphate Fertilizer Industry: Diammonium Phosphate Plants	X	X	X	X	
W X	Phosphate Fertilizer Industry: Triple Superphosphate Plants	X	X	X	X	
Υ	Coal Preparation Plants	X	X	x	X	
Z	Ferroalloy Production Facilities	X		x	Χ	
4A 	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.	X	Х	X	X	
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.	X		X	X	
BB	Kraft pulp Mills	X X		X	X X	
CC DD	Glass Manufacturing Plants	X		X	X	
EE	Grain Elevators	X		x	x	
EE FF	(Reserved).	^		^	^	
GG	Stationary Gas Turbines	Х		x	Х	
HH	Lime Manufacturing Plants	X		l â l	x	
KK	Lead-Acid Battery Manufacturing Plants	x			x	
LL	Metallic Mineral Processing Plants	x		x	x	
MM	Automobile and Light Duty Trucks Surface Coating Operations	X		x	X	
NN	Phosphate Rock Plants	X		x	X	
PP	Ammonium Sulfate Manufacture	x		x	X X X X X	
oo.	Graphic Arts Industry: Publication Rotogravure Printing	X		l x l	X	
RR	Pressure Sensitive Tape and Label Surface Coating Operations	X		x	X	
SS	Industrial Surface Coating: Large Appliances	X		l â l	X	
TT	Metal Coil Surface Coating	X		x	X	
UU	Asphalt Processing and Asphalt Roofing Manufacture	X		x	Х	
VV	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.	X		x	X	

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR MODOC COUNTY AIR POLLUTION CONTROL DISTRICT, MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT, MONTEREY BAY UNIFIED AIR POLLUTION CONTROL DISTRICT—Continued

		Air pollution control agency				
	Subpart	Modoc County APCD	Mojave Desert AQMD	Monterey Bay Uni- fied APCD	North Coast Unified AQMD	
WW XX	Beverage Can Surface Coating Industry	Х		Х	Х	
AAA	New Residential Wool Heaters	l x		x	Х	
BBB CCC	Rubber Tire Manufacturing Industry	Х		Х	Х	
DDD	Volatile Organic Compounds (VOC) Emissions from the Polymer manufacturing Industry.	X		Х		
EEE	(Reserved).					
FFF	Flexible Vinyl and Urethane Coating and Printing	X		X	Х	
GGG	Equipment Leaks of VOC in Petroleum Refineries	X		X	X	
HHH	Synthetic Fiber Production Facilities Volatile Organic Compound (VOC) Emissions From the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.	X		Х	Х	
JJJ	Petroleum Dry Cleaners	l x		X	X	
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.	X		Х	Х	
LLL	Onshore Natural Gas Processing: SO2 Emissions	X		X	X	
MMM	(Reserved).					
NNN	Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Operations.	X		Х		
000	Nonmetallic Mineral Processing Plants	X		X	X	
PPP	Wool Fiberglass Insulation Manufacturing Plants	X		X	X	
QQQ RRR	VOC Emissions From Petroleum Refinery Wastewater Systems Volatile Organic Compound Emissions from Synthetic Organic	X		X	Х	
SSS	Chemical Manufacturing Industry (SOCMI) Reactor Processes.  Magnetic Tape Coating Facilities	x		x	X	
TTT	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.	x		x	x	
UUU	Calciners and Dryers in Mineral Industries			x		
VVV WWW	Polymeric Coating of Supporting Substrates Facilities			X	X	

(vi) Delegations for Northern Sierra Air Quality Management District, Northern Sonoma County Air Pollution Control District, Placer County

Air Pollution Control District, and Sacramento Metropolitan Air Quality Management District are shown in the following table:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR NORTHERN SIERRA AIR QUALITY MANAGEMENT DISTRICT, NORTHERN SONOMA COUNTY AIR POLLUTION CONTROL DISTRICT, PLACER COUNTY AIR POLLUTION CONTROL DISTRICT, AND SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT

		A	Air pollution control agency				
	Subpart	Northern Sierra AQMD	Northern Sonoma County APCD	Placer County APCD	Sac- ramento Metropoli- tan AQMD		
A	General Provisions		Х		Х		
D	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971.		X		×		
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.		X		×		
Db	Industrial-Commercial-Institutional Steam Generating Units				×		
Dc	Small Industrial Steam Generating Units				X		
E	Incinerators	l	X		l x		

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR NORTHERN SIERRA AIR QUALITY MANAGEMENT DISTRICT, NORTHERN SONOMA COUNTY AIR POLLUTION CONTROL DISTRICT, PLACER COUNTY AIR POLLUTION CONTROL DISTRICT, AND SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT—Continued

		Air pollution control agency			
	Subpart	Northern Sierra AQMD	Northern Sonoma County APCD	Placer County APCD	Sac- ramento Metropoli- tan AQMD
Ea	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.				Х
Eb	Municipal Waste Combustors Constructed After September 20, 1994.				X
Ec	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.				x
F	Portland Cement Plants		X		X
G	Nitric Acid Plants		X		X
H	Sulfuric Acid Plants		X		X
<u> </u>	Hot Mix Asphalt Facilities		X		X
J	Petroleum Refineries		X		X X
K	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.		X		, x
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.		X		X
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.				X
1	Secondary Lead Smelters		Х		x
M	Secondary Brass and Bronze Production Plants		x		l x
N	Primary Emissions from Basic Oxygen Process Furnaces for Which		X		l x
••	Construction is Commenced After June 11, 1973.		,		^
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Fa- cilities for Which Construction is Commenced After January 20, 1983.				×
0	Sewage Treatment Plants		X		l x
P	Primary Copper Smelters		X		X
Q	Primary Zinc Smelters		X		X
R	Primary Lead Smelters		X		X
S	Primary Aluminum Reduction Plants		X		X
T	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants		X		X
U	Phosphate Fertilizer Industry: Superphosphoric Acid Plants		X		X
V	Phosphate Fertilizer Industry: Diammonium Phosphate Plants		X		X
W X	Phosphate Fertilizer Industry: Triple Superphosphate Plants		X		X
Υ	Coal Preparation Plants		X		X
Z	Ferroalloy Production Facilities		X		X
AA	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.		X		×
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.				X
BB	Kraft pulp Mills		X		X
CC	Glass Manufacturing Plants		X		X
DD	Grain Elevators		Х		X
EE FF	Surface Coating of Metal Furniture				X
GG	Stationary Gas Turbines		X		X
HH KK	Lime Manufacturing Plants		X		X X
KK LL	Lead-Acid Battery Manufacturing Plants				X
MM	Automobile and Light Duty Trucks Surface Coating Operations		X		l â
NN	Phosphate Rock Plants				l x
PP	Ammonium Sulfate Manufacture		Χ		î
QQ	Graphic Arts Industry: Publication Rotogravure Printing				x
RR	Pressure Sensitive Tape and Label Surface Coating Operations				x x
SS	Industrial Surface Coating: Large Appliances				x x
TT	Metal Coil Surface Coating				X
UU	Asphalt Processing and Asphalt Roofing Manufacture				X
VV	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.				X

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR NORTHERN SIERRA AIR QUALITY MANAGEMENT DISTRICT, NORTHERN SONOMA COUNTY AIR POLLUTION CONTROL DISTRICT, PLACER COUNTY AIR POLLUTION CONTROL DISTRICT, AND SACRAMENTO METROPOLITAN AIR QUALITY MANAGEMENT DISTRICT—Continued

		А	ir pollution co	ontrol agenc	у
	Subpart	Northern Sierra AQMD	Northern Sonoma County APCD	Placer County APCD	Sac- ramento Metropoli- tan AQMD
WW XX	Beverage Can Surface Coating Industry				х
AAA	New Residential Wool Heaters				X
BBB	Rubber Tire Manufacturing Industry				X
CCC	(Reserved).				
DDD	Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry.				X
EEE	(Reserved).				
FFF	Flexible Vinyl and Urethane Coating and Printing				X
GGG	Equipment Leaks of VOC in Petroleum Refineries				X
HHH	Synthetic Fiber Production Facilities				X
III	Volatile Organic Compound (VOC) Emissions From the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.				X
JJJ	Petroleum Dry Cleaners				X
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.				×
LLL	Onshore Natural Gas Processing: SO2 Emissions				X
MMM	(Reserved).				
NNN	Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Operations.				X
000	Nonmetallic Mineral Processing Plants				X
PPP	Wool Fiberglass Insulation Manufacturing Plants				X
QQQ	VOC Emissions From Petroleum Refinery Wastewater Systems				X
RRR	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.				X
SSS	Magnetic Tape Coating Facilities				X
TTT	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.				×
UUU	Calciners and Dryers in Mineral Industries				l x
VVV	Polymeric Coating of Supporting Substrates Facilities				l $\hat{x}$
www	Municipal Solid Waste Landfills				l x
	1			l	

(vii) Delegations for San Diego County Air Pollution Control District, San Joaquin Valley Unified Air Pollution Control District, San Luis Obispo

County Air Pollution Control District, and Santa Barbara County Air Pollution Control District are shown in the following table:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR SAN DIEGO COUNTY AIR POLLUTION CONTROL DISTRICT, SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT, SAN LUIS OBISPO COUNTY AIR POLLUTION CONTROL DISTRICT, AND SANTA BARBARA COUNTY AIR POLLUTION CONTROL DISTRICT

		Ai	r Pollution C	ontrol Agenc	у
	Subpart	San Diego County APCD	San Joa- quin Val- ley Unified APCD	San Luis Obispo County APCD	Santa Barbara County APCD
Α	General Provisions	х	Х	х	Х
D	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971.	×	X	×	×
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.	×	X	×	×
Db	Industrial-Commercial-Institutional Steam Generating Units	X	X	×	×
Dc	Small Industrial Steam Generating Units	Х	Х	X	

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR SAN DIEGO COUNTY AIR POLLUTION CONTROL DISTRICT, SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT, SAN LUIS OBISPO COUNTY AIR POLLUTION CONTROL DISTRICT, AND SANTA BARBARA COUNTY AIR POLLUTION CONTROL DISTRICT—Continued

		Air Pollution Control Agency				
	Subpart	San Diego County APCD	San Joa- quin Val- ley Unified APCD	San Luis Obispo County APCD	Santa Barbara County APCD	
E	Incinerators	Х	Х	Х	Х	
Ea	Municipal Waste Combustors Constructed After December 20,	X	X	X		
Eb	1989, and On or Before September 20, 1994. Municipal Waste Combustors Constructed After September 20,	Х	Х			
Ec	1994. Hospital/Medical/Infectious Waste Incinerators for Which Construc-	X				
F	tion is Commenced After June 20, 1996. Portland Cement Plants	Х	х	x		
Ġ	Nitric Acid Plants	X	x	l â		
H	Sulfuric Acid Plants	X	X	X		
ï	Hot Mix Asphalt Facilities	X	X	X	X	
J	Petroleum Refineries	X	X	x	X	
Ja	Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After May 14, 2007.					
K	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.	Х	X	X	X	
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.	Х	Х	X	X	
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.	X	Х	X	X	
L	Secondary Lead Smelters	X	X	X	Х	
M	Secondary Brass and Bronze Production Plants	X	X	X	X	
N	Primary Emissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.	X	X	X		
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Fa- cilities for Which Construction is Commenced After January 20, 1983.	Х	Х	X		
0	Sewage Treatment Plants	X	X	x	X	
P	Primary Copper Smelters	X	X	X		
Q	Primary Zinc Smelters	X	X	X		
R	Primary Lead Smelters	Χ	X	X		
S	Primary Aluminum Reduction Plants	Х	X	X		
T	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants	X	X	X		
U	Phosphate Fertilizer Industry: Superphosphoric Acid Plants	X	X	X		
V W	Phosphate Fertilizer Industry: Diammonium Phosphate Plants	X X	X	X X		
X	Phosphate Fertilizer Industry: Triple Superphosphate Plants	x	x	x		
Υ	Coal Preparation Plants	X	X	X		
Z	Ferroalloy Production Facilities	X	X	X		
AA	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974, and On or Before August 17, 1983.	Х	X	X		
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.	Х	X	X		
BB	Kraft pulp Mills	Х	X	X		
CC	Glass Manufacturing Plants	X	X	X	X	
DD	Grain Elevators	X	X	X	X	
EE	Surface Coating of Metal Furniture	X	X	X		
FF GG	(Reserved).	Х	X	x	×	
HH	Stationary Gas Turbines  Lime Manufacturing Plants	X	X	x	_ ^	
KK	Lead-Acid Battery Manufacturing Plants	X	x	x		
LL	Metallic Mineral Processing Plants	X	x	x		
MM	Automobile and Light Duty Trucks Surface Coating Operations	X	X	x		
NN	Phosphate Rock Plants	X	X	X		
PP	Ammonium Sulfate Manufacture	Χ	X	X		
QQ	Graphic Arts Industry: Publication Rotogravure Printing	Χ	X	X		
RR	Pressure Sensitive Tape and Label Surface Coating Operations	Χ	X	X		
SS	Industrial Surface Coating: Large Appliances	Х	X	X		
TT	Metal Coil Surface Coating	X	X	X	l	

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR SAN DIEGO COUNTY AIR POLLUTION CONTROL DISTRICT, SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT, SAN LUIS OBISPO COUNTY AIR POLLUTION CONTROL DISTRICT—Continued

		Air Pollution Control Agency				
	Subpart	San Diego County APCD	San Joa- quin Val- ley Unified APCD	San Luis Obispo County APCD	Santa Barbara County APCD	
UU VV	Asphalt Processing and Asphalt Roofing Manufacture Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.	X X	X X	X X		
VVa	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.					
WW XX	Beverage Can Surface Coating Industry	х	Х	X		
AAA BBB CCC	New Residential Wool Heaters  Rubber Tire Manufacturing Industry (Reserved).	X	X	X	X	
DDD	Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry.	х	х			
EEE FFF	(Reserved).   Flexible Vinyl and Urethane Coating and Printing	x	Х	x		
GGG	Equipment Leaks of VOC in Petroleum Refineries	x	x	x		
GGGa	Equipment Leaks of VOC in Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.	^	^	^		
HHH	Synthetic Fiber Production Facilities	X	X	X		
III	Volatile Organic Compound (VOC) Emissions From the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.	X	X			
JJJ	Petroleum Dry Cleaners	X	X	X		
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.	X	X	X		
LLL	Onshore Natural Gas Processing: SO2 Emissions	X	Х	X		
MMM NNN	(Reserved). Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Operations.	x	Х			
000	Nonmetallic Mineral Processing Plants	X	X	X	X	
PPP	Wool Fiberglass Insulation Manufacturing Plants	X	X	X		
QQQ RRR	VOC Emissions From Petroleum Refinery Wastewater Systems Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.	X	X	X		
SSS	Magnetic Tape Coating Facilities	X	X	X		
TTT	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.	X	X	X		
UUU	Calciners and Dryers in Mineral Industries	X	X	X	X	
VVV WWW	Polymeric Coating of Supporting Substrates Facilities	X	X	X	X X	
AAAA	Small Municipal Waste Combustion Units for Which Construction is Commenced After August 30, 1999, or for Which Modification or Reconstruction is Commenced After June 6, 2001.	x	^	^	^	
CCCC	Commercial and Industrial Solid Waste Incineration Units for Which Construction Is Commenced After November 30, 1999, or for Which Modification or Reconstruction Is Commenced on or After June 1, 2001.	X				
EEEE	Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Commenced on or After June 16, 2006.	X				
GGGG IIII JJJJ	(Reserved). Stationary Compression Ignition Internal Combustion Engines. Stationary Spark Ignition Internal Combustion Engines.					
KKKK	Stationary Combustion Turbines					

(viii) Delegations for Shasta County Siskiyou County Air Pollution Control Air Quality Management District,

District, South Coast Air Quality Management District, and Tehama County shown in the following table:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR SHASTA COUNTY AIR QUALITY MANAGEMENT DISTRICT, SISKIYOU COUNTY AIR POLLUTION CONTROL DISTRICT, SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, AND TEHAMA COUNTY AIR POLLUTION CONTROL DISTRICT

		Air Pollution Control Agency			
	Subpart	Shasta County AQMD	Siskiyou County APCD	South Coast AQMD	Tehama County APCD
A D	General Provisions	X X	X X	X X	X X
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.	X	x	Χ	X
Db	Industrial-Commercial-Institutional Steam Generating Units	X	x	Χ	X
Dc	Small Industrial Steam Generating Units	X	X	Χ	X
E	Incinerators		X	X	X
Ea 	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.		Х	X	X
Eb	Municipal Waste Combustors Constructed After September 20, 1994.	Х		Х	
Ec	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.	Х			
F	Portland Cement Plants		X	X	X
G	Nitric Acid Plants		X	X	X
Н	Sulfuric Acid Plants		X	Х	X
1	Hot Mix Asphalt Facilities	X	X	Х	X
J	Petroleum Refineries	X	X	Х	X
Ja	Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After May 14, 2007.				
K	Storage Vessels for Petroleum Liquids for Which Construction, Re- construction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.	Х	Х	Х	X
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978,	Х	х	Х	X
Kb	and Prior to July 23, 1984.  Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.	Х	х	Х	х
L	Secondary Lead Smelters	X	X	X	X
M	Secondary Brass and Bronze Production Plants	Х	X	X	X
N	Primary Emissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.		X	X	X
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Fa- cilities for Which Construction is Commenced After January 20, 1983.		Х	Х	X
0	Sewage Treatment Plants	X	X	X	X
Р	Primary Copper Smelters	X	X	X	X X X X X X
Q	Primary Zinc Smelters		X	X	X
R	Primary Lead Smelters		X	X	X
S	Primary Aluminum Reduction Plants		X	X	X
T	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants		X	X	X
U	Phosphate Fertilizer Industry: Superphosphoric Acid Plants		X	Χ	X
V	Phosphate Fertilizer Industry: Diammonium Phosphate Plants		X	Х	X
W X	Phosphate Fertilizer Industry: Triple Superphosphate Plants		X X	X X	X
Y	age Facilities. Coal Preparation Plants		х	X	X
Z AA	Ferroalloy Production Facilities		X	X	X
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.		х	Х	X
BB	Kraft pulp Mills		x	Х	X
CC	Glass Manufacturing Plants	X	ı î	X	l x
DD	Grain Elevators	x	l â l	X	x
EE	Surface Coating of Metal Furniture		l  î	X	x x
FF	(Reserved).			•	
GG	Stationary Gas Turbines	X	x	Χ	X
HH	Lime Manufacturing Plants	X	x	Χ	X
KK	Lead-Acid Battery Manufacturing Plants	l	x	Χ	X

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR SHASTA COUNTY AIR QUALITY MANAGEMENT DISTRICT, SISKIYOU COUNTY AIR POLLUTION CONTROL DISTRICT, SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, AND TEHAMA COUNTY AIR POLLUTION CONTROL DISTRICT—Continued

		Air Pollution Control Agency			
	Subpart	Shasta County AQMD	Siskiyou County APCD	South Coast AQMD	Tehama County APCD
LL	Metallic Mineral Processing Plants		Х	х	Х
MM	Automobile and Light Duty Trucks Surface Coating Operations		X	X	X
NN	Phosphate Rock Plants		X	X	X
PP QQ	Ammonium Sulfate Manufacture		X X	X X	X
RR	Pressure Sensitive Tape and Label Surface Coating Operations		X	x̂	Ŷ
SS	Industrial Surface Coating: Large Appliances		X	x	x
TT	Metal Coil Surface Coating		X	×	X X X X
UU	Asphalt Processing and Asphalt Roofing Manufacture		X	X	X
VV VVa	Equipment Leaks of VOC in the Synthetic Organic Chemicals Man- ufacturing Industry.  Equipment Leaks of VOC in the Synthetic Organic Chemicals Man-		Х	X	X
***	ufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.				
WW XX	Beverage Can Surface Coating Industry		X	X	X
AAA	New Residential Wool Heaters	x	X	×	X
BBB	Rubber Tire Manufacturing Industry		Χ	X	X
CCC	(Reserved).				
DDD	Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry. (Reserved).		Х		X
FFF	Flexible Vinyl and Urethane Coating and Printing	l	Х	X	x
GGG	Equipment Leaks of VOC in Petroleum Refineries		X	X	X
GGGa	Equipment Leaks of VOC in Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.				
HHH	Synthetic Fiber Production Facilities		X	×	X
III	Volatile Organic Compound (VOC) Emissions From the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.		Х	X	X
JJJ	Petroleum Dry Cleaners		X	X	Х
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.		Χ	×	X
LLL	Onshore Natural Gas Processing: SO <sub>2</sub> Emissions		Х	X	X
MMM NNN	(Reserved).  Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Op-		Х		x
	erations.				
000	Nonmetallic Mineral Processing Plants	X	X	X	X
PPP	Wool Fiberglass Insulation Manufacturing Plants		X	X	X
QQQ	VOC Emissions From Petroleum Refinery Wastewater Systems		X	X	X
RRR	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.  Magnetic Tape Coating Facilities		X X	X X	x x
TTT	Industrial Surface Coating: Surface Coating of Plastic Parts for		X	x	x
	Business Machines.		• •		
UUU	Calciners and Dryers in Mineral Industries	X	X X	X X	X X
WWW	Polymeric Coating of Supporting Substrates Facilities  Municipal Solid Waste Landfills	^	X	x	x
AAAA	Small Municipal Waste Combustion Units for Which Construction is Commenced After August 30, 1999 or for Which Modification or	Х	X	^	^
CCCC	Reconstruction is Commended After June 6, 2001. Commercial and Industrial Solid Waste Incineration Units for Which Construction Is Commenced After November 30, 1999 or for Which Modification or Reconstruction Is Commenced on or After	х			
EEEE	June 1, 2001. Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Commenced on or After June 16, 2006.	х			
GGGG	(Reserved).				
IIII JJJJ KKKK	Stationary Compression Ignition Internal Combustion Engines. Stationary Spark Ignition Internal Combustion Engines. Stationary Combustion Turbines.				

(ix) Delegations for Tuolumne County Air Pollution Control District, Ventura County Air Pollution Control Dis-

trict, and Yolo-Solano Air Quality Management District are shown in the following table:

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR TUOLUMNE COUNTY AIR POLLUTION CONTROL DISTRICT, VENTURA COUNTY AIR POLLUTION CONTROL DISTRICT, AND YOLO-SOLANO AIR QUALITY MANAGEMENT DISTRICT

		Air Pollution Control Agency			
	Subpart	Tuolumne County APCD	Ventura Coun- ty APCD	Yolo-Solano AQMD	
Α	General Provisions	x	X		
D	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971.	x	x		
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.	Х			
Db	Industrial-Commercial-Institutional Steam Generating Units	X	X		
Dc	Small Industrial Steam Generating Units	X			
E	Incinerators	X			
Ea	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.	X			
Eb -	Municipal Waste Combustors Constructed After September 20, 1994.	X			
Ec	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.	X			
F	Portland Cement Plants	X			
G	Nitric Acid Plants	X			
H	Sulfuric Acid Plants	X			
l.	Hot Mix Asphalt Facilities	X	X		
J Ja	Petroleum Refineries Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After May 14, 2007.	X	X		
K	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.	Х	X		
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.	X			
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.	×			
L	Secondary Lead Smelters	l x			
M	Secondary Brass and Bronze Production Plants	X			
N	Primary Emissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.	X			
Na	Secondary Emissions from Basic Oxygen Process Steelmaking Facilities for Which Construction is Commenced After January 20, 1983.	Х			
0	Sewage Treatment Plants	X			
P	Primary Copper Smelters	X			
Q	Primary Zinc Smelters	X			
R	Primary Lead Smelters	X			
S	Primary Aluminum Reduction Plants	X			
Т	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants.	X			
U	Phosphate Fertilizer Industry: Superphosphoric Acid Plants	X			
V	Phosphate Fertilizer Industry: Diammonium Phosphate Plants	X			
W X	Phosphate Fertilizer Industry: Triple Superphosphate Plants Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities.	X X			
Υ	Coal Preparation Plants	×			
ż	Ferroalloy Production Facilities	l			
AA	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.	x	x		
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.	х			
BB	Kraft pulp Mills	X			
CC	Glass Manufacturing Plants	X			
DD	Grain Elevators	X			
EE	Surface Coating of Metal Furniture	X			
FF	(Reserved).	l			
GG	Stationary Gas Turbines	X			
HH	Lime Manufacturing Plants	l X			

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR TUOLUMNE COUNTY AIR POLLUTION CONTROL DISTRICT, VENTURA COUNTY AIR POLLUTION CONTROL DISTRICT, AND YOLO-SOLANO AIR QUALITY MANAGEMENT DISTRICT—Continued

LL MM NN PP QQ RR SS TT	Subpart  Lead-Acid Battery Manufacturing Plants	Tuolumne County APCD  X X X X X X X X X X X X X X X X	Ventura County APCD	Yolo-Soland AQMD
LL MM NN PP QQ RR SS TT	Metallic Mineral Processing Plants Automobile and Light Duty Trucks Surface Coating Operations Phosphate Rock Plants Ammonium Sulfate Manufacture Graphic Arts Industry: Publication Rotogravure Printing Pressure Sensitive Tape and Label Surface Coating Operations			
MM NN PP QQ RR SS IT	Automobile and Light Duty Trucks Surface Coating Operations Phosphate Rock Plants	X X X		
NN PP QQ RR SS IT JU	Phosphate Rock Plants Ammonium Sulfate Manufacture Graphic Arts Industry: Publication Rotogravure Printing Pressure Sensitive Tape and Label Surface Coating Operations	X X X		
PP QQ RR SS T	Ammonium Sulfate Manufacture	X X		
QQ RR SS TT JU	Graphic Arts Industry: Publication Rotogravure Printing	X	i	
RR SS T JU	Pressure Sensitive Tape and Label Surface Coating Operations			
SS T JU		\ \tag{2}		
T JU		\ \frac{\chi}{\chi}		
JU	Metal Coil Surface Coating	x		
	Asphalt Processing and Asphalt Roofing Manufacture	l		
	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.	x		
/Va	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.			
	Beverage Can Surface Coating Industry	Х		
	New Residential Wood Heaters	X		
	Rubber Tire Manufacturing Industry(Reserved).	Х		
	Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry. (Reserved).	X		
	Flexible Vinyl and Urethane Coating and Printing	x		
	Equipment Leaks of VOC in Petroleum Refineries	l $\hat{x}$		
	Equipment Leaks of VOC in Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.			
ннн	Synthetic Fiber Production Facilities	X		
	Volatile Organic Compound (VOC) Emissions From the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.	Х		
JJJ	Petroleum Dry Cleaners	X		
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.	Х		
	Onshore Natural Gas Processing: SO2 Emissions	X		
	(Reserved).			
NNN	Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Operations.	×		
	Nonmetallic Mineral Processing Plants	X	X	
	Wool Fiberglass Insulation Manufacturing Plants	X		
	VOC Emissions From Petroleum Refinery Wastewater Systems	X		
	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.	X		
	Magnetic Tape Coating Facilities	X		
	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.	X		
	Calciners and Dryers in Mineral Industries	X X		
	Municipal Solid Waste Landfills	Â	x	
	Small Municipal Waste Combustion Units for Which Construction is Commenced After August 30, 1999 or for Which Modifica-	x	^	
cccc	tion or Reconstruction is Commenced After June 6, 2001.  Commercial and Industrial Solid Waste Incineration Units for Which Construction Is Commenced After November 30, 1999 or for Which Modification or Reconstruction Is Commenced on or After June 1, 2001.	х		
EEEE	Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Commenced on or After June 16, 2006.			
GGGG	(Reserved).			
JJJJ	Stationary Compression Ignition Internal Combustion Engines. Stationary Spark Ignition Internal Combustion Engines. Stationary Combustion Turbines			

(3) Hawaii. The following table identifies delegations for Hawaii: Delegation Status for New Source Performance Standards for Hawaii:

## DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR HAWAII

	Subpart	Hawai
4	General Provisions	Х
)	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971	X
а	Electric Utility Steam Generating Units Constructed After September 18, 1978	Х
b	Industrial-Commercial-Institutional Steam Generating Units	Х
0	Small Industrial Steam Generating Units	X
	Incinerators	X
a	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.	X
b	Municipal Waste Combustors Constructed After September 20, 1994	X
0	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.	Х
	Portland Cement Plants	Х
	Nitric Acid Plants.	
	Sulfuric Acid Plants.	.,
	Hot Mix Asphalt Facilities	X
	Petroleum Refineries	Х
1	Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After May 14, 2007.	
	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.	Х
а	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.	Х
b	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.	Х
	Secondary Lead Smelters.	
l	Secondary Brass and Bronze Production Plants.	
	Primary Emissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.	
а	Secondary Emissions from Basic Oxygen Process Steelmaking Facilities for Which Construction is Commenced After January 20, 1983.	
)	Sewage Treatment Plants	X
	Primary Copper Smelters.	
	Primary Zinc Smelters.	
	Primary Lead Smelters.	
	Primary Aluminum Reduction Plants.	
	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants.	
	Phosphate Fertilizer Industry: Superphosphoric Acid Plants.	
	Phosphate Fertilizer Industry: Diammonium Phosphate Plants.	
1	Phosphate Fertilizer Industry: Triple Superphosphate Plants.	
	Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities.	
	Coal Preparation Plants	Х
	Ferroalloy Production Facilities.	
A	Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.	Х
Aa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.	Х
В	Kraft pulp Mills.	
С	Glass Manufacturing Plants.	
D	Grain Elevators.	
E	Surface Coating of Metal Furniture.	
F	(Reserved).	
G	Stationary Gas Turbines	X
Н	Lime Manufacturing Plants.	
K	Lead-Acid Battery Manufacturing Plants.	
L.	Metallic Mineral Processing Plants.	
М	Automobile and Light Duty Trucks Surface Coating Operations.	
N	Phosphate Rock Plants.	
P	Ammonium Sulfate Manufacture.	
Q	Graphic Arts Industry: Publication Rotogravure Printing.	
R	Pressure Sensitive Tape and Label Surface Coating Operations.	
S	Industrial Surface Coating: Large Appliances.	
T.	Metal Coil Surface Coating.	
U	Asphalt Processing and Asphalt Roofing Manufacture.	
V Va	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which	Х
va	Construction, Reconstruction, or Modification Commenced After November 7, 2006.	
/W	Beverage Can Surface Coating Industry	Х
X	Bulk Gasoline Terminals	x
	Duir Gastino Tonninais	^

§ 60.4

# DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR HAWAII—Continued

	Subpart	Hawaii
BBB	Rubber Tire Manufacturing Industry.	
CCC	(Reserved).	
DDD	Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry.	
EE	(Reserved).	
FF	Flexible Vinyl and Urethane Coating and Printing.	
GG	Equipment Leaks of VOC in Petroleum Refineries	X
GGGa	Equipment Leaks of VOC in Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.	
HH	Synthetic Fiber Production Facilities.	
III	Volatile Organic Compound (VOC) Emissions From the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.	
JJ	Petroleum Dry Cleaners	X
KKK	Equipment Leaks of VOC From Onshore Natural Gas Processing Plants.	
.LL	Onshore Natural Gas Processing: SO2 Emissions.	
MMN	(Reserved).	
INN	Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Operations.	Х
000	Nonmetallic Mineral Processing Plants	X
PPP	Wool Fiberglass Insulation Manufacturing Plants.	
QQQ	VOC Emissions From Petroleum Refinery Wastewater	X
RRR	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.	
SSS	Magnetic Tape Coating Facilities.	
TT	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.	
IUU	Calciners and Dryers in Mineral Industries	X
'VV	Polymeric Coating of Supporting Substrates Facilities	X
/WW	Municipal Solid Waste Landfills	X
AAAA	Small Municipal Waste Combustion Units for Which Construction is Commenced After August 30, 1999 or for Which Modification or Reconstruction is Commenced After June 6, 2001.	X
CCCC	Commercial and Industrial Solid Waste Incineration Units for Which Construction Is Commenced After November 30, 1999 or for Which Modification or Reconstruction Is Commenced on or After June 1, 2001.	Х
EEE	Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Commenced on or After June 16, 2006.	
GGG	(Reserved).	
II	Stationary Compression Ignition Internal Combustion Engines.	
JJJ	Stationary Spark Ignition Internal Combustion Engines.	
KKK	Stationary Combustion Turbines	

# (4) Nevada. The following table identifies delegations for Nevada:

# DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR NEVADA

		Air Pollu	ition Control	Agency
	Subpart	Nevada DEP	Clark County	Washoe County
A	General Provisions	Х	Х	х
D	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971	X	X	X
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978	X		
Db	Industrial-Commercial-Institutional Steam Generating Units	X		
Dc	Small Industrial Steam Generating Units	X		
E	Incinerators	X	X	X
Ea	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.	Χ		
Eb	Municipal Waste Combustors Constructed After September 20, 1994	X		
Ec	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.	X		
F	Portland Cement Plants	X	X	l x
G	Nitric Acid Plants	X	X	
Н	Sulfuric Acid Plants	X	X	
1	Hot Mix Asphalt Facilities	X	X	X
J	Petroleum Refineries	X	X	
Ja	Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After May 14, 2007.			
K	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.	X	×	X
Ka	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.	Х	Х	X

§ 60.4

DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR NEVADA—Continued

		Air Pollu	ition Control	Agency
	Subpart	Nevada DEP	Clark County	Washoe County
Kb	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984.  Secondary Lead Smelters	x x	x	×
M	Secondary Brass and Bronze Production Plants	x	x	^
N	Primary Émissions from Basic Oxygen Process Furnaces for Which Construction is Commenced After June 11, 1973.	Х	X	
Na O	Secondary Emissions from Basic Oxygen Process Steelmaking Facilities for Which Construction is Commenced After January 20, 1983.  Sewage Treatment Plants	X X	x	x
P	Primary Copper Smelters	X	x	X
Q	Primary Zinc Smelters	X	X	X
R	Primary Lead Smelters	X	X	X
S	Primary Aluminum Reduction Plants	X	X	
T	Phosphate Fertilizer Industry: Wet Process Phosphoric Acid Plants	X	X	
U V	Phosphate Fertilizer Industry: Superphosphoric Acid Plants	X	X	
w	Phosphate Fertilizer Industry: Triple Superphosphate Plants	x	x x	
X	Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities.	Х	X	
Y	Coal Preparation Plants	X	X	X
Z AA	Ferroalloy Production Facilities Steel Plants: Electric Arc Furnaces Constructed After October 21, 1974 and On or Before August 17, 1983.	X	X	
AAa	Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 7, 1983.	Х		
BB	Kraft pulp Mills	X	X	
CC DD	Glass Manufacturing Plants	X X	X	
EE FF	Surface Coating of Metal Furniture (Reserved).	x	x	X
GG	Stationary Gas Turbines	Χ	X	X
HH	Lime Manufacturing Plants	X	X	X
KK	Lead-Acid Battery Manufacturing Plants	Χ	X	X
LL	Metallic Mineral Processing Plants	X	X	X
MM	Automobile and Light Duty Trucks Surface Coating Operations	X	X	X X
NN PP	Phosphate Rock Plants	X	X	_ ^
QQ	Graphic Arts Industry: Publication Rotogravure Printing	X	x	X
RR	Pressure Sensitive Tape and Label Surface Coating Operations	X	X	
SS	Industrial Surface Coating: Large Appliances	X	X	X
TT	Metal Coil Surface Coating	X	X	X
VV VV	Asphalt Processing and Asphalt Roofing Manufacture	X	X	X
VVa	Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006.			
WW	Beverage Can Surface Coating Industry	Х	X	
XX	Bulk Gasoline Terminals	X	X	
AAA	New Residential Wool Heaters.			
BBB	Rubber Tire Manufacturing Industry	Х		
DDD	(Reserved).  Volatile Organic Compounds (VOC) Emissions from the Polymer Manufacturing Industry.	X		
EEE	(Reserved).			
FFF	Flexible Vinyl and Urethane Coating and Printing	X	X	
GGG GGGa	Equipment Leaks of VOC in Petroleum Refineries	Х	X	
HHH III	Synthetic Fiber Production Facilities	X X	x	
	Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes.	v		
JJJ KKK	Petroleum Dry Cleaners  Equipment Leaks of VOC From Onshore Natural Gas Processing Plants	X X	X	X
LLL	Onshore Natural Gas Processing: SO2 Emissions	X		
MMM	(Reserved).	^		
NNN	Volatile Organic Compound (VOC) Emissions From Synthetic Organic Chemical Manufacturing Industry (SOCMI) Distillation Operations.	Х		
000	Nonmetallic Mineral Processing Plants	X	l x	1

## DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR NEVADA—Continued

		Air Pollu	tion Control	Agency
	Subpart	Nevada DEP	Clark County	Washoe County
PPP	Wool Fiberglass Insulation Manufacturing Plants	Х	Х	
QQQ	VOC Emissions From Petroleum Refinery Wastewater Systems	X		
RRR	Volatile Organic Compound Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes.	X		
SSS	Magnetic Tape Coating Facilities	X		
TTT	Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines.	X		
UUU	Calciners and Dryers in Mineral Industries	X		
VVV	Polymeric Coating of Supporting Substrates Facilities	X		
www	Municipal Solid Waste Landfills	X		
AAAA	Small Municipal Waste Combustion Units for Which Construction is Commenced After August 30, 1999 or for Which Modification or Reconstruction is Commended After June 6, 2001.	Х		
CCCC	Commercial and Industrial Solid Waste Incineration Units for Which Construc- tion Is Commenced After November 30, 1999 or for Which Modification or Reconstruction Is Commenced on or After June 1, 2001.	Х		
EEEE	Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Com- menced on or After June 16, 2006.	Х		
GGGG	(Reserved).			
Ш	Stationary Compression Ignition Internal Combustion Engines	X		
JJJJ	Stationary Spark Ignition Internal Combustion Engines	X		
KKKK	Stationary Combustion Turbines	Χ		

(5) Guam. The following table identifies delegations as of June 15, 2001:

# DELEGATION STATUS FOR NEW SOURCE PERFORMANCE STANDARDS FOR GUAM

	Subpart	Guam
A	General Provisions	X
D	Fossil-Fuel Fired Steam Generators Constructed After August 17, 1971.	X
Da	Electric Utility Steam Generating Units Constructed After September 18, 1978.	
Db	Industrial-Commercial-Institutional Steam Generating Units.	
Dc	Small Industrial Steam Generating Units.	
E	Incinerators.	
Ea	Municipal Waste Combustors Constructed After December 20, 1989 and On or Before September 20, 1994.	
Eb	Municipal Waste Combustors Constructed After September 20, 1994.	
Ec	Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996.	
F	Portland Cement Plants	X
G	Nitric Acid Plants.	
Н	Sulfuric Acid Plants.	
1	Hot Mix Asphalt Facilities	X
J	Petroleum Refineries	X
K	Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978.	Х

- (e) The following lists the specific part 60 standards that have been delegated unchanged to the air pollution control agencies in Region 6.
- (1) New Mexico. The New Mexico Environment Department has been delegated all part 60 standards promulgated by EPA, except subpart AAA—Standards of Performance for New Res-
- idential Wood Heaters, as amended in the FEDERAL REGISTER through September 1, 2002.
- (2) Louisiana. The Louisiana Department of Environmental Quality has been delegated all part 60 standards promulgated by EPA, except subpart AAA—Standards for Performance for New Residential Wood Heaters, as

amended in the Federal Register through July 1, 2008.

# DELEGATION STATUS FOR PART 60 STANDARDS—STATE OF LOUISIANA

Subpart	Source category	LDEQ1
Α	General Provisions	Yes.
)	Fossil Fueled Steam Generators (>250 MM BTU/hr). Including amendments issued Jan-	Yes.
	uary 28, 2009. (74 FR 5072).	100.
Da	Electric Utility Steam Generating Units (>250 MM BTU/hr). Including amendments issued January 28, 2009. (74 FR 5072).	Yes.
Ob	Industrial-Commercial-Institutional Steam Generating Units (100 to 250 MM BTU/hr). Including amendments issued January 28, 2009. (74 FR 5072).	Yes.
Oc	Industrial-Commercial-Institutional Small Steam Generating Units (10 to 100 MM BTU/hr). Including amendments issued January 28, 2009. (74 FR 5072).	Yes.
·	Incinerators (>50 tons per day). Including amendments issued January 28, 2009. (74 FR 5072).	Yes.
a	Municipal Waste Combustors	Yes.
b	Large Municipal Waste Combustors	Yes.
ic	Hospital/Medical/Infectious Waste Incinerators	Yes.
	Portland Cement Plants	Yes.
ì	Nitric Acid Plants	Yes.
l	Sulfuric Acid Plants	Yes.
	Hot Mix Asphalt Facilities	Yes.
	Petroleum Refineries	Yes.
a	Petroleum Refineries (After May 14, 2007). Including amendments issued July 28, 2008. (73 FR 43626).	Yes.
·	Storage Vessels for Petroleum Liquids (After 6/11/73 & Before 5/19/78)	Yes.
(a	Storage Vessels for Petroleum Liquids (After 6/11/73 & Before 5/19/78)	Yes.
(b	Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Stg/Vessels) After 7/23/84.	Yes.
	Secondary Lead Smelters	Yes.
1	Secondary Brass and Bronze Production Plants	Yes.
l	Primary Emissions from Basic Oxygen Process Furnaces (Construction Commenced After June 11, 1973).	Yes.
a	Secondary Emissions from Basic Oxygen Process Steelmaking Facilities Construction is Commenced After January 20, 1983.	Yes.
)	Sewage Treatment Plants	Yes.
	Primary Copper Smelters	Yes.
)	Primary Zinc Smelters	Yes.
l	Primary Lead Smelters	Yes.
	Primary Aluminum Reduction Plants	Yes.
	Phosphate Fertilizer Industry: Wet Process Phosphoric Plants	Yes.
	Phosphate Fertilizer Industry: Superphosphoric Acid Plants	Yes.
	Phosphate Fertilizer Industry: Diammonium Phosphate Plants	Yes.
V	Phosphate Fertilizer Industry: Triple Superphosphate Plants	Yes.
, ,	Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities	Yes.
	Coal Preparation Plants	Yes.
	Ferroalloy Production Facilities	Yes.
A Aa	Steel Plants: Electric Arc Furnaces After 10/21/74 & On or Before 8/17/83 Steel Plants: Electric Arc Furnaces & Argon-Oxygen Decarburization Vessels After 8/07/	Yes. Yes.
_	83.	
B	Kraft Pulp Mills	Yes.
C	Glass Manufacturing Plants	Yes.
D	Grain Elevators	Yes.
E	Surface Coating of Metal Furnature	Yes.
iG	Stationary Gas Turbines	Yes.
IH	Lime Manufacturing Plants	Yes.
K	Lead-Acid Battery Manufacturing Plants	Yes.
L	Metallic Mineral Processing Plants	Yes.
1M	Automobile & Light Duty Truck Surface Coating Operations	Yes.
N	Phosphate Manufacturing Plants	Yes.
P	Ammonium Sulfate Manufacture	Yes.
Q	Graphic Arts Industry: Publication Rotogravure Printing	Yes.
R	Pressure Sensitive Tape and Label Surface Coating Operations	Yes.
S	Industrial Surface Coating: Large Appliances	Yes.
Τ	Metal Coil Surface Coating	Yes.
U	Asphalt Processing and Asphalt Roofing Manufacture	Yes.
/V	VOC Equipment Leaks in the SOCMI Industry	Yes.
'Va	VOC Equipment Leaks in the SOCMI Industry (After November 7, 2006)	Yes.
(X	Bulk Gasoline Terminals	Yes.
AA	New Residential Wood Heaters	No
BB	Rubber Tire Manufacturing Industry	Yes.
DD	Volatile Organic Compound (VOC) Emissions from the Polymer Manufacturing Industry	Yes.
FF	Flexible Vinyl and Urethane Coating and Printing	Yes.

DELEGATION STATUS FOR PART 60 STANDARDS—STATE OF LOUISIANA—Continued

Subpart	Source category	LDEQ1
GGG	VOC Equipment Leaks in Petroleum Refineries	Yes.
HHH	Synthetic Fiber Production	Yes.
III	VOC Emissions from the SOCMI Air Oxidation Unit Processes	Yes.
JJJ	Petroleum Dry Cleaners	Yes.
KK	VOC Equipment Leaks From Onshore Natural Gas Processing Plants	Yes.
LL	Onshore Natural Gas Processing: SO2 Emissions	Yes.
NN	VOC Emissions from SOCMI Distillation Operations	Yes.
000	Nonmetallic Mineral Processing Plants	Yes.
PP	Wool Fiberglass Insulation Manufacturing Plants	Yes.
QQQ	VOC Emissions From Petroleum Refinery Wastewater Systems	Yes.
RRR	VOC Emissions from SOCMI Reactor Processes	Yes.
SSS	Magnetic Tape Coating Operations	Yes.
TT	Industrial Surface Coating: Plastic Parts for Business Machines	Yes.
JUU	Calciners and Dryers in Mineral Industries	Yes.
/VV	Polymeric Coating of Supporting Substrates Facilities	Yes.
VWW	Municipal Solid Waste Landfills	Yes.
AAA	Small Municipal Waste Combustion Units (Construction is Commenced After 8/30/99 or Modification/Reconstruction is Commenced After 6/06/2001).	Yes.
CCCC	Commercial & Industrial Solid Waste Incineration Units (Construction is Commenced After 11/30/1999 or Modification/Reconstruction is Commenced on or After 6/01/2001).	Yes.
EEEE	Other Solid Waste Incineration Units (Constructed after 12/09/2004 or Modicatation/Reconstruction is commenced on or after 06/16/2004).	Yes.
III	Stationary Compression Ignition Internal Combustion Engines	Yes.
JJJ	Stationary Spark Ignition Internal Combustion Engines. Including amendments issued October 8, 2008. (73 FR 59175).	Yes.
KKK	Stationary Combustion Turbines (Construction Commenced After 02/18/2005)	Yes

<sup>&</sup>lt;sup>1</sup> The Louisiana Department of Environmental Quality (LDEQ) has been delegated all Part 60 standards promulgated by EPA, except subpart AAA—Standards of Performance for New Residential Wood Heaters—as amended in the **Federal Register** through July 1, 2008.

(3) Albuquerque-Bernalillo County Air Quality Control Board. The Albuquerque-Bernalillo County Air Quality Control Board has been delegated all part 60 standards promulgated by EPA, except Subpart AAA—Standards of Performance for New Residential Wood Heaters; Subpart WWW—Standards of Performance for Municipal Solid Waste Landfills; Subpart Cc—Emissions Guidelines and Compliance Times for Municipal Solid Waste Landfills, as amended in the FEDERAL REGISTER through July 1, 2004.

[40 FR 18169, Apr. 25, 1975]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §60.4 see the List of CFR Sections Affected which appears in the Finding Aids section of the printed volume and on GPO Access.

# § 60.5 Determination of construction or modification.

(a) When requested to do so by an owner or operator, the Administrator will make a determination of whether action taken or intended to be taken by such owner or operator constitutes construction (including reconstruction) or modification or the commencement

thereof within the meaning of this part.

(b) The Administrator will respond to any request for a determination under paragraph (a) of this section within 30 days of receipt of such request.

[40 FR 58418, Dec. 16, 1975]

# § 60.6 Review of plans.

- (a) When requested to do so by an owner or operator, the Administrator will review plans for construction or modification for the purpose of providing technical advice to the owner or operator.
- (b)(1) A separate request shall be submitted for each construction or modification project.
- (2) Each request shall identify the location of such project, and be accompanied by technical information describing the proposed nature, size, design, and method of operation of each affected facility involved in such project, including information on any equipment to be used for measurement or control of emissions.
- (c) Neither a request for plans review nor advice furnished by the Administrator in response to such request shall

(1) relieve an owner or operator of legal responsibility for compliance with any provision of this part or of any applicable State or local requirement, or (2) prevent the Administrator from implementing or enforcing any provision of this part or taking any other action authorized by the Act.

[36 FR 24877, Dec. 23, 1971, as amended at 39 FR 9314, Mar. 8, 1974]

#### § 60.7 Notification and record keeping.

- (a) Any owner or operator subject to the provisions of this part shall furnish the Administrator written notification or, if acceptable to both the Administrator and the owner or operator of a source, electronic notification, as follows:
- (1) A notification of the date construction (or reconstruction as defined under §60.15) of an affected facility is commenced postmarked no later than 30 days after such date. This requirement shall not apply in the case of mass-produced facilities which are purchased in completed form.
  - (2) [Reserved]
- (3) A notification of the actual date of initial startup of an affected facility postmarked within 15 days after such date
- (4) A notification of any physical or operational change to an existing facility which may increase the emission rate of any air pollutant to which a standard applies, unless that change is specifically exempted under an applicable subpart or in §60.14(e). This notice shall be postmarked 60 days or as soon as practicable before the change is commenced and shall include information describing the precise nature of the change, present and proposed emission control systems, productive capacity of the facility before and after the change, and the expected completion date of the change. The Administrator may request additional relevant information subsequent to this notice.
- (5) A notification of the date upon which demonstration of the continuous monitoring system performance commences in accordance with §60.13(c). Notification shall be postmarked not less than 30 days prior to such date.
- (6) A notification of the anticipated date for conducting the opacity observations required by §60.11(e)(1) of this

- part. The notification shall also include, if appropriate, a request for the Administrator to provide a visible emissions reader during a performance test. The notification shall be postmarked not less than 30 days prior to such date.
- (7) A notification that continuous opacity monitoring system data results will be used to determine compliance with the applicable opacity standard during a performance test required by §60.8 in lieu of Method 9 observation data as allowed by §60.11(e)(5) of this part. This notification shall be postmarked not less than 30 days prior to the date of the performance test.
- (b) Any owner or operator subject to the provisions of this part shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative.
- (c) Each owner or operator required to install a continuous monitoring device shall submit excess emissions and monitoring systems performance report (excess emissions are defined in applicable subparts) and-or summary report form (see paragraph (d) of this section) to the Administrator semiannually, except when: more frequent reporting is specifically required by an applicable subpart; or the Administrator, on a case-by-case basis, determines that more frequent reporting is necessary to accurately assess the compliance status of the source. All reports shall be postmarked by the 30th day following the end of each sixmonth period. Written reports of excess emissions shall include the following information:
- (1) The magnitude of excess emissions computed in accordance with §60.13(h), any conversion factor(s) used, and the date and time of commencement and completion of each time period of excess emissions. The process operating time during the reporting period.
- (2) Specific identification of each period of excess emissions that occurs during startups, shutdowns, and malfunctions of the affected facility. The

nature and cause of any malfunction (if known), the corrective action taken or preventative measures adopted.

- (3) The date and time identifying each period during which the continuous monitoring system was inoperative except for zero and span checks and the nature of the system repairs or adjustments.
- (4) When no excess emissions have occurred or the continuous monitoring system(s) have not been inoperative, repaired, or adjusted, such information shall be stated in the report.
- (d) The summary report form shall contain the information and be in the format shown in figure 1 unless otherwise specified by the Administrator. One summary report form shall be submitted for each pollutant monitored at each affected facility.
- (1) If the total duration of excess emissions for the reporting period is less than 1 percent of the total operating time for the reporting period and CMS downtime for the reporting period is less than 5 percent of the total operating time for the reporting period, only the summary report form shall be

submitted and the excess emission report described in §60.7(c) need not be submitted unless requested by the Administrator.

(2) If the total duration of excess emissions for the reporting period is 1 percent or greater of the total operating time for the reporting period or the total CMS downtime for the reporting period is 5 percent or greater of the total operating time for the reporting period, the summary report form and the excess emission report described in §60.7(c) shall both be submitted.

FIGURE 1—SUMMARY REPORT—GASEOUS AND OPACITY EXCESS EMISSION AND Monitoring System Performance

Dollatont (Cirolo Ono CO MO /TDC/H C/CO/

Opacity)
Reporting period dates: From to
Company:
Emission Limitation
Address:
Monitor Manufacturer and Model No.
Date of Latest CMS Certification or Audit
Process Unit(s) Description:
Total source operating time in reporting pe-
riod 1

Emission data summary 1		CMS performance summary <sup>1</sup>	
Duration of excess emissions in reporting period due to:		CMS downtime in reporting period due to:	
a. Startup/shutdown b. Control equipment problems c. Process problems d. Other known causes e. Unknown causes 2. Total duration of excess emission		a. Monitor equipment malfunctions.     b. Non-Monitor equipment malfunctions.     c. Quality assurance calibration.     d. Other known causes.     e. Unknown causes.     2. Total CMS Downtime.	
3. Total duration of excess emissions $\times$ (100) [Total source operating time].	% <sup>2</sup>	[Total CMS Downtime] × (100) [Total source operating time].	% <sup>2</sup>

On a separate page, describe any changes since last quarter in CMS, process or controls. I certify that the information contained in this report is true, accurate, and complete.

Name		
Signature		
Title	 	
Date		

(e)(1) Notwithstanding the frequency of reporting requirements specified in

paragraph (c) of this section, an owner or operator who is required by an applicable subpart to submit excess emissions and monitoring systems performance reports (and summary reports) on a quarterly (or more frequent) basis may reduce the frequency of reporting for that standard to semiannual if the following conditions are met:

(i) For 1 full year (e.g., 4 quarterly or 12 monthly reporting periods) the affected facility's excess emissions and monitoring systems reports submitted to comply with a standard under this

For opacity, record all times in minutes. For gases, record all times in hours.
 For the reporting period: If the total duration of excess emissions is 1 percent or greater of the total operating time or the total CMS downtime is 5 percent or greater of the total operating time, both the summary report form and the excess emission report described in § 60.7(c) shall be submitted.

part continually demonstrate that the facility is in compliance with the applicable standard:

- (ii) The owner or operator continues to comply with all recordkeeping and monitoring requirements specified in this subpart and the applicable standard; and
- (iii) The Administrator does not object to a reduced frequency of reporting for the affected facility, as provided in paragraph (e)(2) of this section.
- (2) The frequency of reporting of excess emissions and monitoring systems performance (and summary) reports may be reduced only after the owner or operator notifies the Administrator in writing of his or her intention to make such a change and the Administrator does not object to the intended change. In deciding whether to approve a reduced frequency of reporting, the Administrator may review information concerning the source's entire previous performance history during the required recordkeeping period prior to the intended change, including performance test results, monitoring data, and evaluations of an owner or operator's conformance with operation and maintenance requirements. Such information may be used by the Administrator to make a judgment about the source's potential for noncompliance in the future. If the Administrator disapproves the owner or operator's request to reduce the frequency of reporting, the Administrator will notify the owner or operator in writing within 45 days after receiving notice of the owner or operator's intention. The notification from the Administrator to the owner or operator will specify the grounds on which the disapproval is based. In the absence of a notice of disapproval within 45 days, approval is automatically granted.
- (3) As soon as monitoring data indicate that the affected facility is not in compliance with any emission limitation or operating parameter specified in the applicable standard, the frequency of reporting shall revert to the frequency specified in the applicable standard, and the owner or operator shall submit an excess emissions and monitoring systems performance report (and summary report, if required) at the next appropriate reporting pe-

riod following the noncomplying event. After demonstrating compliance with the applicable standard for another full year, the owner or operator may again request approval from the Administrator to reduce the frequency of reporting for that standard as provided for in paragraphs (e)(1) and (e)(2) of this section.

- (f) Any owner or operator subject to the provisions of this part shall maintain a file of all measurements, including continuous monitoring system, monitoring device, and performance testing measurements; all continuous monitoring system performance evaluations: all continuous monitoring system or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; and all other information required by this part recorded in a permanent form suitable for inspection. The file shall be retained for at least two years following the date of such measurements, maintenance, reports, and records, except as follows:
- (1) This paragraph applies to owners or operators required to install a continuous emissions monitoring system (CEMS) where the CEMS installed is automated, and where the calculated data averages do not exclude periods of CEMS breakdown or malfunction. An automated CEMS records and reduces the measured data to the form of the pollutant emission standard through the use of a computerized data acquisition system. In lieu of maintaining a file of all CEMS subhourly measurements as required under paragraph (f) of this section, the owner or operator shall retain the most recent consecutive three averaging periods of subhourly measurements and a file that contains a hard copy of the data acquisition system algorithm used to reduce the measured data into the reportable form of the standard.
- (2) This paragraph applies to owners or operators required to install a CEMS where the measured data is manually reduced to obtain the reportable form of the standard, and where the calculated data averages do not exclude periods of CEMS breakdown or malfunction. In lieu of maintaining a file of all CEMS subhourly measurements as required under paragraph (f) of this

section, the owner or operator shall retain all subhourly measurements for the most recent reporting period. The subhourly measurements shall be retained for 120 days from the date of the most recent summary or excess emission report submitted to the Administrator.

- (3) The Administrator or delegated authority, upon notification to the source, may require the owner or operator to maintain all measurements as required by paragraph (f) of this section, if the Administrator or the delegated authority determines these records are required to more accurately assess the compliance status of the affected source.
- (g) If notification substantially similar to that in paragraph (a) of this section is required by any other State or local agency, sending the Administrator a copy of that notification will satisfy the requirements of paragraph (a) of this section.
- (h) Individual subparts of this part may include specific provisions which clarify or make inapplicable the provisions set forth in this section.

[36 FR 24877, Dec. 28, 1971, as amended at 40 FR 46254, Oct. 6, 1975; 40 FR 58418, Dec. 16, 1975; 45 FR 5617, Jan. 23, 1980; 48 FR 48335, Oct. 18, 1983; 50 FR 53113, Dec. 27, 1985; 52 FR 9781, Mar. 26, 1987; 55 FR 51382, Dec. 13, 1990; 59 FR 12428, Mar. 16, 1994; 59 FR 47265, Sep. 15, 1994; 64 FR 7463, Feb. 12, 1999]

#### § 60.8 Performance tests.

- (a) Except as specified in paragraphs (a)(1),(a)(2), (a)(3), and (a)(4) of this section, within 60 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup of such facility, or at such other times specified by this part, and at such other times as may be required by the Administrator under section 114 of the Act, the owner or operator of such facility shall conduct performance test(s) and furnish the Administrator a written report of the results of such performance test(s).
- (1) If a force majeure is about to occur, occurs, or has occurred for which the affected owner or operator intends to assert a claim of force majeure, the owner or operator shall notify the Administrator, in writing as

- soon as practicable following the date the owner or operator first knew, or through due diligence should have known that the event may cause or caused a delay in testing beyond the regulatory deadline, but the notification must occur before the performance test deadline unless the initial force majeure or a subsequent force majeure event delays the notice, and in such cases, the notification shall occur as soon as practicable.
- (2) The owner or operator shall provide to the Administrator a written description of the force majeure event and a rationale for attributing the delay in testing beyond the regulatory deadline to the force majeure; describe the measures taken or to be taken to minimize the delay; and identify a date by which the owner or operator proposes to conduct the performance test. The performance test shall be conducted as soon as practicable after the force majeure occurs.
- (3) The decision as to whether or not to grant an extension to the performance test deadline is solely within the discretion of the Administrator. The Administrator will notify the owner or operator in writing of approval or disapproval of the request for an extension as soon as practicable.
- (4) Until an extension of the performance test deadline has been approved by the Administrator under paragraphs (a)(1), (2), and (3) of this section, the owner or operator of the affected facility remains strictly subject to the requirements of this part.
- (b) Performance tests shall be conducted and data reduced in accordance with the test methods and procedures contained in each applicable subpart unless the Administrator (1) specifies or approves, in specific cases, the use of a reference method with minor changes in methodology, (2) approves the use of an equivalent method, (3) approves the use of an alternative method the results of which he has determined to be adequate for indicating whether a specific source is in compliance, (4) waives the requirement for performance tests because the owner or operator of a source has demonstrated by other means to the Administrator's satisfaction that the affected facility is in compliance with the standard, or (5)

approves shorter sampling times and smaller sample volumes when necessitated by process variables or other factors. Nothing in this paragraph shall be construed to abrogate the Administrator's authority to require testing under section 114 of the Act.

- (c) Performance tests shall be conducted under such conditions as the Administrator shall specify to the plant operator based on representative performance of the affected facility. The owner or operator shall make available to the Administrator such records as may be necessary to determine the conditions of the performance tests. Operations during periods of startup, shutdown, and malfunction shall not constitute representative conditions for the purpose of a performance test nor shall emissions in excess of the level of the applicable emission limit during periods of startup, shutdown, and malfunction be considered a violation of the applicable emission limit unless otherwise specified in the applicable standard.
- (d) The owner or operator of an affected facility shall provide the Administrator at least 30 days prior notice of any performance test, except as specified under other subparts, to afford the Administrator the opportunity to have an observer present. If after 30 days notice for an initially scheduled performance test, there is a delay (due to operational problems, etc.) in conducting the scheduled performance test, the owner or operator of an affected facility shall notify the Administrator (or delegated State or local agency) as soon as possible of any delay in the original test date, either by providing at least 7 days prior notice of the rescheduled date of the performance test, or by arranging a rescheduled date with the Administrator (or delegated State or local agency) by mutual agreement.
- (e) The owner or operator of an affected facility shall provide, or cause to be provided, performance testing facilities as follows:
- (1) Sampling ports adequate for test methods applicable to such facility. This includes (i) constructing the air pollution control system such that volumetric flow rates and pollutant emission rates can be accurately deter-

mined by applicable test methods and procedures and (ii) providing a stack or duct free of cyclonic flow during performance tests, as demonstrated by applicable test methods and procedures.

- (2) Safe sampling platform(s).
- (3) Safe access to sampling platform(s).
- (4) Utilities for sampling and testing equipment.
- (f) Unless otherwise specified in the applicable subpart, each performance test shall consist of three separate runs using the applicable test method. Each run shall be conducted for the time and under the conditions specified in the applicable standard. For the purpose of determining compliance with an applicable standard, the arithmetic means of results of the three runs shall apply. In the event that a sample is accidentally lost or conditions occur in which one of the three runs must be discontinued because of forced shutdown, failure of an irreplaceable portion of the sample train, extreme meteorological conditions, or other circumstances, beyond the owner or operator's control, compliance may, upon the Administrator's approval, be determined using the arithmetic mean of the results of the two other runs.

[36 FR 24877, Dec. 23, 1971, as amended at 39 FR 9314, Mar. 8, 1974; 42 FR 57126, Nov. 1, 1977; 44 FR 33612, June 11, 1979; 54 FR 6662, Feb. 14, 1989; 54 FR 21344, May 17, 1989; 64 FR 7463, Feb. 12, 1999; 72 FR 27442, May 16, 2007]

#### § 60.9 Availability of information.

The availability to the public of information provided to, or otherwise obtained by, the Administrator under this part shall be governed by part 2 of this chapter. (Information submitted voluntarily to the Administrator for the purposes of §§60.5 and 60.6 is governed by §§2.201 through 2.213 of this chapter and not by §2.301 of this chapter.)

#### § 60.10 State authority.

The provisions of this part shall not be construed in any manner to preclude any State or political subdivision thereof from:

(a) Adopting and enforcing any emission standard or limitation applicable to an affected facility, provided that such emission standard or limitation is

not less stringent than the standard applicable to such facility.

(b) Requiring the owner or operator of an affected facility to obtain permits, licenses, or approvals prior to initiating construction, modification, or operation of such facility.

# § 60.11 Compliance with standards and maintenance requirements.

(a) Compliance with standards in this part, other than opacity standards, shall be determined in accordance with performance tests established by §60.8, unless otherwise specified in the applicable standard.

(b) Compliance with opacity standards in this part shall be determined by conducting observations in accordance with Method 9 in appendix A of this part, any alternative method that is approved by the Administrator, or as provided in paragraph (e)(5) of this section. For purposes of determining initial compliance, the minimum total time of observations shall be 3 hours (30 6-minute averages) for the performance test or other set of observations (meaning those fugitive-type emission sources subject only to an opacity standard).

(c) The opacity standards set forth in this part shall apply at all times except during periods of startup, shutdown, malfunction, and as otherwise provided in the applicable standard.

(d) At all times, including periods of startup, shutdown, and malfunction, owners and operators shall, to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.

(e)(1) For the purpose of demonstrating initial compliance, opacity observations shall be conducted concurrently with the initial performance test required in §60.8 unless one of the following conditions apply. If no per-

formance test under §60.8 is required, then opacity observations shall be conducted within 60 days after achieving the maximum production rate at which the affected facility will be operated but no later than 180 days after initial startup of the facility. If visibility or other conditions prevent the opacity observations from being conducted concurrently with the initial performance test required under §60.8, the source owner or operator shall reschedule the opacity observations as soon after the initial performance test as possible, but not later than 30 days thereafter, and shall advise the Administrator of the rescheduled date. In these cases, the 30-day prior notification to the Administrator required in §60.7(a)(6) shall be waived. The rescheduled opacity observations shall be conducted (to the extent possible) under the same operating conditions that existed during the initial performance test conducted under §60.8. The visible emissions observer shall determine whether visibility or other conditions prevent the opacity observations from being made concurrently with the initial performance test in accordance with procedures contained in Method 9 of appendix B of this part. Opacity readings of portions of plumes which contain condensed, uncombined water vapor shall not be used for purposes of determing compliance with opacity standards. The owner or operator of an affected facility shall make available, upon request by the Administrator, such records as may be necessary to determine the conditions under which the visual observations were made and shall provide evidence indicating proof of current visible observer emission certification. Except as provided in paragraph (e)(5) of this section, the results of continuous monitoring by transmissometer which indicate that the opacity at the time visual observations were made was not in excess of the standard are probative but not conclusive evidence of the actual opacity of an emission, provided that the source shall meet the burden of proving that the instrument used meets (at the time of the alleged violation) Performance Specification 1 in appendix B of this part, has been properly maintained

and (at the time of the alleged violation) that the resulting data have not been altered in any way.

- (2) Except as provided in paragraph (e)(3) of this section, the owner or operator of an affected facility to which an opacity standard in this part applies shall conduct opacity observations in accordance with paragraph (b) of this section, shall record the opacity of emissions, and shall report to the Administrator the opacity results along with the results of the initial performance test required under §60.8. The inability of an owner or operator to secure a visible emissions observer shall not be considered a reason for not conducting the opacity observations concurrent with the initial performance
- (3) The owner or operator of an affected facility to which an opacity standard in this part applies may request the Administrator to determine and to record the opacity of emissions from the affected facility during the initial performance test and at such times as may be required. The owner or operator of the affected facility shall report the opacity results. Any request to the Administrator to determine and to record the opacity of emissions from an affected facility shall be included in the notification required in §60.7(a)(6). If, for some reason, the Administrator cannot determine and record the opacity of emissions from the affected facility during the performance test, then the provisions of paragraph (e)(1) of this section shall apply.
- (4) An owner or operator of an affected facility using a continuous opacity monitor (transmissometer) shall record the monitoring data produced during the initial performance test required by §60.8 and shall furnish the Administrator a written report of the monitoring results along with Method 9 and §60.8 performance test results.
- (5) An owner or operator of an affected facility subject to an opacity standard may submit, for compliance purposes, continuous opacity monitoring system (COMS) data results produced during any performance test required under §60.8 in lieu of Method 9 observation data. If an owner or operator elects to submit COMS data for compliance with the opacity standard,

he shall notify the Administrator of that decision, in writing, at least 30 days before any performance test required under §60.8 is conducted. Once the owner or operator of an affected facility has notified the Administrator to that effect, the COMS data results will be used to determine opacity compliance during subsequent tests required under \$60.8 until the owner or operator notifies the Administrator, in writing, to the contrary. For the purpose of determining compliance with the opacity standard during a performance test required under §60.8 using COMS data, the minimum total time of COMS data collection shall be averages of all 6minute continuous periods within the duration of the mass emission performance test. Results of the COMS opacity determinations shall be submitted along with the results of the performance test required under §60.8. The owner or operator of an affected facility using a COMS for compliance purposes is responsible for demonstrating that the COMS meets the requirements specified in §60.13(c) of this part, that the COMS has been properly maintained and operated, and that the resulting data have not been altered in any way. If COMS data results are submitted for compliance with the opacity standard for a period of time during which Method 9 data indicates noncompliance, the Method 9 data will be used to determine compliance with the opacity standard.

(6) Upon receipt from an owner or operator of the written reports of the results of the performance tests required by §60.8, the opacity observation results and observer certification required by §60.11(e)(1), and the COMS results, if applicable, the Administrator will make a finding concerning compliance with opacity and other applicable standards. If COMS data results are used to comply with an opacity standard, only those results are required to be submitted along with the performance test results required by §60.8. If the Administrator finds that an affected facility is in compliance with all applicable standards for which performance tests are conducted in accordance with §60.8 of this part but during the time such performance tests are being conducted fails to meet any

applicable opacity standard, he shall notify the owner or operator and advise him that he may petition the Administrator within 10 days of receipt of notification to make appropriate adjustment to the opacity standard for the affected facility.

(7) The Administrator will grant such a petition upon a demonstration by the owner or operator that the affected facility and associated air pollution control equipment was operated and maintained in a manner to minimize the opacity of emissions during the performance tests; that the performance tests were performed under the conditions established by the Administrator; and that the affected facility and associated air pollution control equipment were incapable of being adjusted or operated to meet the applicable opacity standard.

- (8) The Administrator will establish an opacity standard for the affected facility meeting the above requirements at a level at which the source will be able, as indicated by the performance and opacity tests, to meet the opacity standard at all times during which the source is meeting the mass or concentration emission standard. The Administrator will promulgate the new opacity standard in the FEDERAL REGISTER.
- (f) Special provisions set forth under an applicable subpart shall supersede any conflicting provisions in paragraphs (a) through (e) of this section.
- (g) For the purpose of submitting compliance certifications or establishing whether or not a person has violated or is in violation of any standard in this part, nothing in this part shall preclude the use, including the exclusive use, of any credible evidence or information, relevant to whether a source would have been in compliance with applicable requirements if the appropriate performance or compliance test or procedure had been performed.

[38 FR 28565, Oct. 15, 1973, as amended at 39 FR 39873, Nov. 12, 1974; 43 FR 8800, Mar. 3, 1978; 45 FR 23379, Apr. 4, 1980; 48 FR 48335, Oct. 18, 1983; 50 FR 53113, Dec. 27, 1985; 51 FR 1790, Jan. 15, 1986; 52 FR 9781, Mar. 26, 1987; 62 FR 8328, Feb. 24, 1997; 65 FR 61749, Oct. 17, 20001

## § 60.12 Circumvention.

No owner or operator subject to the provisions of this part shall build, erect, install, or use any article, machine, equipment or process, the use of which conceals an emission which would otherwise constitute a violation of an applicable standard. Such concealment includes, but is not limited to, the use of gaseous diluents to achieve compliance with an opacity standard or with a standard which is based on the concentration of a pollutant in the gases discharged to the atmosphere.

[39 FR 9314, Mar. 8, 1974]

#### § 60.13 Monitoring requirements.

- (a) For the purposes of this section, all continuous monitoring systems required under applicable subparts shall be subject to the provisions of this section upon promulgation of performance specifications for continuous monitoring systems under appendix B to this part and, if the continuous monitoring system is used to demonstrate compliance with emission limits on a continuous basis, appendix F to this part, unless otherwise specified in an applicable subpart or by the Administrator. Appendix F is applicable December 4, 1987.
- (b) All continuous monitoring systems and monitoring devices shall be installed and operational prior to conducting performance tests under §60.8. Verification of operational status shall, as a minimum, include completion of the manufacturer's written requirements or recommendations for installation, operation, and calibration of the device.
- (c) If the owner or operator of an affected facility elects to submit continous opacity monitoring system (COMS) data for compliance with the opacity standard as provided under §60.11(e)(5), he shall conduct a performance evaluation of the COMS as specified in Performance Specification 1, appendix B, of this part before the performance test required under §60.8 is conducted. Otherwise, the owner or operator of an affected facility shall conduct a performance evaluation of the

COMS or continuous emission monitoring system (CEMS) during any performance test required under §60.8 or within 30 days thereafter in accordance with the applicable performance specification in appendix B of this part, The owner or operator of an affected facility shall conduct COMS or CEMS performance evaluations at such other times as may be required by the Administrator under section 114 of the Act.

- (1) The owner or operator of an affected facility using a COMS to determine opacity compliance during any performance test required under §60.8 and as described in §60.11(e)(5) shall furnish the Administrator two or, upon request, more copies of a written report of the results of the COMS performance evaluation described in paragraph (c) of this section at least 10 days before the performance test required under §60.8 is conducted.
- (2) Except as provided in paragraph (c)(1) of this section, the owner or operator of an affected facility shall furnish the Administrator within 60 days of completion two or, upon request, more copies of a written report of the results of the performance evaluation.
- (d)(1) Owners and operators of a CEMS installed in accordance with the provisions of this part, must check the zero (or low level value between 0 and 20 percent of span value) and span (50 to 100 percent of span value) calibration drifts at least once daily in accordance with a written procedure. The zero and span must, as a minimum, be adjusted whenever either the 24-hour zero drift or the 24-hour span drift exceeds two times the limit of the applicable performance specification in appendix B of this part. The system must allow the amount of the excess zero and span drift to be recorded and quantified whenever specified. Owners and operators of a COMS installed in accordance with the provisions of this part, must automatically, intrinsic to the opacity monitor, check the zero and upscale (span) calibration drifts at least once daily. For a particular COMS, the acceptable range of zero and upscale calibration materials is as defined in the applicable version of PS-1 in appendix B of this part. For a COMS, the optical surfaces, exposed to the ef-

fluent gases, must be cleaned before performing the zero and upscale drift adjustments, except for systems using automatic zero adjustments. The optical surfaces must be cleaned when the cumulative automatic zero compensation exceeds 4 percent opacity.

- (2) Unless otherwise approved by the Administrator, the following procedures must be followed for a COMS. Minimum procedures must include an automated method for producing a simulated zero opacity condition and an upscale opacity condition using a certified neutral density filter or other related technique to produce a known obstruction of the light beam. Such procedures must provide a system check of all active analyzer internal optics with power or curvature, all active electronic circuitry including the light source and photodetector assembly, and electronic or electro-mechanical systems and hardware and or software used during normal measurement oper-
- (e) Except for system breakdowns, repairs, calibration checks, and zero and span adjustments required under paragraph (d) of this section, all continuous monitoring systems shall be in continuous operation and shall meet minimum frequency of operation requirements as follows:
- (1) All continuous monitoring systems referenced by paragraph (c) of this section for measuring opacity of emissions shall complete a minimum of one cycle of sampling and analyzing for each successive 10-second period and one cycle of data recording for each successive 6-minute period.
- (2) All continuous monitoring systems referenced by paragraph (c) of this section for measuring emissions, except opacity, shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each successive 15-minute period.
- (f) All continuous monitoring systems or monitoring devices shall be installed such that representative measurements of emissions or process parameters from the affected facility are obtained. Additional procedures for location of continuous monitoring systems contained in the applicable Performance Specifications of appendix B of this part shall be used.

- (g) When the effluents from a single affected facility or two or more affected facilities subject to the same emission standards are combined before being released to the atmosphere. the owner or operator may install applicable continuous monitoring systems on each effluent or on the combined effluent. When the affected facilities are not subject to the same emission standards, separate continuous monitoring systems shall be installed on each effluent. When the effluent from one affected facility is released to the atmosphere through more than one point, the owner or operator shall install an applicable continuous monitoring system on each separate effluent unless the installation of fewer systems is approved by the Administrator. When more than one continuous monitoring system is used to measure the emissions from one affected facility (e.g., multiple breechings, multiple outlets), the owner or operator shall report the results as required from each continuous monitoring system.
- (h)(1) Owners or operators of all continuous monitoring systems for measurement of opacity shall reduce all data to 6-minute averages and for continuous monitoring systems other than opacity to 1-hour averages for time periods as defined in \$60.2. Six-minute opacity averages shall be calculated from 36 or more data points equally spaced over each 6-minute period.
- (2) For continuous monitoring systems other than opacity, 1-hour averages shall be computed as follows, except that the provisions pertaining to the validation of partial operating hours are only applicable for affected facilities that are required by the applicable subpart to include partial hours in the emission calculations:
- (i) Except as provided under paragraph (h)(2)(iii) of this section, for a full operating hour (any clock hour with 60 minutes of unit operation), at least four valid data points are required to calculate the hourly average, i.e., one data point in each of the 15-minute quadrants of the hour.
- (ii) Except as provided under paragraph (h)(2)(iii) of this section, for a partial operating hour (any clock hour with less than 60 minutes of unit operation), at least one valid data point in

- each 15-minute quadrant of the hour in which the unit operates is required to calculate the hourly average.
- (iii) For any operating hour in which required maintenance or quality-assurance activities are performed:
- (A) If the unit operates in two or more quadrants of the hour, a minimum of two valid data points, separated by at least 15 minutes, is required to calculate the hourly average; or
- (B) If the unit operates in only one quadrant of the hour, at least one valid data point is required to calculate the hourly average.
- (iv) If a daily calibration error check is failed during any operating hour, all data for that hour shall be invalidated, unless a subsequent calibration error test is passed in the same hour and the requirements of paragraph (h)(2)(iii) of this section are met, based solely on valid data recorded after the successful calibration.
- (v) For each full or partial operating hour, all valid data points shall be used to calculate the hourly average.
- (vi) Except as provided under paragraph (h)(2)(vii) of this section, data recorded during periods of continuous monitoring system breakdown, repair, calibration checks, and zero and span adjustments shall not be included in the data averages computed under this paragraph.
- (vii) Owners and operators complying with the requirements of §60.7(f)(1) or (2) must include any data recorded during periods of monitor breakdown or malfunction in the data averages.
- (viii) When specified in an applicable subpart, hourly averages for certain partial operating hours shall not be computed or included in the emission averages (e.g. hours with < 30 minutes of unit operation under  $\S 60.47b(d)$ ).
- (ix) Either arithmetic or integrated averaging of all data may be used to calculate the hourly averages. The data may be recorded in reduced or nonreduced form  $(e.g., ppm pollutant and percent <math>O_2$  or ng/J of pollutant).
- (3) All excess emissions shall be converted into units of the standard using the applicable conversion procedures specified in the applicable subpart. After conversion into units of the standard, the data may be rounded to

the same number of significant digits used in the applicable subpart to specify the emission limit.

- (i) After receipt and consideration of written application, the Administrator may approve alternatives to any monitoring procedures or requirements of this part including, but not limited to the following:
- (1) Alternative monitoring requirements when installation of a continuous monitoring system or monitoring device specified by this part would not provide accurate measurements due to liquid water or other interferences caused by substances in the effluent gases.
- (2) Alternative monitoring requirements when the affected facility is infrequently operated.
- (3) Alternative monitoring requirements to accommodate continuous monitoring systems that require additional measurements to correct for stack moisture conditions.
- (4) Alternative locations for installing continuous monitoring systems or monitoring devices when the owner or operator can demonstrate that installation at alternate locations will enable accurate and representative measurements.
- (5) Alternative methods of converting pollutant concentration measurements to units of the standards.
- (6) Alternative procedures for performing daily checks of zero and span drift that do not involve use of span gases or test cells.
- (7) Alternatives to the A.S.T.M. test methods or sampling procedures specified by any subpart.
- (8) Alternative continuous monitoring systems that do not meet the design or performance requirements in Performance Specification 1, appendix B, but adequately demonstrate a definite and consistent relationship between its measurements and the measurements of opacity by a system complying with the requirements in Performance Specification 1. The Administrator may require that such demonstration be performed for each affected facility.
- (9) Alternative monitoring requirements when the effluent from a single affected facility or the combined effluent from two or more affected facilities

is released to the atmosphere through more than one point.

- (j) An alternative to the relative accuracy (RA) test specified in Performance Specification 2 of appendix B may be requested as follows:
- (1) An alternative to the reference method tests for determining RA is available for sources with emission rates demonstrated to be less than 50 percent of the applicable standard. A source owner or operator may petition the Administrator to waive the RA test in Section 8.4 of Performance Specification 2 and substitute the procedures in Section 16.0 if the results of a performance test conducted according to the requirements in §60.8 of this subpart or other tests performed following the criteria in §60.8 demonstrate that the emission rate of the pollutant of interest in the units of the applicable standard is less than 50 percent of the applicable standard. For sources subject to standards expressed as control efficiency levels, a source owner or operator may petition the Administrator to waive the RA test and substitute the procedures in Section 16.0 of Performance Specification 2 if the control device exhaust emission rate is less than 50 percent of the level needed to meet the control efficiency requirement. The alternative procedures do not apply if the continuous emission monitoring system is used to determine compliance continuously with the applicable standard. The petition to waive the RA test shall include a detailed description of the procedures to be applied. Included shall be location and procedure for conducting the alternative, the concentration or response levels of the alternative RA materials, and the other equipment checks included in the alternative procedure. The Administrator will review the petition for completeness and applicability. The determination to grant a waiver will depend on the intended use of the CEMS data (e.g., data collection purposes other than NSPS) and may require specifications more stringent than in Performance Specification 2 (e.g., the applicable emission limit is more stringent than NSPS).
- (2) The waiver of a CEMS RA test will be reviewed and may be rescinded

at such time, following successful completion of the alternative RA procedure, that the CEMS data indicate that the source emissions are approaching the level. The criterion for reviewing the waiver is the collection of CEMS data showing that emissions have exceeded 70 percent of the applicable standard for seven, consecutive, averaging periods as specified by the applicable regulation(s). For sources subject to standards expressed as control efficiency levels, the criterion for reviewing the waiver is the collection of CEMS data showing that exhaust emissions have exceeded 70 percent of the level needed to meet the control efficiency requirement for seven, consecutive, averaging periods as specified by the applicable regulation(s) [e.g., §60.45(g) (2) and (3), §60.73(e), and §60.84(e)]. It is the responsibility of the source operator to maintain records and determine the level of emissions relative to the criterion on the waiver of RA testing. If this criterion is exceeded, the owner or operator must notify the Administrator within 10 days of such occurrence and include a description of the nature and cause of the increasing emissions. The Administrator will review the notification and may rescind the waiver and require the owner or operator to conduct a RA test of the CEMS as specified in Section 8.4 of Performance Specification 2.

[40 FR 46255, Oct. 6, 1975; 40 FR 59205, Dec. 22, 1975, as amended at 41 FR 35185, Aug. 20, 1976; 48 FR 13326, Mar. 30, 1983; 48 FR 23610, May 25, 1983; 48 FR 32986, July 20, 1983; 52 FR 9782, Mar. 26, 1987; 52 FR 17555, May 11, 1987; 52 FR 21007, June 4, 1987; 64 FR 7463, Feb. 12, 1999; 65 FR 48920, Aug. 10, 2000; 65 FR 61749, Oct. 17, 2000; 66 FR 44980, Aug. 27, 2001; 71 FR 31102, June 1, 2006; 72 FR 32714, June 13, 2007]

EDITORIAL NOTE: At 65 FR 61749, Oct. 17, 2000, §60.13 was amended by revising the words "ng/J of pollutant" to read "ng of pollutant per J of heat input" in the sixth sentence of paragraph (h). However, the amendment could not be incorporated because the words "ng/J of pollutant" do not exist in the sixth sentence of paragraph (h).

# § 60.14 Modification.

(a) Except as provided under paragraphs (e) and (f) of this section, any physical or operational change to an existing facility which results in an increase in the emission rate to the at-

mosphere of any pollutant to which a standard applies shall be considered a modification within the meaning of section 111 of the Act. Upon modification, an existing facility shall become an affected facility for each pollutant to which a standard applies and for which there is an increase in the emission rate to the atmosphere.

- (b) Emission rate shall be expressed as kg/hr of any pollutant discharged into the atmosphere for which a standard is applicable. The Administrator shall use the following to determine emission rate:
- (1) Emission factors as specified in the latest issue of "Compilation of Air Pollutant Emission Factors," EPA Publication No. AP-42, or other emission factors determined by the Administrator to be superior to AP-42 emission factors, in cases where utilization of emission factors demonstrates that the emission level resulting from the physical or operational change will either clearly increase or clearly not increase.
- (2) Material balances, continuous monitor data, or manual emission tests in cases where utilization of emission factors as referenced in paragraph (b)(1) of this section does not demonstrate to the Administrator's satisfaction whether the emission level resulting from the physical or operational change will either clearly increase or clearly not increase, or where an owner or operator demonstrates to the Administrator's satisfaction that there are reasonable grounds to dispute the result obtained by the Administrator utilizing emission factors as referenced in paragraph (b)(1) of this section. When the emission rate is based on results from manual emission tests or continuous monitoring systems, the procedures specified in appendix C of this part shall be used to determine whether an increase in emission rate has occurred. Tests shall be conducted under such conditions as the Administrator shall specify to the owner or operator based on representative performance of the facility. At least three valid test runs must be conducted before and at least three after the physical or operational change. All operating parameters which may affect emissions must be held constant to the

maximum feasible degree for all test runs.

- (c) The addition of an affected facility to a stationary source as an expansion to that source or as a replacement for an existing facility shall not by itself bring within the applicability of this part any other facility within that source.
  - (d) [Reserved]
- (e) The following shall not, by themselves, be considered modifications under this part:
- (1) Maintenance, repair, and replacement which the Administrator determines to be routine for a source category, subject to the provisions of paragraph (c) of this section and §60.15.
- (2) An increase in production rate of an existing facility, if that increase can be accomplished without a capital expenditure on that facility.
- (3) An increase in the hours of operation.
- (4) Use of an alternative fuel or raw material if, prior to the date any standard under this part becomes applicable to that source type, as provided by §60.1, the existing facility was designed to accommodate that alternative use. A facility shall be considered to be designed to accommodate an alternative fuel or raw material if that use could be accomplished under the facility's construction specifications as amended prior to the change. Conversion to coal required for energy considerations, as specified in section 111(a)(8) of the Act, shall not be considered a modification.
- (5) The addition or use of any system or device whose primary function is the reduction of air pollutants, except when an emission control system is removed or is replaced by a system which the Administrator determines to be less environmentally beneficial.
- (6) The relocation or change in ownership of an existing facility.
- (f) Special provisions set forth under an applicable subpart of this part shall supersede any conflicting provisions of this section.
- (g) Within 180 days of the completion of any physical or operational change subject to the control measures specified in paragraph (a) of this section, compliance with all applicable standards must be achieved.

- (h) No physical change, or change in the method of operation, at an existing electric utility steam generating unit shall be treated as a modification for the purposes of this section provided that such change does not increase the maximum hourly emissions of any pollutant regulated under this section above the maximum hourly emissions achievable at that unit during the 5 years prior to the change.
- (i) Repowering projects that are awarded funding from the Department of Energy as permanent clean coal technology demonstration projects (or similar projects funded by EPA) are exempt from the requirements of this section provided that such change does not increase the maximum hourly emissions of any pollutant regulated under this section above the maximum hourly emissions achievable at that unit during the five years prior to the change.
- (j)(1) Repowering projects that qualify for an extension under section 409(b) of the Clean Air Act are exempt from the requirements of this section, provided that such change does not increase the actual hourly emissions of any pollutant regulated under this section above the actual hourly emissions achievable at that unit during the 5 years prior to the change.
- (2) This exemption shall not apply to any new unit that:
- (i) Is designated as a replacement for an existing unit;
- (ii) Qualifies under section 409(b) of the Clean Air Act for an extension of an emission limitation compliance date under section 405 of the Clean Air Act; and
- (iii) Is located at a different site than the existing unit.
- (k) The installation, operation, cessation, or removal of a temporary clean coal technology demonstration project is exempt from the requirements of this section. A temporary clean coal control technology demonstration project, for the purposes of this section is a clean coal technology demonstration project that is operated for a period of 5 years or less, and which complies with the State implementation plan for the State in which the project

is located and other requirements necessary to attain and maintain the national ambient air quality standards during the project and after it is terminated.

(l) The reactivation of a very clean coal-fired electric utility steam generating unit is exempt from the requirements of this section.

[40 FR 58419, Dec. 16, 1975, as amended at 43 FR 34347, Aug. 3, 1978; 45 FR 5617, Jan. 23, 1980; 57 FR 32339, July 21, 1992; 65 FR 61750, Oct. 17, 2000]

## § 60.15 Reconstruction.

- (a) An existing facility, upon reconstruction, becomes an affected facility, irrespective of any change in emission rate.
- (b) "Reconstruction" means the replacement of components of an existing facility to such an extent that:
- (1) The fixed capital cost of the new components exceeds 50 percent of the fixed capital cost that would be required to construct a comparable entirely new facility, and
- (2) It is technologically and economically feasible to meet the applicable standards set forth in this part.
- (c) "Fixed capital cost" means the capital needed to provide all the depreciable components.
- (d) If an owner or operator of an existing facility proposes to replace components, and the fixed capital cost of the new components exceeds 50 percent of the fixed capital cost that would be required to construct a comparable entirely new facility, he shall notify the Administrator of the proposed replacements. The notice must be postmarked 60 days (or as soon as practicable) before construction of the replacements is commenced and must include the following information:
- (1) Name and address of the owner or operator.
- (2) The location of the existing facility.
- (3) A brief description of the existing facility and the components which are to be replaced.
- (4) A description of the existing air pollution control equipment and the proposed air pollution control equipment.
- (5) An estimate of the fixed capital cost of the replacements and of con-

structing a comparable entirely new facility.

- (6) The estimated life of the existing facility after the replacements.
- (7) A discussion of any economic or technical limitations the facility may have in complying with the applicable standards of performance after the proposed replacements.
- (e) The Administrator will determine, within 30 days of the receipt of the notice required by paragraph (d) of this section and any additional information he may reasonably require, whether the proposed replacement constitutes reconstruction.
- (f) The Administrator's determination under paragraph (e) shall be based on:
- (1) The fixed capital cost of the replacements in comparison to the fixed capital cost that would be required to construct a comparable entirely new facility;
- (2) The estimated life of the facility after the replacements compared to the life of a comparable entirely new facility:
- (3) The extent to which the components being replaced cause or contribute to the emissions from the facility; and
- (4) Any economic or technical limitations on compliance with applicable standards of performance which are inherent in the proposed replacements.
- (g) Individual subparts of this part may include specific provisions which refine and delimit the concept of reconstruction set forth in this section.

[40 FR 58420, Dec. 16, 1975]

# §60.16 Priority list.

PRIORITIZED MAJOR SOURCE CATEGORIES

Pri- ority Num- ber <sup>1</sup>	Source Category
1.	Synthetic Organic Chemical Manufacturing Industry (SOCMI) and Volatile Organic Liquid Storage Vessels and Handling Equipment (a) SOCMI unit processes (b) Volatile organic liquid (VOL) storage vessels and handling equipment (c) SOCMI fugitive sources (d) SOCMI secondary sources
2.	Industrial Surface Coating: Cans
3.	Petroleum Refineries: Fugitive Sources
4.	Industrial Surface Coating: Paper
5.	Dry Cleaning
	(a) Perchloroethylene

#### PRIORITIZED MAJOR SOURCE CATEGORIES— Continued

Pri- ority Num- ber <sup>1</sup>	Source Category
	(b) Petroleum solvent
_	` '
6.	Graphic Arts
7.	Polymers and Resins: Acrylic Resins
8.	Mineral Wool (Deleted)
9.	Stationary Internal Combustion Engines
10.	Industrial Surface Coating: Fabric
11.	Industrial-Commercial-Institutional Steam Generating Units.
12.	Incineration: Non-Municipal (Deleted)
13.	Non-Metallic Mineral Processing
14.	Metallic Mineral Processing
15.	Secondary Copper (Deleted)
16.	Phosphate Rock Preparation
17.	Foundries: Steel and Gray Iron
18.	Polymers and Resins: Polyethylene
19.	Charcoal Production
20.	Synthetic Rubber
	(a) Tire manufacture
	(b) SBR production
21.	Vegetable Oil
22.	Industrial Surface Coating: Metal Coil
23.	Petroleum Transportation and Marketing
24.	By-Product Coke Ovens
25.	Synthetic Fibers
26.	Plywood Manufacture
27.	Industrial Surface Coating: Automobiles
28.	Industrial Surface Coating: Automobiles  Industrial Surface Coating: Large Appliances
29.	Crude Oil and Natural Gas Production
30.	Secondary Aluminum
31.	Potash (Deleted)
32.	Lightweight Aggregate Industry: Clay, Shale, and
32.	Slate <sup>2</sup>
33.	Glass
34.	
	Gypsum
35.	Sodium Carbonate
36.	Secondary Zinc (Deleted)
37.	Polymers and Resins: Phenolic
38.	Polymers and Resins: Urea-Melamine
39.	Ammonia (Deleted)
40.	Polymers and Resins: Polystyrene
41.	Polymers and Resins: ABS-SAN Resins
42.	Fiberglass
43.	Polymers and Resins: Polypropylene
44.	Textile Processing
45.	Asphalt Processing and Asphalt Roofing Manufacture
46.	Brick and Related Clay Products
47.	Ceramic Clay Manufacturing (Deleted)
48.	Ammonium Nitrate Fertilizer
49.	Castable Refractories (Deleted)
50.	Borax and Boric Acid (Deleted)
51.	Polymers and Resins: Polyester Resins
52.	Ammonium Sulfate
53.	Starch
54.	Perlite
55.	Phosphoric Acid: Thermal Process (Deleted)
56.	Uranium Refining
57.	Animal Feed Defluorination (Deleted)
58.	Urea (for fertilizer and polymers)
59.	Detergent (Deleted)
	Other Source Categories

#### Other Source Categories

Lead acid battery manufacture 3 Organic solvent cleaning 3 Industrial surface coating: metal furniture 3 Stationary gas turbines 4 Municipal solid waste landfills 4

- <sup>2</sup> Formerly titled "Sintering: Clay and Fly Ash".
- <sup>3</sup> Minor source category, but included on list since an NSPS is being developed for that source category.
- <sup>4</sup>Not prioritized, since an NSPS for this major source category has already been promulgated.

[47 FR 951, Jan. 8, 1982, as amended at 47 FR 31876, July 23, 1982; 51 FR 42796, Nov. 25, 1986; 52 FR 11428, Apr. 8, 1987; 61 FR 9919, Mar. 12,

#### § 60.17 Incorporations by reference.

The materials listed below are incorporated by reference in the corresponding sections noted. These incorporations by reference were approved by the Director of the Federal Register on the date listed. These materials are incorporated as they exist on the date of the approval, and a notice of any change in these materials will be published in the FEDERAL REG-ISTER. The materials are available for purchase at the corresponding address noted below, and all are available for inspection at the Library (C267-01), U.S. EPA, Research Triangle Park, NC or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or to: http://www.archives.gov/ go federal\_register/
code\_of\_federal\_regulations/

 $ibr \overline{locations.html}$ .

- (a) The following materials are available for purchase from at least one of the following addresses: American Society for Testing and Materials (ASTM), 100 Barr Harbor Drive, Post Office Box C700, West Conshohocken, PA 19428–2959; or ProQuest, 300 North Zeeb Road, Ann Arbor, MI 48106.
- (1) ASTM A99-76, 82 (Reapproved Standard Specification for Ferromanganese, incorporation by reference (IBR) approved for §60.261.
- (2) ASTM A100-69, 74, 93, Standard Specification for Ferrosilicon, IBR approved for § 60.261.
- (3) ASTM A101-73, 93, Standard Specification for Ferrochromium, IBR approved for §60.261.
- (4) ASTM A482-76, 93, Standard Specification for Ferrochromesilicon, IBR approved for §60.261.
- (5) ASTM A483-64, 74 (Reapproved 1988), Standard Specification for Silicomanganese, IBR approved for § 60.261.

<sup>&</sup>lt;sup>1</sup>Low numbers have highest priority, e.g., No. 1 is high priority, No. 59 is low priority

- (6) ASTM A495–76, 94, Standard Specification for Calcium-Silicon and Calcium Manganese-Silicon, IBR approved for \$60.261.
- (7) ASTM D86-78, 82, 90, 93, 95, 96, Distillation of Petroleum Products, IBR approved for §§ 60.562-2(d), 60.593(d), 60.593a(d), and 60.633(h).
- (8) ASTM D129-64, 78, 95, 00, Standard Test Method for Sulfur in Petroleum Products (General Bomb Method), IBR approved for §§ 60.106(j)(2), 60.335(b)(10)(i), and appendix A: Method 19, 12.5.2.2.3.
- (9) ASTM D129-00 (Reapproved 2005), Standard Test Method for Sulfur in Petroleum Products (General Bomb Method), IBR approved for §60.4415(a)(1)(i).
- (10) ASTM D240-76, 92, Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter, IBR approved for §§ 60.46(c), 60.296(b), and appendix A: Method 19, Section 12.5.2.2.3.
- (11) ASTM D270-65, 75, Standard Method of Sampling Petroleum and Petroleum Products, IBR approved for appendix A: Method 19, Section 12.5.2.2.1.
- (12) ASTM D323-82, 94, Test Method for Vapor Pressure of Petroleum Products (Reid Method), IBR approved for §§ 60.111(1), 60.111a(g), 60.111b(g), and 60.116b(f)(2)(ii).
- (13) ASTM D388-77, 90, 91, 95, 98a, 99 (Reapproved 2004) $^{\rm e1}$ , Standard Specification for Classification of Coals by Rank, IBR approved for §§60.24(h)(8), 60.41 of subpart D of this part, 60.45(f)(4)(i), 60.45(f)(4)(ii), 60.45(f)(4)(vi), 60.41Da of subpart Da of this part, 60.41Da of subpart Db of this part, 60.41c of subpart Dc of this part, 60.41c of subpart Dc of this part, 60.251 of subpart Y of this part, and 60.4102.
- (14) ASTM D396-78, 89, 90, 92, 96, 98, Standard Specification for Fuel Oils, IBR approved for §§ 60.41b of subpart Db of this part, 60.41c of subpart Dc of this part, 60.111(b) of subpart K of this part, and 60.111a(b) of subpart Ka of this part.
- (15) ASTM D975-78, 96, 98a, Standard Specification for Diesel Fuel Oils, IBR approved for §§60.111(b) of subpart K of this part and 60.111a(b) of subpart Ka of this part.
- (16) ASTM D975-08a, Standard Specification for Diesel Fuel Oils, IBR approved for §§ 60.41b of subpart Db of this

- part and 60.41c of subpart Dc of this part.
- (17) ASTM D1072-80, 90 (Reapproved 1994), Standard Test Method for Total Sulfur in Fuel Gases, IBR approved for §60.335(b)(10)(ii).
- (18) ASTM D1072-90 (Reapproved 1999), Standard Test Method for Total Sulfur in Fuel Gases, IBR approved for § 60.4415(a)(1)(ii).
- (19) ASTM D1137-53, 75, Standard Method for Analysis of Natural Gases and Related Types of Gaseous Mixtures by the Mass Spectrometer, IBR approved for §60.45(f)(5)(i).
- (20) ASTM D1193-77, 91, Standard Specification for Reagent Water, IBR approved for appendix A: Method 5, Section 7.1.3; Method 5E, Section 7.2.1; Method 5F, Section 7.2.1; Method 6, Section 7.1.1; Method 7, Section 7.1.1; Method 7C, Section 7.1.1; Method 7D, Section 7.1.1; Method 10A, Section 7.1.1; Method 11, Section 7.1.3; Method 12, Section 7.1.3; Method 13A, Section 7.1.2; Method 26, Section 7.1.2; Method 26A, Section 7.1.2; and Method 29, Section 7.2.2.
- (21) ASTM D1266-87, 91, 98, Standard Test Method for Sulfur in Petroleum Products (Lamp Method), IBR approved for §§ 60.106(j)(2) and 60.335(b)(10)(i).
- (22) ASTM D1266-98 (Reapproved 2003)e1, Standard Test Method for Sulfur in Petroleum Products (Lamp Method), IBR approved for §60.4415(a)(1)(i).
- (23) ASTM D1475-60 (Reapproved 1980), 90, Standard Test Method for Density of Paint, Varnish Lacquer, and Related Products, IBR approved for \$60.435(d)(1), appendix A: Method 24, Section 6.1; and Method 24A, Sections 6.5 and 7.1.
- (24) ASTM D1552-83, 95, 01, Standard Test Method for Sulfur in Petroleum Products (High-Temperature Method), IBR approved for §§ 60.106(j)(2), 60.335(b)(10)(i), and appendix A: Method 19, Section 12.5.2.2.3.
- (25) ASTM D1552-03, Standard Test Method for Sulfur in Petroleum Products (High-Temperature Method), IBR approved for \$60.4415(a)(1)(i).
- (26) ASTM D1826-77, 94, Standard Test Method for Calorific Value of Gases in Natural Gas Range by Continuous Recording Calorimeter, IBR approved for §§ 60.45(f)(5)(ii), 60.46(c)(2), 60.296(b)(3),

- and appendix A: Method 19, Section 12.3.2.4.
- (27) ASTM D1835-87, 91, 97, 03a, Standard Specification for Liquefied Petroleum (LP) Gases, IBR approved for §§ 60.41Da of subpart Da of this part, 60.41b of subpart Db of this part, and 60.41c of subpart Dc of this part.
- (28) ASTM D1945-64, 76, 91, 96, Standard Method for Analysis of Natural Gas by Gas Chromatography, IBR approved for §60.45(f)(5)(i).
- (30) ASTM D2013-72, 86, Standard Method of Preparing Coal Samples for Analysis, IBR approved for appendix A: Method 19, Section 12.5.2.1.3.
- (31) ASTM D2015-77 (Reapproved 1978), 96, Standard Test Method for Gross Calorific Value of Solid Fuel by the Adiabatic Bomb Calorimeter, IBR approved for §60.45(f)(5)(ii), 60.46(c)(2), and appendix A: Method 19, Section 12.5.2.1.3.
- (32) ASTM D2016-74, 83, Standard Test Methods for Moisture Content of Wood, IBR approved for appendix A: Method 28, Section 16.1.1.
- (33) ASTM D2234-76, 96, 97b, 98, Standard Methods for Collection of a Gross Sample of Coal, IBR approved for appendix A: Method 19, Section 12.5.2.1.1.
- (34) ASTM D2369-81, 87, 90, 92, 93, 95, Standard Test Method for Volatile Content of Coatings, IBR approved for appendix A: Method 24, Section 6.2.
- (36) ASTM D2504-67, 77, 88 (Reapproved 1993), Noncondensable Gases in C3 and Lighter Hydrocarbon Products by Gas Chromatography, IBR approved for §§ 60.485(g)(5) and 60.485a(g)(5).
- (37) ASTM D2584-68 (Reapproved 1985), 94, Standard Test Method for Ignition Loss of Cured Reinforced Resins, IBR approved for §60.685(c)(3)(i).

- (38) ASTM D2597-94 (Reapproved 1999), Standard Test Method for Analysis of Demethanized Hydrocarbon Liquid Mixtures Containing Nitrogen and Carbon Dioxide by Gas Chromatography, IBR approved for §60.335(b)(9)(i).
- (39) ASTM D2622-87, 94, 98, Standard Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-Ray Fluorescence Spectrometry, IBR approved for §§ 60.106(j)(2) and 60.335(b)(10)(i).
- (40) ASTM D2622-05, Standard Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-Ray Fluorescence Spectrometry, IBR approved for §60.4415(a)(1)(i).
- (41) ASTM D2879-83, 96, 97, Test Method for Vapor Pressure-Temperature Relationship and Initial Decomposition Temperature Liquids of bv Isoteniscope, **IBR** approved for  $\S\S60.111b(f)(3)$ , 60.116b(e)(3)(ii), 60.485(e)(1),60.116b(f)(2)(i), and 60.485a(e)(1).
- (42) ASTM D2880-78, 96, Standard Specification for Gas Turbine Fuel Oils, IBR approved for §§ 60.111(b), 60.111a(b), and 60.335(d).
- (43) ASTM D2908-74, 91, Standard Practice for Measuring Volatile Organic Matter in Water by Aqueous-Injection Gas Chromatography, IBR approved for §60.564(j).
- (44) ASTM D2986-71, 78, 95a, Standard Method for Evaluation of Air, Assay Media by the Monodisperse DOP (Dioctyl Phthalate) Smoke Test, IBR approved for appendix A: Method 5, Section 7.1.1; Method 12, Section 7.1.1; and Method 13A, Section 7.1.1.2.
- (45) ASTM D3173-73, 87, Standard Test Method for Moisture in the Analysis Sample of Coal and Coke, IBR approved for appendix A: Method 19, Section 12.5.2.1.3.
- (46) ASTM D3176-74, 89, Standard Method for Ultimate Analysis of Coal and Coke, IBR approved for §60.45(f)(5)(i) and appendix A: Method 19, Section 12.3.2.3.
- (47) ASTM D3177-75, 89, Standard Test Method for Total Sulfur in the Analysis Sample of Coal and Coke, IBR approved for appendix A: Method 19, Section 12.5.2.1.3.
- (48) ASTM D3178-73 (Reapproved 1979), 89, Standard Test Methods for

Carbon and Hydrogen in the Analysis Sample of Coal and Coke, IBR approved for §60.45(f)(5)(i).

- (49) ASTM D3246-81, 92, 96, Standard Test Method for Sulfur in Petroleum Gas by Oxidative Microcoulometry, IBR approved for §60.335(b)(10)(ii).
- (50) ASTM D3246-05, Standard Test Method for Sulfur in Petroleum Gas by Oxidative Microcoulometry, IBR approved for 60.4415(a)(1)(ii).
- (51) ASTM D3270-73T, 80, 91, 95, Standard Test Methods for Analysis for Fluoride Content of the Atmosphere and Plant Tissues (Semiautomated Method), IBR approved for appendix A: Method 13A, Section 16.1.
- (52) ASTM D3286-85, 96, Standard Test Method for Gross Calorific Value of Coal and Coke by the Isoperibol Bomb Calorimeter, IBR approved for appendix A: Method 19, Section 12.5.2.1.3.
- (53) ASTM D3370-76, 95a, Standard Practices for Sampling Water, IBR approved for §60.564(j).
- (54) ASTM D3792-79, 91, Standard Test Method for Water Content of Water-Reducible Paints by Direct Injection into a Gas Chromatograph, IBR approved for appendix A: Method 24, Section 6.3.
- (55) ASTM D4017-81, 90, 96a, Standard Test Method for Water in Paints and Paint Materials by the Karl Fischer Titration Method, IBR approved for appendix A: Method 24, Section 6.4.
- (56) ASTM D4057-81, 95, Standard Practice for Manual Sampling of Petroleum and Petroleum Products, IBR approved for appendix A: Method 19, Section 12.5.2.2.3.
- (57) ASTM D4057-95 (Reapproved 2000), Standard Practice for Manual Sampling of Petroleum and Petroleum Products, IBR approved for §60.4415(a)(1).
- (58) ASTM D4084-82, 94, Standard Test Method for Analysis of Hydrogen Sulfide in Gaseous Fuels (Lead Acetate Reaction Rate Method), IBR approved for §60.334(h)(1).
- (59) ASTM D4084-05, Standard Test Method for Analysis of Hydrogen Sulfide in Gaseous Fuels (Lead Acetate Reaction Rate Method), IBR approved for §§ 60.4360 and 60.4415(a)(1)(ii).
- (60) ASTM D4177-95, Standard Practice for Automatic Sampling of Petroleum and Petroleum Products, IBR ap-

- proved for appendix A: Method 19, Section 12.5.2.2.1.
- (61) ASTM D4177-95 (Reapproved 2000), Standard Practice for Automatic Sampling of Petroleum and Petroleum Products, IBR approved for §60.4415(a)(1).
- (62) ASTM D4239-85, 94, 97, Standard Test Methods for Sulfur in the Analysis Sample of Coal and Coke Using High Temperature Tube Furnace Combustion Methods, IBR approved for appendix A: Method 19, Section 12.5.2.1.3.
- (63) ASTM D4294-02, Standard Test Method for Sulfur in Petroleum and Petroleum Products by Energy-Dispersive X-Ray Fluorescence Spectrometry, IBR approved for §60.335(b)(10)(i).
- (64) ASTM D4294-03, Standard Test Method for Sulfur in Petroleum and Petroleum Products by Energy-Dispersive X-Ray Fluorescence Spectrometry, IBR approved for §60.4415(a)(1)(i).
- (65) ASTM D4442-84, 92, Standard Test Methods for Direct Moisture Content Measurement in Wood and Wood-base Materials, IBR approved for appendix A: Method 28, Section 16.1.1.
- (66) ASTM D4444-92, Standard Test Methods for Use and Calibration of Hand-Held Moisture Meters, IBR approved for appendix A: Method 28, Section 16.1.1.
- (67) ASTM D4457-85 (Reapproved 1991), Test Method for Determination of Dichloromethane and 1, 1, 1-Trichloroethane in Paints and Coatings by Direct Injection into a Gas Chromatograph, IBR approved for appendix A: Method 24, Section 6.5.
- (68) ASTM D4468-85 (Reapproved 2000), Standard Test Method for Total Sulfur in Gaseous Fuels by Hydrogenolysis and Rateometric Colorimetry, IBR approved for §§ 60.335(b)(10)(ii) and 60.4415(a)(1)(ii).
- (69) ASTM D4629-02, Standard Test Method for Trace Nitrogen in Liquid Petroleum Hydrocarbons by Syringe/Inlet Oxidative Combustion and Chemiluminescence Detection, IBR approved for §§ 60.49b(e) and 60.335(b)(9)(i).
- (70) ASTM D4809-95, Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter (Precision Method), IBR approved for §§60.18(f)(3), 60.485(g)(6), 60.485a(g)(6), 60.564(f)(3), 60.614(d)(4), 60.664(e)(4), and 60.704(d)(4).

- (71) ASTM D4810-88 (Reapproved 1999), Standard Test Method for Hydrogen Sulfide in Natural Gas Using Length of Stain Detector Tubes, IBR approved for §§ 60.4360 and 60.4415(a)(1)(ii).
- (72) ASTM D5287-97 (Reapproved 2002), Standard Practice for Automatic Sampling of Gaseous Fuels, IBR approved for §60.4415(a)(1).
- (73) ASTM D5403-93, Standard Test Methods for Volatile Content of Radiation Curable Materials, IBR approved for appendix A: Method 24, Section 6.6.
- (74) ASTM D5453-00, Standard Test Method for Determination of Total Sulfur in Light Hydrocarbons, Motor Fuels and Oils by Ultraviolet Fluorescence, IBR approved for §60.335(b)(10)(i).
- (75) ASTM D5453-05, Standard Test Method for Determination of Total Sulfur in Light Hydrocarbons, Motor Fuels and Oils by Ultraviolet Fluorescence, IBR approved for §60.4415(a)(1)(i).
- (76) ASTM D5504-01, Standard Test Method for Determination of Sulfur Compounds in Natural Gas and Gaseous Fuels by Gas Chromatography and Chemiluminescence, IBR approved for §§ 60.334(h)(1) and 60.4360.
- (77) ASTM D5762-02, Standard Test Method for Nitrogen in Petroleum and Petroleum Products by Boat-Inlet Chemiluminescence, IBR approved for §60.335(b)(9)(i).
- (78) ASTM D5865-98, Standard Test Method for Gross Calorific Value of Coal and Coke, IBR approved for §60.45(f)(5)(ii), 60.46(c)(2), and appendix A: Method 19, Section 12.5.2.1.3.
- (79) ASTM D6216-98, Standard Practice for Opacity Monitor Manufacturers to Certify Conformance with Design and Performance Specifications, IBR approved for appendix B, Performance Specification 1.
- (80) ASTM D6228-98, Standard Test Method for Determination of Sulfur Compounds in Natural Gas and Gaseous Fuels by Gas Chromatography and Flame Photometric Detection, IBR approved for §60.334(h)(1).
- (81) ASTM D6228-98 (Reapproved 2003), Standard Test Method for Determination of Sulfur Compounds in Natural Gas and Gaseous Fuels by Gas Chromatography and Flame Photo-

- metric Detection, IBR approved for §§ 60.4360 and 60.4415.
- (82) ASTM D6348-03, Standard Test Method for Determination of Gaseous Compounds by Extractive Direct Interface Fourier Transform Infrared (FTIR) Spectroscopy, IBR approved for table 7 of subpart IIII of this part and table 2 of subpart JJJJ of this part.
- (83) ASTM D6366-99, Standard Test Method for Total Trace Nitrogen and Its Derivatives in Liquid Aromatic Hydrocarbons by Oxidative Combustion and Electrochemical Detection, IBR approved for §60.335(b)(9)(i).
- (84) ASTM D6420-99 (Reapproved 2004) Standard Test Method for Determination of Gaseous Organic Compounds by Direct Interface Gas Chromatography-Mass Spectrometry, IBR approved for table 2 of subpart JJJJ of this part.
- (85) ASTM D6522-00, Standard Test Method for Determination of Nitrogen Oxides, Carbon Monoxide, and Oxygen Concentrations in Emissions from Natural Gas-Fired Reciprocating Engines, Combustion Turbines, Boilers, and Process Heaters Using Portable Analyzers, IBR approved for §60.335(a).
- (86) ASTM D6522-00 (Reapproved 2005), Standard Test Method for Determination of Nitrogen Oxides, Carbon Monoxide, and Oxygen Concentrations in Emissions from Natural Gas-Fired Reciprocating Engines, Combustion Turbines, Boilers, and Process Heaters Using Portable Analyzers, IBR approved for table 2 of subpart JJJJ of this part.
- (87) ASTM D6667-01, Standard Test Method for Determination of Total Volatile Sulfur in Gaseous Hydrocarbons and Liquefied Petroleum Gases by Ultraviolet Fluorescence, IBR approved for §60.335(b)(10)(ii).
- (88) ASTM D6667-04, Standard Test Method for Determination of Total Volatile Sulfur in Gaseous Hydrocarbons and Liquefied Petroleum Gases by Ultraviolet Fluorescence, IBR approved for \$60.4415(a)(1)(ii).
- (89) ASTM D6784–02, Standard Test Method for Elemental, Oxidized, Particle-Bound and Total Mercury in Flue Gas Generated from Coal-Fired Stationary Sources (Ontario Hydro Method), IBR approved for appendix B to part 60, Performance Specification 12A, Section 8.6.2.

- (90) ASTM D6784–02, Standard Test Method for Elemental, Oxidized, Particle-Bound and Total Mercury in Flue Gas Generated from Coal-Fired Stationary Sources (Ontario Hydro Method), IBR approved for Appendix B to part 60, Performance Specification 12A, Section 8.6.2 and §60.56c(b)(13) of subpart Ec of this part.
- (91) ASTM £169-63, 77, 93, General Techniques of Ultraviolet Quantitative Analysis, IBR approved for §§ 60.485a(d)(1), 60.593(b)(2), 60.593a(b)(2), and 60.632(f).
- (92) ASTM E260-73, 91, 96, General Gas Chromatography Procedures, IBR approved for  $\S60.485a(d)(1)$ , 60.593(b)(2), 60.593a(b)(2), and 60.632(f).
- (b) The following material is available for purchase from the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.
- (1) AOAC Method 9, Official Methods of Analysis of the Association of Official Analytical Chemists, 11th edition, 1970, pp. 11–12, IBR approved January 27, 1983 for §§ 60.204(b)(3), 60.214(b)(3), 60.224(b)(3), 60.234(b)(3).
- (c) The following material is available for purchase from the American Petroleum Institute, 1220 L Street NW., Washington, DC 20005.
- (1) API Publication 2517, Evaporation Loss from External Floating Roof Tanks, Second Edition, February 1980, IBR approved January 27, 1983, for §§ 60.111(i), 60.111a(f), 60.111a(f)(1) and 60.116b(e)(2)(i).
- (d) The following material is available for purchase from the Technical Association of the Pulp and Paper Industry (TAPPI), Dunwoody Park, Atlanta, GA 30341.
- (1) TAPPI Method T624 os-68, IBR approved January 27, 1983 for §60.285(d)(3).
- (e) The following material is available for purchase from the Water Pollution Control Federation (WPCF), 2626 Pennsylvania Avenue NW., Washington, DC 20037.
- (1) Method 209A, Total Residue Dried at 103–105 °C, in Standard Methods for the Examination of Water and Wastewater, 15th Edition, 1980, IBR approved February 25, 1985 for §60.683(b).
- (f) The following material is available for purchase from the following address: Underwriter's Laboratories,

- Inc. (UL), 333 Pfingsten Road, Northbrook, IL 60062.
- (1) UL 103, Sixth Edition revised as of September 3, 1986, Standard for Chimneys, Factory-built, Residential Type and Building Heating Appliance.
- (g) The following material is available for purchase from the following address: West Coast Lumber Inspection Bureau, 6980 SW. Barnes Road, Portland, OR 97223.
- (1) West Coast Lumber Standard Grading Rules No. 16, pages 5–21 and 90 and 91, September 3, 1970, revised 1984.
- (h) The following material is available for purchase from the American Society of Mechanical Engineers (ASME), Three Park Avenue, New York, NY 10016-5990.
- (1) ASME QRO-1-1994, Standard for the Qualification and Certification of Resource Recovery Facility Operators, IBR approved for §§ 60.56a, 60.54b(a), 60.54b(b), 60.1185(a), 60.1185(c)(2), 60.1675(a), and 60.1675(c)(2).
- (2) ASME PTC 4.1–1964 (Reaffirmed 1991), Power Test Codes: Test Code for Steam Generating Units (with 1968 and 1969 Addenda), IBR approved for \$\$ (60.46b of subpart Db of this part, 60.58a(h)(6)(ii), 60.58b(i)(6)(ii), 60.1320(a)(3) and 60.1810(a)(3).
- (3) ASME Interim Supplement 19.5 on Instruments and Apparatus: Application, Part II of Fluid Meters, 6th Edition (1971), IBR approved for §§ 60.58a(h)(6)(ii), 60.58b(i)(6)(ii), 60.1320(a)4), and 60.1810(a)(4).
- (4) ANSI/ASME PTC 19.10-1981, Flue and Exhaust Gas Analyses [Part 10, Instruments and Apparatus], IBR approved for §60.56c(b)(4) of subpart Ec,  $\S60.106(e)(2)$  of subpart J,  $\S\S60.104a(d)(3)$ , (d)(5), (d)(6), (h)(3), (h)(4), (h)(5), (i)(3),(i)(5),(j)(3),(i)(4),and (j)(4),60.105a(d)(4), (f)(2), (f)(4), (g)(2), and 60.106a(a)(1)(iii),(g)(4),(a)(2)(iii),(a)(2)(v), (a)(2)(viii), (a)(3)(ii),(a)(3)(v), and 60.107a(a)(1)(ii), (a)(1)(iv), (a)(2)(ii), (c)(2), (c)(4), and (d)(2) of subpart Ja, tables 1 and 3 of subpart EEEE, tables 2 and 4 of subpart FFFF, of subpart JJJJ, §§ 60.4415(a)(2) and 60.4415(a)(3) of subpart KKKK of this part.
- (j) "Standard Methods for the Examination of Water and Wastewater," 16th edition, 1985. Method 303F: "Determination of Mercury by the Cold Vapor

Technique." This document may be obtained from the American Public Health Association, 1015 18th Street, NW., Washington, DC 20036, and is incorporated by reference for appendix A to part 60, Method 29, Sections 9.2.3; 10.3; and 11.1.3.

- (k) This material is available for purchase from the American Hospital Association (AHA) Service, Inc., Post Office Box 92683, Chicago, Illinois 60675–2683. You may inspect a copy at EPA's Air and Radiation Docket and Information Center (Docket A-91-61, Item IV-J-124), Room M-1500, 1200 Pennsylvania Ave., NW., Washington, DC.
- (1) An Ounce of Prevention: Waste Reduction Strategies for Health Care Facilities. American Society for Health Care Environmental Services of the American Hospital Association. Chicago, Illinois. 1993. AHA Catalog No. 057007. ISBN 0-87258-673-5. IBR approved for \$60.35e and \$60.55c.
- (1) This material is available for purchase from the National Technical Information Services, 5285 Port Royal Road, Springfield, Virginia 22161. You may inspect a copy at EPA's Air and Radiation Docket and Information Center (Docket A-91-61, Item IV-J-125), Room M-1500, 1200 Pennsylvania Ave., NW., Washington, DC.
- (1) OMB Bulletin No. 93–17: Revised Statistical Definitions for Metropolitan Areas. Office of Management and Budget, June 30, 1993. NTIS No. PB 93–192–664. IBR approved for § 60.31e.
  - (2) [Reserved]
- (m) This material is available for purchase from at least one of the following addresses: The Gas Processors Association, 6526 East 60th Street, Tulsa, OK, 74145; or Information Handling Services, 15 Inverness Way East, PO Box 1154, Englewood, CO 80150–1154. You may inspect a copy at EPA's Air and Radiation Docket and Information Center, Room B108, 1301 Constitution Ave., NW., Washington, DC 20460. You may inspect a copy at EPA's Air and Radiation Docket and Information Center, Room 3334, 1301 Constitution Ave., NW., Washington, DC 20460.
- (1) Gas Processors Association Standard 2377–86, Test for Hydrogen Sulfide and Carbon Dioxide in Natural Gas Using Length of Stain Tubes, 1986 Revision, IBR approved for §§ 60.105(b)(1)(iv),

- 60.107a(b)(1)(iv), 60.334(h)(1), 60.4360, and 60.4415(a)(1)(ii).
  - (2) [Reserved]
- (n) This material is available for purchase from IHS Inc., 15 Inverness Way East, Englewood, CO 80112.
- (1) International Organization for Standards 8178-4: 1996(E), Reciprocating Internal Combustion Engines— Exhaust Emission Measurement—part 4: Test Cycles for Different Engine Applications, IBR approved for §60.4241(b).
  - (2) [Reserved]

[48 FR 3735, Jan. 27, 1983]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §60.17, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and on GPO Access.

# § 60.18 General control device and work practice requirements.

- (a) Introduction. (1) This section contains requirements for control devices used to comply with applicable subparts of 40 CFR parts 60 and 61. The requirements are placed here for administrative convenience and apply only to facilities covered by subparts referring to this section.
- (2) This section also contains requirements for an alternative work practice used to identify leaking equipment. This alternative work practice is placed here for administrative convenience and is available to all subparts in 40 CFR parts 60, 61, 63, and 65 that require monitoring of equipment with a 40 CFR part 60, Appendix A-7, Method 21 monitor.
- (b) Flares. Paragraphs (c) through (f) apply to flares.
- (c)(1) Flares shall be designed for and operated with no visible emissions as determined by the methods specified in paragraph (f), except for periods not to exceed a total of 5 minutes during any 2 consecutive hours.
- (2) Flares shall be operated with a flame present at all times, as determined by the methods specified in paragraph (f).
- (3) An owner/operator has the choice of adhering to either the heat content specifications in paragraph (c)(3)(ii) of this section and the maximum tip velocity specifications in paragraph (c)(4)

of this section, or adhering to the requirements in paragraph (c)(3)(i) of this section.

(i)(A) Flares shall be used that have a diameter of 3 inches or greater, are nonassisted, have a hydrogen content of 8.0 percent (by volume), or greater, and are designed for and operated with an exit velocity less than 37.2 m/sec (122 ft/sec) and less than the velocity,  $V_{\rm max},$  as determined by the following equation:

$$V_{max} = (X_{H2} - K_1) * K_2$$

Where:

 $V_{max}$ =Maximum permitted velocity, m/sec.  $K_1$ =Constant, 6.0 volume-percent hydrogen.  $K_2$ =Constant, 3.9(m/sec)/volume-percent hydrogen.

 $\rm X_{H2}$ =The volume-percent of hydrogen, on a wet basis, as calculated by using the American Society for Testing and Materials (ASTM) Method D1946–77. (Incorporated by reference as specified in  $\S 60.17$ ).

- (B) The actual exit velocity of a flare shall be determined by the method specified in paragraph (f)(4) of this section.
- (ii) Flares shall be used only with the net heating value of the gas being combusted being 11.2 MJ/scm (300 Btu/scf) or greater if the flare is steam-assisted or air-assisted; or with the net heating value of the gas being combusted being 7.45 MJ/scm (200 Btu/scf) or greater if the flare is nonassisted. The net heating value of the gas being combusted shall be determined by the methods specified in paragraph (f)(3) of this section.
- (4)(i) Steam-assisted and nonassisted flares shall be designed for and operated with an exit velocity, as determined by the methods specified in paragraph (f)(4) of this section, less than 18.3 m/sec (60 ft/sec), except as provided in paragraphs (c)(4) (ii) and (iii) of this section.
- (ii) Steam-assisted and nonassisted flares designed for and operated with an exit velocity, as determined by the methods specified in paragraph (f)(4), equal to or greater than 18.3 m/sec (60 ft/sec) but less than 122 m/sec (400 ft/sec) are allowed if the net heating

value of the gas being combusted is greater than 37.3 MJ/scm (1,000 Btu/scf).

- (iii) Steam-assisted and nonassisted flares designed for and operated with an exit velocity, as determined by the methods specified in paragraph (f)(4), less than the velocity,  $V_{max}$ , as determined by the method specified in paragraph (f)(5), and less than 122 m/sec (400 ft/sec) are allowed.
- (5) Air-assisted flares shall be designed and operated with an exit velocity less than the velocity,  $V_{max}$ , as determined by the method specified in paragraph (f)(6).
- (6) Flares used to comply with this section shall be steam-assisted, air-assisted, or nonassisted.
- (d) Owners or operators of flares used to comply with the provisions of this subpart shall monitor these control devices to ensure that they are operated and maintained in conformance with their designs. Applicable subparts will provide provisions stating how owners or operators of flares shall monitor these control devices.
- (e) Flares used to comply with provisions of this subpart shall be operated at all times when emissions may be vented to them.
- (f)(1) Method 22 of appendix A to this part shall be used to determine the compliance of flares with the visible emission provisions of this subpart. The observation period is 2 hours and shall be used according to Method 22.
- (2) The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame.
- (3) The net heating value of the gas being combusted in a flare shall be calculated using the following equation:

$$H_{T} = K \sum_{i=1}^{n} C_{i}H_{i}$$

where:

 $H_T$ =Net heating value of the sample, MJ/scm; where the net enthalpy per mole of offgas is based on combustion at 25 °C and 760 mm Hg, but the standard temperature for determining the volume corresponding to one mole is 20 °C;

K = Constant, 
$$\frac{1}{1.740 \times 10^{-7}}$$
  $\left(\frac{1}{\text{ppm}}\right)$   $\left(\frac{\text{g mole}}{\text{scm}}\right)$   $\left(\frac{\text{MJ}}{\text{kcal}}\right)$ 

# where the standard temperature for $(\frac{g \text{ mole}}{scm})$ is 20°C;

C<sub>i</sub>=Concentration of sample component i in ppm on a wet basis, as measured for organics by Reference Method 18 and measured for hydrogen and carbon monoxide by ASTM D1946-77 or 90 (Reapproved 1994) (Incorporated by reference as specified in §60.17); and

 $H_i{=}Net\ heat\ of\ combustion\ of\ sample\ component\ i,\ kcal/g\ mole\ at\ 25\ ^{\circ}C\ and\ 760\ mm\ Hg.$  The heats of combustion may be determined using ASTM D2382–76 or 88 or D4809–95 (incorporated by reference as specified in §60.17) if published values are not available or cannot be calculated.

- (4) The actual exit velocity of a flare shall be determined by dividing the volumetric flowrate (in units of standard temperature and pressure), as determined by Reference Methods 2, 2A, 2C, or 2D as appropriate; by the unobstructed (free) cross sectional area of the flare tip.
- (5) The maximum permitted velocity,  $V_{max}$ , for flares complying with paragraph (c)(4)(iii) shall be determined by the following equation.

 $Log_{10} (V_{max}) = (H_T + 28.8)/31.7$ 

 $V_{\rm max}$ =Maximum permitted velocity, M/sec 28.8=Constant

31.7=Constant

 $H_T$ =The net heating value as determined in paragraph (f)(3).

(6) The maximum permitted velocity,  $V_{max}$ , for air-assisted flares shall be determined by the following equation.  $V_{max}$ =8.706+0.7084 ( $H_T$ )

 $V_{max}$ =Maximum permitted velocity, m/sec 8.706=Constant

0.7084=Constant

 $H_T$ =The net heating value as determined in paragraph (f)(3).

(g) Alternative work practice for monitoring equipment for leaks. Paragraphs (g), (h), and (i) of this section apply to all equipment for which the applicable subpart requires monitoring with a 40 CFR part 60, Appendix A-7, Method 21 monitor, except for closed vent systems, equipment designated as leakless, and equipment identified in the applicable subpart as having no de-

tectable emissions, as indicated by an instrument reading of less than 500 ppm above background. An owner or operator may use an optical gas imaging instrument instead of a 40 CFR part 60, Appendix A-7, Method 21 monitor. Requirements in the existing subparts that are specific to the Method 21 instrument do not apply under this section. All other requirements in the applicable subpart that are not addressed in paragraphs (g), (h), and (i) of this section apply to this standard. For example, equipment specification requirements, and non-Method 21 instrument recordkeeping and reporting requirements in the applicable subpart continue to apply. The terms defined in paragraphs (g)(1) through (5) of this section have meanings that are specific to the alternative work practice standard in paragraphs (g), (h), and (i) of this section.

- (1) Applicable subpart means the subpart in 40 CFR parts 60, 61, 63, or 65 that requires monitoring of equipment with a 40 CFR part 60, Appendix A-7, Method 21 monitor.
- (2) Equipment means pumps, valves, pressure relief valves, compressors, open-ended lines, flanges, connectors, and other equipment covered by the applicable subpart that require monitoring with a 40 CFR part 60, Appendix A–7, Method 21 monitor.
- (3) *Imaging* means making visible emissions that may otherwise be invisible to the naked eye.
- (4) Optical gas imaging instrument means an instrument that makes visible emissions that may otherwise be invisible to the naked eve.
- (5) Repair means that equipment is adjusted, or otherwise altered, in order to eliminate a leak.
  - (6) Leak means:
- (i) Any emissions imaged by the optical gas instrument;
  - (ii) Indications of liquids dripping;

- (iii) Indications by a sensor that a seal or barrier fluid system has failed; or
- (iv) Screening results using a 40 CFR part 60, Appendix A-7, Method 21 monitor that exceed the leak definition in the applicable subpart to which the equipment is subject.
- (h) The alternative work practice standard for monitoring equipment for leaks is available to all subparts in 40 CFR parts 60, 61, 63, and 65 that require monitoring of equipment with a 40 CFR part 60, Appendix A-7, Method 21 monitor.
- (1) An owner or operator of an affected source subject to CFR parts 60, 61, 63, or 65 can choose to comply with the alternative work practice requirements in paragraph (i) of this section instead of using the 40 CFR part 60, Appendix A-7, Method 21 monitor to identify leaking equipment. The owner or operator must document the equipment, process units, and facilities for which the alternative work practice will be used to identify leaks.
- (2) Any leak detected when following the leak survey procedure in paragraph (i)(3) of this section must be identified for repair as required in the applicable subpart.
- (3) If the alternative work practice is used to identify leaks, re-screening after an attempted repair of leaking equipment must be conducted using either the alternative work practice or the 40 CFR part 60, Appendix A-7, Method 21 monitor at the leak definition required in the applicable subpart to which the equipment is subject.
- (4) The schedule for repair is as required in the applicable subpart.
- (5) When this alternative work practice is used for detecting leaking equipment, choose one of the monitoring frequencies listed in Table 1 to subpart A of this part in lieu of the monitoring frequency specified for regulated equipment in the applicable subpart. Reduced monitoring frequencies for good performance are not applicable when using the alternative work practice.
- (6) When this alternative work practice is used for detecting leaking equipment the following are not applicable for the equipment being monitored:
- (i) Skip period leak detection and repair;

- (ii) Quality improvement plans; or
- (iii) Complying with standards for allowable percentage of valves and pumps to leak.
- (7) When the alternative work practice is used to detect leaking equipment, the regulated equipment in paragraph (h)(1)(i) of this section must also be monitored annually using a 40 CFR part 60, Appendix A-7, Method 21 monitor at the leak definition required in the applicable subpart. The owner or operator may choose the specific monitoring period (for example, first quarter) to conduct the annual monitoring. Subsequent monitoring must be conducted every 12 months from the initial period. Owners or operators must keep records of the annual Method 21 screening results, as specified in paragraph (i)(4)(vii) of this section.
- (i) An owner or operator of an affected source who chooses to use the alternative work practice must comply with the requirements of paragraphs (i)(1) through (i)(5) of this section.
- (1) Instrument Specifications. The optical gas imaging instrument must comply with the requirements in (i)(1)(i) and (i)(1)(ii) of this section.
- (i) Provide the operator with an image of the potential leak points for each piece of equipment at both the detection sensitivity level and within the distance used in the daily instrument check described in paragraph (i)(2) of this section. The detection sensitivity level depends upon the frequency at which leak monitoring is to be performed.
- (ii) Provide a date and time stamp for video records of every monitoring event.
- (2) Daily Instrument Check. On a daily basis, and prior to beginning any leak monitoring work, test the optical gas imaging instrument at the mass flow rate determined in paragraph (i)(2)(i) of this section in accordance with the procedure specified in paragraphs (i)(2)(ii) through (i)(2)(iv) of this section for each camera configuration used during monitoring (for example, different lenses used), unless an alternative method to demonstrate daily instrument checks has been approved in accordance with paragraph (i)(2)(v) of this section.

- (i) Calculate the mass flow rate to be used in the daily instrument check by following the procedures in paragraphs (i)(2)(i)(A) and (i)(2)(i)(B) of this section.
- (A) For a specified population of equipment to be imaged by the instrument, determine the piece of equipment in contact with the lowest mass fraction of chemicals that are detectable, within the distance to be used in paragraph (i)(2)(iv)(B) of this section, at or below the standard detection sensitivity level.
- (B) Multiply the standard detection sensitivity level, corresponding to the selected monitoring frequency in Table 1 of subpart A of this part, by the mass fraction of detectable chemicals from the stream identified in paragraph (i)(2)(i)(A) of this section to determine the mass flow rate to be used in the daily instrument check, using the following equation.

$$\mathbf{E}_{dic} = \left(\mathbf{E}_{sds}\right) \sum_{i=1}^{k} \mathbf{x}_{i}$$

Where:

 $E_{\rm dic}$  = Mass flow rate for the daily instrument check, grams per hour

 $\mathbf{x}_i$  = Mass fraction of detectable chemical(s) i seen by the optical gas imaging instrument, within the distance to be used in paragraph (i)(2)(iv)(B) of this section, at or below the standard detection sensitivity level,  $\mathbf{E}_{sds}$ .

 $E_{sds}$  = Standard detection sensitivity level from Table 1 to subpart A, grams per hour k = Total number of detectable chemicals emitted from the leaking equipment and seen by the optical gas imaging instrument.

- (ii) Start the optical gas imaging instrument according to the manufacturer's instructions, ensuring that all appropriate settings conform to the manufacturer's instructions.
- (iii) Use any gas chosen by the user that can be viewed by the optical gas imaging instrument and that has a purity of no less than 98 percent.
- (iv) Establish a mass flow rate by using the following procedures:
- (A) Provide a source of gas where it will be in the field of view of the optical gas imaging instrument.
- (B) Set up the optical gas imaging instrument at a recorded distance from the outlet or leak orifice of the flow

meter that will not be exceeded in the actual performance of the leak survey. Do not exceed the operating parameters of the flow meter.

- (C) Open the valve on the flow meter to set a flow rate that will create a mass emission rate equal to the mass rate specified in paragraph (i)(2)(i) of this section while observing the gas flow through the optical gas imaging instrument viewfinder. When an image of the gas emission is seen through the viewfinder at the required emission rate, make a record of the reading on the flow meter.
- (v) Repeat the procedures specified in paragraphs (i)(2)(ii) through (i)(2)(iv) of this section for each configuration of the optical gas imaging instrument used during the leak survey.
- (vi) To use an alternative method to demonstrate daily instrument checks, apply to the Administrator for approval of the alternative under §60.13(i).
- (3) Leak Survey Procedure. Operate the optical gas imaging instrument to image every regulated piece of equipment selected for this work practice in accordance with the instrument manufacturer's operating parameters. All emissions imaged by the optical gas imaging instrument are considered to be leaks and are subject to repair. All emissions visible to the naked eye are also considered to be leaks and are subject to repair.
- (4) Recordkeeping. You must keep the records described in paragraphs (i)(4)(i) through (i)(4)(vii) of this section:
- (i) The equipment, processes, and facilities for which the owner or operator chooses to use the alternative work practice.
- (ii) The detection sensitivity level selected from Table 1 to subpart A of this part for the optical gas imaging instrument.
- (iii) The analysis to determine the piece of equipment in contact with the lowest mass fraction of chemicals that are detectable, as specified in paragraph (i)(2)(i)(A) of this section.
- (iv) The technical basis for the mass fraction of detectable chemicals used in the equation in paragraph (i)(2)(i)(B) of this section.

- (v) The daily instrument check. Record the distance, per paragraph (i)(2)(iv)(B) of this section, and the flow per reading, meter paragraph (i)(2)(iv)(C) of this section, at which the leak was imaged. Keep a video record of the daily instrument check for each configuration of the optical gas imaging instrument used during the leak survey (for example, the daily instrument check must be conducted for each lens used). The video record must include a time and date stamp for each daily instrument check. The video record must be kept for 5 years.
- (vi) Recordkeeping requirements in the applicable subpart. A video record must be used to document the leak survey results. The video record must include a time and date stamp for each monitoring event. A video record can be used to meet the recordkeeping requirements of the applicable subparts if each piece of regulated equipment selected for this work practice can be identified in the video record. The video record must be kept for 5 years.
- (vii) The results of the annual Method 21 screening required in paragraph (h)(7) of this section. Records must be kept for all regulated equipment specified in paragraph (h)(1) of this section. Records must identify the equipment screened, the screening value measured by Method 21, the time and date of the screening, and calibration information required in the existing applicable subpart.
- (5) Reporting. Submit the reports required in the applicable subpart. Submit the records of the annual Method 21 screening required in paragraph (h)(7) of this section to the Administrator via e-mail to CCG-AWP@EPA.GOV.

[51 FR 2701, Jan. 21, 1986, as amended at 63 FR 24444, May 4, 1998; 65 FR 61752, Oct. 17, 2000; 73 FR 78209, Dec. 22, 2008]

# § 60.19 General notification and reporting requirements.

- (a) For the purposes of this part, time periods specified in days shall be measured in calendar days, even if the word "calendar" is absent, unless otherwise specified in an applicable requirement.
- (b) For the purposes of this part, if an explicit postmark deadline is not speci-

fied in an applicable requirement for the submittal of a notification, application, report, or other written communication to the Administrator, the owner or operator shall postmark the submittal on or before the number of days specified in the applicable requirement. For example, if a notification must be submitted 15 days before a particular event is scheduled to take place, the notification shall be postmarked on or before 15 days preceding the event; likewise, if a notification must be submitted 15 days after a particular event takes place, the notification shall be delivered or postmarked on or before 15 days following the end of the event. The use of reliable non-Government mail carriers that provide indications of verifiable delivery of information required to be submitted to the Administrator, similar to the postmark provided by the U.S. Postal Service, or alternative means of delivery, including the use of electronic media, agreed to by the permitting authority, is acceptable.

(c) Notwithstanding time periods or postmark deadlines specified in this part for the submittal of information to the Administrator by an owner or operator, or the review of such information by the Administrator, such time periods or deadlines may be changed by mutual agreement between the owner or operator and the Administrator. Procedures governing the implementation of this provision are specified in paragraph (f) of this section.

(d) If an owner or operator of an affected facility in a State with delegated authority is required to submit periodic reports under this part to the State, and if the State has an established timeline for the submission of periodic reports that is consistent with the reporting frequency(ies) specified for such facility under this part, the owner or operator may change the dates by which periodic reports under this part shall be submitted (without changing the frequency of reporting) to be consistent with the State's schedule by mutual agreement between the owner or operator and the State. The allowance in the previous sentence applies in each State beginning 1 year after the affected facility is required to

be in compliance with the applicable subpart in this part. Procedures governing the implementation of this provision are specified in paragraph (f) of this section.

(e) If an owner or operator supervises one or more stationary sources affected by standards set under this part and standards set under part 61, part 63, or both such parts of this chapter, he/she may arrange by mutual agreement between the owner or operator and the Administrator (or the State with an approved permit program) a common schedule on which periodic reports required by each applicable standard shall be submitted throughout the year. The allowance in the previous sentence applies in each State beginning 1 year after the stationary source is required to be in compliance with the applicable subpart in this part, or 1 year after the stationary source is required to be in compliance with the applicable 40 CFR part 61 or part 63 of this chapter standard, whichever is latest. Procedures governing the implementation of this provision are specified in paragraph (f) of this section.

(f)(1)(i) Until an adjustment of a time period or postmark deadline has been approved by the Administrator under paragraphs (f)(2) and (f)(3) of this section, the owner or operator of an affected facility remains strictly subject to the requirements of this part.

- (ii) An owner or operator shall request the adjustment provided for in paragraphs (f)(2) and (f)(3) of this section each time he or she wishes to change an applicable time period or postmark deadline specified in this part.
- (2) Notwithstanding time periods or postmark deadlines specified in this part for the submittal of information to the Administrator by an owner or operator, or the review of such information by the Administrator, such time periods or deadlines may be changed by mutual agreement between the owner or operator and the Administrator. An owner or operator who wishes to request a change in a time period or postmark deadline for a particular requirement shall request the adjustment in writing as soon as practicable before the subject activity is required to take place. The owner or operator

shall include in the request whatever information he or she considers useful to convince the Administrator that an adjustment is warranted.

- (3) If, in the Administrator's judgment, an owner or operator's request for an adjustment to a particular time period or postmark deadline is warranted, the Administrator will approve the adjustment. The Administrator will notify the owner or operator in writing of approval or disapproval of the request for an adjustment within 15 calendar days of receiving sufficient information to evaluate the request.
- (4) If the Administrator is unable to meet a specified deadline, he or she will notify the owner or operator of any significant delay and inform the owner or operator of the amended schedule.

[59 FR 12428, Mar. 16, 1994, as amended at 64 FR 7463, Feb. 12, 1998]

TABLE 1 TO SUBPART A TO PART 60-DETECTION SENSITIVITY LEVELS (GRAMS PER HOUR)

Monitoring frequency per subpart <sup>a</sup>	Detection sen- sitivity level
Bi-Monthly	60
Semi-Quarterly	85
Monthly	100

a When this alternative work practice is used to identify leaking equipment, the owner or operator must choose one of the monitoring frequencies listed in this table in lieu of the monitoring frequency specified in the applicable subpart. Bimonthly means every other month. Semi-quarterly means twice per quarter. Monthly means once per month.

[73 FR 78211, Dec. 22, 2008]

# Subpart B—Adoption and Submittal of State Plans for Designated Facilities

Source: 40 FR 53346, Nov. 17, 1975, unless otherwise noted.

#### § 60.20 Applicability.

The provisions of this subpart apply to States upon publication of a final guideline document under §60.22(a).

#### § 60.21 Definitions.

Terms used but not defined in this subpart shall have the meaning given them in the Act and in subpart A:

(a) Designated pollutant means any air pollutant, the emissions of which are subject to a standard of performance for new stationary sources, but for