

Pt. 63, Subpt. G, Table 10

40 CFR Ch. I (7-1-10 Edition)

Chemical name	CAS No. ^a	Fr
Vinyl acetate	108054	0.99
Vinyl chloride (Chloroethylene)	75014	0.99
Vinylidene chloride (1,1-Dichloroethylene)	75354	0.99
Xylene (m-)	108383	0.99
Xylene (o-)	95476	0.99
Xylene (p-)	106423	0.99

^a CAS numbers refer to the Chemical Abstracts Service registry number assigned to specific compounds, isomers, or mixtures of compounds.

[59 FR 19468, Apr. 22, 1994, as amended at 71 FR 76615, Dec. 21, 2006]

TABLE 10 TO SUBPART G OF PART 63—WASTEWATER—COMPLIANCE OPTIONS FOR WASTEWATER TANKS

Capacity (m ³)	Maximum true vapor pressure (kPa)	Control requirements
<75		§ 63.133(a)(1)
"75 and <151	<13.1	§ 63.133(a)(1)
	"13.1	§ 63.133(a)(2)
"151	<5.2	§ 63.133(a)(1)
	"5.2	§ 63.133(a)(2)

TABLE 11 TO SUBPART G OF PART 63—WASTEWATER—INSPECTION AND MONITORING REQUIREMENTS FOR WASTE MANAGEMENT UNITS

To comply with	Inspection or monitoring requirement	Frequency of inspection or monitoring	Method
Tanks:			
63.133(b)(1)	Inspect fixed roof and all openings for leaks	Initially Semi-annually ..	Visual.
63.133(c)	Inspect floating roof in accordance with §§ 63.120 (a)(2) and (a)(3).	See § 63.120 (a)(2) and (a)(3).	Visual.
63.133(d)	Measure floating roof seal gaps in accordance with §§ 63.120 (b)(2)(i) through (b)(4). —Primary seal gaps	Once every 5 years Initially Annually.	See § 63.120 (b)(2)(i) through (b)(4).
	—Secondary seal gaps.		
63.133(f) 63.133(g)	Inspect wastewater tank for control equipment failures and improper work practices.	Initially Semi-annually ..	Visual.
Surface impoundments:			
63.134(b)(1)	Inspect cover and all openings for leaks	Initially Semi-annually ..	Visual.
63.134(c)	Inspect surface impoundment for control equipment failures and improper work practices.	Initially Semi-annually ..	Visual.
Containers:			
63.135(b)(1), 63.135(b)(2) (ii).	Inspect cover and all openings for leaks	Initially Semi-annually ..	Visual.
63.135(d)(1)	Inspect enclosure and all openings for leaks	Initially Semi-annually ..	Visual.
63.135(e)	Inspect container for control equipment failures and improper work practices.	Initially Semi-annually ..	Visual.
Individual Drain Systems^a:			
63.136(b)(1)	Inspect cover and all openings to ensure there are no gaps, cracks, or holes.	Initially Semi-annually ..	Visual.
63.136(c)	Inspect individual drain system for control equipment failures and improper work practices.	Initially Semi-annually ..	Visual.
63.136(e)(1)	Verify that sufficient water is present to properly maintain integrity of water seals.	Initially Semi-annually ..	Visual.
63.136(e)(2), 63.136(f)(1).	Inspect all drains using tightly-fitted caps or plugs to ensure caps and plugs are in place and properly installed.	Initially Semi-annually ..	Visual.
63.136(f)(2)	Inspect all junction boxes to ensure covers are in place and have no visible gaps, cracks, or holes.	Initially Semi-annually ..	Visual or smoke test or other means as specified.
63.136(f)(3)	Inspect unburied portion of all sewer lines for cracks and gaps.	Initially Semi-annually ..	Visual.
Oil-water separators:			
63.137(b)(1)	Inspect fixed roof and all openings for leaks	Initially Semi-annually ..	Visual.
63.137(c)	Measure floating roof seal gaps in accordance with 40 CFR 60.696(d)(1). —Primary seal gaps	Initially ^b	See 40 CFR 60.696(d)(1).
		Once every 5 years.	

Environmental Protection Agency

Pt. 63, Subpt. G, Table 13

To comply with	Inspection or monitoring requirement	Frequency of inspection or monitoring	Method
63.137(c) 63.137(d)	—Secondary seal gaps Inspect oil-water separator for control equipment failures and improper work practices.	Initially ^b Annually. Initially Semi-annually ..	Visual.

^a As specified in § 63.136(a), the owner or operator shall comply with either the requirements of § 63.136 (b) and (c) or § 63.136 (e) and (f).

^b Within 60 days of installation as specified in § 63.137(c).

TABLE 12 TO SUBPART G OF PART 63—MONITORING REQUIREMENTS FOR TREATMENT PROCESSES

To comply with	Parameters to be monitored	Frequency	Methods
1. Required mass removal of Table 8 and/or Table 9 compound(s) from wastewater treated in a properly operated biological treatment unit, § 63.138(f), and § 63.138(g).	Appropriate parameters as specified in § 63.143(c) and approved by permitting authority.	Appropriate frequency as specified in § 63.143 and approved by permitting authority.	Appropriate methods as specified in § 63.143 and as approved by permitting authority.
2. Steam stripper	(i) Steam flow rate; and (ii) Wastewater feed mass flow rate; and (iii) Wastewater feed temperature; or (iv) Column operating temperature	Continuously Continuously Continuously	Integrating steam flow monitoring device equipped with a continuous recorder. Liquid flow meter installed at stripper influent and equipped with a continuous recorder. (A) Liquid temperature monitoring device installed at stripper influent and equipped with a continuous or recorder; or (B) Liquid temperature monitoring device installed in the column top tray liquid phase (i.e., at the downcomer) and equipped with a continuous recorder.
3. Other treatment processes or alternative monitoring parameters to those listed in item 2 of this table.	Other parameters may be monitored upon approval from the Administrator with the requirements specified in § 63.151(f).		

TABLE 13 TO SUBPART G OF PART 63—WASTEWATER—MONITORING REQUIREMENTS FOR CONTROL DEVICES

Control Device	Monitoring equipment required	Parameters to be monitored	Frequency
All control devices.	1. Flow indicator installed at all bypass lines to the atmosphere and equipped with continuous recorder ^b or.	1. Presence of flow diverted from the control device to the atmosphere or.	Hourly records of whether the flow indicator was operating and whether a diversion was detected at any time during each hour
	2. Valves sealed closed with car-seal or lock-and-key configuration.	2. Monthly inspections of sealed valves.	Monthly.
Thermal Incinerator.	Temperature monitoring device installed in firebox or in ductwork immediately downstream of firebox ^a and equipped with a continuous recorder ^b .	Firebox temperature	Continuous.