

TABLE 1—GENERAL PROVISIONS APPLICABILITY TO SUBPART X—Continued

Reference	Applies to subpart X	Comment
63.6 (d) and (h)	No	No opacity limits in rule.
63.7	Yes.	
63.8	Yes.	
63.9 (a), (b), (c), (d), (e), (g), (h)(1–3), (h)(5–6), and (j)	Yes.	No opacity or visible emission limits in subpart X.
63.9 (f) and (h)(4)	No	
63.10	Yes.	
63.11	No	
63.12 to 63.15	Yes.	Flares will not be used to comply with the emission limits.

(c) If you are the owner or operator of a source subject to the provisions of this subpart, you are also subject to title V permitting requirements under 40 CFR parts 70 or 71, as applicable. Your title V permitting authority may defer your source from these permitting requirements until December 9, 2004, if your source is not a major source and is not located at a major source as defined under 40 CFR 63.2, 70.2, or 71.2, and is not otherwise required to obtain a title V permit. If you receive a deferral under this section, you must submit a title V permit application by December 9, 2005. You must continue to comply with the provisions of this subpart applicable to area sources, even if you receive a deferral from title V permitting requirements.

[62 FR 32216, June 13, 1997, as amended at 64 FR 4572, Jan. 29, 1999; 64 FR 69643, Dec. 14, 1999]

§ 63.542 Definitions.

Terms used in this subpart are defined in the Act, in subpart A of this part, or in this section as follows:

Agglomerating furnace means a furnace used to melt into a solid mass flue dust that is collected from a baghouse.

Bag leak detection system means an instrument that is capable of monitoring particulate matter (dust) loadings in the exhaust of a baghouse in order to detect bag failures. A bag leak detection system includes, but is not limited to, an instrument that operates on triboelectric, light scattering, transmittance or other effect to monitor relative particulate matter loadings.

Battery breaking area means the plant location at which lead-acid batteries

are broken, crushed, or disassembled and separated into components.

Blast furnace means a smelting furnace consisting of a vertical cylinder atop a crucible, into which lead-bearing charge materials are introduced at the top of the furnace and combustion air is introduced through tuyeres at the bottom of the cylinder, and that uses coke as a fuel source and that is operated at such a temperature in the combustion zone (greater than 980 °C) that lead compounds are chemically reduced to elemental lead metal.

Blast furnace charging location means the physical opening through which raw materials are introduced into a blast furnace.

Collocated blast furnace and reverberatory furnace means operation at the same location of a blast furnace and a reverberatory furnace with the volumetric flow rate discharged from the blast furnace being at equal to or less than that discharged from the reverberatory furnace.

Dryer means a chamber that is heated and that is used to remove moisture from lead-bearing materials before they are charged to a smelting furnace.

Dryer transition piece means the junction between a dryer and the charge hopper or conveyor, or the junction between the dryer and the smelting furnace feed chute or hopper located at the ends of the dryer.

Electric furnace means a smelting furnace consisting of a vessel into which reverberatory furnace slag is introduced and that uses electrical energy to heat the reverberatory furnace slag to such a temperature (greater than 980 °C) that lead compounds are reduced to elemental lead metal.

Enclosure hood means a hood that covers a process fugitive emission source on the top and on all sides, with openings only for access to introduce or remove materials to or from the source and through which an induced flow of air is ventilated.

Fugitive dust source means a stationary source of hazardous air pollutant emissions at a secondary lead smelter that is not associated with a specific process or process fugitive vent or stack. Fugitive dust sources include, but are not limited to, roadways, storage piles, materials handling transfer points, materials transport areas, storage areas, process areas, and buildings.

Furnace and refining/casting area means any area of a secondary lead smelter in which:

- (1) Smelting furnaces are located; or
- (2) Refining operations occur; or
- (3) Casting operations occur.

High efficiency particulate air (HEPA) filter means a filter that has been certified by the manufacturer to remove 99.97 percent of all particles 0.3 micrometers and larger.

Lead alloy means an alloy in which the predominant component is lead.

Materials storage and handling area means any area of a secondary lead smelter in which lead-bearing materials (including, but not limited to, broken battery components, reverberatory furnace slag, flue dust, and dross) are stored or handled between process steps including, but not limited to, areas in which materials are stored in piles, bins, or tubs, and areas in which material is prepared for charging to a smelting furnace. Materials storage and handling area does not include areas used exclusively for storage of blast furnace slag.

Partial enclosure means a structure comprised of walls or partitions on at least three sides or three-quarters of the perimeter surrounding stored materials or process equipment to prevent the entrainment of particulate matter into the air.

Pavement cleaning means the use of vacuum equipment, water sprays, or a combination thereof to remove dust or other accumulated material from the paved areas of a secondary lead smelter.

Plant roadway means any area of a secondary lead smelter that is subject to vehicle traffic, including traffic by fork lifts, front-end loaders, or vehicles carrying whole batteries or cast lead ingots. Excluded from this definition are employee and visitor parking areas, provided they are not subject to traffic by vehicles carrying lead-bearing materials.

Pressurized dryer breaching seal means a seal system connecting the dryer transition pieces which is maintained at a higher pressure than the inside of the dryer.

Process fugitive emission source means a source of hazardous air pollutant emissions at a secondary lead smelter that is associated with lead smelting or refining, but is not the primary exhaust stream from a smelting furnace, and is not a fugitive dust source. Process fugitive sources include, but are not limited to, smelting furnace charging points, smelting furnace lead and slag taps, refining kettles, agglomerating furnaces, and drying kiln transition pieces.

Refining kettle means an open-top vessel that is constructed of cast iron or steel and is indirectly heated from below and contains molten lead for the purpose of refining and alloying the lead. Included are pot furnaces, receiving kettles, and holding kettles.

Reverberatory furnace means a refractory-lined furnace that uses one or more flames to heat the walls and roof of the furnace and lead-bearing scrap to such a temperature (greater than 980 °C) that lead compounds are chemically reduced to elemental lead metal.

Rotary furnace (also known as a rotary reverberatory furnace) means a furnace consisting of a refractory-lined chamber that rotates about a horizontal axis and that uses one or more flames to heat the walls of the furnace and lead-bearing scrap to such a temperature (greater than 980 °C) that lead compounds are chemically reduced to elemental lead metal.

Secondary lead smelter means any facility at which lead-bearing scrap material, primarily, but not limited to, lead-acid batteries, is recycled into elemental lead or lead alloys by smelting.

Smelting means the chemical reduction of lead compounds to elemental

lead or lead alloys through processing in high-temperature (greater than 980 °C) furnaces including, but not limited to, blast furnaces, reverberatory furnaces, rotary furnaces, and electric furnaces.

Total enclosure means a roofed and walled structure with limited openings to allow access and egress for people and vehicles that meets the requirements of 40 CFR 265.1101(a)(1), (a)(2)(i), and (c)(1)(i).

Vehicle wash means a device for removing dust and other accumulated material from the wheels, body, and underside of a vehicle to prevent the inadvertent transfer of lead contaminated material to another area of a secondary lead smelter or to public roadways.

Wet suppression means the use of water, water combined with a chemical surfactant, or a chemical binding agent to prevent the entrainment of dust into the air from fugitive dust sources.

[62 FR 32216, June 13, 1997, as amended at 63 FR 45011, Aug. 24, 1998]

§ 63.543 Standards for process sources.

(a) No owner or operator of a secondary lead smelter shall discharge or cause to be discharged into the atmosphere from any existing, new, or reconstructed blast, reverberatory, rotary, or electric smelting furnace any gases that contain lead compounds in excess of 2.0 milligrams of lead per dry standard cubic meter (0.00087 grains of lead per dry standard cubic foot).

(b) [Reserved]

(c) No owner or operator of a secondary lead smelter with a collocated blast furnace and reverberatory furnace shall discharge or cause to be discharged into the atmosphere from any existing, new, or reconstructed blast furnace or reverberatory furnace any gases that contain total hydrocarbons in excess of 20 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide, except as allowed under Paragraphs (c)(1) and (c)(2) of this section.

(1) No owner or operator of a secondary lead smelter with a collocated blast furnace and reverberatory furnace shall discharge or cause to be discharged into the atmosphere from any existing blast furnace any gases that

contain total hydrocarbons in excess of 360 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide, during periods when the reverberatory furnace is not operating.

(2) No owner or operator of a secondary lead smelter with a collocated blast furnace and reverberatory furnace shall discharge or cause to be discharged into the atmosphere from any blast furnace that commences construction or reconstruction after June 9, 1994, any gases that contain total hydrocarbons in excess of 70 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide, during periods when the reverberatory furnace is not operating.

(d) No owner or operator of a secondary lead smelter with only blast furnaces shall discharge or cause to be discharged into the atmosphere from any existing blast furnace any gases that contain total hydrocarbons in excess of 360 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide.

(e) No owner or operator of a secondary lead smelter with only blast furnaces shall discharge or cause to be discharged into the atmosphere from any blast furnace that commences construction or reconstruction after June 9, 1994, any gases that contain total hydrocarbons in excess of 70 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide.

(f) If the owner or operator of a blast furnace or collocated blast furnace and reverberatory furnace combines the blast furnace charging process fugitive emissions with the blast furnace process emissions and discharges them to the atmosphere through a common emission point, then compliance with the applicable total hydrocarbon concentration limit under paragraph (c) of this section shall be determined downstream from the point at which the two emission streams are combined.

(g) If the owner or operator of a blast furnace or a collocated blast furnace and reverberatory furnace does not combine the blast furnace charging process fugitive emissions with the blast furnace process emissions and