

or fewer passengers are exempted from the requirements of paragraph (a) for fuel tank compartments that:

(1) Contain a permanently installed fuel tank if each electrical component is ignition protected in accordance with 33 CFR 183.410(a); and

(2) Contain fuel tanks that vent to the outside of the boat.

[CGFR 65-50, 30 FR 16653, Dec. 30, 1965, as amended by CGD 76-082A, 44 FR 73047, Dec. 17, 1979; CGD 76-082A, 45 FR 7551, Feb. 4, 1980; CGD 95-012, 60 FR 48048, Sept. 18, 1995; CGD 95-028, 62 FR 51196, Sept. 30, 1997]

Subpart 25.45—Cooking, Heating, and Lighting Systems

§ 25.45-1 Heating and lighting systems on vessels carrying passengers for hire.

(a) No fuel may be used in any heating or lighting system on any vessel carrying passengers for hire without the approval of Commandant (CG-521), except—

- (1) Alcohol, solid,
- (2) Alcohol, liquid, combustible,
- (3) Fuel oil, No. 1, No. 2, or No. 3,
- (4) Kerosene,
- (5) Wood or,
- (6) Coal.

(b) Heating and lighting systems using alcohol must meet the following requirements:

(1) Containers of solidified alcohol must be properly secured to a fixed base.

(2) Fluid alcohol burners, where wet priming is used, must have—

(i) A catch pan of not less than ¾" depth secured inside the frame of the stove; or

(ii) The metal protection under the stove flanged up at least ¾" to form a pan.

(c) Heating and lighting systems using kerosene or fuel oil must meet the following requirements:

(1) Where wet priming is used, each system must have—

(i) A catch pan of not less than ¾" depth secured inside the frame of the stove; or

(ii) The metal protection under the stove flanged up at least ¾" to form a pan.

(2) Fuel tanks must be—

(i) Separated from the stove that they serve;

(ii) Mounted in a location open to the atmosphere or mounted inside a compartment that is vented to the atmosphere; and

(iii) Fitted with an outside fill and vent.

(d) Heating systems using wood or coal installed after August 9, 1989, shall be installed in accordance with the guidelines in chapter 6 of NFPA 302.

[CGD 83-013, 54 FR 6402, Feb. 10, 1989 and CGD 83-013, 55 FR 3959, Feb. 6, 1990; CGD 95-072, 60 FR 50461, Sept. 29, 1995; CGD 96-041, 61 FR 50726, Sept. 27, 1996; USCG-2009-0702, 74 FR 49225, Sept. 25, 2009]

§ 25.45-2 Cooking systems on vessels carrying passengers for hire.

(a) No fuel may be used in any cooking system on any vessel carrying passengers for hire without the approval of Commandant (CG-521) except those listed in § 25.45-1, subject to the requirements stated therein, and liquefied petroleum gas (LPG), or compressed natural gas (CNG).

(b) Cooking systems using LPG or CNG must meet the following requirements:

(1) The design, installation, and testing of each LPG system must meet ABYC A-1-78 or chapter 6 of NFPA 302.

(2) The design, installation, and testing of each CNG system must meet ABYC A-22-78 or chapter 6 of NFPA 302.

(3) Cooking systems using chapter 6 of NFPA 302 as the standard must meet the following additional requirements:

(i) The storage or use of CNG containers within the accommodation area, machinery spaces, bilges, or other enclosed spaces is prohibited.

(ii) LPG or CNG must be odorized in accordance with ABYC A-1.5.d or A-22.5.b, respectively.

(iii) The marking and mounting of LPG cylinders must be in accordance with ABYC A-1.6.b.

(iv) LPG cylinders must be of the vapor withdrawal type as specified in ABYC A-1.5.b.

(4) Continuous pilot lights or automatic glow plugs are prohibited for an LPG or CNG installation using ABYC A-1 or A-22 as the standard.

§ 25.50-1

(5) CNG installations using ABYC A-22 as the standard must meet the following additional requirements:

(i) The stowage or use of CNG containers within the accommodation area, machinery spaces, bilges, or other enclosed spaces is prohibited.

(ii) The CNG cylinders, regulating equipment, and safety equipment must meet the installation, stowage, and testing requirements specified in paragraph 6-5.12 of NFPA 302.

(iii) The use of stowage of stoves with attached CNG cylinders is prohibited as specified in paragraph 6-5.1 of NFPA 302.

(6) If the fuel supply line of an LPG or CNG system enters an enclosed space on the vessel, a remote shut-off valve must be installed that can be operated from a position adjacent to the appliance. The valve must be located between the fuel tank and the point where the fuel supply line enters the enclosed portion of the vessel. A power operated valve installed to meet this requirement must be of a type that will fail closed.

(7) The following variances from ABYC A-1.11.b(1) are allowed for CNG:

(i) The storage locker or housing access opening need not be in the top.

(ii) The locker or housing need not be above the waterline.

(8) The following variances from NFPA 302 are allowed:

(i) The storage locker or housing for CNG tank installations need not be above the waterline as required by paragraph 6-5.12.1.1(a).

(ii) Ignition protection need not be provided as required by paragraph 6-5.4.

NOTE TO §25.45-2: The ABYC and NFPA standards referenced in this section require the posting of placards containing safety precautions for gas cooking systems.

[CGD 83-013, 54 FR 6402, Feb. 10, 1989, as amended by CGD 83-013, 55 FR 3960, Feb. 6, 1990; CGD 95-072, 60 FR 50461, Sept. 29, 1995; CGD 96-041, 61 FR 50726, Sept. 27, 1996; USCG-2000-7790, 65 FR 58458, Sept. 29, 2000; USCG-2009-0702, 74 FR 49225, Sept. 25, 2009]

46 CFR Ch. I (10-1-10 Edition)

Subpart 25.50—Garbage Retention

§ 25.50-1 Criteria.

Each uninspected vessel must meet the garbage discharge, waste management plan, and placard requirements of 33 CFR part 151 applicable to the vessel.

NOTE: 33 CFR 151.67 prohibits the discharge of plastic or garbage mixed with plastic into the sea or the navigable waters of the United States. "Plastic" and "garbage" are defined in 33 CFR 151.05.

[CGD 88-002A, 56 FR 8880, Mar. 1, 1991]

PART 26—OPERATIONS

Subpart 26.01—Application

Sec.

26.01-1 Applicable to all vessels.

Subpart 26.03—Special Operating Requirements

- 26.03-1 Safety orientation.
- 26.03-2 Emergency instructions.
- 26.03-4 Charts and nautical publications.
- 26.03-6 Special permit.
- 26.03-8 Marine Event of National Significance special permits.
- 26.03-9 Voyage plans for uninspected passenger vessels of at least 100 gross tons.
- 26.03-10 Signaling light.

Subpart 26.08—Notice and Reporting of Casualty and Voyage Records

26.08-1 Notice and reporting of casualty and voyage records.

Subpart 26.15—Boarding

26.15-1 May board at any time.

Subpart 26.20—Exhibition of Coast Guard Credential

26.20-1 Must be available.

Subpart 26.25 [Reserved]

Subpart 26.30—Work Vest

- 26.30-1 Approved unicellular plastic foam work vests.
- 26.30-5 Use.
- 26.30-10 Stowage.

AUTHORITY: 46 U.S.C. 3306, 4104, 6101, 8105; Pub. L. 103-206, 107 Stat. 2439; E.O. 12234, 45 FR 58801, 3 CFR, 1980 Comp., p. 277; Department of Homeland Security Delegation No. 0170.1.