

source to the secondary source being either manual or automatic;

(f) The system serves no other purpose, unless it is an engine-room-monitoring system (with fire-detection capability) installed on a vessel whose construction was contracted for before January 18, 2000; and

(g) The system is certified by a Registered Professional Engineer, or by a recognized classification society (under 46 CFR part 8), to comply with paragraphs (a) through (f) of this section.

§ 27.205 What are the requirements for internal communication systems on towing vessels?

(a) You must ensure that your vessel is fitted with a communication system between the engine room and the operating station that—

(1) Consists of either fixed or portable equipment, such as a sound-powered telephone, portable radios, or other reliable method of voice communication, with a main or reserve power supply that is independent of the electrical system on your towing vessel; and

(2) Provides two-way voice communication and calling between the operating station and either—

(i) The engine room; or

(ii) A location immediately adjacent to an exit from the engine room.

(b) Twin-screw vessels with operating-station control for both engines are not required to have internal communication systems.

(c) When the operating-station's engine controls and the access to the engine room are within 3 meters (10 feet) of each other and allow unobstructed visual contact between them, direct voice communication is acceptable instead of a communication system.

§ 27.207 What are the requirements for fuel shut-offs on towing vessels?

To stop the flow of fuel in the event of a break in the fuel line, you must have a positive, remote fuel-shut-off valve fitted on any fuel line that supplies fuel directly to an engine or generator. The valve must be near the source of supply (for instance, at the day tank, storage tank, or fuel-distribution manifold). Furthermore, it must be operable from a safe place outside the space where the valve is in-

stalled. Each remote valve control should be marked in clearly legible letters, at least 25 millimeters (1 inch) high, indicating the purpose of the valve and the way to operate it.

§ 27.209 What are the requirements for training crews to respond to fires?

(a) *Drills and instruction.* The master or person in charge of a vessel must ensure that each crewmember participates in drills and receives instruction at least once each month. The instruction may coincide with the drills, but need not. You must ensure that all crewmembers are familiar with their fire-fighting duties, and, specifically, with the following contingencies:

(1) Fighting a fire in the engine room and elsewhere on board the vessel, including how to—

(i) Operate all of the fire-extinguishing equipment on board the vessel;

(ii) Stop any mechanical ventilation system for the engine room and effectively seal all natural openings to the space to prevent leakage of the extinguishing agent; and

(iii) Operate the fuel shut-off for the engine room.

(2) Activating the general alarm.

(3) Reporting inoperative alarm systems and fire-detection systems.

(4) Putting on a fireman's outfit and a self-contained breathing apparatus, if the vessel is so equipped.

(b) *Alternative form of instruction.* The master or person in charge of a vessel may substitute, for the instruction required in paragraph (a) of this section, the viewing of video training materials concerning at least the contingencies listed in paragraph (a), followed by a discussion led by someone familiar with these contingencies. This instruction may occur either on board or off the vessel.

(c) *Participation in drills.* Drills must take place on board the vessel, as if there were an actual emergency. They must include—

(1) Participation by all crewmembers;

(2) Breaking out and using, or simulating the use of, emergency equipment;

(3) Testing of all alarm and detection systems; and