

(b) When a compartment containing the emergency source of electric power, or vital components thereof, adjoins a space containing either the ship's service generators or machinery necessary for the operation of the ship's service generators, all common bulkheads and/or decks shall be protected by approved "structural insulation" or other approved material. This protection shall be such as to be capable of preventing an excessive temperature rise in the space containing the emergency source of electric power, or vital components thereof, for a period of at least one hour in the event of fire in the adjoining space. Bulkheads or decks meeting Class A-60 requirements, as defined by § 72.05-10 of subchapter H (Passenger Vessels) of this chapter, will be considered as meeting the requirements of this paragraph.

Subpart 32.63—Hull and Cargo Tank Requirements for Tank Barges Constructed or Converted On or After July 1, 1964, and Carrying Certain Dangerous Bulk Cargoes

§ 32.63-1 Application—B/ALL.

(a) The requirements of this subpart shall apply to all tank barges, the construction or conversion of which is started on or after July 1, 1964, and carrying those cargoes listed in Table 30.25-1 which are defined as:

(1) Flammable liquids having a Reid vapor pressure in excess of 25 pounds per square inch, absolute, in independent tanks (part 32).

(2) Liquefied flammable gases (part 38 of this subchapter).

[CGFR 70-10, 35 FR 3709, Feb. 25, 1970]

§ 32.63-5 Barge hull classifications—B/ALL.

(a) Each barge subject to the provision of this subpart shall be assigned a hull type number. The Commandant will designate the barge hull types to be used for carrying cargoes in order to insure that the vessel is designed consistent with the degree and nature of the hazard of the commodity carried.

(b) For this purpose the barge hull types shall be as follows:

(1) *Type I barge hull.* Barge hulls classed as Type I are those designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo to the waterways and/or atmosphere.

(2) *Type II barge hull.* Barge hulls classed as Type II are those designed to carry products which require substantial preventive measures to preclude uncontrolled release to the atmosphere, but whose uncontrolled release to the waterways does not constitute a longlasting public or operating personnel hazard, though local and temporary pollution may occur.

(3) *Type III barge hull.* Barge hulls classed as Type III are those designed to carry products of sufficient hazard to require a moderate degree of control.

§ 32.63-8 Alternative arrangements—B/ALL.

(a) Alternative arrangements, differing from those specifically required by this subpart, may be considered and approved by the Commandant, if it is demonstrated to his satisfaction that a degree of safety is obtained which is consistent with the intent of this subpart.

§ 32.63-10 Rakes and coamings—B/ALL.

(a) Each barge hull shall be constructed with a suitable blow form (length, shape, and height of headlog) to protect against diving at the maximum speed at which the barge is designed to be towed. In any integrated tow, only the lead barge need comply with this requirement. In any case, the operator of the towing vessel shall be guided by appropriate speed limitations.

(b) All open hopper type barge hulls shall be provided with coamings around the hopper space and, additionally, a 36-inch minimum height plowshare breakwater on the forward rake. Coamings shall have a minimum height of 36 inches forward graduated to a minimum height of 24 inches at midlength and 18 inches thereafter.

§ 32.63-20 Hull structure—B/ALL.

(a) *General.* In addition to complying with the requirements of § 32.60-1, as

applicable, barge hulls of Types I and II shall comply with the provisions of this section.

(b) *Types I and II barge hull.* Under an assumed grounding condition such that the forward rake bulkhead rests upon a pinnacle at the water surface, the maximum hull bending stress shall not exceed the following limits:

(1) Independent tanks may be installed in such a manner that they do not contribute to the strength and stiffness of the barge. In such case, the hull stress shall not exceed either 50 percent of the minimum ultimate tensile strength of the material or 70 percent of the yield strength when specified, whichever is greater.

(2) The Commandant may consider a reduction in hull stress when independent tanks are installed in such a manner as to contribute to the strength and stiffness of the barge and this is accounted for in determining the effective section modulus of the barge. In such case, the hull stress shall not exceed the percentage stress values prescribed in paragraph (b)(1) of this section multiplied by the quantity $(1.5 - \text{SWT}/\text{UTS})$, where SWT is the stress calculated without including the effect of the tanks, and UTS is the minimum ultimate tensile strength of the material. The value SWT, however, shall in no case be more than 75 percent of UTS.

§ 32.63-25 Cargo tanks and supports—B/ALL.

(a) *General.* Saddles and hold-down securing straps for independent cargo tanks shall be designed to prevent tank failure due to loads induced in the saddles or straps by barge deflection.

(b) *Collision protection.* (1) All independent cargo tanks installed on Type I and Type II barge hulls shall be protected with suitable collision chocks or collision straps to withstand a longitudinal collision load of one and one-half times the weight of the tank and cargo. All other independent cargo tanks shall be provided with suitable collision chocks or collision straps to withstand a longitudinal collision load equal to the weight of the tank and cargo.

(2) All cargo tanks shall be so located as to reduce the likelihood of their

being damaged in the event of collision. This protection shall be obtained by locating the cargo tanks not less than 4 feet from the side shell and box-end for Type I hulls and 3 feet for Type II barge hulls, and not less than 25 feet from the headlog at the bow for both types.

(c) *Cargo tank design—(1) Types I and II barge hulls.* (i) In addition to requirements provided for in applicable regulations for a specific commodity, cargoes subject to the provisions of this subpart shall be transported in cargo tanks meeting the requirements of this paragraph. Pressure vessel-type cargo tanks shall have sufficient additional strength so as to limit the maximum combined tank stress, including saddle horn and bending stresses, to 1.5 times the maximum allowable hoop stress in still water, and to the yield strength of the tank material or 70 percent of the minimum ultimate tensile strength of the tank material, if less, in the grounded condition as required by § 32.63-20(b).

(ii) Gravity type cargo tanks shall have sufficient additional strength to limit the maximum combined tank stress, including saddle horn and bending stresses, to the yield strength of the tank material or 70 percent of the minimum ultimate tensile strength of the tank material, if less, in the grounded condition as required by § 32.63-20(b).

(2) *Type III barge hulls.* In addition to the requirements of this paragraph, pressure vessel-type cargo tanks shall have sufficient additional strength so as to limit the maximum combined stress, including saddle horn and bending stresses, to 1.5 times the maximum allowable hoop stress.

Subpart 32.65—Hull Requirements for Tank Vessels Constructed On or After November 10, 1936, and Prior to July 1, 1951

§ 32.65-1 Application—TB/ALL.

The requirements in this subpart apply to all tank vessels, the construction or conversion of which was started on or after November 10, 1936, and prior to July 1, 1951.