

§ 108.663

system from which the draft can be determined.

[CGD 73-251, 43 FR 56808, Dec. 4, 1978, as amended by CGD 89-037, 57 FR 41823, Sept. 11, 1992]

§ 108.663 Unit markings: Load line.

Each unit that is assigned a load line must have the load line marked in accordance with Part 42 of this chapter.

§ 108.665 Appliances for watertight integrity.

Each watertight door, scuttle, and hatch required for watertight integrity, which may be opened during normal operations must be marked in letters of contrasting color to the background "KEEP CLOSED".

Subpart H—Miscellaneous Equipment

§ 108.697 Buoyant work vests.

(a) Each buoyant work vest on a unit must be approved under Subpart 160.053 or Subpart 160.077 of this chapter.

(b) Commercial hybrid PFD's carried as work vests must be—

(1) Used, stowed, and maintained in accordance with the procedures set out in the manual required for these devices by §160.077-29 of this chapter and any limitation(s) market on them; and

(2) Of the same or similar design and have the same method of operation as each other hybrid PFD carried on board.

[CGD 78-174A, 51 FR 4351, Feb. 4, 1986]

§ 108.699 Substitution of life preservers.

A work vest may not be substituted for a required life preserver—

(a) For the life saving equipment requirements of this part; or

(b) For use during drills and emergencies.

§ 108.701 Sounding equipment.

Each self-propelled unit must have a mechanical or electronic sounding apparatus.

§ 108.703 Self-contained breathing apparatus.

(a) Each unit must be equipped with a self-contained breathing apparatus

46 CFR Ch. I (10-1-10 Edition)

described in §108.497(a) to use as protection against gas leaking from a refrigeration unit if it is equipped with any refrigeration unit using—

(1) Ammonia to refrigerate any space with a volume of more than 20 cubic feet; or

(2) Fluorocarbons to refrigerate any space with a volume of more than 1000 cubic feet.

(b) The self-contained breathing apparatus required in §108.497 may be used for this purpose.

[CGD 73-251, 43 FR 56808, Dec. 4, 1978, as amended by CGD 86-036, 57 FR 48326, Oct. 23, 1992]

§ 108.705 Anchors, chains, wire rope, and hawsers.

(a) Each unit must be fitted with anchors, chains, wire rope, and hawsers in agreement with the standards established by the American Bureau of Shipping.

(b) Units which are equipped with anchors used as operational equipment are not required to have additional anchors if the operational anchors meet the requirements of paragraph (a) of this section.

[CGD 73-251, 43 FR 56808, Dec. 4, 1978, as amended by USCG-1999-6216, 64 FR 53226, Oct. 1, 1999]

§ 108.707 First aid kit.

Each unit must have a first-aid kit approved by the Mine Safety and Health Administration (Formerly Mining Enforcement and Safety Administration) of a size suitable for the number of persons allowed on board the unit that is stowed in a location that is accessible to persons on board.

§ 108.709 Litter.

Each unit must have a litter that is—

(a) Stowed in a location that is accessible to the persons on board; and

(b) Capable of being used on the type of helicopters serving the unit.

§ 108.713 International Code of Signals.

Each vessel on an international voyage which is required to carry a radiotelegraph or radiotelephone installation in accordance with Chapter IV of the Safety of Life at Sea Convention,