

§ 116.920

(1) Rails in way of embarkation stations and boarding locations; and

(2) Rails on a vessel when the service of the vessel is routinely changed, as determined by the cognizant OCMI, and the required top rail height varies depending on the service of the vessel at a particular time.

§ 116.920 Storm rails.

Suitable storm rails or hand grabs must be installed where necessary in passageways, at deckhouse sides, and at ladders and hatches.

§ 116.940 Guards in vehicle spaces.

On a vessel authorized to carry one or more vehicles, suitable chains, cables, or other barriers must be installed at the end of each vehicle runway. In addition, temporary rails or equivalent protection must be installed in way of each vehicle ramp, in compliance with § 116.900 of this part, when the vessel is underway.

§ 116.960 Guards for exposed hazards.

An exposed hazard, such as gears or rotating machinery, must be protected by a cover, guard, or rail.

§ 116.970 Protection against hot piping.

Piping, including valves, pipe fittings and flanges, conveying vapor, gas, or liquid, the temperature of which exceeds 65.5 °C (150 °F), must be insulated where necessary to prevent injuries.

Subpart J—Window Construction and Visibility

§ 116.1010 Safety glazing materials.

Glass and other glazing material used in windows must be of material that will not break into dangerous fragments if fractured.

§ 116.1020 Strength.

Each window, port hole, and its means of attachment to the hull or deck house, must be capable of withstanding the maximum load from wave and wind conditions expected due to its location on the vessel and the authorized route of the vessel.

46 CFR Ch. I (10–1–10 Edition)

§ 116.1030 Operating station visibility.

(a) Windows and other openings at the operating station must be of sufficient size and properly located to provide an adequate view for safe navigation in all operating conditions.

(b) Glass or other glazing material used in windows at the operating station must have a light transmission of not less than 70 percent according to Test 2 of American National Standards Institute (ANSI) Z 26.1 “Safety Glazing Materials For Motor Vehicles Operating on Land Highways,” and must comply with Test 15 of ANSI Z 26.1 for Class I Optical Deviation.

Subpart K—Drainage and Watertight Integrity of Weather Decks

§ 116.1110 Drainage of flush deck vessels.

(a) Except as provided in paragraph (b) of this section, the weather deck on a flush deck vessel must be watertight and have no obstruction to overboard drainage.

(b) Each flush deck vessel may have solid bulwarks in the forward one-third length of the vessel if:

(1) The bulwarks do not form a well enclosed on all sides; and

(2) The foredeck of the vessel has sufficient sheer to ensure drainage aft.

§ 116.1120 Drainage of cockpit vessels, well deck vessels, and open boats.

Drainage of cockpit vessels, well deck vessels, and open boats must meet the applicable requirements of §§ 178.420, 178.430, 178.440, 178.450 in subchapter T of this chapter.

§ 116.1160 Watertight integrity.

(a) A hatch exposed to the weather must be watertight, except that the following hatches may be weather-tight:

(1) A hatch on a watertight trunk that extends at least 305 millimeters (12 inches) above the weather deck;

(2) A hatch in a cabin top; and

(3) A hatch on a vessel that operates only on protected waters.

(b) A hatch cover must:

(1) Have securing devices; and