

TABLE 118.500(a)—Continued

Space protected	Minimum number required	Type extinguisher permitted		
		CG class	Medium	Min. size
Machinery space	1	B-II, C-II located just outside exit.	Dry chemical	0.9 kg (2 lb)
			Halon	4.5 kg (10 lb)
Open vehicle deck	1 for every 10 vehicles	B-II	CO ₂	6.8 kg (15 lb)
			Dry chemical	4.5 kg (10 lb)
			Foam	9.5 L (2.5 gal)
			Halon	4.5 kg (10 lb)
			CO ₂	6.8 kg (15 lb)
Accommodation space.	1 for each 232.3 square meters (2,500 square feet) or fraction thereof.	A-II	Dry chemical	4.5 kg (10 lb)
			Foam	9.5 L (2.5 gal)
Galley, pantry, concession stand.	1	A-II	Dry chemical	4.5 kg (10 lb)
			Foam	9.5 L (2.5 gal)
		B-II	Dry chemical	4.5 kg (10 lb)

(b) A vehicle deck without a fixed sprinkler system and exposed to weather must have one B-II portable fire extinguisher for every five vehicles, located near an entrance to the space.

(c) The cognizant OCMI may permit the use of a larger portable fire extinguisher, or a semiportable fire extinguisher, in lieu of those required by this section.

(d) The frame or support of each B-V fire extinguisher permitted by paragraph (c) of this section must be welded or otherwise permanently attached to a bulkhead or deck.

[CGD 85-080, 61 FR 917, Jan. 10, 1996, as amended at 62 FR 51351, Sept. 30, 1997]

§ 118.520 Installation and location.

Portable fire extinguishers must be located so that they are clearly visible and readily accessible from the space being protected. The installation and location must be to the satisfaction of the cognizant OCMI.

Subpart F—Additional Equipment

§ 118.600 Fire axe.

A vessel of more than 19.8 meters (65 feet) in length must have at least one fire axe located in or adjacent to the primary operating station.

PART 119—MACHINERY INSTALLATION

Subpart A—General Provisions

- Sec.
- 119.100 Intent.
- 119.115 Applicability to existing vessels.

Subpart B—Propulsion Machinery

- 119.200 General.
- 119.220 Installations.

Subpart C—Auxiliary Machinery

- 119.310 Installations.
- 119.320 Water heaters.
- 119.330 Pressure vessels.

Subpart D—Specific Machinery Requirements

- 119.400 Applicability.
- 119.405 Fuel restrictions.
- 119.410 General requirements.
- 119.420 Engine cooling.
- 119.422 Integral and non-integral keel cooler installations.
- 119.425 Engine exhaust cooling.
- 119.430 Engine exhaust pipe installation.
- 119.435 Integral fuel tanks.
- 119.440 Independent fuel tanks.
- 119.445 Fill and sounding pipes for fuel tanks.
- 119.450 Vent pipes for fuel tanks.
- 119.455 Fuel piping.
- 119.458 Portable fuel systems.
- 119.465 Ventilation of spaces containing diesel machinery.
- 119.470 Ventilation of spaces containing diesel fuel tanks.