

§ 25.255 Procedures for resolving harmful interference related to operation of ancillary terrestrial components operating in the 1.5/1.6 GHz, 1.6/2.4 GHz and 2 GHz bands.

If harmful interference is caused to other services by ancillary MSS ATC operations, either from ATC base stations or mobile terminals, the MSS ATC operator must resolve any such interference. If the MSS ATC operator claims to have resolved the interference and other operators claim that interference has not been resolved, then the parties to the dispute may petition the Commission for a resolution of their claims.

[68 FR 33653, June 5, 2003]

§ 25.256 Special Requirements for operations in the 3.65–3.7 GHz band.

Upon request from a terrestrial licensee authorized under Subpart Z, Part 90 that seeks to place base and fixed stations in operation within 150 km of a primary earth station, licensees of earth stations operating on a primary basis in the fixed satellite service in the 3.65–3.7 GHz band must negotiate in good faith with that terrestrial licensee to arrive at mutually agreeable operating parameters to prevent unacceptable interference.

[70 FR 24725, May 11, 2005]

§ 25.257 Special requirements for operations in the band 29.1–29.25 GHz between NGSO MSS and LMDS.

(a) Non-geostationary mobile satellite service (NGSO MSS) operators shall be licensed to use the 29.1–29.25 GHz band for Earth-to-space transmissions from feeder link earth station complexes. A “feeder link earth station complex” may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by a NGSO MSS licensees or applicants pursuant to §101.147.

(b) A maximum of seven (7) feeder link earth station complexes in the contiguous United States, Alaska and Hawaii may be placed into operation, in the largest 100 MSAs, in the band 29.1–29.25 GHz in accordance with § 25.203 and §101.147 of this chapter.

(c) One of the NGSO MSS operators licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of eight feeder link earth station complexes that transmit in the 29.1–29.25 GHz band. The other NGSO MSS operator licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of two feeder link earth station complexes that transmit in the 29.1–29.25 GHz band.

(d) Additional NGSO MSS operators may be licensed in this band if the additional NGSO MSS operator shows that its system can share with the existing NGSO MSS systems.

(e) All NGSO MSS operators shall cooperate fully and make reasonable efforts to identify mutually acceptable locations for feeder link earth station complexes. In this connection, any single NGSO MSS operator shall only identify one feeder link earth station complex protection zone in each category identified in §101.147(c)(2) of this chapter until the other NGSO MSS operator has been given an opportunity to select a location from the same category.

[61 FR 44181, Aug. 28, 1996]

§ 25.258 Sharing between NGSO MSS Feeder links Stations and GSO FSS services in the 29.25–29.5 GHz Bands.

(a) Operators of NGSO MSS feeder link earth stations and GSO FSS earth stations in the band 29.25 to 29.5 GHz where both services have a co-primary allocation shall cooperate fully in order to coordinate their systems. During the coordination process both service operators shall exchange the necessary technical parameters required for coordination.

(b) Licensed GSO FSS systems shall, to the maximum extent possible, operate with frequency/polarization selections, in the vicinity of operational or planned NGSO MSS feeder link earth station complexes, that will minimize instances of unacceptable interference to the GSO FSS space stations. Earth station licensees operating with GSO FSS systems shall be capable of providing earth station locations to support coordination of NGSO MSS feeder link stations under paragraphs (a) and