

§ 76.1803

unit's workforce collected in the annual employment report will be used only for purposes of analyzing industry trends and making reports to Congress. Such data will not be used for the purpose of assessing any aspect of an individual employment unit's compliance with our EEO rules for multi-channel video program distributors.

[69 FR 34954, June 23, 2004]

EFFECTIVE DATE NOTE: At 69 FR 34954, June 23, 2004, § 76.1802 was revised. This section contains information collection and record-keeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

§ 76.1803 Signal leakage monitoring.

MVPDs subject to § 76.611 must submit the results of ground based measurements derived in accordance with § 76.611(a)(1) or airspace measurements derived in accordance with § 76.611(a)(2), including a description of the method by which compliance with basic signal leakage criteria is achieved and the method of calibrating the measurement equipment. This information shall be provided to the Commission each calendar year via FCC Form 320.

[68 FR 27003, May 19, 2003]

§ 76.1804 Aeronautical frequencies: leakage monitoring (CLI).

An MVPD shall notify the Commission before transmitting any carrier or other signal component with an average power level across a 25 kHz bandwidth in any 160 microsecond time period equal to or greater than 10^{-4} watts at any point in the cable distribution system on any new frequency or frequencies in the aeronautical radio frequency bands (108–137 and 225–400 MHz). The notification shall be made on FCC Form 321. Such notification shall include:

(a) Legal name and local address of the MVPD;

(b) The names and FCC identifiers (e.g., CA0001) of the system communities affected, for a cable system, and the name and FCC identifier (e.g., CAB901), for other MVPDs;

(c) The names and telephone numbers of local system officials who are responsible for compliance with §§ 76.610 through 76.616 and § 76.1803;

(d) Carrier frequency, tolerance, and type of modulation of all carriers in

47 CFR Ch. I (10–1–10 Edition)

the aeronautical bands at any location in the cable distribution system and the maximum of those average powers measured over a 2.5 kHz bandwidth as described in the introductory paragraph to this rule section;

(e) The geographical coordinates (in NAD83) of a point near the center of the system, together with the distance (in kilometers) from the designated point to the most remote point of the plant, existing or planned, that defines a circle enclosing the entire plant;

(f) Certification that the monitoring procedure used is in compliance with § 76.614 or description of the routine monitoring procedure to be used; and

(g) For MVPDs subject to § 76.611, the cumulative signal leakage index derived under § 76.611(a)(1) or the results of airspace measurements derived under § 76.611(a)(2), including a description of the method by which compliance with the basic signal leakage criteria is achieved and the method of calibrating the measurement equipment.

(h) Aeronautical Frequency Notifications, FCC Form 321, shall be personally signed either electronically or manually by the operator; by one of the partners, if the operator is a partnership; by an officer, if the operator is a corporation; by a member who is an officer, if the operator is an unincorporated association; or by any duly authorized employee of the operator.

(i) Aeronautical Frequency Notifications, FCC Form 321, may be signed by the operator's attorney in case of the operator's physical disability or of his absence from the United States. The attorney shall in that event separately set forth the reasons why the FCC Form 321 was not signed by the operator. In addition, if any matter is stated on the basis of the attorney's belief only (rather than the attorney's knowledge), the attorney shall separately set forth the reasons for believing that such statements are true.

(j) The FCC Registration Number (FRN).

[68 FR 27003, May 19, 2003]