

**§ 354.224**

all waste from the various processing operations and to minimize, and if possible to prevent, stoppage and surcharging of the system.

(2) Grease traps which are connected with the sewerage system shall be suitably located but not near any edible products department or in any area where products are unloaded from or loaded into vehicles. To facilitate cleaning, such traps shall have inclined bottoms and be provided with suitable covers.

(3) Toilet soil lines shall be separate from house drainage lines to a point outside the buildings unless they are positively trapped to prevent backing up. Drainage from toilet bowls and urinals shall not be discharged into a grease catch basin.

(4) All floor drains shall be equipped with traps, constructed so as to minimize clogging, and the plumbing shall be so installed as to prevent sewerage from backing up and from flooding the floor.

(5) Floor drainage lines should be of metal and at least 4 inches in diameter and open into main drains of at least 6 inches in diameter and shall be properly vented to outside air.

(6) Where refrigerators are equipped with drains, such drains should be properly trapped and should discharge through an air gap into the sewer system. All new installations, and all replacements, or refrigerators equipped with drains shall meet these requirements.

**§ 354.224 Water supply.**

The water supply shall be ample, clean, and potable with adequate facilities for its distribution in the plant and its protection against contamination and pollution.

(a) Hot water at a temperature not less than 180 °F. shall be available for sanitation purposes.

(b) Hose connections with steam and water mixing valves or hot water hose connections shall be provided at convenient locations throughout the plant for cleaning purposes.

(c) The refuse rooms shall be provided with adequate facilities for washing refuse cans and other equipment in the rooms; the rooms, cans, and equip-

**9 CFR Ch. III (1-1-10 Edition)**

ment shall be cleaned after each day's use.

**§ 354.225 Lavatory accommodations.**

Modern lavatory accommodations and properly located facilities for cleaning utensils and hands shall be provided.

(a) Adequate lavatory and toilet accommodations, including, but not being limited to, running hot water and cold water, soap, and towels, shall be provided. Such accommodations shall be in or near toilet and locker rooms and also at such other places in the plant as may be essential to the cleanliness of all personnel handling products.

(b) Sufficient metal containers shall be provided for used towels and other wastes.

(c) An adequate number of hand washing facilities serving areas where dressed rabbits and edible products are prepared shall be operated by other than hand-operated controls, or shall be of a continuous flow type which provides an adequate flow of water for washing hands.

(d) Durable signs shall be posted conspicuously in each toilet room and locker room directing employees to wash their hands before returning to work.

(e) Toilet facilities shall be provided according to the following formula:

Persons of same sex	Toilet bowls required
1 to 15, inclusive .....	1
16 to 35, inclusive .....	2
36 to 55, inclusive .....	3
56 to 80, inclusive .....	4
For each additional 30 persons in excess of 80 ...	1

<sup>1</sup>Urinals may be substituted for toilet bowls but only to the extent of 1/3 of the total number of bowls stated.

**§ 354.226 Lighting and ventilation.**

There shall be ample light, either natural or artificial or both, of good quality and well distributed, and sufficient ventilation for all rooms and compartments to insure sanitary conditions.

(a) All rooms in which rabbits are killed, eviscerated, or otherwise processed shall have at least 30 foot candles of light intensity on all working surfaces except that at the inspection stations such light intensity shall be of 50