

(2) Provide a systematic identification of both natural and man-made hazards associated with the facility;

(3) Evaluate normal, abnormal, and accident conditions, including consideration of natural and man-made external events, identification of energy sources or processes that might contribute to the generation or uncontrolled release of radioactive and other hazardous materials, and consideration of the need for analysis of accidents which may be beyond the design basis of the facility;

(4) Derive the hazard controls necessary to ensure adequate protection of workers, the public, and the environment, demonstrate the adequacy of these controls to eliminate, limit, or mitigate identified hazards, and define the process for maintaining the hazard controls current at all times and controlling their use;

(5) Define the characteristics of the safety management programs necessary to ensure the safe operation of the facility, including (where applicable) quality assurance, procedures, maintenance, personnel training, conduct of operations, emergency preparedness, fire protection, waste management, and radiation protection; and

(6) With respect to a nonreactor nuclear facility with fissionable material in a form and amount sufficient to pose a potential for criticality, define a criticality safety program that:

- (i) Ensures that operations with fissionable material remain subcritical under all normal and credible abnormal conditions,
- (ii) Identifies applicable nuclear criticality safety standards, and
- (iii) Describes how the program meets applicable nuclear criticality safety standards.

§ 830.205 Technical safety requirements.

(a) A contractor responsible for a hazard category 1, 2, or 3 DOE nuclear facility must:

(1) Develop technical safety requirements that are derived from the documented safety analysis;

(2) Prior to use, obtain DOE approval of technical safety requirements and any change to technical safety requirements; and

(3) Notify DOE of any violation of a technical safety requirement.

(b) A contractor may take emergency actions that depart from an approved technical safety requirement when no actions consistent with the technical safety requirement are immediately apparent, and when these actions are needed to protect workers, the public or the environment from imminent and significant harm. Such actions must be approved by a certified operator for a reactor or by a person in authority as designated in the technical safety requirements for nonreactor nuclear facilities. The contractor must report the emergency actions to DOE as soon as practicable.

(c) A contractor for an environmental restoration activity may follow the provisions of 29 CFR 1910.120 or 1926.65 to develop the appropriate hazard controls (rather than the provisions for technical safety requirements in paragraph (a) of this section), provided the activity involves either:

- (1) Work not done within a permanent structure, or
- (2) The decommissioning of a facility with only low-level residual fixed radioactivity.

§ 830.206 Preliminary documented safety analysis.

If construction begins after December 11, 2000, the contractor responsible for a hazard category 1, 2, or 3 new DOE nuclear facility or a major modification to a hazard category 1, 2, or 3 DOE nuclear facility must:

(a) Prepare a preliminary documented safety analysis for the facility, and

(b) Obtain DOE approval of:

(1) The nuclear safety design criteria to be used in preparing the preliminary documented safety analysis unless the contractor uses the design criteria in DOE Order 420.1, Facility Safety; and

(2) The preliminary documented safety analysis before the contractor can procure materials or components or begin construction; provided that DOE may authorize the contractor to perform limited procurement and construction activities without approval of a preliminary documented safety analysis if DOE determines that the activities are not detrimental to public