

§ 460.8

adopt the change or to reopen the proceeding to consider it further.

§ 460.8 R-value tolerances.

If you are a manufacturer of home insulation, no individual specimen of the insulation you sell can have an R-value more than 10% below the R-value shown in a label, fact sheet, ad, or other promotional material for that insulation. If you are not a manufacturer, you can rely on the R-value data given to you by the manufacturer, unless you know or should know that the data is false or not based on the proper tests.

[70 FR 31275, May 31, 2005]

§ 460.9 What test records you must keep.

Manufacturers and testing labs must keep records of each item of information in the "Report" section of the ASTM test method that is used for a test. They must also keep the following records:

- (a) The name and address of the testing lab that did each test.
- (b) The date of each test.
- (c) For manufacturers, the date each test report was received from a lab. For labs, the date each test report was sent to a manufacturer.
- (d) For extruded polystyrene, polyurethane, and polyisocyanurate, the age (in days) of the specimen that was tested.
- (e) For aluminum foil, the emissivity level that was found in the test.

Manufacturers who own their own testing labs need not keep records of the information in paragraph (c) of this section.

Keep these records for at least three years. If the documents show proof for your claims, the three years will begin again each time you make the claim. Federal Trade Commission staff members can check these records at any time, but they must give you reasonable notice first.

§ 460.10 How statements must be made.

All statements called for by this regulation must be made clearly and conspicuously. Among other things, you must follow the Commission's enforce-

16 CFR Ch. I (1-1-11 Edition)

ment policy statement for clear and conspicuous disclosures in foreign language advertising and sales materials, 16 CFR 14.9.

[61 FR 13666, Mar. 28, 1996]

§ 460.11 Rounding off R-values.

R-values shown in labels, fact sheets, ads, or other promotional materials must be rounded to the nearest tenth. However, R-values of 10 or more may be rounded to the nearest whole number.

§ 460.12 Labels.

If you are a manufacturer, you must label all packages of your insulation. The labels must contain:

- (a) The type of insulation.
- (b) A chart showing these items:
 - (1) For batts and blankets of any type: the R-value, length, width, thickness, and square feet of insulation in the package.
 - (2) For all loose-fill insulation: the minimum settled thickness, initial installed thickness, maximum net coverage area, number of bags per 1,000 square feet, and minimum weight per square foot at R-values of 13, 19, 22, 30, 38, and 49. You must also give this information for any additional R-values you list on the chart. Labels for these products must state the minimum net weight of the insulation in the package. You must also provide information about the blowing machine and machine settings used to derive the initial installed thickness information.
 - (3) For boardstock: the R-value, length, width, and thickness of the boards in the package, and the square feet of insulation in the package.
 - (4) For aluminum foil: the number of foil sheets; the number and thickness of the air spaces; and the R-value provided by that system when the direction of heat flow is up, down, and horizontal. You can show the R-value for only one direction of heat flow if you clearly and conspicuously state that the foil can only be used in that application.
 - (5) For insulation materials with foil facings, you must follow the rule that applies to the material itself. For example, if you manufacture boardstock with a foil facing, follow paragraph (b)(3) of this section. You can also show

Federal Trade Commission

§ 460.14

the R-value of the insulation when it is installed in conjunction with an air space. This is its “system R-value.” If you do this, you must clearly and conspicuously state the conditions under which the system R-value can be attained.

(6) For air duct insulation: the R-value, length, width, thickness, and square feet of insulation in the package.

(c) The following statement: “R means resistance to heat flow. The higher the R-value, the greater the insulating power.”

(d) If installation instructions are included on the label or with the package, add this statement: “To get the marked R-value, it is essential that this insulation be installed properly. If you do it yourself, follow the instructions carefully.”

(e) If no instructions are included, add this statement: “To get the marked R-value, it is essential that this insulation be installed properly. If you do it yourself, get instructions and follow them carefully. Instructions do not come with this package.”

[70 FR 31276, May 31, 2005]

§ 460.13 Fact sheets.

If you are a manufacturer, you must give retailers and installers fact sheets for the insulation products you sell to them. Each sheet must contain what is listed here. You can add any disclosures that are required by federal laws, regulations, rules, or orders. You can add any disclosures that are required by State or local laws, rules, and orders, unless they are inconsistent with the provisions of this regulation. Do not add anything else.

Each fact sheet must contain these items:

(a) The name and address of the manufacturer. It can also include a logo or other symbol that the manufacturer uses.

(b) A heading: “This is _____ insulation.” Fill in the blank with the type and form of your insulation.

(c) The heading must be followed by a chart:

(1) If § 460.12(b) requires a chart for your product’s label, you must use that chart. For foamed-in-place insulations,

you must show the R-value of your product at 3½ inches. You can also show R-values at other thicknesses.

(2) You can put the charts for similar products on the same fact sheet. For example, if you sell insulation boards or batts in three different thicknesses, you can put the label charts for all three products on one fact sheet. If you sell loose-fill insulation in two different bag sizes, you can put both coverage charts on one fact sheet, as long as you state which coverage chart applies to each bag size.

(d) For air duct insulation, the chart must be followed by this statement:

“The R-value of this insulation varies depending on how much it is compressed during installation.”

(e) After the chart and any statement dealing with the specific type of insulation, ALL fact sheets must carry this statement, boxed, in 12-point type:

READ THIS BEFORE YOU BUY

What You Should Know About R-values

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you’ll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly.

[44 FR 50242, Aug. 27, 1979, as amended at 45 FR 68928, Oct. 17, 1980; 70 FR 31276, May 31, 2005]

§ 460.14 How retailers must handle fact sheets.

If you sell insulation to do-it-yourself customers, you must have fact sheets for the insulation products you sell. You must make the fact sheets available to your customers. You can decide how to do this, as long as your insulation customers are likely to notice them. For example, you can put them in a display, and let customers take copies of them. You can keep