§86.413-78

- (2) Any revision to the maintenance instructions which will affect emissions shall be supplied to the Administrator at least 30 days before being supplied to the ultimate purchaser unless the Administrator consents to a lesser period of time.
- (b) Other instructions. The manufacturer of any new motorcycle subject to any of the standards prescribed in this subpart shall submit to the Administrator at the time of issuance by the manufacturer, copies of all sales brochures, instructions, or explanations regarding the use, repair, adjustment, maintenance, or testing of such vehicle relevant to the control of crankcase or exhaust emissions, issued by the manufacturer for use by other manufacturers, assembly plants, distributors, dealers, repair facilities, and ultimate purchasers. Any material not translated into the English language need not be submitted unless specifically requested by the Administrator.

§86.413-78 Labeling.

- (a)(1) The manufacturer of any motorcycle shall, at the time of manufacture, affix a permanent, legible label, of the type and in the manner described below, containing the information hereinafter provided, to all production models of such vehicles available for sale to the public and covered by a certificate of conformity.
- (2) A permanent, legible label shall be affixed in a readily accessible position. Multi-part labels may be used.
- (3) The label shall be affixed by the vehicle manufacturer who has been issued the certificate of conformity for such vehicle, in such a manner that it cannot be removed without destroying or defacing the label.
- (4) The label shall contain the following information lettered in the English language in block letters and numerals, which shall be of a color that contrasts with the background of the label:
- (i) The label heading. Vehicle Emission Control Information:
- (ii) Full corporate name and trademark of the manufacturer;
- (iii) Engine displacement (in cubic centimetres) and engine family identification:

- (iv) Engine tuneup specifications and adjustments, as recommended by the manufacturer, including idle speed, ignition timing, and the idle air-fuel mixture setting procedure and value (e.g., idle CO, idle air-fuel ratio, idle speed drop). These specifications shall indicate the proper transmission position during tuneup;
- (v) Any specific fuel or engine lubricant requirements (e.g., lead content, Research octane number, engine lubricant type);
- (vi) An unconditional statement of conformity to USEPA regulations which includes the model year; for example, This Vehicle Conforms to USEPA Regulation Applicable to Model Year New Motorcycles.
- (b) The provisions of this section shall not prevent a manufacturer from also reciting on the label that such vehicle conforms to any other applicable Federal or State standards for new motorcycles or any other information that such manufacturer deems necessary for, or useful to, the proper operation and satisfactory maintenance of the vehicle.

 $[42 \ \mathrm{FR} \ 1126, \ \mathrm{Jan.} \ 5, \ 1977, \ \mathrm{as} \ \mathrm{amended} \ \mathrm{at} \ 42 \ \mathrm{FR} \ 56737, \ \mathrm{Oct.} \ 28, \ 1977]$

§86.413-2006 Labeling.

- (a)(1) The manufacturer of any motorcycle shall, at the time of manufacture, affix a permanent, legible label, of the type and in the manner described in this section, containing the information provided in this section, to all production models of such vehicles available for sale to the public and covered by a certificate of conformity.
- (2) A permanent, legible label shall be affixed in a readily accessible position. Multi-part labels may be used.
- (3) The label shall be affixed by the vehicle manufacturer who has been issued the certificate of conformity for such vehicle, in such a manner that it cannot be removed without destroying or defacing the label, and shall not be affixed to any part which is easily detached from the vehicle or is likely to be replaced during the useful life of the vehicle.
- (4) The label shall contain the following information lettered in the English language in block letters and numerals, which shall be of a color