

Environmental Protection Agency

§ 421.83

§ 421.80 Applicability: Description of the primary zinc subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of primary zinc by either electrolytic or pyrolytic means.

§ 421.81 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *product* shall mean zinc metal.

§ 421.82 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

EFFLUENT LIMITATIONS		
Effluent characteristics	Maximum for any 1 day	Average of Daily values for 30 consecutive days shall not exceed
	(1) Metric Units (kg/kg of product)	(1) English Units (pounds per 1,000 pounds of product)
TSS	0.42	0.21
As	0.0016	0.0008
Cd	0.008	0.004
Se	0.08	0.04
Zn	0.08	0.04
pH	(¹)	(¹)

Within the range of 6.0 to 9.0.

[49 FR 8808, Mar. 8, 1984; 49 FR 26739, June 29, 1984]

§ 421.83 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Subpart H—Zinc Reduction Furnace Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc reduced	
Cadmium334	.134
Copper	2.135	1.018
Lead467	.217
Zinc	1.702	.701

(b) Subpart H—Preleach of Zinc Concentrates.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of concentrate leached	
Cadmium180	.072
Copper	1.153	.550
Lead252	.117
Zinc919	.378

(c) Subpart H—Leaching Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc processed through leaching	
Cadmium000	.000
Copper000	.000
Lead000	.000
Zinc000	.000

(d) Subpart H—Electrolyte Bleed Wastewater.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of cathode zinc produced	
Cadmium086	.035

§ 421.84

BAT EFFLUENT LIMITATIONS—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Copper553	.264
Lead121	.056
Zinc441	.182

(e) Subpart H—Cathode and Anode Wash Wastewater.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of cathode zinc produced	
Cadmium150	.060
Copper961	.458
Lead210	.098
Zinc766	.315

(f) Subpart H—Casting Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc cast	
Cadmium051	.021
Copper329	.157
Lead072	.033
Zinc262	.108

(g) Subpart H—Casting Contact Cooling.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc cast	
Cadmium036	.014
Copper232	.110
Lead051	.024
Zinc185	.076

(h) Subpart H—Cadmium Plant Wastewater.

40 CFR Ch. I (7–1–09 Edition)

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of cadmium produced	
Cadmium	1.234	.494
Copper	7.899	3.765
Lead	1.728	.802
Zinc	6.295	2.592

§ 421.84 Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Subpart H—Zinc Reduction Furnace Wet Air Pollution Control.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of zinc reduced	
Cadmium334	.134
Copper	2.135	1.018
Lead467	.217
Zinc	1.702	.701
Total suspended solids	25.020	20.020
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Subpart H—Preleach of Zinc Concentrates.

NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of concentrate leached	
Cadmium180	.072
Copper	1.153	.550
Lead252	.117
Zinc919	.378
Total suspended solids	13.520	10.810
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(c) Subpart H—Leaching Wet Air Pollution Control.