

shall be the responsibility of the master and chief engineer to ascertain that a sufficient number of the crew are familiar with the operation of the equipment.

(f) Boots and gloves shall be of rubber or other electrically nonconducting material.

(g) The helmet shall provide effective protection against impact.

(h) Protective clothing shall be of material that will protect the skin from the heat of fire and burns from scalding steam. The outer surface shall be water resistant.

[CGFR 65-50, 30 FR 17008, Dec. 30, 1965, as amended by CGFR 69-72, 34 FR 17485, Oct. 29, 1969; CGD 82-042, 53 FR 17705, May 18, 1988; CGD 86-036, 57 FR 48325, Oct. 23, 1992; USCG 1999-5151, 64 FR 67181, Dec. 1, 1999]

§ 96.35-10 Fireman's outfit.

(a) Each fireman's outfit must consist of one self-contained breathing apparatus, one lifeline with a belt or a suitable harness, one flashlight, one flame safety lamp, one rigid helmet, boots and gloves, protective clothing, and one fire ax. In lieu of the flame safety lamp, vessels may carry an oxygen depletion meter which is listed by a Coast Guard recognized independent laboratory as intrinsically safe.

(b) Every vessel shall carry at least two firemen's outfits.

[CGFR 69-72, 34 FR 17485, Oct. 29, 1969, as amended by CGD 86-036, 57 FR 48325, Oct. 23, 1992; CGD 95-028, 62 FR 51207, Sept. 30, 1997]

§ 96.35-15 Stowage.

The fireman's outfits must be stored in widely separated, accessible locations.

[CGD 75-074, 42 FR 5964, Jan. 31, 1977]

§ 96.35-20 Spare charges.

(a) A complete recharge shall be carried for each self-contained breathing apparatus, and a complete set of spare batteries shall be carried for each flashlight. The spares shall be stowed in the same location as the equipment it is to reactivate.

§ 96.35-90 Vessels contracted for before November 23, 1992.

Vessels contracted for before November 23, 1992, must meet the following requirements:

(a) Each vessel must satisfy §§ 96.35-5 through 96.35-20 concerning the number of items and method of stowage of equipment.

(b) Items of equipment previously approved, but not meeting the applicable specifications set forth in § 96.35-5, may continue in service as long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection; but each item in an installation or a replacement must meet all applicable specifications.

(c) After November 23, 1994, each respirator must either satisfy § 96.35-5(b) or be a self-contained compressed-air breathing apparatus previously approved by MSHA and NIOSH under part 160, subpart 160.011, of this chapter.

[CGD 86-036, 57 FR 48326, Oct. 23, 1992]

Subpart 96.40—Pilot Boarding Equipment

§ 96.40-1 Pilot boarding equipment.

(a) This section applies to each vessel that normally embarks or disembarks a pilot from a pilot boat or other vessel.

(b) Each vessel must have suitable pilot boarding equipment available for use on each side of the vessel. If a vessel has only one set of equipment, the equipment must be capable of being easily transferred to and rigged for use on either side of the vessel.

(c) Pilot boarding equipment must be capable of resting firmly against the vessel's side and be secured so that it is clear from overboard discharges.

(d) Each vessel must have lighting positioned to provide adequate illumination for the pilot boarding equipment and each point of access.

(e) Each vessel must have a point of access that has—

(1) A gateway in the rails or bulwark with adequate handholds; or

(2) Two handhold stanchions and a bulwark ladder that is securely attached to the bulwark rail and deck.

(f) The pilot boarding equipment required by paragraph (b) of this section

Pt. 97

must include at least one pilot ladder approved under subpart 163.003 of this chapter. Each pilot ladder must be of a single length and capable of extending from the point of access to the water's edge during each condition of loading and trim, with an adverse list of 15°.

(g) Whenever the distance from the water's edge to the point of access is more than 30 feet, access from a pilot ladder to the vessel must be by way of an accommodation ladder or equally safe and convenient means.

(h) Pilot hoists, if used, must be approved under subpart 163.002 of this chapter.

[CGD 79-032, 49 FR 25455, June 21, 1984]

PART 97—OPERATIONS

Subpart 97.01—Application

Sec.

97.01-1 General.

97.01-2 Incorporation by reference.

Subpart 97.05—Notice to Mariners and Aids to Navigation

97.05-1 Duty of officers.

97.05-5 Charts and nautical publications.

Subpart 97.07—Notice and Reporting of Casualty and Voyage Records

97.07-1 Notice and reporting of casualty and voyage records.

Subpart 97.10—Persons Allowed in Pilothouse and on Navigation Bridge

97.10-1 Application.

97.10-5 Persons excluded.

Subpart 97.11—Stability Letter

97.11-1 Posting.

Subpart 97.12—Bulk Solid Cargoes

97.12-1 Definition of a bulk solid cargo.

97.12-3 Guidance for the master.

97.12-5 Bulk solid cargoes that may liquefy.

Subpart 97.13—Station Bills

97.13-1 Muster lists, emergency signals, and manning.

Subpart 97.15—Tests, Drills, and Inspections

97.15-1 Application.

97.15-3 Steering gear, whistle, and means of communication.

97.15-5 Drafts and load line markings.

46 CFR Ch. I (10-1-11 Edition)

97.15-7 Verification of vessel compliance with applicable stability requirements.

97.15-10 Sanitation.

97.15-15 Examination of boilers and machinery.

97.15-17 Loading doors.

97.15-20 Hatches and other openings.

97.15-30 Emergency lighting and power systems.

97.15-35 Emergency training, musters, and drills.

97.15-55 Requirements for fuel oil.

97.15-60 Firefighting equipment, general.

97.15-75 Test of inflatable hopper gate seals on Great Lakes bulk dry cargo vessels.

Subpart 97.16—Auto Pilot

97.16-1 Use of auto pilot.

Subpart 97.19—Maneuvering Characteristics

97.19-1 Data required.

Subpart 97.20—Whistling

97.20-1 Unnecessary whistling prohibited.

Subpart 97.25—Searchlights

97.25-1 Improper use prohibited.

Subpart 97.27—Lookouts

97.27-5 Master's and officer's responsibility.

Subpart 97.30—Reports of Accidents, Repairs, and Unsafe Equipment

97.30-1 Repairs to boilers and pressure vessels.

97.30-5 Accidents to machinery.

97.30-10 Notice required before repair.

Subpart 97.33—Communication Between Deckhouses

97.33-1 When required.

Subpart 97.34—Work Vests

97.34-1 Application.

97.34-5 Approved types of work vests.

97.34-10 Use.

97.34-15 Shipboard stowage.

97.34-20 Shipboard inspections.

97.34-25 Additional requirements for hybrid work vests.

Subpart 97.35—Logbook Entries

97.35-1 Application.

97.35-3 Logbooks and records.

97.35-5 Actions required to be logged.

Subpart 97.36—Display of Plans

97.36-1 When required.