

SUBCHAPTER N—DANGEROUS CARGOES

PARTS 140–146 [RESERVED]

PART 147—HAZARDOUS SHIPS' STORES

Subpart A—General Provisions

- Sec.
147.1 Purpose and applicability.
147.3 Definitions.
147.5 Commandant (CG-522); address.
147.7 Incorporation by reference.
147.8 OMB control numbers assigned pursuant to the Paperwork Reduction Act.
147.9 Waivers.
147.15 Hazardous ships' stores permitted on board vessels.
147.30 Labeling.
147.33 Right of appeal.

Subpart B—Stowage and Other Special Requirements for Particular Materials

- 147.35 Purpose of subpart.
147.40 Materials requiring Commandant (CG-522) approval.
147.45 Flammable and combustible liquids.
147.50 Fuel for cooking, heating, and lighting.
147.60 Compressed gases.
147.65 Carbon dioxide and halon fire extinguishing systems.
147.70 Acetylene.
147.85 Oxygen.
147.90 Refrigerants.
147.95 Explosives.
147.100 Radioactive materials.
147.105 Anesthetics, drugs, and medicines.

AUTHORITY: 46 U.S.C. 3306; E.O. 12234, 45 FR 58801, 3 CFR, 1980 Comp., p. 277; Department of Homeland Security Delegation No. 0170.1.

EDITORIAL NOTE: Nomenclature changes to part 147 appear at 74 FR 49235, Sept. 25, 2009.

SOURCE: CGD 84-044, 53 FR 7749, Mar. 10, 1988, unless otherwise noted.

Subpart A—General Provisions

§ 147.1 Purpose and applicability.

(a) This part prescribes regulations designating what hazardous materials may be on board vessels as ships' stores and prescribes requirements for the labeling, stowage, and use of those materials.

(b) This part applies to all vessels listed in 46 U.S.C. 3301 as subject to inspection under part B of 46 U.S.C. Subtitle II. On foreign vessels in the navi-

gable waters of the United States, the Captain of the Port or District Commander may prohibit the unsafe use or stowage of hazardous ships' stores under 33 CFR 160.109.

(c) All certifications previously issued by the Coast Guard under this part permitting the use of particular materials or products as ships' stores are null and void.

§ 147.3 Definitions.

As used in this part:

Accommodation, control, or service spaces means living quarters, including walkways, dining rooms, galleys, pantries, lounges, lavatories, cabins, state-rooms, offices, hospitals, cinemas, and game and hobby rooms; areas containing controls for equipment and navigation; workshops, other than those forming part of machinery spaces; and store rooms adjacent to these spaces.

Combustible liquid means *combustible liquid* as the term is defined in 49 CFR 173.120(b).

Compressed gas means *compressed gas* as the term is defined in 49 CFR 173.115.

Consumer commodity means a commodity, such as a polish, insecticide, cleaning compound, or distillate, that is packaged and distributed in a form and quantity intended for sale through retail sales establishments.

Flammable liquid means *flammable liquid* as the term is defined in 49 CFR 173.120(a).

Hazardous material means *hazardous material* as the term is defined in 49 CFR 171.8.

Hazardous ships' stores means ships' stores that are hazardous materials.

Proper shipping name means the name of the hazardous ships' stores shown in Roman print (not in italics) in 49 CFR 172.101.

Ships' stores means materials which are on board a vessel for the upkeep, maintenance, safety, operation, or navigation of the vessel (except for fumigants under part 147A of this chapter, for fuel and compressed air used

§ 147.5

for the vessel's primary propulsion machinery, or for fixed auxiliary equipment) or for the safety or comfort of the vessel's passengers or crew.

Technical name means the recognized chemical name used in scientific or technical publications.

[CGD 84-044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 97-057, 62 FR 51048, Sept. 30, 1997]

§ 147.5 Commandant (CG-522); address.

Commandant (CG-522) is the Office of Operating and Environmental Standards, Marine Safety, Security and Environmental Protection. The address is Commandant (CG-522), U.S. Coast Guard Headquarters, 2100 2nd St. SW., Stop 7126, Washington, DC 20593-7126, and the telephone number is (202) 372-1401.

[CGD 96-041, 61 FR 50731, Sept. 27, 1996, as amended by USCG-2004-18884, 69 FR 58349, Sept. 30, 2004; USCG-2006-25697, 71 FR 55746, Sept. 25, 2006]

§ 147.7 Incorporation by reference.

(a) In this part, portions or the entire text of certain standards and specifications are incorporated by reference as the governing requirements for materials, equipment, tests, or procedures to be followed. These standards and specification requirements specifically referred to in this part are the governing requirements for the subject matters covered, unless specifically limited, modified, or replaced by the regulations.

(b) These materials are incorporated by reference into this part under 5 U.S.C. 552(a) with the approval of the Director of the Federal Register. The Office of the Federal Register publishes a table, "Material Approved for Incorporation by Reference," which appears in the Finding Aids section of this volume. To enforce any edition other than the one listed in paragraph (c) of this section, notice of the change must be published in the FEDERAL REGISTER and the material made available. All approved material is on file at the U.S. Coast Guard Headquarters, 2100 Second Street, SW., Washington, DC 20593-0001 or at the National Archives and Records Administration (NARA). For information on the availability of this

46 CFR Ch. I (10-1-11 Edition)

material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html. Copies may be obtained from the sources indicated in paragraph (c) of this section.

(c) The materials approved for incorporation by reference in this part are:

- American Boat and Yacht Council, Inc. (ABYC), 3069 Solomons Island Road, Edgewater, MD 21037
- ABYC H-25-81—Portable Fuel Systems and Portable Containers for Flammable Liquids, May 12, 1981.
- American Society of Heating, Refrigerating, and Air-Conditioning Engineers, Inc. (ASHRAE), Publication Sales Department, 1791 Tullie Circle, NE, Atlanta, GA 30329
- ANSI/ASHRAE 34-78—Number Designation of Refrigerants, approved 1978.
- Public Health Service, Department of Health and Human Services (DHHS), Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402
- DHHS Publication No. (PHS) 84-2024—The Ship's Medicine Chest and Medical Aid at Sea, revised 1984.
- Underwriters Laboratories, Inc. (UL), 12 Laboratory Drive, Research Triangle Park, NC 27709-3995
- UL 30—Standard for Metal Safety Cans, 7th Ed., March 11, 1985, revised March 12, 1985 and March 3, 1987.
- UL 1185—Standard for Portable Marine Fuel Tanks, Second Edition, March 13, 1978, revised July 6, 1984.
- UL 1313—Standard for Nonmetallic Safety Cans for Petroleum Products, 1st Ed., March 15, 1982, revised January 3, 1984 and March 22, 1985.
- UL 1314—Standard for Special-Propose Containers, 1st Ed., July 7, 1983, revised February 7, 1984 and September 23, 1986.

[CGD 84-044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 97-057, 62 FR 51048, Sept. 30, 1997; USCG-1999-6216, 64 FR 53227, Oct. 1, 1999; 69 FR 18803, Apr. 9, 2004]

§ 147.8 OMB control numbers assigned pursuant to the Paperwork Reduction Act.

(a) *Purpose.* This section collects and displays the control numbers assigned to information collection and record-keeping requirements in this subchapter by the Office of Management and Budget (OMB) pursuant to the Paperwork Reduction Act of 1980 (44 U.S.C. 3501 et seq.). The Coast Guard intends that this section comply with

Coast Guard, DHS

§ 147.40

the requirements of 44 U.S.C. 3507(f), which requires that agencies display a current control number assigned by the Director of the OMB for each approved agency information collection requirement.

(b) *Display.*

46 CFR part or section where identified or described	Current OMB control no.
§ 147.9	1625-0034
§ 147.30	1625-0034
§ 147.40	1625-0034
§ 147.60(c)(2)	1625-0034

[CGD 88-072, 53 FR 34298, Sept. 6, 1988; 88-072, 53 FR 37570, Sept. 27, 1988, as amended by USCG-2004-18884, 69 FR 58349, Sept. 30, 2004]

§ 147.9 Waivers.

(a) Any requirement in this part may be waived on a case by case basis if it is determined by Commandant (CG-522) that the requirement is impracticable under the circumstances and that an acceptable level of safety can be maintained.

(b) Requests for issuance of a waiver must be in writing and contain a detailed explanation of—

(1) Why the requirement is impracticable; and

(2) What measures will be taken to maintain an acceptable or equivalent level of safety.

[CGD 84-044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 95-072, 60 FR 50465, Sept. 29, 1995; CGD 96-041, 61 FR 50731, Sept. 27, 1996]

§ 147.15 Hazardous ships' stores permitted on board vessels.

Unless prohibited under subpart B of this part, any hazardous material may be on board a vessel as ships' stores if the material—

(a) Is labeled according to § 147.30; and

(b) Meets the requirements, if any, in subpart B of this part applicable to the material.

§ 147.30 Labeling.

(a) Except as provided in paragraph (b) of this section, all immediate receptacles, containers, or packages containing hazardous ships' stores must be labeled in English with the following information concerning the contents:

(1) Technical name or proper shipping name.

(2) For hazardous ships' stores other than liquid fuels, manufacturer's or supplier's name and address.

(3) Hazard classification under 49 CFR 172.101, 173.2, and 173.2(a).

(4) For hazardous ships' stores other than liquid fuels, step by step procedures for proper use.

(5) First aid instructions in the event of personnel contact, including antidotes in the event of ingestion.

(6) Stowage and segregation requirements.

(b) Hazardous ships' stores that are consumer commodities labeled in accordance with the Federal Hazardous Substances Act Regulations in 16 CFR part 1500 need not be labeled as specified in paragraph (a) of this section.

[CGD 84-044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 97-057, 62 FR 51048, Sept. 30, 1997; USCG-2005-22329, 70 FR 57183, Sept. 30, 2005]

§ 147.33 Right of appeal.

Any person directly affected by a decision or action taken under this part, by or on behalf of the Coast Guard, may appeal therefrom in accordance with subpart 1.03 of this chapter.

[CGD 88-033, 54 FR 50381, Dec. 6, 1989; 55 FR 21386, May 24, 1990]

Subpart B—Stowage and Other Special Requirements for Particular Materials

§ 147.35 Purpose of subpart.

This subpart prescribes special requirements applicable to particular, named materials. These requirements are in addition to the general requirements in subpart A applicable to those materials.

§ 147.40 Materials requiring Commandant (CG-522) approval.

(a) Commandant (CG-522) approval is required before the following hazardous materials may be on board a vessel as ships' stores:

(1) Poison gases of Class 2, Division 2.3 and toxic liquids of Class 6, Division 6.1 which are poisonous by inhalation in Hazard Zone A.

(2) Explosives of Divisions 1.1 or 1.2.

§ 147.45

46 CFR Ch. I (10–1–11 Edition)

(3) Flammable gases, other than those addressed specifically in this subpart.

(4) Forbidden materials listed in 49 CFR 172.101.

(b) Request for approval must be submitted to the Commandant (CG–522), identify the material, and explain the need for its use.

(c) Upon approval, the material is added to the list of materials approved under this section. A copy of this list is available from the Commandant (CG–522) at the address in §147.5.

[CGD 84–044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 95–072, 60 FR 50465, Sept. 29, 1995; CGD 96–041, 61 FR 50731, Sept. 27, 1996; CGD 97–057, 62 FR 51048, Sept. 30, 1997]

§ 147.45 Flammable and combustible liquids.

(a) This section applies to the stowage and transfer of flammable and combustible liquids (including gasoline and diesel oil), other than liquids used as fuel for cooking, heating, and lighting under §147.50.

(b) No flammable or combustible liquids may be stowed in any accommodation, control, or service space (other than a paint locker).

(c) No more than 19 liters (five gallons) of flammable liquids may be stowed in any machinery space. The flammable liquids must be in containers of 3.8 liters (one gallon) or less.

(d) No more than 208 liters (55 gallons) of combustible liquids may be stowed in any machinery space.

(e) An aggregate of more than 7.6 liters (two gallons) of flammable or combustible liquids stowed outside of an accommodation, control, or service space (other than a paint locker) or outside of a machinery space must be stowed in a paint locker that is marked with a warning sign indicating flammable or combustible liquid storage.

(f) Flammable and combustible liquids used as fuel for portable auxiliary equipment must be stored in—

(1) Integral tanks that form part of the vessel's structure;

(2) An independent tank meeting the requirements of subpart 58.50 of Part 58 of this chapter;

(3) A non-bulk packaging authorized for Class 3 (flammable) liquids or combustible liquids under 49 CFR 173.201,

173.202, or 173.203, as referenced for the specific liquid in column 8B of the Hazardous Materials Table of 49 CFR 172.101.

(4) A portable outboard fuel tank meeting the specifications of ABYC H–25–81 or one identified by Underwriters Laboratories as meeting the specifications of UL 1185;

(5) A portable safety container identified by Underwriters Laboratories as meeting the specifications of UL 30 or UL 1313; or

(6) A portable safety container identified by Underwriters Laboratories as meeting the requirements of UL 1314.

(g) Each portable container of flammable or combustible liquid used for portable auxiliary equipment must be stowed in a paint locker or an open location designated by the master.

(h) Fuel tanks for portable auxiliary equipment using flammable or combustible liquids may only be refilled on a vessel—

(1) By using a container described in paragraph (f)(2), (f)(3), or (f)(5) of this section which has a capacity not exceeding 23 liters (6 gallons); or

(2) In the case of portable outboard fuel tanks described in paragraph (f)(4) of this section, in accordance with paragraph (i) of this section.

(i) Portable containers or portable outboard fuel tanks may be refilled from a larger container of flammable or combustible liquid on the weather deck of a vessel, other than a small passenger vessel subject to Subchapter T of this chapter, provided that—

(1) A drip pan of adequate size is used to collect any drippings; and

(2) At least one Coast Guard approved Type B, Size I, fire extinguisher is within three meters (9.75 feet) of the refilling location.

[CGD 84–044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 92–100, 59 FR 17001, Apr. 11, 1994; CGD 97–057, 62 FR 51048, Sept. 30, 1997]

§ 147.50 Fuel for cooking, heating, and lighting.

(a) Flammable and combustible liquids and gases not listed in this section are prohibited for cooking, heating, or lighting on any vessel, with the exception of combustible liquids on cargo vessels.

(b) Fluid alcohol is prohibited for cooking, heating, or lighting on ferry vessels. Fluid alcohol burners, where wet primed, must have a catch pan not less than $\frac{3}{4}$ of an inch deep secured inside of the frame of the stove or have the metal protection under the stove flanged up $\frac{3}{4}$ of an inch to form a pan.

(c) Containers of solidified alcohol must be secured on a fixed base.

(d) Liquefied or non-liquefied gas is prohibited for cooking, heating, and lighting on ferry vessels, but may be used on other inspected vessels if the system in which it is used meets the applicable requirements of subpart 58.16 or subpart 184.05 of this chapter, as appropriate, or is approved by the Commandant (CG-521).

(e) Kerosene and commercial standard fuel oil No. 1, No. 2, and No. 3 are prohibited for cooking, heating, or lighting on ferry or passenger vessels, unless the following conditions are met:

(1) Pressure or gravity feed must be used.

(2) Where wet priming is used in a cooking device, the device must have a catch pan not less than three fourths of an inch deep secured inside the frame of the device or a metal protector under the device with a least a three fourths inch flange to form a pan.

(3) Where wet priming is used, a non-flammable priming liquid must be used.

(4) Fuel tanks for fixed stoves must be separated from the stove and mounted in a location open to the atmosphere or mounted inside a compartment with an outside fill and vent.

(5) Fuel lines must have an easily accessible shut-off valve at the tank.

(6) If the fuel tank is outside of a stove compartment, a shut-off valve must be fitted at the stove.

[CGD 84-044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 83-013, 54 FR 6402, Feb. 10, 1989; CGD 95-072, 60 FR 50465, Sept. 29, 1995; CGD 96-041, 61 FR 50731, Sept. 27, 1996]

§ 147.60 Compressed gases.

(a) *Cylinder requirements.* Cylinders used for containing hazardous ships' stores that are compressed gases must be—

(1) Authorized for the proper shipping name of the gas in accordance with 49 CFR 172.101 and 49 CFR part 173;

(2) Constructed in accordance with subpart C of 49 CFR part 178 or exempted under 49 CFR part 107;

(3) Filled, marked, and inspected in accordance with 49 CFR 173.301 through 173.308; and

(4) Except as provided in § 147.65, maintained and retested in accordance with 49 CFR 173.34

(b) *Stowage and care of cylinders.* (1) Cylinders must always be secured and, when not in use, they must be stowed in a rack in an upright position, with the valve protection cap in place.

(2) Lockers or housings must be vented to the open air near the top and bottom for positive circulation of vapors.

(3) Cylinders must be protected from all sources of heat which may cause the cylinders to be heated to a temperature higher than 130 °F.

(c) *Pressure vessels other than cylinders.* Pressure vessels, other than cylinders subject to paragraph (a) of this section, used for containing ships' stores that are compressed gases must—

(1) Be constructed and inspected in accordance with part 54 of this chapter; and

(2) Carry only nitrogen or air, unless permission is granted by Commandant (CG-522) to do otherwise.

[CGD 84-044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 95-072, 60 FR 50465, Sept. 29, 1995; CGD 96-041, 61 FR 50731, Sept. 27, 1996]

§ 147.65 Carbon dioxide and halon fire extinguishing systems.

(a) Carbon dioxide or halon cylinders forming part of a fixed fire extinguishing system must be retested, at least, every 12 years. If a cylinder is discharged and more than five years have elapsed since the last test, it must be retested before recharging.

(b) Carbon dioxide or halon cylinders must be rejected for further service when they—

(1) Leak;

(2) Are dented, bulging, severely corroded, or otherwise in a weakened condition;

(3) Have lost more than five percent of their tare weight; or

(4) Have been involved in a fire.

§ 147.70

(c) Cylinders which have contained carbon dioxide or halon and have not been tested within five years must not be used to contain another compressed gas on board a vessel, unless the cylinder is retested and re-marked in accordance with § 147.60 (a)(3) and (a)(4).

(d) Flexible connections between cylinders and distribution piping of semi-portable or fixed carbon dioxide fire extinguishing systems and discharge hoses in semi-portable carbon dioxide fire extinguishing systems must be renewed or tested at a pressure of 6.9 MPa (1000 psig). At test pressure, the pressure must not drop at a rate greater than 1.03 MPa (150 psi) per minute for a two minute period. The test must be performed when the cylinders are retested.

(e) Flexible connections between cylinders and distribution piping of fixed halon fire extinguishing systems must be tested at a pressure of one and one-half times the cylinder service pressure as marked on the cylinder. At test pressure, the pressure must not drop at a rate greater than 1.03 MPa (150 psi) per minute for a two minute period. The test must be performed when the cylinders are retested.

§ 147.70 Acetylene.

(a) Seventeen cubic meters (600 standard cubic feet) or less of acetylene may be stowed on or below decks on any vessel.

(b) More than 17 m³ (600 standard cubic feet) of acetylene may be on board a vessel engaged in industrial operations, if it is stowed on deck.

§ 147.85 Oxygen.

(a) Eighty five cubic meters (3000 standard cubic feet) or less of oxygen may be on board any vessel.

(b) More than 85 m³ (3000 standard cubic feet) of oxygen may be on board a vessel engaged in industrial operations, if it is stowed on deck or in a well ventilated space.

§ 147.90 Refrigerants.

(a) Only refrigerants listed in ANSI/ASHRAE 34-78 may be carried as ships' stores.

(b) Refrigerants contained in a vessel's operating system are not considered as being carried as ship's stores.

46 CFR Ch. I (10-1-11 Edition)

§ 147.95 Explosives.

(a) *Explosives—general.* Except as provided for elsewhere in this subchapter, explosives, as defined in 49 CFR 173.50, which are hazardous ships' stores must be stowed in a magazine which is constructed and located in accordance with 49 CFR 176.122 through 176.138.

(b) *Small arms ammunition.* (1) No person shall bring, have in their possession, or use on board a vessel any small arms ammunition, except by express permission of the master of the vessel.

(2) All small arms ammunition must be stowed in a locked metal magazine or locker. The key to the locker must be kept in the possession of the master or a person designated by the master.

(c) *Ships' signals and emergency equipment.* (1) Explosive ships' signals and emergency equipment, including pyrotechnic distress signals and line throwing equipment, must be stowed in watertight containers or wood lined magazine chests.

(2) All pyrotechnic distress signals, rockets, and line throwing guns must be stowed in accordance with the requirements of 49 CFR 176.140 through 176.146.

[CGD 84-044, 53 FR 7749, Mar. 10, 1988, as amended by CGD 92-100, 59 FR 17001, Apr. 11, 1994; CGD 97-057, 62 FR 51048, Sept. 30, 1997]

§ 147.100 Radioactive materials.

(a) Radioactive materials must not be brought on board, used in any manner, or stored on the vessel, unless the use of the materials is authorized by a current license issued by the Nuclear Regulatory Commission (NRC) under 10 CFR parts 30 and 34.

(b) Stowage of radioactive materials must conform to the requirements of the NRC license.

§ 147.105 Anesthetics, drugs, and medicines.

Anesthetics, drugs, and medicines must be stowed and dispensed in accordance with the DHHS Publication No. (PHS) 84-2024.

PART 147A—INTERIM REGULATIONS FOR SHIPBOARD FUMIGATION

GENERAL

Sec.

Coast Guard, DHS

§ 147A.10

- 147A.1 Purpose.
- 147A.3 Applicability.
- 147A.5 General requirement.
- 147A.6 Right of appeal.
- 147A.7 Definitions.
- 147A.9 Persons in charge of fumigation and the vessel; designation.
- 147A.10 Notice to Captain of the Port.

BEFORE FUMIGATION

- 147A.11 Person in charge of fumigation; before fumigation.
- 147A.13 Person in charge of the vessel; before fumigation.

DURING FUMIGATION

- 147A.21 Person in charge of fumigation; during fumigation.
- 147A.23 Person in charge of vessel; during fumigation.
- 147A.25 Entry.

AFTER VENTILATION

- 147A.31 Removal of fumigation material and warning signs.

SPECIAL REQUIREMENTS FOR FLAMMABLE FUMIGANTS

- 147A.41 Person in charge of fumigation; flammable fumigants.
- 147A.43 Other sources of ignition; flammable fumigants.

AUTHORITY: 46 U.S.C. 5103; Department of Homeland Security Delegation No. 0170.1.

SOURCE: CGD 74-144, 39 FR 32998, Sept. 13, 1974, unless otherwise noted.

GENERAL

§ 147A.1 Purpose.

The purpose of this part is to prescribe the requirements for shipboard fumigation that are critical for the health and safety of the crew and any other person who is on board a vessel during fumigation. These are interim rules pending further study and promulgation of comprehensive regulations on shipboard fumigation.

§ 147A.3 Applicability.

This part prescribes the rules for shipboard fumigation on vessels to which 49 CFR parts 171-179 apply under 49 CFR 176.5.

[CGD 86-033, 53 FR 36026, Sept. 16, 1988]

§ 147A.5 General requirement.

No person may cause or authorize shipboard fumigation contrary to the rules in this part.

§ 147A.6 Right of appeal.

Any person directly affected by a decision or action taken under this part, by or on behalf of the Coast Guard, may appeal therefrom in accordance with subpart 1.03 of this chapter.

[CGD 88-033, 54 FR 50381, Dec. 6, 1989]

§ 147A.7 Definitions.

As used in this part:

(a) *Qualified person* means a person who has experience with the particular fumigant or knowledge of its properties and is familiar with fumigant detection equipment and procedures, or an applicator who is certified by the Environmental Protection Agency if his certification covers the fumigant that is used.

(b) *Fumigant* means a substance or mixture of substances that is a gas or is rapidly or progressively transformed to the gaseous state though some non-gaseous or particulate matter may remain in the space that is fumigated.

(c) *Fumigation* means the application of a fumigant on board a vessel to a specific treatment space.

§ 147A.9 Persons in charge of fumigation and the vessel; designation.

(a) The person, including any individual, firm, association, partnership, or corporation, that is conducting a fumigation operation shall designate a person in charge of fumigation for each operation.

(b) The operator of each vessel shall designate a person in charge of the vessel for each fumigation operation.

§ 147A.10 Notice to Captain of the Port.

Unless otherwise authorized by the Captain of the Port, at least 24 hours before fumigation the operator of the vessel shall notify the Coast Guard Captain of the Port, for the area where the vessel is to be fumigated, of the time and place of the fumigation, and the name of the vessel that is to be fumigated.

§ 147A.11

46 CFR Ch. I (10–1–11 Edition)

BEFORE FUMIGATION

§ 147A.11 Person in charge of fumigation; before fumigation.

(a) The person in charge of fumigation shall notify the person in charge of the vessel of:

- (1) The space that is to be fumigated;
- (2) The name, address, and emergency telephone number of the fumigation company;
- (3) The dates and times of fumigation;
- (4) The characteristics of the fumigant;
- (5) The spaces that are determined to be safe for occupancy paragraph (b)(1)(i) of this section;
- (6) The maximum allowable concentration of fumigant in spaces, if any, that are determined to be safe for occupancy under paragraph (b)(1)(i) of this section;
- (7) The symptoms of exposure to the fumigant; and
- (8) Emergency first aid treatment for exposure to the fumigant.

(b) The person in charge of fumigation shall ensure that:

(1) A marine chemist or other qualified person who has knowledge of and experience in shipboard fumigation evaluates the vessel's construction and configuration and determines:

- (i) Which spaces, if any, are safe for occupancy during fumigation; and
- (ii) The intervals that inspections must be made under § 147A.21(a)(1);

(2) No persons or domestic animals are in the space that is to be fumigated or the spaces that are designated as unsafe for occupancy under paragraph (b)(1)(i) of this section;

(3) There is proper and secure sealing to confine the fumigant to the space that is to be fumigated, including blanking off and sealing any ventilation ducts and smoke detectors;

(4) The personal protection and fumigation detection equipment for the fumigant that is to be used is on board the vessel;

(5) Warning signs are:

- (i) Posted upon all gangplanks, ladders, and other points of access to the vessel;
- (ii) Posted on all entrances to the spaces that are designated as unsafe for

occupancy under paragraph (b)(1)(i) of this section; and

(iii) In accordance with 49 CFR 173.9(c) or section 8.10 of the *General Introduction of the International Maritime Dangerous Goods Code*. The word “unit” on the warning sign may be replaced with “vessel,” “barge,” “hold,” or “space,” as appropriate.

(6) Watchmen are stationed at all entrances to:

(i) Spaces that are not determined to be safe for occupancy under paragraph (b)(1)(i) of this section; or

(ii) The vessel, if no spaces are determined to be safe for occupancy under paragraph (b)(1)(i) of this section.

[CGD 74–144, 39 FR 32998, Sept. 13, 1974; 39 FR 37771, Oct. 24, 1974; CGD 96–041, 61 FR 50731, Sept. 27, 1996; CGD 97–057, 62 FR 51048, Sept. 30, 1997]

§ 147A.13 Person in charge of the vessel; before fumigation.

(a) After notice under § 147A.11 (a)(5), the person in charge of the vessel shall notify the crew and all other persons on board the vessel who are not participating in the fumigation of the spaces that are determined to be safe for occupancy under § 147A.11(b)(1)(i).

(b) If no spaces are determined to be safe for occupancy under § 147A.11 (b)(1)(i), the person in charge of the vessel shall ensure that the crew and all persons who are not participating in the fumigation leave the vessel and remain away during fumigation.

DURING FUMIGATION

§ 147A.21 Person in charge of fumigation; during fumigation.

(a) Until ventilation begins, or until the vessel leaves port, the person in charge of fumigation shall ensure that a qualified person inspects the vessel as follows:

(1) He must use detection equipment for the fumigant that is used to ensure that the fumigant is confined to:

(i) The space that is fumigated, if partial occupancy is allowed under § 147A.11(b)(1)(i); or

(ii) The vessel, if no space is determined to be safe for occupancy under § 147A.11(b)(1)(i).

(2) He must make inspections at the intervals that are determined to be

Coast Guard, DHS

§ 147A.23

necessary by the marine chemist or qualified person under § 147A.11 (b)(1)(ii).

(b) If leakage occurs, the person in charge of fumigation shall:

(1) Notify the person in charge of the vessel that there is leakage;

(2) Ensure that all necessary measures are taken for the health and safety of any person; and

(3) Notify the person in charge of the vessel when there is no danger to the health and safety of any person.

(c) After the exposure period, if the vessel is in port, the person in charge of fumigation shall ensure that fumigators or other qualified persons ventilate the space that is fumigated as follows:

(1) Hatch covers and vent seals must be removed, other routes of access to the atmosphere must be opened, and if necessary, mechanical ventilation must be used.

(2) Personal protection equipment that is appropriate for the fumigant that is used must be worn.

(d) If ventilation is completed before the vessel leaves port, the person in charge of fumigation shall:

(1) Ensure that a qualified person, who is wearing the personal protection equipment for the fumigant that is used if remote detection equipment is not used, tests the space that is fumigated and determines if there is any danger to the health and safety of any person, including a danger from fumigant that may be retained in bagged, baled, or other absorbent cargo;

(2) Notify the person in charge of the vessel of this determination; and

(3) If it is determined that there is a danger:

(i) Ensure that all measures are taken that are necessary for the health and safety of all persons; and

(ii) Notify the person in charge of the vessel when there is no danger to the health and safety of any person.

§ 147A.23 Person in charge of vessel; during fumigation.

(a) The person in charge of the vessel shall ensure that the crew and all other persons on board the vessel who are not participating in the fumigation restrict their movement during fumigation to the spaces that are determined to be

safe for occupancy under § 147A.11(b)(1)(i).

(b) The person in charge of the vessel shall ensure that the crew and all other persons who are not participating in the fumigation follow any instructions of the person in charge of fumigation that are issued under § 147A.21(b)(2) or (d)(3)(i) and that the vessel does not leave port if he is notified under:

(1) Section 147A.21(b)(1) that there is leakage, unless the person in charge of fumigation notifies him under § 147A.21(b)(3) of this subpart that there is no danger; or

(2) Section 147A.21(d)(2) that there is a danger after ventilation, unless the person in charge of the fumigation notifies him under § 147A.21(d)(3)(ii) that there is no danger.

(c) If fumigation is not completed before the vessel leaves port, the person in charge of the vessel shall ensure that personal protection and fumigant detection equipment for the fumigant that is used is on board the vessel.

(d) If the vessel leaves port before fumigation is completed, the person in charge of the vessel shall ensure that a qualified person makes periodic inspections until ventilation is completed and this person shall use detection equipment for the fumigant that is used to determine if:

(1) There is leakage of fumigant; or

(2) There is a concentration of fumigant that is a danger to the health and safety of any person.

(e) If the qualified person determines under paragraph (d) of this section that there is leakage or a concentration of fumigant that is a danger to the health and safety of any person, the person in charge of the vessel shall take all measures that are, in his discretion, necessary to ensure health and safety of all persons who are on board the vessel. If the danger is due to leakage, he shall also ensure that qualified persons immediately ventilate in accordance with paragraphs (c)(1) and (2) of § 147A.21.

(f) If the vessel leaves port during the exposure period, the person in charge of the vessel shall ensure that the space that is fumigated is ventilated by qualified persons after the exposure period in accordance with paragraphs (c)(1) and (2) of § 147A.21.

§ 147A.25

(g) If ventilation is completed after the vessel leaves port, the person in charge of the vessel shall ensure that a qualified person, who is wearing the personal protection equipment for the fumigant that is used if remote detection equipment is not used, tests the space that is fumigated to determine if there is a danger to the health and safety of any person, including a danger from fumigant that may be retained in bagged, baled, or other absorbent cargo. If the qualified person determines that there is a danger, the person in charge of the vessel shall take all measures that are, in his discretion, necessary to ensure the health and safety of all persons who are on board the vessel.

§ 147A.25 Entry.

(a) No person may enter the spaces that immediately adjoin the space that is fumigated during fumigation unless entry is for emergency purposes or the space is tested and declared safe for human occupancy by a marine chemist or other qualified person and is inspected under § 147A.21(a)(2) or § 147A.23(d).

(b) If entry is made for emergency purposes:

(1) No person may enter the space that is fumigated or any adjoining spaces during fumigation unless he wears the personal protection equipment for the fumigant that is in use;

(2) No person may enter the space that is fumigated unless the entry is made by a two person team; and

(3) No person may enter the space that is fumigated unless he wears a lifeline and safety harness and each life-line is tended by a person who is outside the space and who is wearing the personal protection equipment for the fumigant that is in use.

AFTER VENTILATION

§ 147A.31 Removal of fumigation material and warning signs.

After ventilation is completed and a marine chemist or other qualified person determines that there is no danger to the health and safety of any person under § 147A.21(d) or § 147A.23(g), the person in charge of fumigation, or, if the vessel has left port, the person in

46 CFR Ch. I (10–1–11 Edition)

charge of the vessel, shall ensure that all warning signs are removed and fumigation containers and materials are removed and disposed of in accordance with the manufacturer's recommendations.

SPECIAL REQUIREMENTS FOR FLAMMABLE FUMIGANTS

§ 147A.41 Person in charge of fumigation; flammable fumigants.

(a) The person in charge of fumigation shall ensure that:

(1) Before the space that is to be fumigated is sealed, it is thoroughly cleaned, and all refuse, oily waste, and other combustible material is removed;

(2) Before fumigation, all fire fighting equipment, including sprinklers and fire pumps, is in operating condition; and

(3) Before and during fumigation, electrical circuits that are in the space that is fumigated are de-energized.

(b) [Reserved]

§ 147A.43 Other sources of ignition; flammable fumigants.

While the space that is fumigated is being sealed or during fumigation, no person may use matches, smoking materials, fires, open flames, or any other source of ignition in any spaces that are not determined to be safe for occupancy under § 147A.11(b)(1)(i).

PART 148—CARRIAGE OF BULK SOLID MATERIALS THAT REQUIRE SPECIAL HANDLING

Subpart A—General

Sec.

148.1 Purpose and applicability.

148.2 Responsibility and compliance.

148.3 Definitions.

148.5 Alternative procedures.

148.7 OMB control numbers assigned under the Paperwork Reduction Act.

148.8 Incorporation by reference.

148.9 Right of appeal.

148.10 Permitted materials.

148.11 Hazardous or potentially dangerous characteristics.

148.12 Assignment and certification.

Subpart B—Special Permits

148.15 Petition for a special permit.

148.20 Deadlines for submission of petition and related requests.

Coast Guard, DHS

§ 148.1

- 148.21 Necessary information.
- 148.25 Activities covered by a special permit.
- 148.26 Standard conditions for special permits.
- 148.30 Records of special permits issued.

Subpart C—Minimum Transportation Requirements

- 148.50 Cargoes subject to this subpart.
- 148.51 Temperature readings.
- 148.55 International shipments.
- 148.60 Shipping papers.
- 148.61 Emergency response information.
- 148.62 Location of shipping papers and emergency response information.
- 148.70 Dangerous cargo manifest; general.
- 148.71 Information included in the dangerous cargo manifest.
- 148.72 Dangerous cargo manifest; exceptions.
- 148.80 Supervision of cargo transfer.
- 148.85 Required equipment for confined spaces.
- 148.86 Confined space entry.
- 148.90 Preparations before loading.
- 148.100 Log book entries.
- 148.110 Procedures followed after unloading.
- 148.115 Report of incidents.

Subpart D—Stowage and Segregation

- 148.120 Stowage and segregation requirements.
- 148.125 Stowage and segregation for materials of Class 4.1.
- 148.130 Stowage and segregation for materials of Class 4.2.
- 148.135 Stowage and segregation for materials of Class 4.3.
- 148.140 Stowage and segregation for materials of Class 5.1.
- 148.145 Stowage and segregation for materials of Class 7.
- 148.150 Stowage and segregation for materials of Class 9.
- 148.155 Stowage and segregation for potentially dangerous materials.

Subpart E—Special Requirements for Certain Materials

- 148.200 Purpose.
- 148.205 Ammonium nitrate and ammonium nitrate fertilizers.
- 148.220 Ammonium nitrate-phosphate fertilizers.
- 148.225 Calcined pyrites (pyritic ash, fly ash).
- 148.227 Calcium nitrate fertilizers.
- 148.230 Calcium oxide (lime, unslaked).
- 148.235 Castor beans.
- 148.240 Coal.
- 148.242 Copra.
- 148.245 Direct reduced iron (DRI); lumps, pellets, and cold-molded briquettes.

- 148.250 Direct reduced iron (DRI); hot-molded briquettes.
- 148.255 Ferrosilicon, aluminum ferrosilicon, and aluminum silicon containing more than 30% but less than 90% silicon.
- 148.260 Ferrous metal.
- 148.265 Fish meal or fish scrap.
- 148.270 Hazardous substances.
- 148.275 Iron oxide, spent; iron sponge, spent.
- 148.280 Magnesia, unslaked (lightburned magnesia, calcined magnesite, caustic calcined magnesite).
- 148.285 Metal sulfide concentrates.
- 148.290 Peat moss.
- 148.295 Petroleum coke, calcined or uncalcined, at 55 °C (131 °F) or above.
- 148.300 Radioactive materials.
- 148.310 Seed cake.
- 148.315 Sulfur.
- 148.320 Tankage; garbage tankage; rough ammonia tankage; or tankage fertilizer.
- 148.325 Wood chips; wood pellets; wood pulp pellets.
- 148.330 Zinc ashes; zinc dross; zinc residues; zinc skimmings.

Subpart F—Additional Special Requirements

- 148.400 Applicability.
- 148.405 Sources of ignition.
- 148.407 Smoking.
- 148.410 Fire hoses.
- 148.415 Toxic gas analyzers.
- 148.420 Flammable gas analyzers.
- 148.435 Electrical circuits in cargo holds.
- 148.445 Adjacent spaces.
- 148.450 Cargoes subject to liquefaction.

AUTHORITY: 33 U.S.C. 1602; E.O. 12234, 45 FR 58801, 3 CFR, 1980 Comp., p. 277; 46 U.S.C. 3306, 5111; 49 U.S.C. 5103; Department of Homeland Security Delegation No. 0170.1.

SOURCE: 75 FR 64591, Oct. 19, 2010, unless otherwise noted.

Subpart A—General

§ 148.1 Purpose and applicability.

(a) This part prescribes special handling procedures for certain solid materials that present hazards when transported in bulk by vessel.

(b) Except as noted in paragraph (c) of this section, this part applies to all domestic and foreign vessels in the navigable waters of the United States that transport bulk solid materials requiring special handling.

(c) This part does not apply to an unmanned barge on a domestic voyage carrying a Potentially Dangerous Material (PDM) found in Table 148.10 of this part. All barges on international

§ 148.2

voyages must follow the requirements for PDM.

(d) The regulations in this part have preemptive impact over State law on the same subject. The Coast Guard has determined, after considering the factors developed by the Supreme Court in *U.S. v. Locke*, 529 U.S. 89 (2000), that in directing the Secretary to regulate the safe transportation of hazardous material and the safety of individuals and property on board vessels subject to inspection, as well as the provision of loading information, Congress intended to preempt the field of safety standards for solid materials requiring special handling when transported in bulk on vessels.

§ 148.2 Responsibility and compliance.

Each master of a vessel, person in charge of a barge, owner, operator, shipper, charterer, or agent must ensure compliance with this part. These persons are also responsible for communicating requirements to every person performing any function covered by this part.

§ 148.3 Definitions.

As used in this part—

A-60 class division means a division as defined in § 32.57–5 of this chapter.

Adjacent space means any enclosed space on a vessel, such as a cargo hold, cargo compartment, accommodation space, working space, storeroom, passageway, or tunnel, that shares a common bulkhead or deck with a hatch, door, scuttle, cable fitting or other penetration, with a cargo hold or compartment containing a material listed in Table 148.10 of this part.

Away from means a horizontal separation of at least 3 meters (10 feet) projected vertically is maintained between incompatible materials carried in the same hold or on deck.

Bulk applies to any solid material, consisting of a combination of particles, granules, or any larger pieces of

46 CFR Ch. I (10–1–11 Edition)

material generally uniform in composition, that is loaded directly into the cargo spaces of a vessel without any intermediate form of containment.

Bulk Cargo Shipping Name or *BCSN* identifies a bulk solid material during transport by sea. When a cargo is listed in this Part, the BCSN of the cargo is identified by Roman type and is listed in Column 1 of Table 148.10 of this part. When the cargo is a hazardous material, as defined in 49 CFR part 173, the proper shipping name of that material is the BCSN.

Cold-molded briquettes are briquettes of direct reduced iron (DRI) that have been molded at a temperature of under 650 °C (1,202 °F) or that have a density of under 5.0 g/cm³.

Commandant (CG–5223) means the Chief, Hazardous Materials Standards Division of the Office of Operating and Environmental Standards, United States Coast Guard, 2100 2nd St., SW., Stop 7126, Washington, DC 20593–7126. CG–5223 can be contacted at 202–372–1420 or Hazmat@comdt.uscg.mil.

Compartment means any space on a vessel that is enclosed by the vessel's decks and its sides or permanent steel bulkheads.

Competent authority means a national agency responsible under its national law for the control or regulation of a particular aspect of the transportation of hazardous materials.

Confined space means a cargo hold containing a material listed in Table 148.10 of this part or an adjacent space not designed for human occupancy.

Domestic voyage means transportation between places within the United States other than through a foreign country.

Hazard class means the category of hazard assigned to a material under this part and 49 CFR parts 171 through 173.

HAZARD CLASS DEFINITIONS

HAZARD CLASSES USED IN THIS PART ARE DEFINED IN THE FOLLOWING SECTIONS OF TITLE 49

Class No.	Division No. (if any)	Description	Reference (49 CFR)
1	1.1, 1.2, 1.3, 1.4, 1.5, 1.6	Explosives	§ 173.50
2	2.1, 2.2, 2.3	Flammable Gas, Non-Flammable Compressed Gas, Poisonous Gas.	§ 173.115
3		Flammable and Combustible Liquid	§ 173.120

Coast Guard, DHS

§ 148.3

HAZARD CLASSES USED IN THIS PART ARE DEFINED IN THE FOLLOWING SECTIONS OF TITLE 49—
Continued

Class No.	Division No. (if any)	Description	Reference (49 CFR)
4	4.1, 4.2, 4.3	Flammable Solid, Spontaneously Combustible Material, Dangerous When Wet Material.	§ 173.124
5	5.1	Oxidizer	§ 173.127
5	5.2	Organic Peroxide	§ 173.128
6	6.1	Poisonous Materials	§ 173.132
6	6.2	Infectious Substance	§ 173.134
7		Radioactive Material	§ 173.403
8		Corrosive Material	§ 173.136
9		Miscellaneous Hazardous Material	§ 173.140

Hazardous substance is a hazardous substance as defined in 49 CFR 171.8.

Hold means a compartment below deck that is used exclusively for the stowage of cargo.

Hot-molded briquettes are briquettes of DRI that have been molded at a temperature of 650 °C (1,202 °F) or higher, and that have a density of 5.0 g/cm³ (312 lb/ft³) or greater.

IMSBC Code means the English version of the “International Maritime Solid Bulk Cargoes Code” published by the International Maritime Organization (incorporated by reference, see § 148.8).

Incompatible materials means two materials whose stowage together may result in undue hazards in the case of leakage, spillage, or other accident.

International voyage means voyages—

(1) Between any place in the United States and any place in a foreign country;

(2) Between places in the United States through a foreign country; or

(3) Between places in one or more foreign countries through the United States.

Lower flammability limit or *LFL* means the lowest concentration of a material or gas that will propagate a flame. The LFL is usually expressed as a percent by volume of a material or gas in air.

Master means the officer having command of a vessel. The functions assigned to the master in this part may also be performed by a representative of the master or by a person in charge of a barge.

Material safety data sheet or *MSDS* is as defined in 29 CFR 1910.1200.

Person in charge of a barge means an individual designated by the owner or

operator of a barge to have charge of the barge.

Potentially Dangerous Material or *PDM* means a material that does not fall into a particular hazard class but can present a danger when carried in bulk aboard a vessel. The dangers often result from the material’s tendency to self-heat or cause oxygen depletion. Materials that present a potential danger due solely to their tendency to shift in the cargo hold are not PDMs. For international shipments prepared in accordance with the IMSBC Code (incorporated by reference, see § 148.8), equivalent terminology to PDM is Material Hazardous only in Bulk (MHB).

Readily combustible material means a material that may not be a hazardous material but that can easily ignite and support combustion. Examples are wood, straw, vegetable fibers, and products made from these materials, and coal lubricants and oils. The term does not include packaging material or dunnage.

Reportable quantity or *RQ* means the quantity of a hazardous substance spilled or released that requires a report to the National Response Center. The specific RQs for each hazardous substance are available in 49 CFR 172.101, Appendix A.

Responsible person means a knowledgeable person who the master of a vessel or owner or operator of a barge makes responsible for all decisions relating to his or her specific task.

Seed cake means the residue remaining after vegetable oil has been extracted by a solvent or mechanical process from oil-bearing seeds, such as coconuts, cotton seed, peanuts, and linseed.

§ 148.5

Shipper means any person by whom, or in whose name, or on whose behalf, a contract of carriage of goods by sea has been concluded with a carrier; or any person by whom or in whose name, or on whose behalf, the goods are actually delivered to the carrier in relation to the contract of carriage by sea.

Shipping paper means a shipping order, bill of lading, manifest, or other shipping document serving a similar purpose.

Stowage factor means the volume in cubic meters of 1,000 kilograms (0.984 long tons) of a bulk solid material.

Threshold limit value or *TLV* means the time-weighted average concentration of a material that the average worker can be exposed to over a normal eight-hour working day, day after day, without adverse effect. This is a trademark term of the American Conference of Governmental Industrial Hygienists (ACGIH).

Transported includes the various operations associated with cargo transportation, such as loading, off-loading, handling, stowing, carrying, and conveying.

Trimming means any leveling of a cargo within a cargo hold or compartment, either partial or total.

Tripartite agreement means an agreement between the national administrations of the port of loading, the port of discharge, and the flag state of the vessel, on the conditions of carriage of a cargo.

Ventilation means exchange of air from outside to inside a cargo space and includes the following types:

(1) *Continuous ventilation* means ventilation that is operating at all times. Continuous ventilation may be either natural or mechanical;

(2) *Mechanical ventilation* means power-generated ventilation;

(3) *Natural ventilation* means ventilation that is not power-generated; and

(4) *Surface ventilation* means ventilation of the space above the cargo. Surface ventilation may be either natural or mechanical.

Vessel means a cargo ship or barge.

§ 148.5 Alternative procedures.

(a) The Commandant (CG-5223) may authorize the use of an alternative procedure, including exemptions to the

46 CFR Ch. I (10–1–11 Edition)

IMSBC Code (incorporated by reference, see §148.8), in place of any requirement of this part if it is demonstrated to the satisfaction of the Coast Guard that the requirement is impracticable or unnecessary and that an equivalent level of safety can be maintained.

(b) Each request for authorization of an alternative procedure must—

(1) Be in writing;

(2) Name the requirement for which the alternative is requested; and

(3) Contain a detailed explanation of—

(i) Why the requirement is impracticable or unnecessary; and

(ii) How an equivalent level of safety will be maintained.

§ 148.7 OMB control numbers assigned under the Paperwork Reduction Act.

The information collection requirements in this part are approved by the Office of Management and Budget, and assigned OMB control number 1625-0025.

§ 148.8 Incorporation by reference.

(a) Certain material is incorporated by reference into this part with the approval of the Director of the Federal Register under 5 U.S.C. 552(a) and 1 CFR part 51. To enforce any edition other than that specified in this section, the Coast Guard must publish notice of change in the FEDERAL REGISTER and the material must be available to the public. All approved material is available for inspection at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030 or go to http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html. Also, it is available for inspection at the U.S. Coast Guard Hazardous Materials Standards Division (CG-5223), 2100 2nd St., SW., Stop 7126, Washington, DC 20593-7126, and is available from the sources listed below.

(b) International Maritime Organization (IMO), 4 Albert Embankment, London SE1 7SR, United Kingdom, +44 (0)20 7735 7611, <http://www.imo.org>.

(1) International Maritime Solid Bulk Cargoes Code and Supplement,

2009 edition (“IMSBC Code”), incorporation by reference, excluding supplemental materials, approved for §§148.3; 148.5(a); 148.15(d); 148.55(b); 148.205(b); 148.220(b) and (c); 148.240(h); 148.450(a), (d), and (g).

(2) [Reserved]

(c) United Nations Publications, 2 United Nations Plaza, Room DC2-853, Dept. C089, New York, NY 10017, (800) 253-9646, <http://unp.un.org>.

(1) Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Fifth revised edition (2009) (“UN Manual of Tests and Criteria”), incorporation by reference approved for §§148.205(b); 148.220(b) and (c).

(2) [Reserved]

§ 148.9 Right of appeal.

Any person directly affected by enforcement of this part by or on behalf of the Coast Guard may appeal the decision or action under Subpart 1.03 of this chapter.

§ 148.10 Permitted materials.

(a) A material listed in Table 148.10 of this section may be transported as a bulk solid cargo on a vessel if it is carried according to this part. A material that is not listed in Table 148.10 of this section, but which is hazardous or a Potentially Dangerous Material (PDM), requires a Special Permit under §148.15 of this part to be transported on the navigable waters of the United States.

(b) For each listed material, Table 148.10 identifies the hazard class and gives the BCSN or directs the user to the preferred BCSN. In addition, the table lists specific hazardous or potentially dangerous characteristics associated with each material and specifies or references detailed special requirements in this part pertaining to the stowage or transport of specific bulk solid materials. The column descriptions for Table 148.10 are defined as follows:

(1) *Column 1: Bulk Solid Material Descriptions and Bulk Cargo Shipping Names (BCSN)*. Column 1 lists the bulk solid material descriptions and the BCSNs of materials designated as hazardous or PDM. BCSNs are limited to those shown in Roman type. Trade names and additional descriptive text are shown in italics.

(2) *Column 2: I.D. Number*. Column 2 lists the identification number assigned to each BCSN associated with a hazardous material. Those preceded by the letters “UN” are associated with BCSNs considered appropriate for international voyages as well as domestic voyages. Those preceded by the letters “NA” are associated with BCSNs not recognized for international voyages, except to and from Canada.

(3) *Column 3: Hazard Class or Division*. Column 3 designates the hazard class or division, or PDM, as appropriate, corresponding to each BCSN.

(4) *Column 4: References*. Column 4 refers the user to the preferred BCSN corresponding to bulk solid material descriptions listed in Column 1.

(5) *Column 5: Hazardous or Potentially Dangerous Characteristics*. Column 5 specifies codes for hazardous or potentially dangerous characteristics applicable to specific hazardous materials or PDMs. Refer to §148.11 of this part for the meaning of each code.

(6) *Column 6: Other Characteristics*. Column 6 contains other pertinent characteristics applicable to specific bulk solid materials listed in Column 1.

(7) *Column 7: Special Requirements*. Column 7 specifies the applicable sections of Part 148 of this chapter that contain detailed special requirements pertaining to stowage and/or transportation of specific bulk solid materials in this part. This column is completed in a manner which indicates that “§148.” precedes the designated numerical entry.

(c) The following requirements apply to combinations of bulk solids carried at the same time and in the same compartment or hold:

Combinations of bulk solid materials	Requirements
(1) Material listed in Table 148.10 carried with any other non-hazardous bulk solid material.	Requirements specified in Table 148.10 for the listed material.
(2) Material carried under Special Permit with any non-hazardous bulk solid material.	Requirements specified in the Special Permit.

§ 148.10

46 CFR Ch. I (10–1–11 Edition)

<i>Combinations of bulk solid materials</i>	<i>Requirements</i>
(3) Two or more materials listed in Table 148.10	Must apply for a Special Permit.

(d) An owner, agent, master, operator, or person in charge of a vessel or barge carrying materials listed in Table 148.10 of this section must follow the requirements contained in 46 CFR part 4 for providing notice and reporting of marine casualties and retaining voyage records.

TABLE 148.10—BULK SOLID HAZARDOUS MATERIALS TABLE

Bulk solid material descriptions and bulk cargo shipping names	I.D. No.	Hazard class or division	References	Hazardous or potentially dangerous characteristics (see § 148.11)	Other characteristics	Special requirements (§ 148.* * *)
(1)	(2)	(3)	(4)	(5)	(6)	(7)
Aluminum Ferrosilicon Powder.	UN1395	4.3, 6.1		2, 3	Fine powder or briquettes.	135, 255, 405(b), 407, 415(a) & (e), 420(b), 445, 140
Aluminum Nitrate	UN1438	5.1		4	Colorless or white crystals.	135, 255, 405(b), 407, 415(a) & (e), 420(b), 445, 140
Aluminum Silicon Powder, Uncoated.	UN1398	4.3		2, 3		135, 255, 405(b), 407, 415(a) & (e), 420(b), 445, 135, 405(b), 420(b), 445
Aluminum Smelting By-products or Aluminum Re-melting Byproducts.	UN3170	4.3		1, 2, 3	Includes aluminum dross, residues, spent cathodes, spent potliner, and skimmings.	140, 205, 405(a), 407, 410
Ammonium Nitrate	UN1942	5.1		5, 27		140, 205, 405(a), 407, 410
Ammonium Nitrate Based Fertilizer.	UN2067	5.1		5, 27		140, 205, 405(a), 407, 410
Ammonium Nitrate Based Fertilizer.	UN2071	9		6	Nitrogen, Phosphate, or Potash.	140, 220, 405(a), 407
Barium Nitrate	UN1466	5.1, 6.1		4, 7		140
Brown Coal Briquettes ...		PDM		11, 12, 14, 25		155, 240, 405(b), 407, 415(b), 420(a), 445
Calcium fluoride			See Fluoropar.		.	.
Calcium Nitrate	UN1454	5.1		4	White crystals or powder.	140, 227
Calcium Oxide			See Lime, Unslaked.		.	.
Castor Beans	UN2969	9		10	Whole beans	150, 235
Charcoal		PDM		1, 11, 12	Screenings, briquettes.	155
Chili Saltpeter			See Sodium Nitrate.		.	.
Chilean Natural Nitrate ...			See Sodium Nitrate.		.	.
Coal		PDM		11, 12, 13, 14, 25		155, 240, 405(b), 407, 415(b), 420(a) & (c), 445, 450
Copra	UN1363	4.2		11, 12	Dry	130, 242
Direct reduced iron (A) with not more than 5% fines.		PDM		1, 2, 12	Hot-molded briquettes.	155, 250, 420(b)

TABLE 148.10—BULK SOLID HAZARDOUS MATERIALS TABLE—Continued

Bulk solid material descriptions and bulk cargo shipping names	I.D. No.	Hazard class or division	References	Hazardous or potentially dangerous characteristics (see § 148.11)	Other characteristics	Special requirements (§ 148.* * *)
(1)	(2)	(3)	(4)	(5)	(6)	(7)
Direct reduced iron (B) with not more than 5% fines.		PDM		1, 2, 12	Lumps, pellets, and cold-molded briquettes.	155, 245, 405(b), 407, 420(b), 445
Environmentally Hazardous Substances, Solid, n.o.s..	UN3077	9	Hazardous substances listed in 40 CFR part 302.	15		150, 270
Ferrophosphorous		PDM		2, 3	Including briquettes	155, 415(e), 445
Ferrosilicon with 30–90% silicon.	UN1408	4.3, 6.1		2, 3		135, 255, 405(b), 407, 415(a) & (e), 420(b), 445
Ferrosilicon with 25%–30% silicon or 90% or more silicon.		PDM				155, 255, 405(b), 407, 415 (a) & (e), 420(b), 445
Ferrous Sulfate			See Environmentally Hazardous Substances, Solid, n.o.s.		.	
Ferrous Metal Borings, Shavings, Turnings, or Cuttings.	UN2793	4.2		11, 12		130, 260
Fish Meal Stabilized or Fish Scrap, Stabilized.	UN2216	9		11, 12	Ground and pelletized (mixture), anti-oxidant treated.	150, 265
Fluorospar		PDM		8, 24		155, 440(a), 450
Garbage Tankage			See Tankage.		.	
Iron Oxide, Spent or Iron Sponge, Spent.	UN1376	4.2		3, 11, 12, 14		130, 275, 415(c), (d) & (f), 445
Iron Swarf			See Ferrous Metal Borings, Shavings, Turnings, or Cuttings.		.	
Lead Nitrate	UN1469	5.1, 6.1		4, 7, 22, 26		140, 270
Lignite			See Brown Coal Briquettes.		.	
Lime, Unslaked		PDM		1		155, 230
Linted Cotton Seed containing not more than 9% moisture and not more than 20.5% oil.		PDM		11, 12		155
Magnesia, Unslaked		PDM		1	Lightburned magnesia, calcined magnesite.	155, 280
Magnesium Nitrate	UN1474	5.1		4		140

TABLE 148.10—BULK SOLID HAZARDOUS MATERIALS TABLE—Continued

Bulk solid material descriptions and bulk cargo shipping names	I.D. No.	Hazard class or division	References	Hazardous or potentially dangerous characteristics (see § 148.11)	Other characteristics	Special requirements (§ 148.* * *)
(1)	(2)	(3)	(4)	(5)	(6)	(7)
Metal Sulfide Concentrates.		PDM		8, 11, 12, 22, 24	Solid, finely divided sulfide concentrates of copper, iron, lead, nickel, zinc, or other metalliferous ores.	155, 285, 450
Peat Moss with moisture content of more than 65% by weight.		PDM		8, 12, 13, 14, 24	Fine to coarse fibrous structure.	155, 290, 450
Pencil Pitch			See Pitch Prill.		.	
Petroleum Coke calcined or uncalcined at > 55 °C (131 °F).		PDM		11		155, 295
Pitch Prill		PDM		14, 16		155
Potassium Nitrate	UN1486	5.1		4		140
Prilled Coal Tar			See Pitch Prill.		.	
Pyrites, Calcined		PDM		8, 9, 24	Fly ash	155, 225, 450
Pyritic ash			See Pyrites, Calcined.		.	
Quicklime			See Lime, Unslaked.		.	
Radioactive Material	UN2912	7		17	Low specific activity	145, 300
Radioactive Material	UN2913	7		17	Surface contaminated objects.	145, 300
Rough Ammonia Tankage.			See Tankage.		.	
Saltpeter			See Potassium Nitrate.		.	
Sawdust		PDM		12, 18		155, 405(a), 407
Seed Cake	UN1386	4.2		12, 19	Mechanically expelled or solvent extractions.	130, 310
Seed Cake	UN2217	4.2		12, 19	Solvent extractions	130, 310
Silicomanganese with silicon content of 25% or more.		PDM		2, 3, 12	With known hazard profile or known to evolve gases.	155, 405(b), 407, 415(a) & (d), 420(b), 445
Sodium Nitrate	UN1498	5.1		4		140
Sodium Nitrate and Potassium Nitrate Mixture.	UN1499	5.1		4	Mixtures prepared as fertilizer.	140
Steel Swarf			See Ferrous Metal Borings, Shavings, Turnings, or Cuttings.		.	
Sulfur	UN1350	4.1		14, 20	Lumps or coarse-grained powder.	125, 315, 405(a), 407, 435

TABLE 148.10—BULK SOLID HAZARDOUS MATERIALS TABLE—Continued

Bulk solid material descriptions and bulk cargo shipping names	I.D. No.	Hazard class or division	References	Hazardous or potentially dangerous characteristics (see § 148.11)	Other characteristics	Special requirements (§ 148.2 * *)
Sulfur	NA1350	9		14, 20	Not subject to the requirements of this subchapter when formed into specific shapes (i.e., prills, granules, pellets, pastiles, or flakes).	125, 315, 405(a), 407, 435
Tankage		PDM		11		155, 320
Tankage Fertilizer			See Tankage.			
Vanadium Ore		PDM		21		155
Wood chips, Wood Pellets, Wood Pulp Pellets.		PDM		12		155, 325
Zinc Ashes	UN1435	4.3		2, 3, 23	Includes zinc dross, residues, and skimmings.	135, 330, 405(b), 407, 420(b), 435, 445

§ 148.11 Hazardous or potentially dangerous characteristics.

(a) General. When Column 5 refers to a code for a hazardous material or

PDM, the meaning of that code is set forth in this section.

(b) Table of Hazardous or Potentially Dangerous Characteristics.

Code	Hazardous or potentially dangerous characteristic
1	Contact with water may cause heating.
2	Contact with water may cause evolution of flammable gases, which may form explosive mixtures with air.
3	Contact with water may cause evolution of toxic gases.
4	If involved in a fire, will greatly intensify the burning of combustible materials.
5	A major fire aboard a vessel carrying this material may involve a risk of explosion in the event of contamination (e.g., by a fuel oil) or strong confinement. If heated strongly will decompose, giving off toxic gases that support combustion.
6	These mixtures may be subject to self-sustaining decomposition if heated. Decomposition, once initiated, may spread throughout the remainder, producing gases that are toxic.
7	Toxic if swallowed and by dust inhalation.
8	Harmful and irritating by dust inhalation.
9	Highly corrosive to steel.
10	Powerful allergen. Toxic by ingestion. Skin contact or inhalation of dust may cause severe irritation of skin, eyes, and mucous membranes in some people.
11	May be susceptible to spontaneous heating and ignition.
12	Liable to cause oxygen depletion in the cargo space.
13	Liable to emit methane gas which can form explosive mixtures with air.
14	Dust forms explosive mixtures with air.
15	May present substantial danger to the public health or welfare or the environment when released into the environment. Skin contact and dust inhalation should be avoided.
16	Combustible. Burns with dense black smoke. Dust may cause skin and eye irritation.
17	Radiation hazard from dust inhalation and contact with mucous membranes.
18	Susceptible to fire from sparks and open flames.
19	May self-heat slowly and, if wet or containing an excessive proportion of unoxidized oil, ignite spontaneously.
20	Fire may produce irritating or poisonous gases.
21	Dust may contain toxic constituents.
22	Lead nitrate and lead sulfide are hazardous substances; see code 15 of this table and § 148.270.
23	Hazardous substance when consisting of pieces having a diameter less than 100 micrometers (0.004 in.); see code 15 of this table and § 148.270.
24	Cargo subject to liquefaction.
25	Subject to liquefaction if average particle size of cargo is less than 10 mm (.394 in.).
26	This entry is considered a Marine Pollutant in accordance with 49 CFR 172.101 Appendix B.
27	This entry is considered a certain dangerous cargo in accordance with 33 CFR 160.204.

§ 148.12

46 CFR Ch. I (10–1–11 Edition)

§ 148.12 Assignment and certification.

(a) The National Cargo Bureau is authorized to assist the Coast Guard in administering the provisions of this part by—

(1) Inspecting vessels for suitability for loading solid materials in bulk;

(2) Examining stowage of solid materials loaded in bulk on board vessels;

(3) Making recommendations on stowage requirements applicable to the transportation of solid materials in bulk; and

(4) Issuing certificates of loading that verify stowage of the solid material in bulk meets requirements of this part.

(b) Certificates of loading from the National Cargo Bureau are accepted as evidence of compliance with bulk solid transport regulations.

Subpart B—Special Permits

§ 148.15 Petition for a special permit.

(a) Each shipper who wishes to ship a bulk solid material not listed in Table 148.10 of this part must determine whether the material meets the definition of any hazard class, or the definition of a PDM, as those terms are defined in § 148.3 of this part.

(b) If the material meets any of the definitions described in paragraph (a) of this section, the shipper then must submit a petition in writing to the Commandant (CG–5223) for authorization to ship any hazardous material or PDM not listed in Table 148.10 of this part.

(c) If the Commandant (CG–5223) approves a petition for authorization, the Commandant (CG–5223) issues the petitioner a Coast Guard special permit. The permit allows the material to be transported in bulk by vessel and outlines requirements for this transport.

(d) A tripartite agreement developed in conjunction with the United States and in accordance with the IMSBC Code (incorporated by reference, see § 148.8) may be used in lieu of a special permit.

§ 148.20 Deadlines for submission of petition and related requests.

(a) A petition for a special permit must be submitted at least 45 days before the requested effective date. Re-

quests for extension or renewal of an existing special permit must be submitted 20 days before the date of expiration.

(b) Requests for extension or renewal must include the information required under § 148.21(a), (f), and (g) of this part.

§ 148.21 Necessary information.

Each petition for a special permit must contain at least the following:

(a) A description of the material, including, if a hazardous material—

(1) The proper shipping name from the table in 49 CFR 172.101;

(2) The hazard class and division of the material; and

(3) The identification number of the material.

(b) A material safety data sheet (MSDS) for the material or—

(1) The chemical name and any trade names or common names of the material;

(2) The composition of the material, including the weight percent of each constituent;

(3) Physical data, including color, odor, appearance, melting point, and solubility;

(4) Fire and explosion data, including auto-ignition temperature, any unusual fire or explosion hazards, and any special fire fighting procedures;

(5) Health hazards, including any dust inhalation hazards and any chronic health effects;

(6) The threshold limit value (TLV) of the material or its major constituents, if available, and any relevant toxicity data;

(7) Reactivity data, including any hazardous decomposition products and any incompatible materials; and

(8) Special protection information, including ventilation requirements and personal protection equipment required.

(c) Other potentially dangerous characteristics of the material not covered by paragraph (b) of this section, including—

(1) Self-heating;

(2) Depletion of oxygen in the cargo space;

(3) Dust explosion; and

(4) Liquefaction.

Coast Guard, DHS

§ 148.55

(d) A detailed description of the proposed transportation operation, including—

(1) The type of vessel proposed for water movements;

(2) The expected loading and discharge ports, if known;

(3) Procedures to be used for loading and unloading the material;

(4) Precautions to be taken when handling the material; and

(5) The expected temperature of the material at the time it will be loaded on the vessel.

(e) Test results (if required under Subpart E of this part).

(f) Previous approvals or permits.

(g) Any relevant shipping or accident experience (or any other relevant transportation history by any mode of transport).

§ 148.25 Activities covered by a special permit.

(a) Each special permit covers any shipment of the permitted material by the shipper and also covers for each shipment—

(1) Each transfer operation;

(2) Each vessel involved in the shipment; and

(3) Each individual involved in any cargo handling operation.

(b) Each special permit is valid for a period determined by the Commandant (CG-5223) and specified in the special permit. The period will not exceed 4 years and is subject to suspension or revocation before its expiration date.

§ 148.26 Standard conditions for special permits.

(a) Each special permit holder must comply with all the requirements of this part unless specifically exempted by the terms of the special permit.

(b) Each special permit holder must provide a copy of the special permit and the information required in §148.60 of this part to the master or person in charge of each vessel carrying the material.

(c) The master of a vessel transporting a special permit material must ensure that a copy of the special permit is on board the vessel. The special permit must be kept with the dangerous cargo manifest if such a manifest is required by §148.70 of this part.

(d) The person in charge of a barge transporting any special permit material must ensure that a copy of the special permit is on board the tug or towing vessel. When the barge is moored, the special permit must be kept on the barge with the shipping papers as prescribed in §148.62 of this part.

§ 148.30 Records of special permits issued.

A list of all special permits issued, and copies of each, are available from the Commandant (CG-5223).

Subpart C—Minimum Transportation Requirements

§ 148.50 Cargoes subject to this subpart.

The regulations in this subpart apply to each bulk shipment of—

(a) A material listed in Table 148.10 of this part; and

(b) Any solid material shipped under the terms of a Coast Guard special permit.

§ 148.51 Temperature readings.

When Subpart D of this part sets a temperature limit for loading or transporting a material, apply the following rules:

(a) The temperature of the material must be measured 20 to 36 centimeters (8 to 14 inches) below the surface at 3 meter (10 foot) intervals over the length and width of the stockpile or cargo hold.

(b) The temperature must be measured at every spot in the stockpile or cargo hold that shows evidence of heating.

(c) Before loading or transporting the material, all temperatures measured must be below the temperature limit set in Subpart D of this part.

§ 148.55 International shipments.

(a) *Importer's responsibility.* Each person importing any bulk solid material requiring special handling into the United States must provide the shipper and the forwarding agent at the place of entry into the United States with timely and complete information as to the requirements of this part that will apply to the shipment of the material within the United States.

§ 148.60

46 CFR Ch. I (10–1–11 Edition)

(b) *IMSBC Code*. Notwithstanding the provisions of this part, a bulk solid material that is classed, described, stowed, and segregated in accordance with the *IMSBC Code* (incorporated by reference, see §148.8), and otherwise conforms to the requirements of this section, may be offered and accepted for transportation and transported within the United States. The following conditions and limitations apply:

(1) A bulk solid material that is listed in Table 148.10 of this part, but is not subject to the requirements of the *IMSBC Code*, may not be transported under the provisions of this section and is subject to the requirements of this part. Examples of such materials include environmentally hazardous substances, solid, n.o.s.

(2) Zinc Ashes must conform to the requirements found in §148.330 of this part.

(3) Exemptions granted by other competent authorities in accordance with the *IMSBC Code* must be approved by the Commandant (CG-5223) in accordance with §148.5 of this part.

(4) Tripartite agreements granted by other competent authorities in accordance with the *IMSBC Code* must be authorized for use in the United States by the Commandant (CG-5223).

§ 148.60 Shipping papers.

The shipper of a material listed in Table 148.10 of this part must provide the master or his representative with appropriate information on the cargo in the form of a shipping paper, in English, prior to loading. Information on the shipping paper must include the following:

(a) The appropriate BCSN. Secondary names may be used in addition to the BCSN;

(b) The identification number, if applicable;

(c) The hazard class of the material as listed in Table 148.10 of this part or on the Special Permit for the material;

(d) The total quantity of the material to be transported;

(e) The stowage factor;

(f) The need for trimming and the trimming procedures, as necessary;

(g) The likelihood of shifting, including angle of repose, if applicable;

(h) A certificate on the moisture content of the cargo and its transportable moisture limit for cargoes that are subject to liquefaction;

(i) Likelihood of formation of a wet base;

(j) Toxic or flammable gases that may be generated by the cargo, if applicable;

(k) Flammability, toxicity, corrosiveness, and propensity to oxygen depletion of the cargo, if applicable;

(l) Self-heating properties of the cargo, if applicable;

(m) Properties on emission of flammable gases in contact with water, if applicable;

(n) Radioactive properties, if applicable;

(o) The name and address of the U.S. shipper (consignor) or, if the shipment originates in a foreign country, the U.S. consignee.

(p) A certification, signed by the shipper, that bears the following statement: “This is to certify that the above named material is properly named, prepared, and otherwise in proper condition for bulk shipment by vessel in accordance with the applicable regulations of the U.S. Coast Guard.”

§ 148.61 Emergency response information.

The shipper of a material listed in Table 148.10 of this part must provide the master or his representative with appropriate emergency response information. This information may be included on the shipping papers or in a separate document such as a material safety data sheet (MSDS). The information must include preliminary first aid measures and emergency procedures to be carried out in the event of an incident or fire involving the cargo.

§ 148.62 Location of shipping papers and emergency response information.

(a) The shipping paper and emergency response information required by §§148.60 and 148.61 of this part must be kept on board the vessel along with the dangerous cargo manifest required by §148.70 of this part. When the shipment

Coast Guard, DHS

§ 148.86

is by unmanned barge the shipping papers and emergency response information must be kept on the tug or towing vessel. When an unmanned barge is moored, the shipping paper and emergency response information must be on board the barge in a readily retrievable location.

(b) Any written certification or statement from the shipper to the master of a vessel or to the person in charge of a barge must be on, or attached to, the shipping paper. See Subparts E and F of this part for required certifications.

§ 148.70 Dangerous cargo manifest; general.

(a) Except as provided in paragraph (b) of this section and in §148.72 of this part, each vessel transporting materials listed in Table 148.10 of this part must have a dangerous cargo manifest on board.

(b) This document must be kept in a designated holder on or near the vessel's bridge. When required for an unmanned barge, the document must be on board the tug or towing vessel.

§ 148.71 Information included in the dangerous cargo manifest.

The dangerous cargo manifest must include the following:

(a) The name and official number of the vessel. If the vessel has no official number, the international radio call sign must be substituted;

(b) The nationality of the vessel;

(c) The name of the material as listed in Table 148.10 of this part;

(d) The hold or cargo compartment in which the material is being transported;

(e) The quantity of material loaded in each hold or cargo compartment; and

(f) The signature of the master acknowledging that the manifest is correct, and the date of the signature.

§ 148.72 Dangerous cargo manifest; exceptions.

(a) No dangerous cargo manifest is required for—

(1) Shipments by unmanned barge, except on an international voyage; and

(2) Shipments of materials designated as potentially dangerous materials in Table 148.10 of this part.

(b) When a dangerous cargo manifest is required for an unmanned barge on an international voyage, §148.71(d) of this part does not apply, unless the barge has more than one cargo compartment.

§ 148.80 Supervision of cargo transfer.

The master must ensure that cargo transfer operations are supervised by a responsible person as defined in §148.3 of this part.

§ 148.85 Required equipment for confined spaces.

When transporting a material that is listed in Table 148.10 of this part, each vessel, other than an unmanned barge, must have on board the following:

(a) Equipment capable of measuring atmospheric oxygen. At least two members of the crew must be knowledgeable in the use of the equipment, which must be maintained in a condition ready for use and calibrated according to the manufacturer's instructions.

(b) At least two self-contained, pressure-demand-type, air breathing apparatus approved by the Mine Safety and Health Administration (MSHA) or the National Institute for Occupational Safety and Health (NIOSH), each having at least a 30-minute air supply. Each foreign flag vessel must have on board at least two such apparatus that are approved by the flag state administration. The master must ensure that the breathing apparatus is used only by persons trained in its use.

§ 148.86 Confined space entry.

(a) Except in an emergency, no person may enter a confined space unless that space has been tested to ensure there is sufficient oxygen to support life. If the oxygen content is below 19.5 percent, the space must be ventilated and retested before entry.

(b) In an emergency, a confined space may be entered by a trained person wearing self-contained breathing apparatus, suitable protective clothing as necessary, and a wire rope safety line tended by a trained person outside the

§ 148.90

hold or in an adjacent space. Emergency entry into a confined space must be supervised by a responsible person as defined in §148.3 of this part.

§ 148.90 Preparations before loading.

Before loading any material listed in Table 148.10 of this part, in bulk on board a vessel, the following conditions must be met:

(a) If a hold previously has contained any material required under Subpart D of this part to be segregated from the material to be loaded, the hold must be thoroughly cleaned of all residue of the previous cargoes.

(b) If the material to be loaded is Class 4.1, 4.2, or 5.1, then all combustible materials must be removed from the hold. Examples of some combustible materials are residue of previous cargoes, loose debris, and dunnage. Permanent wooden battens or sheathing may remain in the hold unless forbidden by Subpart E of this part.

(c) If the material to be loaded is classified as Class 4.3, or is subject to liquefaction, the hold and associated bilge must be as dry as practicable.

§ 148.100 Log book entries.

During the transport in bulk of a material listed in Table 148.10 of this part, the master must keep a record of each temperature measurement and each test for toxic or flammable gases required by this part. The date and time of each measurement and test must be recorded in the vessel's log.

§ 148.110 Procedures followed after unloading.

(a) After a material covered by this part has been unloaded from a vessel, each hold or cargo compartment must be thoroughly cleaned of all residue of such material unless the hold is to be reloaded with that same cargo.

(b) When on U.S. territorial seas or inland waters, cargo associated wastes, cargo residue, and deck sweepings must be retained on the vessel and disposed of in accordance with 33 CFR parts 151.51 through 151.77.

§ 148.115 Report of incidents.

(a) When a fire or other hazardous condition occurs on a vessel transporting a material covered by this

46 CFR Ch. I (10–1–11 Edition)

part, the master must notify the nearest Captain of the Port as soon as possible and comply with any instructions given.

(b) Any incident or casualty occurring while transporting a material covered by this part must also be reported as required under 49 CFR 171.15, if applicable. A copy of the written report required under 49 CFR 171.16 must also be sent to the Commandant (CG-5223), U.S. Coast Guard, 2100 2nd St., SW., Stop 7126, Washington, DC 20593-7126, at the earliest practicable moment.

(c) Any release to the environment of a hazardous substance in a quantity equal to or in excess of its reportable quantity (RQ) must be reported immediately to the National Response Center at (800) 424-8802 (toll free) or (202) 267-2675.

Subpart D—Stowage and Segregation

§ 148.120 Stowage and segregation requirements.

(a) Each material listed in Table 148.10 of this part must be segregated from incompatible materials in accordance with—

(1) The requirements of Tables 148.120A and 148.120B of this section that pertain to the primary or subsidiary hazard class to which the materials belong. Whenever a subsidiary hazard may exist, the most stringent segregation requirement applies; and

(2) Any specific requirements in Subpart D of this part.

(b) Materials that are required to be separated during stowage must not be handled at the same time. Any residue from a material must be removed before a material required to be separated from it is loaded.

(c) Definitions and application of segregation terms:

(1) “*Separated from*” means located in different cargo compartments or holds when stowed under deck. If the intervening deck is resistant to fire and liquid, a vertical separation, i.e., in different cargo compartments, is acceptable as equivalent to this segregation.

(2) “*Separated by a complete cargo compartment or hold from*” means either a vertical or horizontal separation, for

Coast Guard, DHS

§ 148.125

example, by a complete cargo compartment or hold. If the intervening decks are not resistant to fire and liquid, only horizontal separation is acceptable.

(3) “*Separated longitudinally by an intervening complete cargo compartment or hold from*” means that vertical separation alone does not meet this requirement.

TABLE 148.120A—SEGREGATION BETWEEN INCOMPATIBLE BULK SOLID CARGOES

Bulk solid materials	Class	4.1	4.2	4.3	5.1	6.1	7	8	9/PDM
Flammable solid	4.1	X							
Spontaneously combustible material	4.2	2	X						
Dangerous when wet material	4.3	3	3	X					
Oxidizer	5.1	3	3	3	X				
Poisonous material	6.1	X	X	X	2	X			
Radioactive material	7	2	2	2	2	2	X		
Corrosive material	8	2	2	2	2	X	X	X	
Miscellaneous hazardous material and potential dangerous material	9/PDM	X	X	X	X	X	2	X	X

Numbers and symbols indicate the following terms as defined in § 148.3 of this part:

2—“Separated from”.

3—“Separated by a complete hold or compartment from”.

X—No segregation required, except as specified in an applicable section of this subpart or Subpart E of this part.

TABLE 148.120B—SEGREGATION BETWEEN BULK SOLID CARGOES AND INCOMPATIBLE PACKAGED CARGOES

Packaged hazardous material	Bulk solid material								
	Class	4.1	4.2	4.3	5.1	6.1	7	8	9/PDM
Explosives	1.1	4	4	4	4	2	2	4	X
	1.2								
	1.5								
Explosives	1.3	3	3	4	4	2	2	2	X
	1.6								
Explosives	1.4	2	2	2	2	X	2	2	X
Flammable gas	2.1	2	2	1	2	X	2	2	X
Non-flammable compressed gas	2.2	2	2	X	X	X	2	1	X
Poisonous gas	2.3	2	2	X	X	X	2	1	X
Flammable liquid	3	2	2	2	2	X	2	1	X
Flammable solid	4.1	X	1	X	1	X	2	1	X
Spontaneously combustible material	4.2	1	X	1	2	1	2	1	X
Dangerous when wet material	4.3	X	1	X	2	X	2	1	X
Oxidizer	5.1	1	2	2	X	1	1	2	X
Organic peroxide	5.2	2	2	2	2	1	2	2	X
Poisonous material	6.1	X	1	X	1	X	X	X	X
Infectious substance	6.2	3	3	2	3	1	3	3	X
Radioactive material	7	2	2	2	1	X	X	2	X
Corrosive material	8	1	1	1	2	X	2	X	X
Miscellaneous hazardous material	9	X	X	X	X	X	X	X	X

Numbers and symbols indicate the following terms as defined in § 148.3 of this part:

1—“Away from”.

2—“Separated from”.

3—“Separated by a complete hold or compartment from”.

4—“Separated longitudinally by an intervening complete compartment or hold from”.

X—No segregation required, except as specified in an applicable section of this subpart or Subpart E of this part.

§ 148.125 Stowage and segregation for materials of Class 4.1.

(a) Class 4.1 materials listed in Table 148.10 of this part must—

(1) Be kept as cool and dry as practical before loading;

(2) Not be loaded or transferred between vessels during periods of rain or snow;

(3) Be stowed separated from food-stuffs; and

(4) Be stowed clear of sources of heat and ignition and protected from sparks and open flame.

(b) Bulkheads between a hold containing a Class 4.1 material and incompatible materials must have cable and conduit penetrations sealed against the passage of gas and vapor.

§ 148.130

§ 148.130 Stowage and segregation for materials of Class 4.2.

(a) Class 4.2 materials listed in Table 148.10 of this part must—

(1) Be kept as cool and dry as practical before loading;

(2) Not be loaded or transferred between vessels during periods of rain or snow;

(3) Be stowed clear of sources of heat and ignition and protected from sparks and open flame; and

(4) Except for copra and seed cake, be stowed separate from foodstuffs.

(b) The bulkhead between a hold containing a Class 4.2 material and a hold containing a material not permitted to mix with Class 4.2 materials must have cable and conduit penetrations sealed against the passage of gas and vapor.

§ 148.135 Stowage and segregation for materials of Class 4.3.

(a) Class 4.3 materials listed in Table 148.10 of this part which, in contact with water, emit flammable gases, must—

(1) Be kept as cool and dry as practical before loading;

(2) Not be loaded or transferred between vessels during periods of rain or snow;

(3) Be stowed separate from foodstuffs and all Class 8 liquids; and

(4) Be stowed in a mechanically ventilated hold. Exhaust gases must not penetrate into accommodation, work or control spaces. Unmanned barges that have adequate natural ventilation need not have mechanical ventilation.

(b) The bulkhead between a hold containing a Class 4.3 material and incompatible materials must have cable and conduit penetrations sealed against the passage of gas and vapor.

§ 148.140 Stowage and segregation for materials of Class 5.1.

(a) Class 5.1 materials listed in Table 148.10 of this part must—

(1) Be kept as cool and dry as practical before loading;

(2) Be stowed away from all sources of heat or ignition; and

(3) Be stowed separate from foodstuffs and all readily combustible materials.

(b) Special care must be taken to ensure that holds containing Class 5.1

46 CFR Ch. I (10–1–11 Edition)

materials are clean and, whenever practical, only noncombustible securing and protecting materials are used.

(c) Class 5.1 materials must be prevented from entering bilges or other cargo holds.

§ 148.145 Stowage and segregation for materials of Class 7.

(a) Class 7 material listed in Table 148.10 of this part must be stowed—

(1) Separate from foodstuffs; and

(2) In a hold or barge closed or covered to prevent dispersal of the material during transportation.

(b) [Reserved]

§ 148.150 Stowage and segregation for materials of Class 9.

(a) A bulk solid cargo of Class 9 material (miscellaneous hazardous material) listed in Table 148.10 of this part must be stowed and segregated as required by this section.

(b) Ammonium nitrate fertilizer of Class 9 must be segregated as required for Class 5.1 materials in §§148.120 and 148.140 of this part and must be stowed—

(1) Separated by a complete hold or compartment from readily combustible materials, chlorates, hypochlorites, nitrites, permanganates, and fibrous materials (*e.g.*, cotton, jute, sisal, *etc.*);

(2) Clear of all sources of heat, including insulated piping; and

(3) Out of direct contact with metal engine-room boundaries.

(c) Castor beans must be stowed separate from foodstuffs and Class 5.1 materials.

(d) Fish meal must be stowed and segregated as required for Class 4.2 materials in §§148.120 and 148.130 of this part. In addition, its temperature at loading must not exceed 35 °C (95 °F), or 5 °C (9 °F) above ambient temperature, whichever is higher.

(e) Sulfur must be stowed and segregated as required under §§148.120 and 148.125 of this part for a material of Class 4.1.

§ 148.155 Stowage and segregation for potentially dangerous materials.

(a) A PDM must be stowed and segregated according to the requirements of this section and Table 148.155 of this section.

(b) When transporting coal—

(1) Coal must be stowed separate from materials of Class/division 1.4 and Classes 2, 3, 4, and 5 in packaged form; and separated from bulk solid materials of Classes 4 and 5.1;

(2) No material of Class 5.1, in either packaged or bulk solid form, may be stowed above or below a cargo of coal; and

(3) Coal must be separated longitudinally by an intervening complete cargo compartment or hold from materials of Class 1 other than Class/division 1.4.

(c) When transporting direct reduced iron (DRI)—

(1) DRI lumps, pellets, or cold-molded briquettes, and DRI hot-molded bri-

quettes, must be separated from materials of Class/division 1.4, Classes 2, 3, 4, 5, Class 8 acids in packaged form, and bulk solid materials of Classes 4 and 5.1; and

(2) No material of Class 1, other than Class/division 1.4, may be transported on the same vessel with DRI.

(d) Petroleum coke, calcined or uncalcined, must be—

(1) Separated longitudinally by an intervening complete cargo compartment or hold from materials of Class/divisions 1.1 and 1.5; and

(2) Separated by a complete cargo compartment or hold from all hazardous materials and other potentially dangerous materials in packaged and bulk solid form.

TABLE 148.155—STOWAGE AND SEGREGATION REQUIREMENTS FOR POTENTIALLY DANGEROUS MATERIAL

Potentially dangerous material	Segregate as for class listed ¹	"Separate from" food-stuffs	Load only under dry weather conditions	Keep dry	Mechanical ventilation required	"Separate from" material listed	Special provisions
Aluminum Smelting By-products or Aluminum Remelting By-products.	4.3	X	X	X	X	Class 8 liquids	
Brown Coal Briquettes.						See paragraph (b) of this section.	See paragraph (b) of this section.
Charcoal	4.1			X		Oily materials	
Coal						See paragraph (b) of this section.	See paragraph (b) of this section.
Direct reduced iron (A).						See paragraph (c) of this section.	See paragraph (c) of this section.
Direct reduced iron (B).						See paragraph (c) of this section.	See paragraph (c) of this section.
Ferrophosphorus.	4.3	X	X	X	X	Class 8 liquids	
Ferrollicon	4.3	X	X	X	X	Class 8 liquids	
Fluorospar		X				Class 8 liquids	
Lime, Unslaked				X		All packaged and bulk solid hazardous materials.	
Linted Cotton Seed.				X			
Magnesia, Unslaked.						All packaged and bulk solid hazardous materials.	
Metal Sulfide Concentrates.	4.2	X				Class 8 liquids	
Petroleum Coke		X					See section 148.155(d).
Pitch Prill	4.1						
Pyrites, Calcined.		X	X	X	X		
Sawdust	4.1			X		All Class 5.1 and 8 liquids.	

TABLE 148.155—STOWAGE AND SEGREGATION REQUIREMENTS FOR POTENTIALLY DANGEROUS MATERIAL—Continued

Potentially dangerous material	Segregate as for class listed ¹	“Separate from” food-stuffs	Load only under dry weather conditions	Keep dry	Mechanical ventilation required	“Separate from” material listed	Special provisions
Silicomanganese.	4.3	X	X	X	X	Class 8 liquids	
Tankage	4.2	X	X				
Vanadium	6.1	X					
Wood chips	4.1						
Wood pellets	4.1						
Wood pulp pellets.	4.1						

¹ See Tables 148.120A and B.

Subpart E—Special Requirements for Certain Materials

§ 148.200 Purpose.

This subpart prescribes special requirements for specific materials. These requirements are in addition to the minimum transportation requirements in Subpart C of this part that are applicable to all materials listed in Table 148.10 of this part.

§ 148.205 Ammonium nitrate and ammonium nitrate fertilizers.

(a) This section applies to the stowage and transportation in bulk of ammonium nitrate and the following fertilizers composed of uniform, non-segregating mixtures containing ammonium nitrate:

(1) Ammonium nitrate containing added organic matter that is chemically inert towards the ammonium nitrate; containing at least 90 percent ammonium nitrate and a maximum of 0.2 percent of combustible material (including organic material calculated as carbon); or containing less than 90 percent but more than 70 percent of ammonium nitrate and a maximum of 0.4 percent combustible material;

(2) Ammonium nitrate with calcium carbonate and/or dolomite, containing more than 80 percent but less than 90 percent of ammonium nitrate and a maximum of 0.4 percent of total combustible material;

(3) Ammonium nitrate with ammonium sulfate containing more than 45 percent but a maximum of 70 percent of ammonium nitrate and containing a maximum of 0.4 percent of combustible material; and

(4) Nitrogen phosphate or nitrogen/potash type fertilizers or complete nitrogen/phosphate/potash type fertilizers containing more than 70 percent but less than 90 percent of ammonium nitrate and a maximum of 0.4 percent of combustible material.

(b) No material covered by this section may be transported in bulk unless it demonstrates resistance to detonation when tested by one of the following methods:

(1) Appendix 2, Section 5, of the IMSBC Code (incorporated by reference, see § 148.8);

(2) Test series 1 and 2 of the Class 1 (explosive) in the UN Manual of Tests and Criteria, Part I (incorporated by reference, see § 148.8); or

(3) An equivalent test satisfactory to the Administration of the country of shipment.

(c) Before loading a material covered by this section—

(1) The shipper must give the master of the vessel written certification that the material has met the test requirements of paragraph (b) of this section;

(2) The cargo hold must be inspected for cleanliness and free from readily combustible materials;

(3) Each cargo hatch must be weathertight as defined in § 42.13–10 of this chapter;

(4) The temperature of the material must be less than 55 °C (131 °F); and

(5) Each fuel tank under a cargo hold where the material is stowed must be pressure tested before loading to ensure that there is no leakage of manholes or piping systems leading through the cargo hold.

(d) Bunkering or transferring of fuel to or from the vessel may not be performed during cargo loading and unloading operations involving a material covered by this section.

(e) When a material covered by this section is transported on a cargo vessel—

(1) No other material may be stowed in the same hold with that material;

(2) In addition to the segregation requirements in §148.140 of this part, the material must be separated by a complete cargo compartment or hold from readily combustible materials, chlorates, chlorides, chlorites, hypochlorites, nitrites, permanganates, and fibrous materials; and

(3) The bulkhead between a cargo hold containing a material covered by this section and the engine room must be insulated to “A-60” class division or an equivalent arrangement to the satisfaction of the cognizant Coast Guard Captain of the Port or the Administration of the country of shipment.

§ 148.220 Ammonium nitrate-phosphate fertilizers.

(a) This section applies to the stowage and transportation of uniform, nonsegregating mixtures of nitrogen/phosphate or nitrogen/potash type fertilizers, or complete fertilizers of nitrogen/phosphate/potash type containing a maximum of 70 percent of ammonium nitrate and containing a maximum of 0.4 percent total added combustible material or containing a maximum of 45 percent ammonium nitrate with unrestricted combustible material.

(b) A fertilizer mixture described in paragraph (a) of this section is exempt if—

(1) When tested in accordance with the trough test prescribed in Appendix 2, Section 4, of the IMSBC Code or in the UN Manual of Tests and Criteria, Part III, Subsection 38.2 (incorporated by reference, see §148.8), it is found to be free from the risk of self-sustaining decomposition.

(2) [Reserved]

(c) No fertilizer covered by this section may be transported in bulk if, when tested in accordance with the trough test prescribed in Appendix 2, Section 4, of the IMSBC Code or in the UN Manual of Tests and Criteria, Part

III, Subsection 38.2 (incorporated by reference, see §148.8), it has a self-sustaining decomposition rate that is greater than 0.25 meters per hour, or is liable to self-heat sufficient to initiate decomposition.

(d) Fertilizers covered by this section must be stowed away from all sources of heat, and out of direct contact with a metal engine compartment boundary.

(e) Bunkering or transferring of fuel may not be performed during loading and unloading of fertilizer covered by this section.

(f) Fertilizer covered by this section must be segregated as prescribed in §§148.140 and 148.220(d) of this part.

§ 148.225 Calcined pyrites (pyritic ash, fly ash).

(a) This part does not apply to the shipment of calcined pyrites that are the residual ash of oil or coal fired power stations.

(b) This section applies to the stowage and transportation of calcined pyrites that are the residual product of sulfuric acid production or elemental metal recovery operations.

(c) Before loading calcined pyrites covered by this section—

(1) The cargo space must be as clean and dry as practical;

(2) The calcined pyrites must be dry; and

(3) Precautions must be taken to prevent the penetration of calcined pyrites into other cargo spaces, bilges, wells, and ceiling boards.

(d) After calcined pyrites covered by this section have been unloaded from a cargo space, the cargo space must be thoroughly cleaned. Cargo residues and sweepings must be disposed of as prescribed in 33 CFR parts 151.55 through 151.77.

§ 148.227 Calcium nitrate fertilizers.

This part does not apply to commercial grades of calcium nitrate fertilizers consisting mainly of a double salt (calcium nitrate and ammonium nitrate) and containing a maximum of 15.5 percent nitrogen and at least 12 percent of water.

§ 148.230

46 CFR Ch. I (10–1–11 Edition)

§ 148.230 Calcium oxide (lime, unslaked).

(a) When transported by barge, unslaked lime (calcium oxide) must be carried in an unmanned, all steel, double-hulled barge equipped with weathertight hatches or covers. The barge must not carry any other cargo while unslaked lime is on board.

(b) The shipping paper requirements in § 148.60 of this part and the dangerous cargo manifest requirements in § 148.70 of this part do not apply to the transportation of unslaked lime under paragraph (a) of this section.

§ 148.235 Castor beans.

(a) This part applies only to the stowage and transportation of whole castor beans. Castor meal, castor pomace, and castor flakes may not be shipped in bulk.

(b) Persons handling castor beans must wear dust masks and goggles.

(c) Care must be taken to prevent castor bean dust from entering accommodation, control, or service spaces during cargo transfer operations.

§ 148.240 Coal.

(a) The electrical equipment in cargo holds carrying coal must meet the requirements of Subpart 111.105 of this chapter or an equivalent standard approved by the administration of the vessel's flag state.

(b) Before coal is loaded in a cargo hold, the bilges must be as clean and dry as practical. The hold must also be free of any readily combustible material, including the residue of previous cargoes if other than coal.

(c) The master of each vessel carrying coal must ensure that—

(1) All openings to the cargo hold, except for unloading gates on self-unloading vessels, are sealed before loading the coal and, unless the coal is as described in paragraph (f) of this section, the hatches must also be sealed after loading;

(2) As far as practical, gases emitted by the coal do not accumulate in enclosed working spaces such as storerooms, shops, or passageways, and tunnel spaces on self-unloading vessels, and that such spaces are adequately ventilated;

(3) The vessel has adequate ventilation as required by paragraph (f) of this section; and

(4) If the temperature of the coal is to be monitored under paragraph (e)(2)(i) of this section, the vessel has instruments that are capable of measuring the temperature of the cargo in the range 0°–100 °C (32 °–212 °F) without entry into the cargo hold.

(d) A cargo hold containing coal must not be ventilated unless the conditions of paragraph (f) of this section are met, or unless methane is detected under paragraph (h) of this section.

(e) If coal waiting to be loaded has shown a tendency to self-heat, has been handled so that it may likely self-heat, or has been observed to be heating, the master is responsible for monitoring the temperature of the coal at several intervals during these times:

(1) Before loading; and

(2) During the voyage, by—

(i) Measuring the temperature of the coal;

(ii) Measuring the emission of carbon monoxide; or

(iii) Both.

(f) If coal waiting to be loaded has a potential to emit dangerous amounts of methane, for example it is freshly mined, or has a history of emitting dangerous amounts of methane, then:

(1) Surface ventilation, either natural or from fixed or portable non-sparking fans, must be provided; and

(2) The atmosphere above the coal must be monitored for the presence of methane as prescribed in paragraph (h) of this section. The results of this monitoring must be recorded at least twice in every 24-hour period, unless the conditions of paragraph (m) of this section are met.

(g) Electrical equipment and cables in a hold containing a coal described in paragraph (f) of this section must be either suitable for use in an explosive gas atmosphere or de-energized at a point outside the hold. Electrical equipment and cables necessary for continuous safe operations, such as lighting fixtures, must be suitable for use in an explosive gas atmosphere. The master of the vessel must ensure that the affected equipment and cables remain de-energized as long as this coal remains in the hold.

(h) For all coal loaded on a vessel, other than an unmanned barge, the atmosphere above the coal must be routinely tested for the presence of methane, carbon monoxide, and oxygen, following the procedures in the Appendices to the schedules for Coal and Brown Coal Briquettes as contained in the IMSBC Code (incorporated by reference, see § 148.8). This testing must be performed in such a way that the cargo hatches are not opened and entry into the hold is not necessary.

(i) When carrying a coal described in paragraph (e) of this section, the atmosphere above the coal must be monitored for the presence of carbon monoxide as prescribed in paragraph (h) of this section. The results of this monitoring must be recorded at least twice in every 24-hour period, unless the conditions of paragraph (m) of this section are met. If the level of carbon monoxide is increasing rapidly or reaches 20 percent of the lower flammability limit (LFL), the frequency of monitoring must be increased.

(j) When a cargo of coal has a potential to self-heat or has been observed to be heating, the hatches should be closed and sealed and all surface ventilation halted except as necessary to remove any methane that may have accumulated.

(k) If the level of carbon monoxide monitored under paragraph (i) of this section continues to increase rapidly or the temperature of coal carried on board a vessel exceeds 55 °C (131 °F) and is increasing rapidly, the master must notify the nearest Coast Guard Captain of the Port of—

(1) The name, nationality, and position of the vessel;

(2) The most recent temperature, if measured, and levels of carbon monoxide and methane;

(3) The port where the coal was loaded and the destination of the coal;

(4) The last port of call of the vessel and its next port of call; and

(5) What action has been taken.

(l) If the level of methane as monitored under paragraph (h) of this section reaches 20 percent of the LFL or is increasing rapidly, ventilation of the cargo hold, under paragraph (f) of this section, must be initiated. If this ventilation is provided by opening the

cargo hatches, care must be taken to avoid generating sparks.

(m) The frequency of monitoring required by paragraph (f) of this section may be reduced at the discretion of the master provided that—

(1) The level of gas measured is less than 20 percent of the LFL;

(2) The level of gas measured has remained steady or decreased over three consecutive readings, or has increased by less than 5 percent over four consecutive readings spanning at least 48 hours; and

(3) Monitoring continues at intervals sufficient to determine that the level of gas remains within the parameters of paragraphs (m)(1) and (m)(2) of this section.

§ 148.242 Copra.

Copra must have surface ventilation. It must not be stowed against heated surfaces including fuel oil tanks which may require heating.

§ 148.245 Direct reduced iron (DRI); lumps, pellets, and cold-molded briquettes.

(a) Before loading DRI lumps, pellets, or cold-molded briquettes—

(1) The master must have a written certification from a competent person appointed by the shipper and recognized by the Commandant (CG-5223) stating that the DRI, at the time of loading, is suitable for shipment;

(2) The DRI must be aged for at least 3 days, or be treated with an air passivation technique or some other equivalent method that reduces its reactivity to at least the same level as the aged DRI; and

(3) Each hold and bilge must be as clean and dry as practical. Other than double bottom tanks, adjacent ballast tanks must be kept empty when possible. All wooden fixtures, such as battens, must be removed from the hold.

(b) Each boundary of a hold where DRI lumps, pellets, or cold-molded briquettes are to be carried must be resistant to fire and passage of water.

(c) DRI lumps, pellets, or cold-molded briquettes that are wet, or that are known to have been wetted, may not be accepted for transport. The moisture content of the DRI must not exceed 0.3 percent prior to loading.

§ 148.250

46 CFR Ch. I (10–1–11 Edition)

(d) DRI lumps, pellets and cold-molded briquettes must be protected at all times from contact with water, and must not be loaded or transferred from one vessel to another during periods of rain or snow.

(e) DRI lumps, pellets, or cold-molded briquettes may not be loaded if their temperature is greater than 65 °C (150 °F).

(f) The shipper of DRI lumps, pellets, or cold-molded briquettes in bulk must ensure that an inert atmosphere of less than 5 percent oxygen and 1 percent hydrogen, by volume, is maintained throughout the voyage in any hold containing these materials.

(g) When DRI lumps, pellets, or cold-molded briquettes are loaded, precautions must be taken to avoid the concentration of fines (pieces less than 6.35mm in size) in any one location in the cargo hold.

(h) Radar and RDF scanners must be protected against the dust generated during cargo transfer operations of DRI lumps, pellets, or cold-molded briquettes.

§ 148.250 Direct reduced iron (DRI); hot-molded briquettes.

(a) Before loading DRI hot-molded briquettes—

(1) The master must have a written certification from a competent person appointed by the shipper and recognized by the Commandant (CG-5223) that at the time of loading the DRI hot-molded briquettes are suitable for shipment; and

(2) Each hold and bilge must be as clean and dry as practical. Except double bottom tanks, adjacent ballast tanks must be kept empty where possible. All wooden fixtures, such as batens, must be removed.

(b) All boundaries of a hold must be resistant to fire and passage of water to carry DRI hot-molded briquettes.

(c) DRI hot-molded briquettes must be protected at all times from contact with water. They must not be loaded or transferred from one vessel to another during periods of rain or snow.

(d) DRI hot-molded briquettes may not be loaded if their temperature is greater than 65 °C (150 °F).

(e) When loading DRI hot-molded briquettes, precautions must be taken to

avoid the concentration of fines (pieces less than 6.35mm in size) in any one location in the cargo hold.

(f) Adequate surface ventilation must be provided when carrying or loading DRI hot-molded briquettes.

(g) When DRI hot-molded briquettes are carried by unmanned barge—

(1) The barge must be fitted with vents adequate to provide natural ventilation; and

(2) The cargo hatches must be closed at all times after loading the DRI hot-molded briquettes.

(h) Radar and RDF scanners must be adequately protected against dust generated during cargo transfer operations of DRI hot-molded briquettes.

(i) During final discharge only, a fine spray of water may be used to control dust from DRI hot-molded briquettes.

§ 148.255 Ferrosilicon, aluminum ferrosilicon, and aluminum silicon containing more than 30% but less than 90% silicon.

(a) This section applies to the stowage and transportation of ferrosilicon, aluminum ferrosilicon, and aluminum silicon containing more than 30 percent but less than 90 percent silicon.

(b) The shipper of material described in paragraph (a) of this section must give the master a written certification stating that after manufacture the material was stored under cover, but exposed to the weather, in the particle size in which it is to be shipped, for at least three days before shipment.

(c) Material described in paragraph (a) of this section must be protected at all times from contact with water, and must not be loaded or unloaded during periods of rain or snow.

(d) Except as provided in paragraph (e) of this section, each hold containing material described in paragraph (a) of this section must be mechanically ventilated by at least two separate fans. The total ventilation must be at least five air changes per hour, based on the empty hold. Ventilation must not allow escaping gas to reach accommodation or work spaces, on or under deck.

(e) An unmanned barge which is provided with natural ventilation need not comply with paragraph (d) of this section.

(f) Each space adjacent to a hold containing material described in paragraph (a) of this section must be well ventilated with mechanical fans. No person may enter that space unless it has been tested to ensure that it is free from phosphine and arsine gases.

(g) Scuttles and windows in accommodation and work spaces adjacent to holds containing material described in paragraph (a) of this section must be kept closed while this material is being loaded and unloaded.

(h) Any bulkhead between a hold containing material described in paragraph (a) of this section and an accommodation or work space must be gas tight and adequately protected against damage from any unloading equipment.

(i) When a hold containing material described in paragraph (a) of this section is equipped with atmosphere sampling type smoke detectors with lines that terminate in accommodation or work spaces, those lines must be blanked off gas-tight.

(j) If a hold containing material described in paragraph (a) of this section must be entered at any time, the hatches must be open for two hours before entry to dissipate any accumulated gases. The atmosphere in the hold must be tested to ensure that there is no phosphine or arsine gas present.

(k) After unloading material described in paragraph (a) of this section, each cargo hold must be thoroughly cleaned and tested to ensure that no phosphine or arsine gas remains.

§ 148.260 Ferrous metal.

(a) This part does not apply to the stowage and transportation in bulk of stainless steel borings, shavings, turnings, or cuttings; nor does this part apply to an unmanned barge on a voyage entirely on the navigable waters of United States.

(b) Ferrous metal may not be stowed or transported in bulk unless the following conditions are met:

(1) All wooden sweat battens, dunnage, and debris must be removed from the hold before the ferrous metal is loaded;

(2) If weather is inclement during loading, hatches must be covered or

otherwise protected to keep the material dry;

(3) During loading and transporting, the bilge of each hold in which ferrous metal is stowed or will be stowed must be kept as dry as practical;

(4) During loading, the ferrous metal must be compacted in the hold as frequently as practicable with a bulldozer or other means that provides equivalent surface compaction;

(5) No other material may be loaded in a hold containing ferrous metal unless—

(i) The material to be loaded in the same hold with the ferrous metal is not a material listed in Table 148.10 of this part or a readily combustible material;

(ii) The loading of the ferrous metal is completed first; and

(iii) The temperature of the ferrous metal in the hold is below 55 °C (131 °F) or has not increased in eight hours before the loading of the other material; and

(6) During loading, the temperature of the ferrous metal in the pile being loaded must be below 55 °C (131 °F).

(c) The master of a vessel that is loading or transporting a ferrous metal must ensure that the temperature of the ferrous metal is taken—

(1) Before loading;

(2) During loading, in each hold and pile being loaded, at least once every twenty-four hours and, if the temperature is rising, as often as is necessary to ensure that the requirements of this section are met; and

(3) After loading, in each hold, at least once every 24 hours.

(d) During loading, if the temperature of the ferrous metal in a hold is 93 °C (200 °F) or higher, the master must notify the Coast Guard Captain of the Port and suspend loading until the Captain of the Port is satisfied that the temperature of the ferrous metal is 88 °C (190 °F) or less.

(e) After loading ferrous metal—

(1) If the temperature of the ferrous metal in each hold is 65 °C (150 °F) or above, the master must notify the Coast Guard Captain of the Port, and the vessel must remain in the port area until the Captain of the Port is satisfied that the temperature of ferrous metal has shown a downward trend below 65 °C (150 °F) for at least eight

§ 148.265

hours after completion of loading of the hold; or

(2) If the temperature of the ferrous metal in each hold is less than 88 °C (190 °F) and has shown a downward trend for at least eight hours after the completion of loading, the master must notify the Coast Guard Captain of the Port, and the vessel must remain in the port area until the Captain of the Port confirms that the vessel is sailing directly to another port, no further than 12 hours sailing time, for the purpose of loading more ferrous metal in bulk or to completely off-load the ferrous metal.

(f) Except for shipments of ferrous metal in bulk which leave the port of loading under the conditions specified in paragraph (e)(2) of this section, if after the vessel leaves the port, the temperature of the ferrous metal in the hold rises above 65 °C (150 °F), the master must notify the nearest Coast Guard Captain of the Port as soon as possible of—

- (1) The name, nationality, and position of the vessel;
- (2) The most recent temperature taken;
- (3) The length of time that the temperature has been above 65 °C (150 °F) and the rate of rise, if any;
- (4) The port where the ferrous metal was loaded and the destination of the ferrous metal;
- (5) The last port of call of the vessel and its next port of call;
- (6) What action has been taken; and
- (7) Whether any other cargo is endangered.

§ 148.265 Fish meal or fish scrap.

(a) This part does not apply to fish meal or fish scrap that contains less than 5 percent moisture by weight.

(b) Fish meal or fish scrap may contain a maximum of 12 percent moisture by weight and a maximum of 15 percent fat by weight.

(c) At the time of production, fish meal or fish scrap must be treated with an effective antioxidant (at least 400 mg/kg (ppm) ethoxyquin, at least 1000 mg/kg (ppm) butylated hydroxytoluene, or at least 1000 mg/kg (ppm) of tocopherol-based liquid antioxidant).

(d) Shipment of the fish meal or fish scrap must take place a maximum of 12

46 CFR Ch. I (10–1–11 Edition)

months after the treatment prescribed in paragraph (c) of this section.

(e) Fish meal or fish scrap must contain at least 100 mg/kg (ppm) of ethoxyquin or butylated hydroxytoluene or at least 250 mg/kg (ppm) of tocopherol-based antioxidant at the time of shipment.

(f) At the time of loading, the temperature of the fish meal or fish scrap to be loaded may not exceed 35 °C (95 °F), or 5 °C (9 °F) above the ambient temperature, whichever is higher.

(g) For each shipment of fish meal or fish scrap, the shipper must give the master a written certification stating—

- (1) The total weight of the shipment;
- (2) The moisture content of the material;
- (3) The fat content of the material;
- (4) The type of antioxidant and its concentration in the fish meal or fish scrap at the time of shipment;
- (5) The date of production of the material; and
- (6) The temperature of the material at the time of shipment.

(h) During a voyage, temperature readings must be taken of fish meal or fish scrap three times a day and recorded. If the temperature of the material exceeds 55 °C (131 °F) and continues to increase, ventilation to the hold must be restricted. This paragraph does not apply to shipments by unmanned barge.

§ 148.270 Hazardous substances.

(a) Each bulk shipment of a hazardous substance must—

(1) Be assigned a shipping name in accordance with 49 CFR 172.203(c); and

(2) If the hazardous substance is also listed as a hazardous solid waste in 40 CFR part 261, follow the applicable requirements of 40 CFR chapter I, subchapter I.

(b) Each release of a quantity of a designated substance equal to or greater than the reportable quantity, as set out in Table 1 to Appendix A of 49 CFR 171.101, when discharged into or upon the navigable waters of the United States, adjoining shorelines, into or upon the contiguous zone, or beyond the contiguous zone, must be reported as required in subpart B of 33 CFR part 153.

(c) A hazardous substance must be stowed in a hold or barge that is closed or covered and prevents dispersal of the material during transportation.

(d) During cargo transfer operations, a spill or release of a hazardous substance must be minimized to the greatest extent possible. Each release must be reported as required in paragraph (b) of this section.

(e) After a hazardous substance is unloaded, the hold in which it was carried must be cleaned thoroughly. The residue of the substance must be disposed of pursuant to 33 CFR 151.55 through 151.77 and the applicable regulations of 40 CFR subchapter I.

§ 148.275 Iron oxide, spent; iron sponge, spent.

(a) Before spent iron oxide or spent iron sponge is loaded in a closed hold, the shipper must give the master a written certification that the material has been cooled and weathered for at least eight weeks.

(b) Both spent iron oxide and spent iron sponge may be transported on open hold all-steel barges after exposure to air for a period of at least ten days.

§ 148.280 Magnesia, unslaked (lightburned magnesia, calcined magnesite, caustic calcined magnesite).

(a) This part does not apply to the transport of natural magnesite, magnesium carbonate, or magnesia clinkers.

(b) When transported by barge, unslaked magnesia must be carried in an unmanned, all-steel, double-hulled barge equipped with weathertight hatches or covers. The barge may not carry any other cargo while unslaked magnesia is on board.

(c) The shipping paper requirements in § 148.60 of this part and the dangerous cargo manifest requirements in § 148.70 of this part do not apply to unslaked magnesia transported under the requirements of paragraph (b) of this section.

§ 148.285 Metal sulfide concentrates.

(a) When information given by the shipper under § 148.60 of this part indicates that the metal sulfide concentrate may generate toxic or flam-

mable gases, the appropriate gas detection equipment from §§ 148.415 and 148.420 of this part must be on board the vessel.

(b) No cargo hold containing a metal sulfide concentrate may be ventilated.

(c) No person may enter a hold containing a metal sulfide concentrate unless—

(1) The atmosphere in the cargo hold has been tested and contains sufficient oxygen to support life and, where the shipper indicates that toxic gas(es) may be generated, the atmosphere in the cargo hold has been tested for the toxic gas(es) and the concentration of the gas(es) is found to be less than the TLV; or

(2) An emergency situation exists and the person entering the cargo hold is wearing the appropriate self-contained breathing apparatus.

§ 148.290 Peat moss.

(a) Before shipment, peat moss must be stockpiled under cover to allow drainage and reduce its moisture content.

(b) The cargo must be ventilated so that escaping gases cannot reach living quarters on or above deck.

(c) Persons handling or coming into contact with peat moss must wear gloves, a dust mask, and goggles.

§ 148.295 Petroleum coke, calcined or uncalcined, at 55 °C (131 °F) or above.

(a) This part does not apply to shipments of petroleum coke, calcined or uncalcined, on any vessel when the temperature of the material is less than 55 °C (131 °F).

(b) Petroleum coke, calcined or uncalcined, or a mixture of calcined and uncalcined petroleum coke may not be loaded when its temperature exceeds 107 °C (225 °F).

(c) No other hazardous materials may be stowed in any hold adjacent to a hold containing petroleum coke except as provided in paragraph (d) of this section.

(d) Before petroleum coke at 55 °C (131 °F) or above may be loaded into a hold over a tank containing fuel or material having a flashpoint of less than 93 °C (200 °F), a 0.6 to 1.0 meter (2 to 3 foot) layer of the petroleum coke at a

§ 148.300

temperature not greater than 43 °C (110 °F) must first be loaded.

(e) Petroleum coke must be loaded as follows:

(1) For a shipment in a hold over a fuel tank, the loading of a cooler layer of petroleum coke in the hold as required by paragraph (d) of this section must be completed before loading the petroleum coke at 55 °C (131 °F) or above in any hold of the vessel;

(2) Upon completion of the loading described in paragraph (e)(1) of this section, a 0.6 to 1.0 meter (2 to 3 foot) layer of the petroleum coke at 55 °C (131 °F) or above must first be loaded into each hold, including those holds already containing a cooler layer of the petroleum coke; and

(3) Upon completion of the loading described in paragraph (e)(2) of this section, normal loading of the petroleum coke may be completed.

(f) The master of the vessel must warn members of a crew that petroleum coke is hot, and that injury due to burns is possible.

(g) During the voyage, the temperature of the petroleum coke must be monitored often enough to detect spontaneous heating.

§ 148.300 Radioactive materials.

(a) Radioactive materials that may be stowed or transported in bulk are limited to those radioactive materials defined in 49 CFR 173.403 as Low Specific Activity Material, LSA-1, or Surface Contaminated Object, SCO-1.

(b) Skin contact, inhalation or ingestion of dusts generated by Class 7 material listed in Table 148.10 of this part must be minimized.

(c) Each hold used for the transportation of Class 7 material (radioactive) listed in Table 148.10 of this part must be surveyed after the completion of off-loading by a qualified person using appropriate radiation detection instruments. Such holds must not be used for the transportation of any other material until the non-fixed contamination on any surface, when averaged over an area of 300 cm², does not exceed the following levels:

(1) 4.0 Bq/cm² (10⁻⁴ uCi/cm²;) for beta and gamma emitters and low toxicity alpha emitters, natural uranium, natural thorium, uranium-235, uranium-

46 CFR Ch. I (10-1-11 Edition)

238, thorium-232, thorium-228 and thorium-230 when contained in ores or physical or chemical concentrates, and radionuclides with a half-life of less than 10 days; and

(2) 0.4 Bq/cm² (10⁻⁵ uCi/cm²) for all other alpha emitters.

§ 148.310 Seed cake.

(a) This part does not apply to solvent-extracted rape seed meal, pellets, soya bean meal, cotton seed meal, or sunflower seed meal that—

(1) Contains a maximum of 4 percent vegetable oil and a maximum of 15 percent vegetable oil and moisture combined; and

(2) As far as practical, is free from flammable solvent.

(b) This part does not apply to mechanically expelled citrus pulp pellets containing not more than 2.5 percent oil and a maximum of 14 percent oil and moisture combined.

(c) Before loading, the seed cake must be aged per the instructions of the shipper.

(d) Before loading, the shipper must give the master or person in charge of a barge a certificate from a competent testing laboratory stating the oil and moisture content of the seed cake.

(e) The seed cake must be kept as dry as practical at all times.

(f) If the seed cake is solvent-extracted, it must be—

(1) As free as practical from flammable solvent; and

(2) Stowed in a mechanically ventilated hold.

(g) For a voyage with a planned duration greater than 5 days, the vessel must be equipped with facilities for introducing carbon dioxide or another inert gas into the hold.

(h) Temperature readings of the seed cake must be taken at least once in every 24-hour period. If the temperature exceeds 55 °C (131 °F) and continues to increase, ventilation to the cargo hold must be discontinued. If heating continues after ventilation has been discontinued, carbon dioxide or the inert gas required under paragraph (g) of this section must be introduced into the hold. If the seed cake is solvent-extracted, the use of inert gas

must not be introduced until fire is apparent, to avoid the possibility of igniting the solvent vapors by the generation of static electricity.

(i) Seed cake must be carried under the terms of a Special Permit issued by the Commandant (CG-5223) per subpart B of this part if—

(1) The oil was mechanically expelled; and

(2) It contains more than 10 percent vegetable oil or more than 20 percent vegetable oil and moisture combined.

§ 148.315 Sulfur.

(a) This part applies to lump or coarse grain powder sulfur only. Fine-grained powder (“flowers of sulfur”) may not be transported in bulk.

(b) After the loading or unloading of lump or coarse grain powder sulfur has been completed, sulfur dust must be removed from the vessel’s decks, bulkheads, and overheads. Cargo residues and deck sweepings must be disposed of pursuant to 33 CFR 151.55 through 151.77.

(c) A cargo space that contains sulfur or the residue of a sulfur cargo must be adequately ventilated, preferably by mechanical means. Each ventilator intake must be fitted with a spark-arresting screen.

§ 148.320 Tankage; garbage tankage; rough ammonia tankage; or tankage fertilizer.

(a) This part applies to rough ammonia tankage in bulk that contains 7 percent or more moisture by weight, and garbage tankage and tankage fertilizer that contains 8 percent or more moisture by weight.

(b) Tankage to which this part applies may not be loaded in bulk if its temperature exceeds 38 °C (100 °F).

(c) During the voyage, the temperature of the tankage must be monitored often enough to detect spontaneous heating.

§ 148.325 Wood chips; wood pellets; wood pulp pellets.

(a) This part applies to wood chips and wood pulp pellets in bulk that may oxidize, leading to depletion of oxygen and an increase in carbon dioxide in the cargo hold.

(b) No person may enter a cargo hold containing wood chips, wood pellets, or wood pulp pellets, unless—

(1) The atmosphere in the cargo hold has been tested and contains enough oxygen to support life; or

(2) The person entering the cargo hold is wearing the appropriate self-contained breathing apparatus.

§ 148.330 Zinc ashes; zinc dross; zinc residues; zinc skimmings.

(a) The shipper must inform the cognizant Coast Guard Captain of the Port in advance of any cargo transfer operations involving zinc ashes, zinc dross, zinc residues, or zinc skimmings (collectively, “zinc material”) in bulk.

(b) Zinc material must be aged by exposure to the elements for at least one year before shipment in bulk.

(c) Before loading in bulk, zinc material must be stored under cover for a period of time to ensure that it is as dry as practical. No zinc material that is wet may be accepted for shipment.

(d) Zinc material may not be loaded in bulk if its temperature is greater than 11.1 °C (52 °F) in excess of the ambient temperature.

(e) Paragraphs (e)(1) through (e)(5) of this section apply only when zinc materials are carried by a cargo vessel:

(1) Zinc material in bulk must be stowed in a mechanically ventilated hold that—

(i) Is designed for at least one complete air change every 30 minutes based on the empty hold;

(ii) Has explosion-proof motors approved for use in Class I, Division 1, Group B atmospheres or equivalent motors approved by the vessel’s flag state administration for use in hydrogen atmospheres; and

(iii) Has nonsparking fans.

(2) Combustible gas detectors capable of measuring hydrogen concentrations of 0 to 4.1 percent by volume must be permanently installed in holds that will carry zinc material. If the concentration of hydrogen in the space above the cargo exceeds 1 percent by volume, the ventilation system must be run until the concentration drops below 1 percent by volume.

(3) Thermocouples must be installed approximately 6 inches below the surface of the zinc material or in the space

§ 148.400

immediately above the zinc material. If an increase in temperature is detected, the mechanical ventilation system required by paragraph (d) of this section must be used until the temperature of the zinc material is below 55 °C (131 °F).

(4) Except as provided in paragraph (e)(5) of this section, the cargo hatches of holds containing zinc material must remain sealed to prevent the entry of seawater.

(5) If the concentration of hydrogen is near 4.1 percent by volume and increasing, despite ventilation, or the temperature of the zinc material reaches 65 °C (150 °F), the cargo hatches should be opened provided that weather and sea conditions are favorable. When hatches are opened take care to prevent sparks and minimize the entry of water.

Subpart F—Additional Special Requirements

§ 148.400 Applicability.

Unless stated otherwise, the requirements of this subpart apply only to the shipment or loading of materials, listed in Table 148.10 of this part, for which Table 148.10 contains a reference to a section or paragraph of this subpart.

§ 148.405 Sources of ignition.

(a) Except in an emergency, no welding, burning, cutting, chipping, or other operations involving the use of fire, open flame, sparks, or arc-producing equipment, may be performed in a cargo hold containing a Table 148.10 material or in an adjacent space.

(b) A cargo hold or adjacent space must not have any flammable gas concentrations over 10 percent of the LFL before the master may approve operations involving the use of fire, open flame, or spark- or arc-producing equipment in that hold or adjacent space.

§ 148.407 Smoking.

When Table 148.10 of this part associates a material with a reference to this section, and that material is being loaded or unloaded, smoking is prohibited anywhere on the weatherdeck of the vessel. While such a material is on board the vessel, smoking is prohibited

46 CFR Ch. I (10–1–11 Edition)

in spaces adjacent to the cargo hold and on the vessel's deck in the vicinity of cargo hatches, ventilator outlets, and other accesses to the hold containing the material. "NO SMOKING" signs must be displayed in conspicuous locations in the areas where smoking is prohibited.

§ 148.410 Fire hoses.

When Table 148.10 of this part associates a material with a reference to this section, a fire hose must be available at each hatch through which the material is being loaded.

§ 148.415 Toxic gas analyzers.

When Table 148.10 of this part associates a material with a reference to a paragraph in this section, each vessel transporting the material, other than an unmanned barge, must have on board a gas analyzer appropriate for the toxic gas listed in that paragraph. At least two members of the crew must be knowledgeable in the use of the equipment. The equipment must be maintained in a condition ready for use and calibrated according to the instructions of its manufacturer. The atmosphere in the cargo hold and adjacent spaces must be tested before a person is allowed to enter these spaces. If toxic gases are detected, the space must be ventilated and retested before entry. The toxic gases for which the requirements of this section must be met are:

- (a) Arsine;
- (b) Carbon monoxide;
- (c) Hydrogen cyanide;
- (d) Hydrogen sulfide;
- (e) Phosphine; and
- (f) Sulfur dioxide.

§ 148.420 Flammable gas analyzers.

When Table 148.10 of this part associates a material with a reference to a paragraph in this section, each vessel transporting the material, other than an unmanned barge, must have on board a gas analyzer appropriate for the flammable gas listed in that paragraph. At least two members of the crew must be knowledgeable in the use of the equipment. The equipment must be maintained in a condition ready for use, capable of measuring 0 to 100 percent LFL for the gas indicated, and

calibrated in accordance with the instructions of its manufacturer. The atmosphere in the cargo hold must be tested before any person is allowed to enter. If flammable gases are detected, the space must be ventilated and retested before entry. The flammable gases for which the requirements of this section must be met are:

- (a) Carbon monoxide;
- (b) Hydrogen; and
- (c) Methane.

§ 148.435 Electrical circuits in cargo holds.

During transport of a material that Table 148.10 of this part associates with a reference to this section, each electrical circuit terminating in a cargo hold containing the material must be electrically disconnected from the power source at a point outside of the cargo hold. The point of disconnection must be marked to prevent the circuit from being reenergized while the material is on board.

§ 148.445 Adjacent spaces.

When transporting a material that Table 148.10 of this part associates with a reference to this section, the following requirements must be met:

- (a) Each space adjacent to a cargo hold must be ventilated by natural ventilation or by ventilation equipment safe for use in an explosive gas atmosphere.
- (b) Each space adjacent to a cargo hold containing the material must be regularly monitored for the presence of the flammable gas indicated by reference to § 148.420 of this part. If the level of flammable gas in any space reaches 30 percent of the LFL, all electrical equipment that is not certified safe for use in an explosive gas atmosphere must be de-energized at a location outside of that space. This location must be labeled to prohibit reenergizing until the atmosphere in the space is tested and found to be less than 30 percent of the LFL.
- (c) Each person who enters any space adjacent to a cargo hold or compartment containing the material must wear a self-contained breathing apparatus unless—

(1) The space has been tested, or is routinely monitored, for the appropriate flammable gas and oxygen;

(2) The level of flammable gas is less than 10 percent of the LFL; and

(3) The level of toxic gas, if required to be tested, is less than the TLV.

(d) No person may enter an adjacent space if the level of flammable gas is greater than 30 percent of the LFL. If emergency entry is necessary, each person who enters the space must wear a self-contained breathing apparatus and caution must be exercised to ensure that no sparks are produced.

§ 148.450 Cargoes subject to liquefaction.

(a) This section applies only to cargoes identified in Table 148.10 of this part with a reference to this section and cargoes identified in the IMSBC Code (incorporated by reference, see § 148.8) as cargoes that may liquefy.

(b) This section does not apply to—

(1) Shipments by unmanned barge; or

(2) Cargoes of coal that have an average particle size of 10mm (.394 in.) or greater.

(c) Definitions as used in this section—

(1) *Cargo subject to liquefaction* means a material that is subject to moisture migration and subsequent liquefaction if shipped with moisture content in excess of the transportable moisture limit.

(2) *Moisture migration* is the movement of moisture by settling and consolidation of a material, which may result in the development of a flow state in the material.

(3) *Transportable moisture limit* or *TML* of a cargo that may liquefy is the maximum moisture content that is considered safe for carriage on vessels.

(d) Except on a vessel that is specially constructed or specially fitted for the purpose of carrying such cargoes (see also section 7 of the IMSBC Code, incorporated by reference, see § 148.8), a cargo subject to liquefaction may not be transported by vessel if its moisture content exceeds its TML.

(e) The shipper of a cargo subject to liquefaction must give the master the material's moisture content and TML.

§ 148.450

(f) The master of a vessel shipping a cargo subject to liquefaction must ensure that—

(1) A cargo containing a liquid is not stowed in the same cargo space with a cargo subject to liquefaction; and

(2) Precautions are taken to prevent the entry of liquids into a cargo space

46 CFR Ch. I (10–1–11 Edition)

containing a cargo subject to liquefaction.

(g) The moisture content and TML of a material may be determined by the tests described in Appendix 2, Section 1, of the IMSBC Code (incorporated by reference, see §148.8).

PART 149 [RESERVED]