

§ 148.300

temperature not greater than 43 °C (110 °F) must first be loaded.

(e) Petroleum coke must be loaded as follows:

(1) For a shipment in a hold over a fuel tank, the loading of a cooler layer of petroleum coke in the hold as required by paragraph (d) of this section must be completed before loading the petroleum coke at 55 °C (131 °F) or above in any hold of the vessel;

(2) Upon completion of the loading described in paragraph (e)(1) of this section, a 0.6 to 1.0 meter (2 to 3 foot) layer of the petroleum coke at 55 °C (131 °F) or above must first be loaded into each hold, including those holds already containing a cooler layer of the petroleum coke; and

(3) Upon completion of the loading described in paragraph (e)(2) of this section, normal loading of the petroleum coke may be completed.

(f) The master of the vessel must warn members of a crew that petroleum coke is hot, and that injury due to burns is possible.

(g) During the voyage, the temperature of the petroleum coke must be monitored often enough to detect spontaneous heating.

§ 148.300 Radioactive materials.

(a) Radioactive materials that may be stowed or transported in bulk are limited to those radioactive materials defined in 49 CFR 173.403 as Low Specific Activity Material, LSA-1, or Surface Contaminated Object, SCO-1.

(b) Skin contact, inhalation or ingestion of dusts generated by Class 7 material listed in Table 148.10 of this part must be minimized.

(c) Each hold used for the transportation of Class 7 material (radioactive) listed in Table 148.10 of this part must be surveyed after the completion of off-loading by a qualified person using appropriate radiation detection instruments. Such holds must not be used for the transportation of any other material until the non-fixed contamination on any surface, when averaged over an area of 300 cm², does not exceed the following levels:

(1) 4.0 Bq/cm² (10⁻⁴ uCi/cm²;) for beta and gamma emitters and low toxicity alpha emitters, natural uranium, natural thorium, uranium-235, uranium-

46 CFR Ch. I (10-1-11 Edition)

238, thorium-232, thorium-228 and thorium-230 when contained in ores or physical or chemical concentrates, and radionuclides with a half-life of less than 10 days; and

(2) 0.4 Bq/cm² (10⁻⁵ uCi/cm²) for all other alpha emitters.

§ 148.310 Seed cake.

(a) This part does not apply to solvent-extracted rape seed meal, pellets, soya bean meal, cotton seed meal, or sunflower seed meal that—

(1) Contains a maximum of 4 percent vegetable oil and a maximum of 15 percent vegetable oil and moisture combined; and

(2) As far as practical, is free from flammable solvent.

(b) This part does not apply to mechanically expelled citrus pulp pellets containing not more than 2.5 percent oil and a maximum of 14 percent oil and moisture combined.

(c) Before loading, the seed cake must be aged per the instructions of the shipper.

(d) Before loading, the shipper must give the master or person in charge of a barge a certificate from a competent testing laboratory stating the oil and moisture content of the seed cake.

(e) The seed cake must be kept as dry as practical at all times.

(f) If the seed cake is solvent-extracted, it must be—

(1) As free as practical from flammable solvent; and

(2) Stowed in a mechanically ventilated hold.

(g) For a voyage with a planned duration greater than 5 days, the vessel must be equipped with facilities for introducing carbon dioxide or another inert gas into the hold.

(h) Temperature readings of the seed cake must be taken at least once in every 24-hour period. If the temperature exceeds 55 °C (131 °F) and continues to increase, ventilation to the cargo hold must be discontinued. If heating continues after ventilation has been discontinued, carbon dioxide or the inert gas required under paragraph (g) of this section must be introduced into the hold. If the seed cake is solvent-extracted, the use of inert gas

must not be introduced until fire is apparent, to avoid the possibility of igniting the solvent vapors by the generation of static electricity.

(i) Seed cake must be carried under the terms of a Special Permit issued by the Commandant (CG-5223) per subpart B of this part if—

(1) The oil was mechanically expelled; and

(2) It contains more than 10 percent vegetable oil or more than 20 percent vegetable oil and moisture combined.

§ 148.315 Sulfur.

(a) This part applies to lump or coarse grain powder sulfur only. Fine-grained powder (“flowers of sulfur”) may not be transported in bulk.

(b) After the loading or unloading of lump or coarse grain powder sulfur has been completed, sulfur dust must be removed from the vessel’s decks, bulkheads, and overheads. Cargo residues and deck sweepings must be disposed of pursuant to 33 CFR 151.55 through 151.77.

(c) A cargo space that contains sulfur or the residue of a sulfur cargo must be adequately ventilated, preferably by mechanical means. Each ventilator intake must be fitted with a spark-arresting screen.

§ 148.320 Tankage; garbage tankage; rough ammonia tankage; or tankage fertilizer.

(a) This part applies to rough ammonia tankage in bulk that contains 7 percent or more moisture by weight, and garbage tankage and tankage fertilizer that contains 8 percent or more moisture by weight.

(b) Tankage to which this part applies may not be loaded in bulk if its temperature exceeds 38 °C (100 °F).

(c) During the voyage, the temperature of the tankage must be monitored often enough to detect spontaneous heating.

§ 148.325 Wood chips; wood pellets; wood pulp pellets.

(a) This part applies to wood chips and wood pulp pellets in bulk that may oxidize, leading to depletion of oxygen and an increase in carbon dioxide in the cargo hold.

(b) No person may enter a cargo hold containing wood chips, wood pellets, or wood pulp pellets, unless—

(1) The atmosphere in the cargo hold has been tested and contains enough oxygen to support life; or

(2) The person entering the cargo hold is wearing the appropriate self-contained breathing apparatus.

§ 148.330 Zinc ashes; zinc dross; zinc residues; zinc skimmings.

(a) The shipper must inform the cognizant Coast Guard Captain of the Port in advance of any cargo transfer operations involving zinc ashes, zinc dross, zinc residues, or zinc skimmings (collectively, “zinc material”) in bulk.

(b) Zinc material must be aged by exposure to the elements for at least one year before shipment in bulk.

(c) Before loading in bulk, zinc material must be stored under cover for a period of time to ensure that it is as dry as practical. No zinc material that is wet may be accepted for shipment.

(d) Zinc material may not be loaded in bulk if its temperature is greater than 11.1 °C (52 °F) in excess of the ambient temperature.

(e) Paragraphs (e)(1) through (e)(5) of this section apply only when zinc materials are carried by a cargo vessel:

(1) Zinc material in bulk must be stowed in a mechanically ventilated hold that—

(i) Is designed for at least one complete air change every 30 minutes based on the empty hold;

(ii) Has explosion-proof motors approved for use in Class I, Division 1, Group B atmospheres or equivalent motors approved by the vessel’s flag state administration for use in hydrogen atmospheres; and

(iii) Has nonsparking fans.

(2) Combustible gas detectors capable of measuring hydrogen concentrations of 0 to 4.1 percent by volume must be permanently installed in holds that will carry zinc material. If the concentration of hydrogen in the space above the cargo exceeds 1 percent by volume, the ventilation system must be run until the concentration drops below 1 percent by volume.

(3) Thermocouples must be installed approximately 6 inches below the surface of the zinc material or in the space