

§ 58.315

§ 58.315 Continuous churns.

All product contact surfaces of the churn and related equipment shall be of noncorrosive material. All non-metallic product contact surfaces shall comply with 3-A Standards for Plastic, Rubber, and Rubber-Like Materials. All product contact surfaces of the churn and related equipment shall be readily accessible for cleaning and inspection. Construction shall follow the applicable principles of the 3-A Sanitary Standards.

§ 58.316 Conventional churns.

Churns shall be constructed of aluminum, stainless steel or equally corrosion resistant metal, free from cracks, and in good repair. All gasket material shall be fat resistant, nontoxic and reasonably durable. Seals around the doors shall be tight.

§ 58.317 Bulk butter trucks, boats, texturizers, and packers.

Bulk butter trucks, boats, texturizers, and packers shall be constructed of aluminum, stainless steel, or equally corrosion resistant metal free from cracks, seams and must have a surface that is relatively smooth and easily cleanable. All non-metallic product surfaces shall comply with 3-A Standards for Plastic, Rubber, and Rubber-Like Material.

§ 58.318 Butter, frozen or plastic cream melting machines.

Shavers, shredders or melting machines used for rapid melting of butter, frozen or plastic cream shall be of stainless steel or equally corrosion resistant metal, free from cracks and of sanitary construction, and readily cleanable.

§ 58.319 Printing equipment.

All printing equipment shall be designed so as to adequately protect the product and be readily demountable for cleaning of product contact surfaces. All product contact surfaces shall be aluminum, stainless steel or equally corrosion resistant metal, or plastic, rubber and rubber like material which comply with 3-A standards, except that conveyors may be constructed of material which can be properly cleaned and maintained in a satisfactory manner.

7 CFR Ch. I (1-1-11 Edition)

§ 58.320 Brine tanks.

Brine tanks used for the treating of parchment liners shall be constructed of noncorrosive material and have an adequate and safe means of heating the salt solution for the treatment of the liners. The tank should also be provided with a satisfactory drainage outlet.

§ 58.321 Cream storage tanks.

Cream storage tanks shall meet the requirements of § 58.128(d). Cream storage tanks for continuous churns should be equipped with effective temperature controls and recording devices.

QUALITY SPECIFICATIONS FOR RAW MATERIAL

§ 58.322 Cream.

Cream separated at an approved plant and used for the manufacture of butter shall have been derived from raw material meeting the requirements as listed under §§ 58.132 through 58.138 of this subpart.

[50 FR 34673, Aug. 27, 1985]

§ 58.323 [Reserved]

§ 58.324 Butteroil.

To produce butteroil eligible for official certification, the butter used shall conform to the flavor requirements of U.S. Grade AA, U.S. Grade A, or U.S. Grade B, and shall have been manufactured in an approved plant.

§ 58.325 Anhydrous milkfat.

If cream is used in the production of anhydrous milkfat that is eligible for official certification, the anhydrous milkfat shall be made by a continuous separation process directly from milk or cream. The cream used shall be comparable to the flavor quality specified above for U.S. Grade AA or U.S. Grade A butter. The milkfat from cream may then be further concentrated into oil. The cream or oil shall be pasteurized in accordance with the procedures for cream for buttermaking (§ 58.334a). If butter is used in the production of anhydrous milkfat that is eligible for official certification, the butter used shall conform to the flavor requirements of U.S. Grade AA or U.S. Grade