

§ 63.3004

40 CFR Ch. I (7–1–12 Edition)

Ventilation: A Manual of Recommended Practice,” American Conference of Governmental Industrial Hygienists, (23rd edition, 1998). The incorporation by reference of this material is approved by the Director of the Office of the Federal Register as of the date of publication of the final rule according to 5 U.S.C. 552(a) and 1 CFR part 51. This material is incorporated as it exists on the date of approval and notice of any change in the material will be published in the FEDERAL REGISTER.

(b) The materials referenced in this section are incorporated by reference and are available for inspection at the National Archives and Records Administration (NARA); and at the Air and Radiation Docket and Information Center, U.S. EPA, 401 M Street SW, Washington, DC. For information on the availability of this material at NARA, call 202–741–6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html. The material is also available for purchase from the following address: Customer Service Department, American Conference of Governmental Industrial Hygienists (ACGIH), 1330 Kemper Meadow Drive, Cincinnati, OH 45240, telephone number (513) 742–2020.

[67 FR 17835, Apr. 11, 2002, as amended at 69 FR 18803, Apr. 9, 2004]

§ 63.3004 What definitions apply to this subpart?

Terms used in this subpart are defined the Clean Air Act, in § 63.2, and in this section as follows:

Administrator means the Administrator of the United States Environmental Protection Agency or his or her authorized representative (e.g., a State that has been delegated the authority to implement the provisions of this part).

Binder application vacuum exhaust means the exhaust from the vacuum system used to remove excess resin solution from the wet-formed fiberglass mat before it enters the drying and curing oven.

Deviation means any instance in which an affected source subject to this

subpart, or an owner or operator of such a source:

(1) Fails to meet any requirement or obligation established by this subpart, including but not limited to any emission limit, or operating limit, or work practice standard;

(2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or

(3) Fails to meet any emission limit, or operating limit, or work practice standard in this subpart during start-up, shutdown, or malfunction, regardless of whether or not such failure is permitted by this subpart.

Drying and curing oven means the process section that evaporates excess moisture from a fiberglass mat and cures the resin that binds the fibers.

Emission limitation means an emission limit, operating limit, or work practice standard.

Fiberglass mat production rate means the weight of finished fiberglass mat produced per hour of production including any trim removed after the binder is applied and before final packaging.

Loss-on-ignition means the percentage decrease in weight of fiberglass mat measured before and after it has been ignited to burn off the applied binder. The loss-on-ignition is used to monitor the weight percent of binder in fiberglass mat.

Nonwoven wet-formed fiberglass mat manufacturing means the production of a fiberglass mat by bonding glass fibers to each other using a resin solution. Nonwoven wet-formed fiberglass mat manufacturing is also referred to as wet-formed fiberglass mat manufacturing.

Roofing square means the amount of finished product needed to cover an area 10 feet by 10 feet (100 square feet) of finished roof.

Thermal oxidizer means an air pollution control device that uses controlled flame combustion inside a combustion chamber to convert combustible materials to noncombustible gases.

Environmental Protection Agency

Pt. 63, Subpt. HHHH, Table 2

Urea-formaldehyde content in binder formulation means the mass-based percent of urea-formaldehyde resin in the

total binder mix as it is applied to the glass fibers to form the mat.

§§ 63.3005–63.3079 [Reserved]

TABLE 1 TO SUBPART HHHH OF PART 63—MINIMUM REQUIREMENTS FOR MONITORING AND RECORDKEEPING

As stated in §63.2998(c), you must comply with the minimum requirements for monitoring and recordkeeping in the following table:

| You must monitor these parameters: | At this frequency: | And record for the monitored parameter: |
|---|--|---|
| 1. Thermal oxidizer temperature ^a | Continuously | 15-minute and 3-hour block averages. |
| 2. Other process or control device parameters specified in your OMM ^b plan. | As specified in your OMM plan | As specified in your OMM plan. |
| 3. Urea-formaldehyde resin solids application rate. | On each operating day, calculate the average lb/hr application rate for each product manufactured during that day. | The average lb/hr value for each product manufactured during the day. |
| 4. Resin free-formaldehyde content | For each lot of resin purchased | The value for each lot used during the operating day. |
| 5. Loss-on-ignition ^c | Measured at least once per day, for each product manufactured during that day. | The value for each product manufactured during the operating day. |
| 6. UF-to-latex ratio in the binder ^c | For each batch of binder prepared the operating day. | The value for each batch of binder prepared during the operating day. |
| 7. Weight of the final mat product per square (lb/roofing square) ^c . | Each product manufactured during the operating day. | The value for each product manufactured during the operating day. |
| 8. Average nonwoven wet-formed fiberglass mat production rate (roofing squares per the hour) ^c . | For each product manufactured during the operating day. | The average value for each product manufactured during operating day. |

^a Required if a thermal oxidizer is used to control formaldehyde emissions.
^b Required if process modifications or a control device other than a thermal oxidizer is used to control emissions.
^c These parameters must be monitored and values recorded, but no operating limits apply.

TABLE 2 TO SUBPART HHHH OF PART 63—APPLICABILITY OF GENERAL PROVISIONS (40 CFR PART 63, SUBPART A) TO SUBPART HHHH

As stated in §63.3001, you must comply with the applicable General Provisions requirements according to the following table:

| Citation | Requirement | Applies to subpart HHHH | Explanation |
|--------------------------|--|-------------------------|--------------------------------------|
| § 63.1(a)(1)–(4) | General Applicability | Yes. | |
| § 63.1(a)(5) | | No | [Reserved]. |
| § 63.1(a)(6)–(8) | | Yes. | |
| § 63.1(a)(9) | | No | [Reserved]. |
| § 63.1(a)(10)–(14) | | Yes. | |
| § 63.1(b) | Initial Applicability Determination | Yes. | |
| § 63.1(c)(1) | Applicability After Standard Established. | Yes. | |
| § 63.1(c)(2) | | Yes | Some plants may be area sources. |
| § 63.1(c)(3) | | No | [Reserved]. |
| § 63.1(c)(4)–(5) | | Yes. | |
| § 63.1(d) | | No | [Reserved]. |
| § 63.1(e) | Applicability of Permit Program .. | Yes. | |
| § 63.2 | Definitions | Yes | Additional definitions in § 63.3004. |
| § 63.3 | Units and Abbreviations | Yes. | |
| § 63.4(a)(1)–(3) | Prohibited Activities | Yes. | |
| § 63.4(a)(4) | | No | [Reserved]. |
| § 63.4(a)(5) | | Yes. | |
| § 63.4(b)–(c) | Circumvention/Severability | Yes. | |
| § 63.5(a) | Construction/Reconstruction | Yes. | |
| § 63.5(b)(1) | Existing/Constructed/Reconstruction. | Yes. | |
| § 63.5(b)(2) | | No | [Reserved]. |
| § 63.5(b)(3)–(6) | | Yes. | |
| § 63.5(c) | | No | [Reserved]. |
| § 63.5(d) | Application for Approval of Construction/Reconstruction. | Yes. | |