

**§ 407.10**

**40 CFR Ch. I (7–1–12 Edition)**

**Subpart F—Canned and Preserved Fruits Subcategory**

- 407.60 Applicability; description of the canned and preserved fruits subcategory.
- 407.61 Specialized definitions.
- 407.62 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 407.63 [Reserved]
- 407.64 Pretreatment standards for existing sources.
- 407.65 [Reserved]
- 407.66 Pretreatment standards for new sources.
- 407.67 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart G—Canned and Preserved Vegetables Subcategory**

- 407.70 Applicability; description of the canned and preserved vegetables subcategory.
- 407.71 Specialized definitions.
- 407.72 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 407.73 [Reserved]
- 407.74 Pretreatment standards for existing sources.
- 407.75 [Reserved]
- 407.76 Pretreatment standards for new sources.
- 407.77 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart H—Canned and Miscellaneous Specialties Subcategory**

- 407.80 Applicability; description of the canned and miscellaneous specialties subcategory.
- 407.81 Specialized definitions.
- 407.82 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 407.83 [Reserved]
- 407.84 Pretreatment standards for existing sources.
- 407.85 [Reserved]
- 407.86 Pretreatment standards for new sources.
- 407.87 Effluent limitations guidelines representing the degree of effluent reduction

attainable by the application of the best conventional pollutant control technology (BCT).

AUTHORITY: Secs. 301, 304 (b) and (c), 306 (b) and (c), 307(c) of the Federal Water Pollution Control Act, as amended; 33 U.S.C. 1251, 1311, 1314 (b) and (c), 1316 (b) and (c), 1317(c); 86 Stat. 816 *et seq.*, Pub. L. 92-500; 91 Stat. 1567, Pub. L. 95-217.

SOURCE: 39 FR 10864, Mar. 21, 1974, unless otherwise noted.

**Subpart A—Apple Juice Subcategory**

**§ 407.10 Applicability; description of the apple juice subcategory.**

The provisions of this subpart are applicable to discharges resulting from the processing of apples into apple juice or apple cider. When a plant is subject to effluent limitations covering more than one subcategory, the plant discharge limitation shall be set by proration limitations for each subcategory based on the total raw material covered by each subcategory.

**§ 407.11 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

**§ 407.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kilograms per 1,000 kg of raw material)	
BOD5 .....	0.60	0.30
TSS .....	0.80	.40
pH .....	( <sup>1</sup> )	( <sup>1</sup> )