

applicable to such barges when empty (not necessarily cleaned or gas-freed).

(c)(1) Except as otherwise provided in this section, no such open hopper type barge shall be placed as a lead barge in any tow. Such barges shall be placed in protected positions within the tow so that the danger from diving or swamping will be minimized. Where, due to operating conditions, compliance with this paragraph is impossible, the provisions of paragraph (c)(3) of this section apply. The person in charge of the towing vessels shall be responsible for compliance with this paragraph.

(2) No such open hopper type barge shall be moved from a loading facility unless all void spaces and bilges are substantially free of water. Periodic inspections and necessary pumping shall be carried out to insure the maintenance of such water-free conditions, in order to minimize the free surface effect in both the longitudinal and transverse directions. Except when otherwise considered necessary for inspection or pumping, all hatch covers and other hull closure devices for void spaces and hull compartments shall be closed and secured at all times. In the case of unmanned barges, the person in charge of the towing vessel shall be deemed to be in charge of the barge, and all requirements to be carried out on the barge shall be carried out by or under the direction of such person.

(3) When an open hopper type barge is in an exposed position, such that protection from swamping provided by adjoining barges cannot be obtained from location within the tow alone, it shall be the responsibility of the person in charge of the towing vessel to control speed so as to insure protection against diving and swamping of the barge, having due regard to its design and freeboard, and to the operating conditions.

(d) To show that special operating requirements apply to a specific open hopper type barge, additional placards or signs shall be displayed in at least four different locations on the barge when the cargoes described in paragraph (a) of this section are carried in any form in the cargo tanks. The placards or signs shall be posted on the barge approximately amidships on each side and near the centerline of each

end, facing outboard. Racks, or other suitable means, for mounting such placards or signs shall be so arranged as to provide clear visibility and shall be protected from becoming readily damaged or obscured. The placards or signs shall be at least equal in dimensions to the DOT standard tank car "Dangerous" placard (10<sup>3</sup>/<sub>4</sub> inches square or larger), and shall display a circle (10 inches in diameter or larger) with alternating quadrants of white and red, and so mounted that the red quadrants are centered on the vertical axis. The shipper and/or owner of the barge shall be responsible for the installation of the required placards or signs, including maintenance of them while such barge is in temporary storage with cargo aboard. The person in charge of the towing vessel shall be responsible for the continued maintenance of the placards or signs while such barge is in transit.

[CGFR 65-50, 30 FR 16704, Dec. 30, 1965, as amended by CGFR 70-10, 35 FR 3709, Feb. 25, 1970; CGD 86-033, 53 FR 36024, Sept. 16, 1988]

**§ 35.01-50 Special operating requirements for tank barges carrying certain dangerous bulk cargoes—B/ALL.**

(a) The requirements of this section shall apply to all tank barges carrying those cargoes listed on Table 30.25-1, of this chapter, which are defined as:

(1) Flammable liquids having a Reid vapor pressure in excess of 25 pounds per square inch, absolute, in independent tanks (part 32 of this subchapter).

(2) Liquefied flammable gases (part 38 of this subchapter).

(b) All tank barges constructed or modified in conformance with the requirements of subpart 32.63 of this subchapter are exempt from the provisions of § 35.01-45.

(c) When it is necessary to operate box or square-end barges as lead barges of tows, the person in charge of the towing vessel shall control the speed to insure protection against diving and swamping of such barges, having due regard to their design and freeboard, and to the operating conditions.

(d) All barges, while carrying in bulk any of the cargoes described in paragraph (a) of this section, shall be operated in conformance with the provisions of this section. However, the provisions of this section are not applicable to such barges when empty and gas-freed.

(e) Barges shall not be moved from a loading facility unless all bilges and void spaces (except those used for ballasting) are substantially free of water. Periodic inspections and necessary pumping shall be carried out to insure maintenance of such water-free condition in order to minimize the free surface effects, both in the longitudinal and transverse directions. Except when otherwise considered necessary for inspection or pumping, all hatch covers and other hull closure devices for void spaces and hull compartments other than cargo spaces shall be closed and secured at all times.

(f) During the time the cargo tanks contain dangerous cargoes described in paragraph (a) of this section in any amount, in the liquid or gaseous state, the barge shall be under constant surveillance.

(1) A strict watch of each unmanned barge in tow shall be maintained from the towing vessel while underway.

(2) A towing vessel engaged in transporting such unmanned barges shall not leave them unattended. When a barge is moored, but not gas free, it shall be under the observation of a watchman who may be a member of the complement of the towing vessel, or a terminal employee, or other person. Such person shall be responsible for the security of the barge and for keeping unauthorized persons off the barge.

(g) The owner, operator, master, or person in charge of any barge carrying dangerous cargoes described in paragraph (a) of this section shall insure that, while the barge is being towed and during cargo transfer operations, the persons as required by §31.15-5 of this subchapter and §35.35-1 are provided.

[CGFR 65-50, 30 FR 16704, Dec. 30, 1965, as amended by CGFR 70-10, 35 FR 3709, Feb. 25, 1970; CGD 73-243, 45 FR 18000, Mar. 20, 1980]

#### § 35.01-55 Pilot boarding operation.

(a) The master shall ensure that pilot boarding equipment is maintained as follows:

(1) The equipment must be kept clean and in good working order.

(2) Each damaged step or spreader step on a pilot ladder must be replaced in kind with an approved replacement step or spreader step, prior to further use of the ladder. The replacement step or spreader step must be secured by the method used in the original construction of the ladder, and in accordance with manufacturer instructions.

(b) The master shall ensure compliance with the following during pilot boarding operations:

(1) Only approved pilot boarding equipment may be used.

(2) The pilot boarding equipment must rest firmly against the hull of the vessel and be clear of overboard discharges.

(3) Two man ropes, a safety line and an approved lifebuoy with an approved water light must be at the point of access and be immediately available for use during boarding operations.

(4) Rigging of the equipment and embarkation/debarkation of a pilot must be supervised in person by a deck officer.

(5) Both the equipment over the side and the point of access must be adequately lit during night operations.

(6) If a pilot hoist is used, a pilot ladder must be kept on deck adjacent to the hoist and available for immediate use.

[CGD 79-032, 49 FR 25455, June 21, 1984]

#### § 35.01-60 Person excluded.

Masters and pilots shall exclude from the pilothouse and navigation bridge while underway, all persons not connected with the navigation of the vessel. However, licensed officers of vessels, persons regularly engaged in training, regulating, evaluating, or learning the profession of pilot, officials of the United States Coast Guard, United States Navy, United States Coast and Geodetic Survey, United States Army Corps of Engineers, Maritime Administration, and National Transportation Safety Board may be allowed in the pilothouse or upon the