

(v) The group of lifefloats must be stowed to prevent shifting with easily detached lashings.

[CGD 84-069, 61 FR 25304, May 20, 1996, as amended at 63 FR 52816, Oct. 1, 1998]

§ 133.135 Rescue boats.

(a) Each OSV must carry at least one rescue boat. Each rescue boat must be approved under approval series 160.156 and equipped as specified in table 133.175 of this part.

(b) Offshore supply vessels, as an alternative to the requirement in paragraph (a) of this section, may carry a motor-propelled workboat or a launch if the workboat or launch must meet the embarkation, launching, and recovery arrangement requirements in § 133.160(a), (c), (d), (e), and (f).

(c) A rescue boat is not required for a vessel operating on the continental shelf of the United States, if—

(1) The OCMI determines the vessel is arranged to allow a helpless person to be recovered from the water;

(2) The recovery of the helpless person can be observed from the navigating bridge; and

(3) The vessel does not regularly engage in operations that restrict its maneuverability.

[CGD 84-069, 61 FR 25304, May 20, 1996, as amended by USCG-2000-7790, 65 FR 58463, Sept. 29, 2000; USCG-2011-0618, 76 FR 60754, Sept. 30, 2011]

§ 133.140 Stowage of rescue boats.

(a) Rescue boats must be stowed as follows:

(1) Each rescue boat must be ready for launching in not more than 5 minutes.

(2) Each rescue boat must be in a position suitable for launching and recovery.

(3) Each rescue boat must be stowed in a way that neither the rescue boat nor its stowage arrangements will interfere with the operation of any survival craft at any other launching station.

(b) Each rescue boat must be provided a means for recharging the rescue boat batteries from the OSV's power supply at a supply voltage not exceeding 50 volts.

(c) Each inflated rescue boat must be kept fully inflated at all times.

§ 133.145 Marine evacuation system launching arrangements.

(a) *Arrangements.* Each marine evacuation system must have the following arrangements:

(1) Each marine evacuation system must be capable of being deployed by one person.

(2) Each marine evacuation system must enable the total number of persons for which it is designed, to be transferred from the OSV into the inflated liferafts within a period of 10 minutes from the time an abandon-ship signal is given.

(3) Each marine evacuation system must be arranged so that liferafts may be securely attached to the platform and released from the platform by a person either in the liferaft or on the platform.

(4) Each marine evacuation system must be capable of being deployed from the OSV under unfavorable conditions of trim of up to 10 degrees either way and of list of up to 20 degrees either way.

(5) If the marine evacuation system has an inclined slide, the angle of the slide from horizontal must be within a range of 30 to 35 degrees when the OSV is upright and in the lightest seagoing condition.

(6) Each marine evacuation system platform must be capable of being restrained by a bowsing line or other positioning system that is designed to deploy automatically, and if necessary, be capable of being adjusted to the position required for evacuation.

(b) *Stowage.* Each marine evacuation system must be stowed as follows:

(1) There must not be any openings between the marine evacuation system's embarkation station and the OSV's side at the OSV's waterline in the lightest seagoing condition.

(2) The marine evacuation system's launching positions must be arranged, as far as practicable, to be straight down the OSV's side and safely clear the propeller and any steeply overhanging positions of the hull.

(3) The marine evacuation system must be protected from any projections of the OSV's structure or equipment.

(4) The marine evacuation system's passage and platform, when deployed;

its stowage container; and its operational arrangement must not interfere with the operation of any other lifesaving appliance at any other launching station.

(5) Where appropriate, the marine evacuation system's stowage area must be protected from damage by heavy seas.

(c) *Stowage of associated liferafts.* Inflatable liferafts used in conjunction with the marine evacuation system must be stowed as follows:

(1) Each inflatable liferaft used in conjunction with the marine evacuation system must be close to the system container, but capable of dropping clear of the deployed chute and boarding platform.

(2) Each inflatable liferaft used in conjunction with the marine evacuation system must be capable of individual release from its stowage rack.

(3) Each inflatable liferaft used in conjunction with the marine evacuation system must be stowed in accordance with § 133.130.

(4) Each inflatable liferaft used in conjunction with the marine evacuation system must be provided with preconnected or easily connected retrieving lines to the platform.

§ 133.150 Survival craft launching and recovery arrangements: General.

(a) All survival craft required for abandonment by the total number of persons on board must be capable of being launched with their full complement of persons and equipment within 10 minutes from the time the abandon-ship signal is given.

(b)(1) Each launching appliance must be a davit approved under 46 CFR part 160, subpart 160.132 for use with the intended craft, with a winch approved under 46 CFR part 160, subpart 160.115 for use with the intended craft.

(2) Each launching appliance for a davit-launched liferaft must include an automatic disengaging apparatus approved under 46 CFR part 160, subpart 160.170 and be either—

(i) A launching appliance described in paragraph (b)(1) of this section; or

(ii) A launching appliance approved on or before November 10, 2011 under approval series 160.163.

(c) Unless expressly provided otherwise, each survival craft must be provided launching appliances or marine evacuation systems, except—

(1) Those survival craft that can be boarded from a position on deck less than 4.5 meters (14.75 feet) above the waterline in the lightest seagoing condition and that have a mass of not more than 185 kilograms (407 pounds);

(2) Those survival craft that can be boarded from a position on deck less than 4.5 meters (14.75 feet) above the waterline in the lightest seagoing condition and that are stowed for launching directly from the stowed position, under unfavorable conditions of trim of 10 degrees and list of 20 degrees either way;

(3) Those survival craft that are carried in excess of the survival craft for 200 percent of the total number of persons on board the OSV, and that have a mass of not more than 185 kilograms (407 pounds);

(4) Those survival craft carried in excess of the survival craft for 200 percent of the total number of persons on board the OSV, and are stowed for launching directly from the stowed position under unfavorable conditions of trim of 10 degrees and list of 20 degrees either way;

(5) Those survival craft that are provided for use in conjunction with a marine evacuation system, and stowed for launching directly from the stowed position under unfavorable conditions of trim of 10 degrees and list of 20 degrees either way; or

(6) Liferafts installed on liftboats.

(d) Each launching appliance must be arranged so that the fully equipped survival craft the launching appliance serves can be safely launched against unfavorable conditions of trim of up to 10 degrees either way and of list of up to 20 degrees either way,—

(1) When the survival craft is loaded with its full complement of persons; and

(2) When not more than the required operating crew is on board.

(e) A launching appliance must not depend on any means other than gravity or stored mechanical power, independent of the OSV's power supplies, to launch the survival craft the launching appliance serves, in the fully loaded