

### § 83.25

### 33 CFR Ch. I (7-1-13 Edition)

or object towed or at least to indicate the presence of the unlighted vessel or object.

(i) *Western Rivers or other specified waters; exception.* Notwithstanding paragraph (c), on the Western Rivers (except below the Huey P. Long Bridge on the Mississippi River) and on waters specified by the Secretary, a power-driven vessel when pushing ahead or towing alongside, except as paragraph (b) applies, shall exhibit:

(1) Sidelights; and

(2) Two towing lights in a vertical line.

(j) *Towing another vessel in distress or otherwise in need of assistance.* Where from any sufficient cause it is impracticable for a vessel not normally engaged in towing operations to display the lights prescribed by paragraph (a), (c) or (i) of this Rule, such vessel shall not be required to exhibit those lights when engaged in towing another vessel in distress or otherwise in need of assistance. All possible measures shall be taken to indicate the nature of the relationship between the towing vessel and the vessel being assisted. The searchlight authorized by Rule 36 may be used to illuminate the tow.

#### § 83.25 Sailing vessels underway and vessels under oars (Rule 25).

(a) *Sailing vessels underway.* A sailing vessel underway shall exhibit:

(1) Sidelights; and

(2) A sternlight.

(b) *Sailing vessels of less than 20 meters in length.* In a sailing vessel of less than 20 meters in length the lights prescribed in paragraph (a) of this Rule may be combined in one lantern carried at or near the top of the mast where it can best be seen.

(c) *Additional lights.* A sailing vessel underway may, in addition to the lights prescribed in paragraph (a) of this Rule, exhibit at or near the top of the mast, where they can best be seen, two all-round lights in a vertical line, the upper being red and the lower green, but these lights shall not be exhibited in conjunction with the combined lantern permitted by paragraph (b) of this Rule.

(d) *Sailing vessels of less than 7 meters in length; vessels under oars.*

(1) A sailing vessel of less than 7 meters in length shall, if practicable, exhibit the lights prescribed in paragraph (a) or (b) of this Rule, but if she does not, she shall have ready at hand an electric torch or lighted lantern showing a white light which shall be exhibited in sufficient time to prevent collision.

(2) A vessel under oars may exhibit the lights prescribed in this Rule for sailing vessels, but if she does not, she shall have ready at hand an electric torch or lighted lantern showing a white light which shall be exhibited in sufficient time to prevent collision.

(e) *Vessels proceeding under sail.* A vessel proceeding under sail when also being propelled by machinery shall exhibit forward where it can best be seen a conical shape, apex downward. A vessel of less than 12 meters in length is not required to exhibit this shape, but may do so.

#### § 83.26 Fishing vessels (Rule 26).

(a) *Exhibition of only prescribed lights and shapes.* A vessel engaged in fishing, whether underway or at anchor, shall exhibit only the lights and shapes prescribed in this Rule.

(b) *Vessels engaged in trawling.* A vessel when engaged in trawling, by which is meant the dragging through the water of a dredge net or other apparatus used as a fishing appliance, shall exhibit:

(1) Two all-round lights in a vertical line, the upper being green and the lower white, or a shape consisting of two cones with their apexes together in a vertical line one above the other;

(2) A masthead light abaft of and higher than the all-round green light; a vessel of less than 50 meters in length shall not be obliged to exhibit such a light but may do so; and

(3) When making way through the water, in addition to the lights prescribed in this paragraph, sidelights and a sternlight.

(c) *Vessels engaged in fishing other than trawling.* A vessel engaged in fishing, other than trawling, shall exhibit:

(1) Two all-round lights in a vertical line, the upper being green and the lower white, or a shape consisting of two cones with their apexes together in a vertical line one above the other;