

$$\text{emiss}_{\text{allow, month}} = \sum_{j=1}^m \left(\sum_{i=1}^n \frac{(\text{limit}_i) (\text{polyol}_i)}{100} \right) j \quad (\text{Equation 6})$$

Where:

$\text{emiss}_{\text{allow, month}}$ = Allowable HAP ABA storage and equipment leak emissions, HAP ABA emissions from the production line, and equipment cleaning HAP emissions from the slabstock foam production source for the month, pounds.

m = Number of slabstock foam production lines.

polyol_i = Amount of polyol used in the month in the production of foam grade i on foam production line j , determined in accordance with § 63.1303(b), pounds.

n = Number of foam grades produced in the month on foam production line j .

limit_i = HAP ABA formulation limit for foam grade i , parts HAP ABA per 100 parts polyol. The HAP ABA formulation limits are determined in accordance with § 63.1297(d).

(e) *Compliance using recovery devices.*

If a recovery device is used to comply with paragraphs (a) or (b) of this section, the owner or operator shall determine the allowable source-wide HAP emissions for each month using Equation 6 in paragraph (d) of this section, and the actual monthly source-wide HAP emissions in accordance with paragraph (e)(1) of this section. The owner or operator shall also comply with the provisions of paragraph (e)(2) of this section.

(1) Actual monthly source-wide HAP emissions shall be determined using Equation 7.

$$E_{\text{actual}} = E_{\text{unc}} - \text{HAPABA}_{\text{recovered}} \quad (\text{Equation 7})$$

Where:

E_{actual} = Actual source-wide HAP emissions after control, pounds/month.

E_{unc} = Uncontrolled source-wide HAP emissions, pounds/month, determined in accordance with paragraph (c) (1) through (3) of this section.

$\text{HAPABA}_{\text{recovered}}$ = HAP ABA recovered, pounds/month, determined in accordance with paragraph (e)(2) of this section.

(2) The amount of HAP ABA recovered shall be determined in accordance with § 63.1303(c).

§ 63.1300 Standards for molded flexible polyurethane foam production.

Each owner or operator of a new or existing molded affected source shall comply with the provisions in paragraphs (a) and (b) of this section.

(a) A HAP or HAP-based material shall not be used as an equipment cleaner to flush the mixhead, nor shall it be used elsewhere as an equipment cleaner in a molded flexible polyurethane foam process, with the following exception. Diisocyanates may be used to flush the mixhead and associated piping during periods of startup

or maintenance, provided that the diisocyanate compounds are contained in a closed-loop system and are re-used in production.

(b) A HAP-based mold release agent shall not be used in a molded flexible polyurethane foam source process.

§ 63.1301 Standards for rebond foam production.

Each owner or operator of a new or existing rebond foam affected source shall comply with the provisions in paragraphs (a) and (b) of this section.

(a) A HAP or HAP-based material shall not be used as an equipment cleaner at a rebond foam source.

(b) A HAP-based mold release agent shall not be used in a rebond foam source.

§ 63.1302 Applicability of subpart A requirements.

The owner or operator of an affected source shall comply with the applicable requirements of subpart A of this part, as specified in Table 2 of this subpart.