AUTHENTICATED
U.S. GOVERNMENT
INFORMATION
GPO



amendable to measurement by the method described in ''Methods for Chemical Analysis of Water and Wastes,'' 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 131.

### § 417.92 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations | |
|---|---|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kilograms per 1,000 kg of anhydrous product) | |
| BOD*5* | 0.09 | 0.02 |
| COD | 0.40 | .09 |
| TSS | 0.15 | .03 |
| Surfactants | 0.15 | .03 |
| Oil and grease | 0.25 | .07 |
| pH | (1) | (1) |
| | English units (pounds per 1,000 lb of anhydrous product) | |
| BOD*5* | 0.09 | 0.02 |
| COD | 0.40 | .09 |
| TSS | 0.15 | .03 |
| Surfactants | 0.15 | .03 |
| Oil and grease | 0.25 | .07 |
| pH | (1) | (1) |

[1] Within the range 6.0 to 9.0.

[39 FR 13372, Apr. 12, 1974, as amended at 60 FR 33954, June 29, 1995]

### § 417.93 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable:

| Effluent characteristic | Effluent limitations | |
|---|---|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| | Metric units (kilograms per 1,000 kg of anhydrous product) | |
| BOD*5* | 0.07 | 0.02 |
| COD | 0.27 | .09 |
| TSS | 0.09 | .03 |
| Surfactants | 0.09 | .03 |
| Oil and grease | 0.21 | .07 |
| pH | (1) | (1) |
| | English units (pounds per 1,000 lb of anhydrous product) | |
| BOD*5* | 0.07 | 0.02 |
| COD | 0.27 | .09 |
| TSS | 0.09 | .03 |
| Surfactants | 0.09 | .03 |
| Oil and grease | 0.21 | .07 |
| pH | (1) | (1) |

[1] Within the range 6.0 to 9.0.

### § 417.94 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---|---|
| pH | No limitation. |
| BOD*5* | Do. |
| TSS | Do. |
| Oil and grease | Do. |
| COD | Do. |
| Surfactants | Do. |

[40 FR 6443, Feb. 11, 1975, as amended at 60 FR 33954, June 29, 1995]

### § 417.95 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart: