

**§ 98.25-35**

the insulation and vapor proof coating when specifically authorized by the Commandant.

(b) Where unlagged tanks are installed in insulated holds or insulated 'tween deck spaces, such tanks shall be considered lagged provided the thermal conductance of the insulation is not less than that required by paragraph (a) of this section.

**§ 98.25-35 Refrigerated systems.**

(a) Where refrigerated systems are installed to maintain the temperature of the liquid below atmospheric, at least two complete refrigeration plants automatically regulated by pressure variations within the tanks shall be provided, each to be complete with the necessary auxiliaries for proper operation. The capacity of each refrigeration compressor shall be sufficient to maintain the vapor pressure in the tanks during the peak atmospheric temperature conditions below the pressure for which the tanks are designed.

(b) An alternate arrangement may consist of three compressors, any two of which shall be capable of maintaining the vapor pressure in the tanks during peak atmospheric temperature conditions below the pressure for which the tanks are designed, the third compressor acting as a stand-by unit.

(c) Refrigerated tanks shall be insulated in conformance with the requirements of § 98.25-30.

**§ 98.25-40 Valves, fittings, and accessories.**

(a) All valves, flanges, fittings and accessory equipment shall be of a type suitable for use with anhydrous ammonia and shall be made of steel, or malleable or nodular iron meeting the requirements of § 56.60-1 of subchapter F (Marine Engineering) of this chapter. Valves shall be fitted with noncorrosive material suitable for ammonia service. Valves, flanges, and pipe fittings shall be of the square or round tongue and groove type or raised-face, United States of America Standard 300-pound standard minimum, fitted with suitable soft gasket material. Welded fittings shall be used wherever possible and the number of pipe joints shall be held to a minimum. Screwed joints are not permitted for pipe diameters ex-

**46 CFR Ch. I (10-1-13 Edition)**

ceeding 2 inches. Nonferrous materials, such as copper, copper alloys and aluminum alloys, shall not be used in the construction of valves, fittings or accessory equipment. Brazed joints are prohibited.

(b) Each tank shall be provided with the necessary fill and discharge liquid and vapor shut-off valves, safety relief valves, liquid level gaging devices, thermometer well and pressure gage, and shall be provided with suitable access for convenient operation. Connections to tanks installed below the weather deck shall be made to a trunk or dome extending above the weather deck. Connections to the tanks shall be protected against mechanical damage and tampering. Other openings in the tanks, except as specifically permitted by this part, are prohibited.

(c) All connections to the tanks, except safety devices and liquid level gaging devices, shall have manually operated shut-off valves located as close to the tank as possible.

(d) Excess flow valves where required by this section shall close automatically at the rated flow of vapor or liquid as specified by the manufacturer. The piping, including valves, fittings and appurtenances, protected by an excess flow valve, shall have a greater capacity than the rated flow of the excess flow valve.

(e) Liquid level gaging devices which are so constructed that outward flow of tank contents shall not exceed that passed by a No. 54 drill size opening, need not be equipped with excess flow valves.

(f) Pressure gage connections need not be equipped with excess flow valves if the openings are not larger than No. 54 drill size.

(g) Excess flow valves may be designed with a bypass, not to exceed a No. 60 drill size opening, to allow equalization of pressure.

(h) Prior to disconnecting shore lines, the pressure in the liquid and vapor lines shall be relieved through suitable valves installed at the loading header.

(i) Relief valves shall be fitted in liquid lines which may be subject to excessive pressure caused by liquid full