

§ 1915.75

(c) *Access to barges and river towboats.* (1) Ramps for access of vehicles to or between barges shall be of adequate strength, provided with side boards, well maintained and properly secured.

(2) Unless employees can step safely to or from the wharf, float, barge, or river towboat, either a ramp meeting the requirements of paragraph (c)(1) of this section or a safe walkway meeting the requirements of paragraph (a)(7) of this section shall be provided. When a walkway is impracticable, a substantial straight ladder, extending at least 36 inches above the upper landing surface and adequately secured against shifting or slipping, shall be provided. When conditions are such that neither a walkway nor a straight ladder can be used, a Jacob's ladder in accordance with the requirements of paragraph (d) of this section may be used.

(3) The means of access shall be in accordance with the requirements of paragraphs (a) (9), (10), and (11) of this section.

(d) *Jacob's ladders.* (1) Jacob's ladders shall be of the double rung or flat tread type. They shall be well maintained and properly secured.

(2) A Jacob's ladder shall either hang without slack from its lashings or be pulled up entirely.

[47 FR 16986, Apr. 20, 1982, as amended at 67 FR 44542, July 3, 2002]

§ 1915.75 Access to and guarding of dry docks and marine railways.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking.

(a) A gangway, ramp or permanent stairway of not less than 20 inches walking surface, of adequate strength, maintained in safe repair and securely fastened, shall be provided between a floating dry dock and the pier or bulkhead.

(b) Each side of such gangway, ramp or permanent stairway, including those which are used for access to wing walls from dry dock floors, shall have a railing with a midrail. Such railings on gangways or ramps shall be approximately 42 inches in height; and railings on permanent stairways shall be not less than approximately 30 or more than approximately 34 inches in height. Rails shall be of wood, pipe, chain,

29 CFR Ch. XVII (7-1-14 Edition)

wire, or rope, and shall be kept taut at all times.

(c) Railings meeting the requirements of paragraph (b) of this section shall be provided on the means of access to and from the floors of graving docks.

(d) Railings approximately 42 inches in height, with a midrail, shall be provided on the edges of wing walls of floating dry docks and on edges of graving docks. Sections of the railings may be temporarily removed where necessary to permit line handling while a vessel is entering or leaving the dock.

(e) When employees are working on the floor of a floating dry dock where they are exposed to the hazard of falling into the water, the end of the dry dock shall be equipped with portable stanchions and 42 inch railings with a midrail. When such a railing would be impracticable or ineffective, other effective means shall be provided to prevent employees from falling into the water.

(f) Access to wing walls from floors of dry docks shall be by ramps, permanent stairways or ladders meeting the applicable requirements of § 1915.72.

(g) Catwalks on stiles of marine railways shall be no less than 20 inches wide and shall have on at least one side a guardrail and midrail meeting the requirements of § 1915.71(j) (1) and (2).

[47 FR 16986, Apr. 20, 1982, as amended at 67 FR 44542, July 3, 2002]

§ 1915.76 Access to cargo spaces and confined spaces.

The provisions of this section apply to ship repairing, shipbuilding and shipbreaking except that paragraph (a)(4) of this section applies to ship repairing only.

(a) *Cargo spaces.* (1) There shall be at least one safe and accessible ladder in any cargo space which employees must enter.

(2) When any fixed ladder is visibly unsafe, the employer shall prohibit its use by employees.

(3) Straight ladders of adequate strength and suitably secured against shifting or slipping shall be provided as necessary when fixed ladders in cargo spaces do not meet the requirements of paragraph (a)(1) of this section. When

conditions are such that a straight ladder cannot be used, a Jacob's ladder meeting the requirements of §1915.74(d) may be used.

(4) When cargo is stowed within 4 inches of the back of ladder rungs, the ladder shall be deemed "unsafe" for the purpose of this section.

(5) Fixed ladders or straight ladders provided for access to cargo spaces shall not be used at the same time that cargo drafts, equipment, materials, scrap or other loads are entering or leaving the hold. Before using these ladders to enter or leave the hold, the employee shall be required to inform the winchman or crane signalman of his intention.

(b) *Confined spaces.* (1) More than one means of access shall be provided to a confined space in which employees are working and in which the work may generate a hazardous atmosphere in the space except where the structure or arrangement of the vessel makes this provision impractical.

(2) When the ventilation ducts required by these regulations must pass through these means of access, the ducts shall be of such a type and so arranged as to permit free passage of an employee through at least two of these means of access.

§ 1915.77 Working surfaces.

(a) Paragraphs (b) through (d) of this section shall apply to ship repairing and shipbuilding operations, and shall not apply to shipbreaking. Paragraph (e) of this section shall apply to shipbuilding, ship repairing and shipbreaking operations.

(b) When firebox floors present tripping hazards of exposed tubing or of missing or removed refractory, sufficient planking to afford safe footing shall be laid while work is being carried on within the boiler.

(c) When employees are working aloft, or elsewhere at elevations more than 5 feet above a solid surface, either scaffolds or a sloping ladder, meeting the requirements of this subpart, shall be used to afford safe footing, or the employees shall be protected by safety belts and lifelines meeting the requirements of §§1915.159 and 1915.160. Employees visually restricted by blasting hoods, welding helmets, and burning

goggles shall work from scaffolds, not from ladders, except for the initial and final welding or burning operation to start or complete a job, such as the erection and dismantling of hung scaffolding, or other similar, nonrepetitive jobs of brief duration.

(d) For work performed in restricted quarters, such as behind boilers and in between congested machinery units and piping, work platforms at least 20 inches wide meeting the requirements of §1915.71(i)(1) shall be used. Backrails may be omitted if bulkheading, boilers, machinery units, or piping afford proper protection against falling.

(e) When employees are boarding, leaving, or working from small boats or floats, they shall be protected by personal flotation devices meeting the requirements of §1915.158(a).

[47 FR 16986, Apr. 20, 1982, as amended at 67 FR 44543, July 3, 2002]

Subpart F—General Working Conditions

SOURCE: 76 FR 24698, May 2, 2011., unless otherwise noted.

§ 1915.80 Scope, application, definitions, and effective dates.

(a) The provisions of this subpart apply to general working conditions in shipyard employment, including work on vessels, on vessel sections, and at landside operations, regardless of geographic location.

(b) *Definitions applicable to this subpart.*

(1) *Additional safety measure.* A component of the tags-plus system that provides an impediment (in addition to the energy-isolating device) to the release of energy or the energization or startup of the machinery, equipment, or system being serviced. Examples of additional safety measures include, but are not limited to, removing an isolating circuit element; blocking a controlling switch; blocking, blanking, or bleeding lines; removing a valve handle or wiring it in place; opening an extra disconnecting device.

(2) *Affected employee.* An employee who normally operates or uses the machinery, equipment, or system that is going to be serviced under lockout/