

process (or process condenser or control condenser, where applicable), but which has not yet been introduced into a destruction device to reduce the mass of fluorinated GHG in the stream. If the emissions from the process are not routed to a destruction device, uncontrolled emissions are those fluorinated GHG emissions released to the atmosphere.

Unsafe-to-monitor means that monitoring personnel would be exposed to an immediate danger as a consequence of monitoring the piece of equipment. Examples of unsafe-to-monitor equipment include, but are not limited to, equipment under extreme pressure or heat.

[75 FR 74831, Dec. 1, 2010, as amended at 77 FR 51490, Aug. 24, 2012]

Subpart M [Reserved]

Subpart N—Glass Production

§ 98.140 Definition of the source category.

(a) A glass manufacturing facility manufactures flat glass, container glass, pressed and blown glass, or wool fiberglass by melting a mixture of raw materials to produce molten glass and form the molten glass into sheets, containers, fibers, or other shapes. A glass manufacturing facility uses one or more continuous glass melting furnaces to produce glass.

(b) A glass melting furnace that is an experimental furnace or a research and development process unit is not subject to this subpart.

§ 98.141 Reporting threshold.

You must report GHG emissions under this subpart if your facility contains a glass production process and the facility meets the requirements of either § 98.2(a)(1) or (2).

§ 98.142 GHGs to report.

You must report:

(a) CO₂ process emissions from each continuous glass melting furnace.

(b) CO₂ combustion emissions from each continuous glass melting furnace.

(c) CH₄ and N₂O combustion emissions from each continuous glass melting furnace. You must calculate and re-

port these emissions under subpart C of this part (General Stationary Fuel Combustion Sources) by following the requirements of subpart C.

(d) CO₂, CH₄, and N₂O emissions from each stationary fuel combustion unit other than continuous glass melting furnaces. You must report these emissions under subpart C of this part (General Stationary Fuel Combustion Sources) by following the requirements of subpart C.

§ 98.143 Calculating GHG emissions.

You must calculate and report the annual process CO₂ emissions from each continuous glass melting furnace using the procedure in paragraphs (a) through (c) of this section.

(a) For each continuous glass melting furnace that meets the conditions specified in § 98.33(b)(4)(ii) or (iii), you must calculate and report under this subpart the combined process and combustion CO₂ emissions by operating and maintaining a CEMS to measure CO₂ emissions according to the Tier 4 Calculation Methodology specified in § 98.33(a)(4) and all associated requirements for Tier 4 in subpart C of this part (General Stationary Fuel Combustion Sources).

(b) For each continuous glass melting furnace that is not subject to the requirements in paragraph (a) of this section, calculate and report the process and combustion CO₂ emissions from the glass melting furnace by using either the procedure in paragraph (b)(1) of this section or the procedure in paragraph (b)(2) of this section, except as specified in paragraph (c) of this section.

(1) Calculate and report under this subpart the combined process and combustion CO₂ emissions by operating and maintaining a CEMS to measure CO₂ emissions according to the Tier 4 Calculation Methodology specified in § 98.33(a)(4) and all associated requirements for Tier 4 in subpart C of this part (General Stationary Fuel Combustion Sources).

(2) Calculate and report the process and combustion CO₂ emissions separately using the procedures specified in paragraphs (b)(2)(i) through (b)(2)(vi) of this section.