

modulation of a carrier identification system (DVB-CID) for satellite transmission.” This document is incorporated by reference in accordance with 5 U.S.C. 552(a) and 1 CFR part 51 and approved by the Director of the Federal Register. The ETSI document may be obtained from ETSI, 650 Route des Lucioles, 06921 Sophia Antipolis Cedex, France and by email to [webstore@etsi.org](mailto:webstore@etsi.org) and a copy can be downloaded from <http://www.etsi.org>. You may inspect a copy at the Federal Communications Commission, 445 12th Street SW., Washington, DC 20554, or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030 or go to: [http://www.archives.gov/federal\\_register/code\\_of\\_federal\\_regulations/ibr\\_locations.html](http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html).

(2) The ATIS message must continuously repeat.

(c) ATIS equipment must be integrated into the uplink transmitter chain with a method that cannot easily be defeated.

[79 FR 8325, Feb. 12, 2014]

#### § 25.282 Orbit raising maneuvers.

A space station authorized to operate in the geostationary satellite orbit under this part is also authorized to transmit in connection with short-term, transitory maneuvers directly related to post-launch, orbit-raising maneuvers, provided that the following conditions are met:

(a) Authority is limited to those tracking, telemetry, and control frequencies in which the space station is authorized to operate once it reaches its assigned geostationary orbital location;

(b) In the event that any unacceptable interference does occur, the space station licensee shall cease operations until the issue is rectified;

(c) The space station licensee is required to accept interference from any lawfully operating satellite network or radio communication system.

[69 FR 54587, Sept. 9, 2004]

#### § 25.283 End-of-life disposal.

(a) *Geostationary orbit space stations.* Unless otherwise explicitly specified in

an authorization, a space station authorized to operate in the geostationary satellite orbit under this part shall be relocated, at the end of its useful life, barring catastrophic failure of satellite components, to an orbit with a perigee with an altitude of no less than:

$$36,021 \text{ km} + (1000 \cdot C_R \cdot A/m)$$

where  $C_R$  is the solar radiation pressure coefficient of the spacecraft, and  $A/m$  is the Area to mass ratio, in square meters per kilogram, of the spacecraft.

(b) A space station authorized to operate in the geostationary satellite orbit under this part may operate using its authorized tracking, telemetry and control frequencies, and outside of its assigned orbital location, for the purpose of removing the satellite from the geostationary satellite orbit at the end of its useful life, provided that the conditions of paragraph (a) of this section are met, and on the condition that the space station's tracking, telemetry and control transmissions are planned so as to avoid electrical interference to other space stations, and coordinated with any potentially affected satellite networks.

(c) *All space stations.* Upon completion of any relocation authorized by paragraph (b) of this section, or any relocation at end-of-life specified in an authorization, or upon a spacecraft otherwise completing its authorized mission, a space station licensee shall ensure, unless prevented by technical failures beyond its control, that all stored energy sources on board the satellite are discharged, by venting excess propellant, discharging batteries, relieving pressure vessels, and other appropriate measures.

(d) The minimum perigee requirement of paragraph (a) of this section shall not apply to space stations launched prior to March 18, 2002.

[69 FR 54588, Sept. 9, 2004, as amended at 78 FR 8431, Feb. 6, 2013]

#### § 25.284 Emergency Call Center Service.

(a) Providers of Mobile-Satellite Service to end-user customers (part 25, subparts A–D) must provide Emergency Call Center service to the extent that

**§ 25.285**

they offer real-time, two way switched voice service that is interconnected with the public switched network and utilize an in-network switching facility which enables the provider to reuse frequencies and/or accomplish seamless hand-offs of subscriber calls. Emergency Call Center personnel must determine the emergency caller's phone number and location and then transfer or otherwise redirect the call to an appropriate public safety answering point. Providers of Mobile-Satellite Services that utilize earth terminals that are not capable of use while in motion are exempt from providing Emergency Call Center service for such terminals.

(b) Beginning February 11, 2005, each Mobile-Satellite Service carrier that is subject to the provisions of paragraph (a) of this section must maintain records of all 911 calls received at its emergency call center. Beginning October 15, 2005, and on each following October 15, Mobile-Satellite Service carriers providing service in the 1.6/2.4 GHz and 2 GHz bands must submit a report to the Commission regarding their call center data, current as of September 30 of that year. Beginning June 30, 2006, and on each following June 30, Mobile-Satellite Service carriers providing service in bands other than 1.6/2.4 GHz and 2 GHz must submit a report to the Commission regarding their call center data, current as of May 31 of that year. These reports must include, at a minimum, the following:

- (1) The name and address of the carrier, the address of the carrier's emergency call center, and emergency call center contact information;
- (2) The aggregate number of calls received by the call center each month during the relevant reporting period;
- (3) An indication of how many calls received by the call center each month during the relevant reporting period required forwarding to a public safety answering point and how many did not require forwarding to a public safety answering point.

[69 FR 6582, Feb. 11, 2004, as amended at 69 FR 54042, Sept. 7, 2004; 78 FR 8431, Feb. 6, 2013]

**47 CFR Ch. I (10–1–14 Edition)**

**§ 25.285 Operation of MSS and ATC transmitters or transceivers on board civil aircraft.**

(a) Operation of any of the following devices aboard civil aircraft is prohibited, unless the device is installed in a manner approved by the Federal Aviation Administration or is used by the pilot or with the pilot's consent:

- (1) Earth stations capable of transmitting in the 1.5/1.6 GHz, 1.6/2.4 GHz, or 2 GHz Mobile-Satellite Service frequency bands;
- (2) ATC terminals capable of transmitting in the 1.5/1.6 GHz or 1.6/2.4 GHz MSS bands;
- (3) Earth stations used for non-voice, non-geostationary Mobile-Satellite Service communication that can emit radiation in the 108–137 MHz band.

(b) No portable device of any type identified in paragraph (a) of this section (including transmitter or transceiver units installed in other devices that are themselves portable) may be sold or distributed to users unless it conspicuously bears the following warning: "This device must be turned off at all times while on board aircraft." For purposes of this section, a device is portable if it is a "portable device" as defined in § 2.1093(b) of this chapter or is designed to be carried by hand.

[79 FR 8325, Feb. 12, 2014]

EFFECTIVE DATE NOTE: At 79 FR 44140, July 30, 2014, in § 25.285, paragraph (a)(2) was corrected. This text contains information collection and recordkeeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

**§ 25.286 Antenna painting and lighting.**

The owner of an earth station antenna structure must comply with all applicable painting, marking, and/or lighting requirements in part 17 of this chapter. In the event of default by the owner, the station licensee will be responsible for ensuring that such requirements are met.

[79 FR 8326, Feb. 12, 2014]