AUTHENTICATED
U.S. GOVERNMENT
INFORMATION
GPO

TABLE 2B TO SUBPART E OF PART 59—REACTIVITY FACTORS FOR ALIPHATIC HYDROCARBON SOLVENT MIXTURES

Bin	Average boiling point* (degrees F)	Criteria	Reactivity factor (g O_3/g VOC)
1	80–205	Alkanes (<2% Aromatics)	2.08
2	80–205	N- & Iso-Alkanes (≥90% and <2% Aromatics)	1.59
3	80–205	Cyclo-Alkanes (≥90% and <2% Aromatics)	2.52
4	80–205	Alkanes (2 to <8% Aromatics)	2.24
5	80–205	Alkanes (8 to 22% Aromatics)	2.56
6	>205–340	Alkanes (<2% Aromatics)	1.41
7	>205–340	N- & Iso-Alkanes (≥90% and <2% Aromatics)	1.17
8	>205–340	Cyclo-Alkanes (≥90% and <2% Aromatics)	1.65
9	>205–340	Alkanes (2 to <8% Aromatics)	1.62
10	>205–340	Alkanes (8 to 22% Aromatics)	2.03
11	>340–460	Alkanes (<2% Aromatics)	0.91
12	>340–460	N- & Iso-Alkanes (≥90% and <2% Aromatics)	0.81
13	>340–460	Cyclo-Alkanes (≥90% and <2% Aromatics)	1.01
14	>340–460	Alkanes (2 to <8% Aromatics)	1.21
15	>340–460	Alkanes (8 to 22% Aromatics)	1.82
16	>460–580	Alkanes (<2% Aromatics)	0.57
17	>460–580	N- & Iso-Alkanes (≥90% and <2% Aromatics)	0.51
18	>460–580	Cyclo-Alkanes (≥90% and <2% Aromatics)	0.63
19	>460–580	Alkanes (2 to <8% Aromatics)	0.88
20	>460–580	Alkanes (8 to 22% Aromatics)	1.49

*Average Boiling Point = (Initial Boiling Point + Dry Point)/2(b) Aromatic Hydrocarbon Solvents

[77 FR 14286, Mar. 9, 2012]

TABLE 2C TO SUBPART E OF PART 59—REACTIVITY FACTORS FOR AROMATIC HYDROCARBON SOLVENT MIXTURES

Bin	Boiling range (degrees F)	Criteria	Reactivity factor (g O_3/g VOC)
21	280–290	Aromatic Content (≥98%)	7.37
22	320–350	Aromatic Content (≥98%)	7.51
23	355–420	Aromatic Content (≥98%)	8.07
24	450–535	Aromatic Content (≥98%)	5.00

[77 FR 14286, Mar. 9, 2012]

Subpart F—Control of Evaporative Emissions From New and In-Use Portable Fuel Containers

SOURCE: 72 FR 8533, Feb. 26, 2007, unless otherwise noted.

OVERVIEW AND APPLICABILITY

§ 59.600 Does this subpart apply for my products?

(a) Except as provided in § 59.605 and paragraph (b) of this section, the regulations in this subpart F apply for all portable fuel containers (defined in § 59.680) that are manufactured on or after January 1, 2009.

(b) See § 59.602 (a) and (b) to determine how to apply the provisions of this subpart for containers that were manufactured before January 1, 2009.

§ 59.601 Do the requirements of this subpart apply to me?

(a) Unless specified otherwise in this subpart, the requirements and prohibitions of this subpart apply to all manufacturers and importers of portable fuel containers. Certain prohibitions in § 59.602 apply to all other persons.

(b) New portable fuel containers that are subject to the emissions standards of this part must be covered by a certificate of conformity that is issued to the manufacturer of the container. If more than one person meets the definition of manufacturer for a portable fuel container, see § 59.621 to determine if you are the manufacturer who may

apply for and receive a certificate of conformity.

(c) Unless specifically noted otherwise, the term ''you'' means manufacturers, as defined in § 59.680.

§ 59.602 What are the general prohibitions and requirements of this subpart?

(a) *General prohibition for manufacturers and importers.* No manufacturer or importer may sell, offer for sale, introduce or deliver for introduction into commerce in the United States, or import any new portable fuel container that is subject to the emissions standards of this subpart and is manufactured after December 31, 2008 unless it is covered by a valid certificate of conformity, it is labeled as required, and it complies with all of the applicable requirements of this subpart, including compliance with the emissions standards for its useful life. After June 30, 2009, no manufacturer or importer may sell, offer for sale, introduce or deliver into commerce in the United States, or import any new portable fuel container that was manufactured prior to January 1, 2009 unless it meets the requirements of this subpart.

(b) *General prohibition for wholesale distributors.* No wholesale distributor may sell, offer for sale, or distribute any portable fuel container in the United States that is subject to the emissions standards of this subpart and is manufactured after December 31, 2008 unless it is covered by a valid certificate of conformity and is labeled as required. After December 31, 2009, no wholesale distributor may sell, offer for sale, or distribute in the United States any portable fuel container that was manufactured prior to January 1, 2009 unless it meets the requirements of this subpart. After December 31, 2009, all new portable fuel containers shall be deemed to be manufactured after December 31, 2008 unless they are in retail inventory.

(c) *Reporting and recordkeeping.* (1) You must keep the records and submit the reports specified in § 59.628. Records must be retained for at least 5 years from the date of manufacture or importation and must be supplied to EPA upon request.

(2) No person may alter, destroy, or falsify any record or report required by this subpart.

(d) *Testing and access to facilities.* You may not keep us from entering your facility to observe tests or inspect facilities if we are authorized to do so. Also, you must perform the tests we require (or have the tests done for you). Failure to perform this testing is prohibited.

(e) *Warranty.* You may not fail to offer, provide notice of, or honor the emissions warranty required under this subpart.

(f) *Replacement components.* No person may sell, offer for sale, introduce or deliver for introduction into commerce in the United States, import, or install any replacement component for portable fuel containers subject to the standards of this subpart where the component has the effect of disabling, bypassing, or rendering inoperative the emissions controls of the containers.

(g) *Violations.* If a person violates any prohibition or requirement of this subpart or the Act concerning portable fuel containers, it shall be considered a separate violation for each portable fuel container.

(h) *Assessment of penalties and injunctions.* We may assess administrative penalties, bring a civil action to assess and recover civil penalties, bring a civil action to enjoin and restrain violations, or bring criminal action as provided by the Clean Air Act.

§ 59.603 How must manufacturers apply good engineering judgment?

(a) In addition to other requirements and prohibitions set forth in this subpart, you must use good engineering judgment for decisions related to any requirements under this subpart. This includes your applications for certification, any testing you do to show that your portable fuel containers comply with requirements that apply to them, and how you select, categorize, determine, and apply these requirements.

(b) Upon request, you must provide EPA a written description of the engineering judgment in question. Such information must be provided within 15 working days unless EPA specifies a different period of time to respond.