

Environmental Protection Agency

§ 261.4

the debris as defined in part 268 of this chapter does not exhibit a characteristic identified at subpart C of this part, the following materials are not subject to regulation under 40 CFR parts 260, 261 to 266, 268, or 270:

(1) Hazardous debris as defined in part 268 of this chapter that has been treated using one of the required extraction or destruction technologies specified in Table 1 of § 268.45 of this chapter; persons claiming this exclusion in an enforcement action will have the burden of proving by clear and convincing evidence that the material meets all of the exclusion requirements; or

(2) Debris as defined in part 268 of this chapter that the Regional Administrator, considering the extent of contamination, has determined is no longer contaminated with hazardous waste.

(g)(1) A hazardous waste that is listed in subpart D of this part solely because it exhibits one or more characteristics of ignitability as defined under § 261.21, corrosivity as defined under § 261.22, or reactivity as defined under § 261.23 is not a hazardous waste, if the waste no longer exhibits any characteristic of hazardous waste identified in subpart C of this part.

(2) The exclusion described in paragraph (g)(1) of this section also pertains to:

(i) Any mixture of a solid waste and a hazardous waste listed in subpart D of this part solely because it exhibits the characteristics of ignitability, corrosivity, or reactivity as regulated under paragraph (a)(2)(iv) of this section; and

(ii) Any solid waste generated from treating, storing, or disposing of a hazardous waste listed in subpart D of this part solely because it exhibits the characteristics of ignitability, corrosivity, or reactivity as regulated under paragraph (c)(2)(i) of this section.

(3) Wastes excluded under this section are subject to part 268 of this chapter (as applicable), even if they no longer exhibit a characteristic at the point of land disposal.

(4) Any mixture of a solid waste excluded from regulation under § 261.4(b)(7) and a hazardous waste list-

ed in subpart D of this part solely because it exhibits one or more of the characteristics of ignitability, corrosivity, or reactivity as regulated under paragraph (a)(2)(iv) of this section is not a hazardous waste, if the mixture no longer exhibits any characteristic of hazardous waste identified in subpart C of this part for which the hazardous waste listed in subpart D of this part was listed.

(h)(1) Hazardous waste containing radioactive waste is no longer a hazardous waste when it meets the eligibility criteria and conditions of 40 CFR part 266, Subpart N (“eligible radioactive mixed waste”).

(2) The exemption described in paragraph (h)(1) of this section also pertains to:

(i) Any mixture of a solid waste and an eligible radioactive mixed waste; and

(ii) Any solid waste generated from treating, storing, or disposing of an eligible radioactive mixed waste.

(3) Waste exempted under this section must meet the eligibility criteria and specified conditions in 40 CFR 266.225 and 40 CFR 266.230 (for storage and treatment) and in 40 CFR 266.310 and 40 CFR 266.315 (for transportation and disposal). Waste that fails to satisfy these eligibility criteria and conditions is regulated as hazardous waste.

[57 FR 7632, Mar. 3, 1992; 57 FR 23063, June 1, 1992, as amended at 57 FR 37263, Aug. 18, 1992; 57 FR 41611, Sept. 10, 1992; 57 FR 49279, Oct. 30, 1992; 59 FR 38545, July 28, 1994; 60 FR 7848, Feb. 9, 1995; 63 FR 28637, May 26, 1998; 63 FR 42184, Aug. 6, 1998; 66 FR 27297, May 16, 2001; 66 FR 50333, Oct. 3, 2001; 70 FR 34561, June 14, 2005; 70 FR 57784, Oct. 4, 2005; 71 FR 40258, July 14, 2006]

§ 261.4 Exclusions.

(a) *Materials which are not solid wastes.* The following materials are not solid wastes for the purpose of this part:

(1)(i) Domestic sewage; and

(ii) Any mixture of domestic sewage and other wastes that passes through a sewer system to a publicly-owned treatment works for treatment. “Domestic sewage” means untreated sanitary wastes that pass through a sewer system.

§ 261.4

40 CFR Ch. I (7–1–18 Edition)

(2) Industrial wastewater discharges that are point source discharges subject to regulation under section 402 of the Clean Water Act, as amended.

[*Comment:* This exclusion applies only to the actual point source discharge. It does not exclude industrial wastewaters while they are being collected, stored or treated before discharge, nor does it exclude sludges that are generated by industrial wastewater treatment.]

(3) Irrigation return flows.

(4) Source, special nuclear or by-product material as defined by the Atomic Energy Act of 1954, as amended, 42 U.S.C. 2011 *et seq.*

(5) Materials subjected to in-situ mining techniques which are not removed from the ground as part of the extraction process.

(6) Pulping liquors (*i.e.*, black liquor) that are reclaimed in a pulping liquor recovery furnace and then reused in the pulping process, unless it is accumulated speculatively as defined in § 261.1(c) of this chapter.

(7) Spent sulfuric acid used to produce virgin sulfuric acid provided it is not accumulated speculatively as defined in § 261.1(c) of this chapter.

(8) Secondary materials that are reclaimed and returned to the original process or processes in which they were generated where they are reused in the production process provided:

(i) Only tank storage is involved, and the entire process through completion of reclamation is closed by being entirely connected with pipes or other comparable enclosed means of conveyance;

(ii) Reclamation does not involve controlled flame combustion (such as occurs in boilers, industrial furnaces, or incinerators);

(iii) The secondary materials are never accumulated in such tanks for over twelve months without being reclaimed; and

(iv) The reclaimed material is not used to produce a fuel, or used to produce products that are used in a manner constituting disposal.

(9)(i) Spent wood preserving solutions that have been reclaimed and are reused for their original intended purpose; and

(ii) Wastewaters from the wood preserving process that have been reclaimed and are reused to treat wood.

(iii) Prior to reuse, the wood preserving wastewaters and spent wood preserving solutions described in paragraphs (a)(9)(i) and (a)(9)(ii) of this section, so long as they meet all of the following conditions:

(A) The wood preserving wastewaters and spent wood preserving solutions are reused on-site at water borne plants in the production process for their original intended purpose;

(B) Prior to reuse, the wastewaters and spent wood preserving solutions are managed to prevent release to either land or groundwater or both;

(C) Any unit used to manage wastewaters and/or spent wood preserving solutions prior to reuse can be visually or otherwise determined to prevent such releases;

(D) Any drip pad used to manage the wastewaters and/or spent wood preserving solutions prior to reuse complies with the standards in part 265, subpart W of this chapter, regardless of whether the plant generates a total of less than 100 kg/month of hazardous waste; and

(E) Prior to operating pursuant to this exclusion, the plant owner or operator prepares a one-time notification stating that the plant intends to claim the exclusion, giving the date on which the plant intends to begin operating under the exclusion, and containing the following language: "I have read the applicable regulation establishing an exclusion for wood preserving wastewaters and spent wood preserving solutions and understand it requires me to comply at all times with the conditions set out in the regulation." The plant must maintain a copy of that document in its on-site records until closure of the facility. The exclusion applies so long as the plant meets all of the conditions. If the plant goes out of compliance with any condition, it may apply to the appropriate Regional Administrator or state Director for reinstatement. The Regional Administrator or state Director may reinstate the exclusion upon finding that the plant has returned to compliance with all conditions and that the violations are not likely to recur.

Environmental Protection Agency

§ 261.4

(10) EPA Hazardous Waste Nos. K060, K087, K141, K142, K143, K144, K145, K147, and K148, and any wastes from the coke by-products processes that are hazardous only because they exhibit the Toxicity Characteristic (TC) specified in section 261.24 of this part when, subsequent to generation, these materials are recycled to coke ovens, to the tar recovery process as a feedstock to produce coal tar, or mixed with coal tar prior to the tar's sale or refining. This exclusion is conditioned on there being no land disposal of the wastes from the point they are generated to the point they are recycled to coke ovens or tar recovery or refining processes, or mixed with coal tar.

(11) Nonwastewater splash condenser dross residue from the treatment of K061 in high temperature metals recovery units, provided it is shipped in drums (if shipped) and not land disposed before recovery.

(12)(i) Oil-bearing hazardous secondary materials (*i.e.*, sludges, byproducts, or spent materials) that are generated at a petroleum refinery (SIC code 2911) and are inserted into the petroleum refining process (SIC code 2911—including, but not limited to, distillation, catalytic cracking, fractionation, or thermal cracking units (*i.e.*, cokers)) unless the material is placed on the land, or speculatively accumulated before being so recycled. Materials inserted into thermal cracking units are excluded under this paragraph, provided that the coke product also does not exhibit a characteristic of hazardous waste. Oil-bearing hazardous secondary materials may be inserted into the same petroleum refinery where they are generated, or sent directly to another petroleum refinery and still be excluded under this provision. Except as provided in paragraph (a)(12)(ii) of this section, oil-bearing hazardous secondary materials generated elsewhere in the petroleum industry (*i.e.*, from sources other than petroleum refineries) are not excluded under this section. Residuals generated from processing or recycling materials excluded under this paragraph (a)(12)(i), where such materials as generated would have otherwise met a listing under subpart D of this part, are

designated as F037 listed wastes when disposed of or intended for disposal.

(ii) Recovered oil that is recycled in the same manner and with the same conditions as described in paragraph (a)(12)(i) of this section. Recovered oil is oil that has been reclaimed from secondary materials (including wastewater) generated from normal petroleum industry practices, including refining, exploration and production, bulk storage, and transportation incident thereto (SIC codes 1311, 1321, 1381, 1382, 1389, 2911, 4612, 4613, 4922, 4923, 4789, 5171, and 5172.) Recovered oil does not include oil-bearing hazardous wastes listed in subpart D of this part; however, oil recovered from such wastes may be considered recovered oil. Recovered oil does not include used oil as defined in 40 CFR 279.1.

(13) Excluded scrap metal (processed scrap metal, unprocessed home scrap metal, and unprocessed prompt scrap metal) being recycled.

(14) Shredded circuit boards being recycled provided that they are:

(i) Stored in containers sufficient to prevent a release to the environment prior to recovery; and

(ii) Free of mercury switches, mercury relays and nickel-cadmium batteries and lithium batteries.

(15) Condensates derived from the overhead gases from kraft mill steam strippers that are used to comply with 40 CFR 63.446(e). The exemption applies only to combustion at the mill generating the condensates.

(16) [Reserved]

(17) Spent materials (as defined in § 261.1) (other than hazardous wastes listed in subpart D of this part) generated within the primary mineral processing industry from which minerals, acids, cyanide, water, or other values are recovered by mineral processing or by beneficiation, provided that:

(i) The spent material is legitimately recycled to recover minerals, acids, cyanide, water or other values;

(ii) The spent material is not accumulated speculatively;

(iii) Except as provided in paragraph (a)(17)(iv) of this section, the spent material is stored in tanks, containers, or buildings meeting the following minimum integrity standards: a building

§ 261.4

40 CFR Ch. I (7-1-18 Edition)

must be an engineered structure with a floor, walls, and a roof all of which are made of non-earthen materials providing structural support (except smelter buildings may have partially earthen floors provided the secondary material is stored on the non-earthen portion), and have a roof suitable for diverting rainwater away from the foundation; a tank must be free standing, not be a surface impoundment (as defined in 40 CFR 260.10), and be manufactured of a material suitable for containment of its contents; a container must be free standing and be manufactured of a material suitable for containment of its contents. If tanks or containers contain any particulate which may be subject to wind dispersal, the owner/operator must operate these units in a manner which controls fugitive dust. Tanks, containers, and buildings must be designed, constructed and operated to prevent significant releases to the environment of these materials.

(iv) The Regional Administrator or State Director may make a site-specific determination, after public review and comment, that only solid mineral processing spent material may be placed on pads rather than tanks, containers, or buildings. Solid mineral processing spent materials do not contain any free liquid. The decision-maker must affirm that pads are designed, constructed and operated to prevent significant releases of the secondary material into the environment. Pads must provide the same degree of containment afforded by the non-RCRA tanks, containers and buildings eligible for exclusion.

(A) The decision-maker must also consider if storage on pads poses the potential for significant releases via groundwater, surface water, and air exposure pathways. Factors to be considered for assessing the groundwater, surface water, air exposure pathways are: The volume and physical and chemical properties of the secondary material, including its potential for migration off the pad; the potential for human or environmental exposure to hazardous constituents migrating from the pad via each exposure pathway, and the possibility and extent of harm to

human and environmental receptors via each exposure pathway.

(B) Pads must meet the following minimum standards: Be designed of non-earthen material that is compatible with the chemical nature of the mineral processing spent material, capable of withstanding physical stresses associated with placement and removal, have run on/runoff controls, be operated in a manner which controls fugitive dust, and have integrity assurance through inspections and maintenance programs.

(C) Before making a determination under this paragraph, the Regional Administrator or State Director must provide notice and the opportunity for comment to all persons potentially interested in the determination. This can be accomplished by placing notice of this action in major local newspapers, or broadcasting notice over local radio stations.

(v) The owner or operator provides notice to the Regional Administrator or State Director providing the following information: The types of materials to be recycled; the type and location of the storage units and recycling processes; and the annual quantities expected to be placed in land-based units. This notification must be updated when there is a change in the type of materials recycled or the location of the recycling process.

(vi) For purposes of paragraph (b)(7) of this section, mineral processing spent materials must be the result of mineral processing and may not include any listed hazardous wastes. Listed hazardous wastes and characteristic hazardous wastes generated by non-mineral processing industries are not eligible for the conditional exclusion from the definition of solid waste.

(18) Petrochemical recovered oil from an associated organic chemical manufacturing facility, where the oil is to be inserted into the petroleum refining process (SIC code 2911) along with normal petroleum refinery process streams, provided:

(i) The oil is hazardous only because it exhibits the characteristic of ignitability (as defined in § 261.21) and/or toxicity for benzene (§ 261.24, waste code D018); and

Environmental Protection Agency

§ 261.4

(ii) The oil generated by the organic chemical manufacturing facility is not placed on the land, or speculatively accumulated before being recycled into the petroleum refining process. An "associated organic chemical manufacturing facility" is a facility where the primary SIC code is 2869, but where operations may also include SIC codes 2821, 2822, and 2865; and is physically co-located with a petroleum refinery; and where the petroleum refinery to which the oil being recycled is returned also provides hydrocarbon feedstocks to the organic chemical manufacturing facility. "Petrochemical recovered oil" is oil that has been reclaimed from secondary materials (i.e., sludges, byproducts, or spent materials, including wastewater) from normal organic chemical manufacturing operations, as well as oil recovered from organic chemical manufacturing processes.

(19) Spent caustic solutions from petroleum refining liquid treating processes used as a feedstock to produce cresylic or naphthenic acid unless the material is placed on the land, or accumulated speculatively as defined in § 261.1(c).

(20) Hazardous secondary materials used to make zinc fertilizers, provided that the following conditions specified are satisfied:

(i) Hazardous secondary materials used to make zinc micronutrient fertilizers must not be accumulated speculatively, as defined in § 261.1 (c)(8).

(ii) Generators and intermediate handlers of zinc-bearing hazardous secondary materials that are to be incorporated into zinc fertilizers must:

(A) Submit a one-time notice to the Regional Administrator or State Director in whose jurisdiction the exclusion is being claimed, which contains the name, address and EPA ID number of the generator or intermediate handler facility, provides a brief description of the secondary material that will be subject to the exclusion, and identifies when the manufacturer intends to begin managing excluded, zinc-bearing hazardous secondary materials under the conditions specified in this paragraph (a)(20).

(B) Store the excluded secondary material in tanks, containers, or buildings that are constructed and maintained in

a way that prevents releases of the secondary materials into the environment. At a minimum, any building used for this purpose must be an engineered structure made of non-earthen materials that provide structural support, and must have a floor, walls and a roof that prevent wind dispersal and contact with rainwater. Tanks used for this purpose must be structurally sound and, if outdoors, must have roofs or covers that prevent contact with wind and rain. Containers used for this purpose must be kept closed except when it is necessary to add or remove material, and must be in sound condition. Containers that are stored outdoors must be managed within storage areas that:

(1) Have containment structures or systems sufficiently impervious to contain leaks, spills and accumulated precipitation; and

(2) Provide for effective drainage and removal of leaks, spills and accumulated precipitation; and

(3) Prevent run-on into the containment system.

(C) With each off-site shipment of excluded hazardous secondary materials, provide written notice to the receiving facility that the material is subject to the conditions of this paragraph (a)(20).

(D) Maintain at the generator's or intermediate handlers's facility for no less than three years records of all shipments of excluded hazardous secondary materials. For each shipment these records must at a minimum contain the following information:

(1) Name of the transporter and date of the shipment;

(2) Name and address of the facility that received the excluded material, and documentation confirming receipt of the shipment; and

(3) Type and quantity of excluded secondary material in each shipment.

(iii) Manufacturers of zinc fertilizers or zinc fertilizer ingredients made from excluded hazardous secondary materials must:

(A) Store excluded hazardous secondary materials in accordance with the storage requirements for generators and intermediate handlers, as specified in paragraph (a)(20)(ii)(B) of this section.

§261.4

40 CFR Ch. I (7-1-18 Edition)

(B) Submit a one-time notification to the Regional Administrator or State Director that, at a minimum, specifies the name, address and EPA ID number of the manufacturing facility, and identifies when the manufacturer intends to begin managing excluded, zinc-bearing hazardous secondary materials under the conditions specified in this paragraph (a)(20).

(C) Maintain for a minimum of three years records of all shipments of excluded hazardous secondary materials received by the manufacturer, which must at a minimum identify for each shipment the name and address of the generating facility, name of transporter and date the materials were received, the quantity received, and a brief description of the industrial process that generated the material.

(D) Submit to the Regional Administrator or State Director an annual report that identifies the total quantities of all excluded hazardous secondary materials that were used to manufacture zinc fertilizers or zinc fertilizer ingredients in the previous year, the name and address of each generating facility, and the industrial process(s) from which they were generated.

(iv) Nothing in this section preempts, overrides or otherwise negates the provision in §262.11 of this chapter, which requires any person who generates a solid waste to determine if that waste is a hazardous waste.

(v) Interim status and permitted storage units that have been used to store only zinc-bearing hazardous wastes prior to the submission of the one-time notice described in paragraph (a)(20)(ii)(A) of this section, and that afterward will be used only to store hazardous secondary materials excluded under this paragraph, are not subject to the closure requirements of 40 CFR Parts 264 and 265.

(21) Zinc fertilizers made from hazardous wastes, or hazardous secondary materials that are excluded under paragraph (a)(20) of this section, provided that:

(i) The fertilizers meet the following contaminant limits:

(A) For metal contaminants:

Constituent	Maximum Allowable Total Concentration in Fertilizer, per Unit (1% of Zinc (ppm))
Arsenic	0.3
Cadmium	1.4
Chromium	0.6
Lead	2.8
Mercury	0.3

(B) For dioxin contaminants the fertilizer must contain no more than eight (8) parts per trillion of dioxin, measured as toxic equivalent (TEQ).

(ii) The manufacturer performs sampling and analysis of the fertilizer product to determine compliance with the contaminant limits for metals no less than every six months, and for dioxins no less than every twelve months. Testing must also be performed whenever changes occur to manufacturing processes or ingredients that could significantly affect the amounts of contaminants in the fertilizer product. The manufacturer may use any reliable analytical method to demonstrate that no constituent of concern is present in the product at concentrations above the applicable limits. It is the responsibility of the manufacturer to ensure that the sampling and analysis are unbiased, precise, and representative of the product(s) introduced into commerce.

(iii) The manufacturer maintains for no less than three years records of all sampling and analyses performed for purposes of determining compliance with the requirements of paragraph (a)(21)(ii) of this section. Such records must at a minimum include:

(A) The dates and times product samples were taken, and the dates the samples were analyzed;

(B) The names and qualifications of the person(s) taking the samples;

(C) A description of the methods and equipment used to take the samples;

(D) The name and address of the laboratory facility at which analyses of the samples were performed;

(E) A description of the analytical methods used, including any cleanup and sample preparation methods; and

(F) All laboratory analytical results used to determine compliance with the

Environmental Protection Agency

§ 261.4

contaminant limits specified in this paragraph (a)(21).

(22) Used cathode ray tubes (CRTs)

(i) Used, intact CRTs as defined in § 260.10 of this chapter are not solid wastes within the United States unless they are disposed, or unless they are speculatively accumulated as defined in § 261.1(c)(8) by CRT collectors or glass processors.

(ii) Used, intact CRTs as defined in § 260.10 of this chapter are not solid wastes when exported for recycling provided that they meet the requirements of § 261.40.

(iii) Used, broken CRTs as defined in § 260.10 of this chapter are not solid wastes provided that they meet the requirements of § 261.39.

(iv) Glass removed from CRTs is not a solid waste provided that it meets the requirements of § 261.39(c).

(23) Hazardous secondary material generated and legitimately reclaimed within the United States or its territories and under the control of the generator, provided that the material complies with paragraphs (a)(23)(i) and (ii) of this section:

(i)(A) The hazardous secondary material is generated and reclaimed at the generating facility (for purposes of this definition, generating facility means all contiguous property owned, leased, or otherwise controlled by the hazardous secondary material generator); or

(B) The hazardous secondary material is generated and reclaimed at different facilities, if the reclaiming facility is controlled by the generator or if both the generating facility and the reclaiming facility are controlled by a person as defined in § 260.10 of this chapter, and if the generator provides one of the following certifications: “on behalf of [insert generator facility name], I certify that this facility will send the indicated hazardous secondary material to [insert reclaimer facility name], which is controlled by [insert generator facility name] and that [insert name of either facility] has acknowledged full responsibility for the safe management of the hazardous secondary material,” or “on behalf of [insert generator facility name], I certify that this facility will send the indicated hazardous secondary material to

[insert reclaimer facility name], that both facilities are under common control, and that [insert name of either facility] has acknowledged full responsibility for the safe management of the hazardous secondary material.” For purposes of this paragraph, “control” means the power to direct the policies of the facility, whether by the ownership of stock, voting rights, or otherwise, except that contractors who operate facilities on behalf of a different person as defined in § 260.10 shall not be deemed to “control” such facilities. The generating and receiving facilities must both maintain at their facilities for no less than three years records of hazardous secondary materials sent or received under this exclusion. In both cases, the records must contain the name of the transporter, the date of the shipment, and the type and quantity of the hazardous secondary material shipped or received under the exclusion. These requirements may be satisfied by routine business records (e.g., financial records, bills of lading, copies of DOT shipping papers, or electronic confirmations); or

(C) The hazardous secondary material is generated pursuant to a written contract between a tolling contractor and a toll manufacturer and is reclaimed by the tolling contractor, if the tolling contractor certifies the following: “On behalf of [insert tolling contractor name], I certify that [insert tolling contractor name] has a written contract with [insert toll manufacturer name] to manufacture [insert name of product or intermediate] which is made from specified unused materials, and that [insert tolling contractor name] will reclaim the hazardous secondary materials generated during this manufacture. On behalf of [insert tolling contractor name], I also certify that [insert tolling contractor name] retains ownership of, and responsibility for, the hazardous secondary materials that are generated during the course of the manufacture, including any releases of hazardous secondary materials that occur during the manufacturing process”. The tolling contractor must maintain at its facility for no less than three years records of hazardous secondary materials received pursuant to its written contract with

§ 261.4

40 CFR Ch. I (7–1–18 Edition)

the tolling manufacturer, and the tolling manufacturer must maintain at its facility for no less than three years records of hazardous secondary materials shipped pursuant to its written contract with the tolling contractor. In both cases, the records must contain the name of the transporter, the date of the shipment, and the type and quantity of the hazardous secondary material shipped or received pursuant to the written contract. These requirements may be satisfied by routine business records (*e.g.*, financial records, bills of lading, copies of DOT shipping papers, or electronic confirmations). For purposes of this paragraph, tolling contractor means a person who arranges for the production of a product or intermediate made from specified unused materials through a written contract with a toll manufacturer. Toll manufacturer means a person who produces a product or intermediate made from specified unused materials pursuant to a written contract with a tolling contractor.

(ii)(A) The hazardous secondary material is contained as defined in § 260.10 of this chapter. A hazardous secondary material released to the environment is discarded and a solid waste unless it is immediately recovered for the purpose of reclamation. Hazardous secondary material managed in a unit with leaks or other continuing or intermittent unpermitted releases is discarded and a solid waste.

(B) The hazardous secondary material is not speculatively accumulated, as defined in § 261.1(c)(8).

(C) Notice is provided as required by § 260.42 of this chapter.

(D) The material is not otherwise subject to material-specific management conditions under paragraph (a) of this section when reclaimed, and it is not a spent lead-acid battery (see §§ 266.80 and 273.2 of this chapter).

(E) Persons performing the recycling of hazardous secondary materials under this exclusion must maintain documentation of their legitimacy determination on-site. Documentation must be a written description of how the recycling meets all three factors in § 260.43(a) and how the factor in § 260.43(b) was considered. Documentation must be maintained for three

years after the recycling operation has ceased.

(F) The emergency preparedness and response requirements found in subpart M of this part are met.

(24) Hazardous secondary material that is generated and then transferred to another person for the purpose of reclamation is not a solid waste, provided that:

(i) The material is not speculatively accumulated, as defined in § 261.1(c)(8);

(ii) The material is not handled by any person or facility other than the hazardous secondary material generator, the transporter, an intermediate facility or a reclaimer, and, while in transport, is not stored for more than 10 days at a transfer facility, as defined in § 260.10 of this chapter, and is packaged according to applicable Department of Transportation regulations at 49 CFR parts 173, 178, and 179 while in transport;

(iii) The material is not otherwise subject to material-specific management conditions under paragraph (a) of this section when reclaimed, and it is not a spent lead-acid battery (see §§ 266.80 and 273.2 of this chapter);

(iv) The reclamation of the material is legitimate, as specified under § 260.43 of this chapter;

(v) The hazardous secondary material generator satisfies all of the following conditions:

(A) The material must be contained as defined in § 260.10. A hazardous secondary material released to the environment is discarded and a solid waste unless it is immediately recovered for the purpose of recycling. Hazardous secondary material managed in a unit with leaks or other continuing releases is discarded and a solid waste.

(B) Prior to arranging for transport of hazardous secondary materials to a reclamation facility (or facilities) where the management of the hazardous secondary materials is not addressed under a RCRA part B permit or interim status standards, the hazardous secondary material generator must make reasonable efforts to ensure that each reclaimer intends to properly and legitimately reclaim the hazardous secondary material and not discard it, and that each reclaimer will manage the hazardous secondary material in a

manner that is protective of human health and the environment. If the hazardous secondary material will be passing through an intermediate facility where the management of the hazardous secondary materials is not addressed under a RCRA part B permit or interim status standards, the hazardous secondary material generator must make contractual arrangements with the intermediate facility to ensure that the hazardous secondary material is sent to the reclamation facility identified by the hazardous secondary material generator, and the hazardous secondary material generator must perform reasonable efforts to ensure that the intermediate facility will manage the hazardous secondary material in a manner that is protective of human health and the environment. Reasonable efforts must be repeated at a minimum of every three years for the hazardous secondary material generator to claim the exclusion and to send the hazardous secondary materials to each reclaimer and any intermediate facility. In making these reasonable efforts, the generator may use any credible evidence available, including information gathered by the hazardous secondary material generator, provided by the reclaimer or intermediate facility, and/or provided by a third party. The hazardous secondary material generator must affirmatively answer all of the following questions for each reclamation facility and any intermediate facility:

(1) Does the available information indicate that the reclamation process is legitimate pursuant to §260.43 of this chapter? In answering this question, the hazardous secondary material generator can rely on their existing knowledge of the physical and chemical properties of the hazardous secondary material, as well as information from other sources (*e.g.*, the reclamation facility, audit reports, etc.) about the reclamation process.

(2) Does the publicly available information indicate that the reclamation facility and any intermediate facility that is used by the hazardous secondary material generator notified the appropriate authorities of hazardous secondary materials reclamation activities pursuant to §260.42 of this

chapter and have they notified the appropriate authorities that the financial assurance condition is satisfied per paragraph (a)(24)(vi)(F) of this section? In answering these questions, the hazardous secondary material generator can rely on the available information documenting the reclamation facility's and any intermediate facility's compliance with the notification requirements per §260.42 of this chapter, including the requirement in §260.42(a)(5) to notify EPA whether the reclaimer or intermediate facility has financial assurance.

(3) Does publicly available information indicate that the reclamation facility or any intermediate facility that is used by the hazardous secondary material generator has not had any formal enforcement actions taken against the facility in the previous three years for violations of the RCRA hazardous waste regulations and has not been classified as a significant non-complier with RCRA Subtitle C? In answering this question, the hazardous secondary material generator can rely on the publicly available information from EPA or the state. If the reclamation facility or any intermediate facility that is used by the hazardous secondary material generator has had a formal enforcement action taken against the facility in the previous three years for violations of the RCRA hazardous waste regulations and has been classified as a significant non-complier with RCRA Subtitle C, does the hazardous secondary material generator have credible evidence that the facilities will manage the hazardous secondary materials properly? In answering this question, the hazardous secondary material generator can obtain additional information from EPA, the state, or the facility itself that the facility has addressed the violations, taken remedial steps to address the violations and prevent future violations, or that the violations are not relevant to the proper management of the hazardous secondary materials.

(4) Does the available information indicate that the reclamation facility and any intermediate facility that is used by the hazardous secondary material generator have the equipment and trained personnel to safely recycle the

§261.4

40 CFR Ch. I (7-1-18 Edition)

hazardous secondary material? In answering this question, the generator may rely on a description by the reclamation facility or by an independent third party of the equipment and trained personnel to be used to recycle the generator's hazardous secondary material.

(5) If residuals are generated from the reclamation of the excluded hazardous secondary materials, does the reclamation facility have the permits required (if any) to manage the residuals? If not, does the reclamation facility have a contract with an appropriately permitted facility to dispose of the residuals? If not, does the hazardous secondary material generator have credible evidence that the residuals will be managed in a manner that is protective of human health and the environment? In answering these questions, the hazardous secondary material generator can rely on publicly available information from EPA or the state, or information provided by the facility itself.

(C) The hazardous secondary material generator must maintain for a minimum of three years documentation and certification that reasonable efforts were made for each reclamation facility and, if applicable, intermediate facility where the management of the hazardous secondary materials is not addressed under a RCRA part B permit or interim status standards prior to transferring hazardous secondary material. Documentation and certification must be made available upon request by a regulatory authority within 72 hours, or within a longer period of time as specified by the regulatory authority. The certification statement must:

(1) Include the printed name and official title of an authorized representative of the hazardous secondary material generator company, the authorized representative's signature, and the date signed;

(2) Incorporate the following language: "I hereby certify in good faith and to the best of my knowledge that, prior to arranging for transport of excluded hazardous secondary materials to [insert name(s) of reclamation facility and any intermediate facility], reasonable efforts were made in accordance with §261.4(a)(24)(v)(B) to ensure

that the hazardous secondary materials would be recycled legitimately, and otherwise managed in a manner that is protective of human health and the environment, and that such efforts were based on current and accurate information."

(D) The hazardous secondary material generator must maintain at the generating facility for no less than three (3) years records of all off-site shipments of hazardous secondary materials. For each shipment, these records must, at a minimum, contain the following information:

(1) Name of the transporter and date of the shipment;

(2) Name and address of each reclaimer and, if applicable, the name and address of each intermediate facility to which the hazardous secondary material was sent;

(3) The type and quantity of hazardous secondary material in the shipment.

(E) The hazardous secondary material generator must maintain at the generating facility for no less than three (3) years confirmations of receipt from each reclaimer and, if applicable, each intermediate facility for all off-site shipments of hazardous secondary materials. Confirmations of receipt must include the name and address of the reclaimer (or intermediate facility), the type and quantity of the hazardous secondary materials received and the date which the hazardous secondary materials were received. This requirement may be satisfied by routine business records (e.g., financial records, bills of lading, copies of DOT shipping papers, or electronic confirmations of receipt);

(F) The hazardous secondary material generator must comply with the emergency preparedness and response conditions in subpart M of this part.

(vi) Reclaimers of hazardous secondary material excluded from regulation under this exclusion and intermediate facilities as defined in §260.10 of this chapter satisfy all of the following conditions:

(A) The reclaimer and intermediate facility must maintain at its facility for no less than three (3) years records of all shipments of hazardous secondary material that were received at

Environmental Protection Agency

§ 261.4

the facility and, if applicable, for all shipments of hazardous secondary materials that were received and subsequently sent off-site from the facility for further reclamation. For each shipment, these records must at a minimum contain the following information:

(1) Name of the transporter and date of the shipment;

(2) Name and address of the hazardous secondary material generator and, if applicable, the name and address of the reclaimer or intermediate facility which the hazardous secondary materials were received from;

(3) The type and quantity of hazardous secondary material in the shipment; and

(4) For hazardous secondary materials that, after being received by the reclaimer or intermediate facility, were subsequently transferred off-site for further reclamation, the name and address of the (subsequent) reclaimer and, if applicable, the name and address of each intermediate facility to which the hazardous secondary material was sent.

(B) The intermediate facility must send the hazardous secondary material to the reclaimer(s) designated by the hazardous secondary materials generator.

(C) The reclaimer and intermediate facility must send to the hazardous secondary material generator confirmations of receipt for all off-site shipments of hazardous secondary materials. Confirmations of receipt must include the name and address of the reclaimer (or intermediate facility), the type and quantity of the hazardous secondary materials received and the date which the hazardous secondary materials were received. This requirement may be satisfied by routine business records (*e.g.*, financial records, bills of lading, copies of DOT shipping papers, or electronic confirmations of receipt).

(D) The reclaimer and intermediate facility must manage the hazardous secondary material in a manner that is at least as protective as that employed for analogous raw material and must be contained. An "analogous raw material" is a raw material for which a hazardous secondary material is a substitute and serves the same function

and has similar physical and chemical properties as the hazardous secondary material.

(E) Any residuals that are generated from reclamation processes will be managed in a manner that is protective of human health and the environment. If any residuals exhibit a hazardous characteristic according to subpart C of 40 CFR part 261, or if they themselves are specifically listed in subpart D of 40 CFR part 261, such residuals are hazardous wastes and must be managed in accordance with the applicable requirements of 40 CFR parts 260 through 272.

(F) The reclaimer and intermediate facility have financial assurance as required under subpart H of 40 CFR part 261.

(vii) In addition, all persons claiming the exclusion under this paragraph (a)(24) of this section must provide notification as required under § 260.42 of this chapter.

(25) Hazardous secondary material that is exported from the United States and reclaimed at a reclamation facility located in a foreign country is not a solid waste, provided that the hazardous secondary material generator complies with the applicable requirements of paragraph (a)(24)(i)-(v) of this section (excepting paragraph (a)(24)(v)(B)(2) of this section for foreign reclaimers and foreign intermediate facilities), and that the hazardous secondary material generator also complies with the following requirements:

(i) Notify EPA of an intended export before the hazardous secondary material is scheduled to leave the United States. A complete notification must be submitted at least sixty (60) days before the initial shipment is intended to be shipped off-site. This notification may cover export activities extending over a twelve (12) month or lesser period. The notification must be in writing, signed by the hazardous secondary material generator, and include the following information:

(A) Name, mailing address, telephone number and EPA ID number (if applicable) of the hazardous secondary material generator;

§ 261.4

40 CFR Ch. I (7-1-18 Edition)

(B) A description of the hazardous secondary material and the EPA hazardous waste number that would apply if the hazardous secondary material was managed as hazardous waste and the U.S. DOT proper shipping name, hazard class and ID number (UN/NA) for each hazardous secondary material as identified in 49 CFR parts 171 through 177;

(C) The estimated frequency or rate at which the hazardous secondary material is to be exported and the period of time over which the hazardous secondary material is to be exported;

(D) The estimated total quantity of hazardous secondary material;

(E) All points of entry to and departure from each foreign country through which the hazardous secondary material will pass;

(F) A description of the means by which each shipment of the hazardous secondary material will be transported (*e.g.*, mode of transportation vehicle (air, highway, rail, water, etc.), type(s) of container (drums, boxes, tanks, etc.));

(G) A description of the manner in which the hazardous secondary material will be reclaimed in the country of import;

(H) The name and address of the reclaimer, any intermediate facility and any alternate reclaimer and intermediate facilities; and

(I) The name of any countries of transit through which the hazardous secondary material will be sent and a description of the approximate length of time it will remain in such countries and the nature of its handling while there (for purposes of this section, the terms "EPA Acknowledgement of Consent", "country of import" and "country of transit" are used as defined in 40 CFR 262.81 with the exception that the terms in this section refer to hazardous secondary materials, rather than hazardous waste);

(ii) Notifications must be submitted electronically using EPA's Waste Import Export Tracking System (WIETS), or its successor system.

(iii) Except for changes to the telephone number in paragraph (a)(25)(i)(A) of this section and decreases in the quantity of hazardous secondary material indicated pursuant to paragraph

(a)(25)(i)(D) of this section, when the conditions specified on the original notification change (including any exceedance of the estimate of the quantity of hazardous secondary material specified in the original notification), the hazardous secondary material generator must provide EPA with a written renotification of the change. The shipment cannot take place until consent of the country of import to the changes (except for changes to paragraph (a)(25)(i)(I) of this section and in the ports of entry to and departure from countries of transit pursuant to paragraphs (a)(25)(i)(E) of this section) has been obtained and the hazardous secondary material generator receives from EPA an EPA Acknowledgment of Consent reflecting the country of import's consent to the changes.

(iv) Upon request by EPA, the hazardous secondary material generator shall furnish to EPA any additional information which a country of import requests in order to respond to a notification.

(v) EPA will provide a complete notification to the country of import and any countries of transit. A notification is complete when EPA receives a notification which EPA determines satisfies the requirements of paragraph (a)(25)(i) of this section. Where a claim of confidentiality is asserted with respect to any notification information required by paragraph (a)(25)(i) of this section, EPA may find the notification not complete until any such claim is resolved in accordance with 40 CFR 260.2.

(vi) The export of hazardous secondary material under this paragraph (a)(25) is prohibited unless the country of import consents to the intended export. When the country of import consents in writing to the receipt of the hazardous secondary material, EPA will send an EPA Acknowledgment of Consent to the hazardous secondary material generator. Where the country of import objects to receipt of the hazardous secondary material or withdraws a prior consent, EPA will notify the hazardous secondary material generator in writing. EPA will also notify the hazardous secondary material generator of any responses from countries of transit.

Environmental Protection Agency

§261.4

(vii) For exports to OECD Member countries, the receiving country may respond to the notification using tacit consent. If no objection has been lodged by any country of import or countries of transit to a notification provided pursuant to paragraph (a)(25)(i) of this section within thirty (30) days after the date of issuance of the acknowledgement of receipt of notification by the competent authority of the country of import, the transboundary movement may commence. In such cases, EPA will send an EPA Acknowledgment of Consent to inform the hazardous secondary material generator that the country of import and any relevant countries of transit have not objected to the shipment, and are thus presumed to have consented tacitly. Tacit consent expires one (1) calendar year after the close of the thirty (30) day period; renotification and renewal of all consents is required for exports after that date.

(viii) A copy of the EPA Acknowledgment of Consent must accompany the shipment. The shipment must conform to the terms of the EPA Acknowledgment of Consent.

(ix) If a shipment cannot be delivered for any reason to the reclaimer, intermediate facility or the alternate reclaimer or alternate intermediate facility, the hazardous secondary material generator must re-notify EPA of a change in the conditions of the original notification to allow shipment to a new reclaimer in accordance with paragraph (iii) of this section and obtain another EPA Acknowledgment of Consent.

(x) Hazardous secondary material generators must keep a copy of each notification of intent to export and each EPA Acknowledgment of Consent for a period of three years following receipt of the EPA Acknowledgment of Consent. They may satisfy this record-keeping requirement by retaining electronically submitted notifications or electronically generated Acknowledgments in their account on EPA's Waste Import Export Tracking System (WIETS), or its successor system, provided that such copies are readily available for viewing and production if requested by any EPA or authorized state inspector. No hazardous sec-

ondary material generator may be held liable for the inability to produce a notification or Acknowledgment for inspection under this section if they can demonstrate that the inability to produce such copies are due exclusively to technical difficulty with EPA's Waste Import Export Tracking System (WIETS), or its successor system for which the hazardous secondary material generator bears no responsibility.

(xi) Hazardous secondary material generators must file with the Administrator no later than March 1 of each year, a report summarizing the types, quantities, frequency and ultimate destination of all hazardous secondary materials exported during the previous calendar year. Annual reports must be submitted electronically using EPA's Waste Import Export Tracking System (WIETS), or its successor system. Such reports must include the following information:

(A) Name, mailing and site address, and EPA ID number (if applicable) of the hazardous secondary material generator;

(B) The calendar year covered by the report;

(C) The name and site address of each reclaimer and intermediate facility;

(D) By reclaimer and intermediate facility, for each hazardous secondary material exported, a description of the hazardous secondary material and the EPA hazardous waste number that would apply if the hazardous secondary material was managed as hazardous waste, the DOT hazard class, the name and U.S. EPA ID number (where applicable) for each transporter used, the total amount of hazardous secondary material shipped and the number of shipments pursuant to each notification;

(E) A certification signed by the hazardous secondary material generator which states: "I certify under penalty of law that I have personally examined and am familiar with the information submitted in this and all attached documents, and that based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant

§ 261.4

40 CFR Ch. I (7-1-18 Edition)

penalties for submitting false information including the possibility of fine and imprisonment.”

(xii) All persons claiming an exclusion under this paragraph (a)(25) must provide notification as required by § 260.42 of this chapter.

(26) Solvent-contaminated wipes that are sent for cleaning and reuse are not solid wastes from the point of generation, provided that

(i) The solvent-contaminated wipes, when accumulated, stored, and transported, are contained in non-leaking, closed containers that are labeled “Excluded Solvent-Contaminated Wipes.” The containers must be able to contain free liquids, should free liquids occur. During accumulation, a container is considered closed when there is complete contact between the fitted lid and the rim, except when it is necessary to add or remove solvent-contaminated wipes. When the container is full, or when the solvent-contaminated wipes are no longer being accumulated, or when the container is being transported, the container must be sealed with all lids properly and securely affixed to the container and all openings tightly bound or closed sufficiently to prevent leaks and emissions;

(ii) The solvent-contaminated wipes may be accumulated by the generator for up to 180 days from the start date of accumulation for each container prior to being sent for cleaning;

(iii) At the point of being sent for cleaning on-site or at the point of being transported off-site for cleaning, the solvent-contaminated wipes must contain no free liquids as defined in § 260.10 of this chapter.

(iv) Free liquids removed from the solvent-contaminated wipes or from the container holding the wipes must be managed according to the applicable regulations found in 40 CFR parts 260 through 273;

(v) Generators must maintain at their site the following documentation:

(A) Name and address of the laundry or dry cleaner that is receiving the solvent-contaminated wipes;

(B) Documentation that the 180-day accumulation time limit in 40 CFR 261.4(a)(26)(ii) is being met;

(C) Description of the process the generator is using to ensure the sol-

vent-contaminated wipes contain no free liquids at the point of being laundered or dry cleaned on-site or at the point of being transported off-site for laundering or dry cleaning;

(vi) The solvent-contaminated wipes are sent to a laundry or dry cleaner whose discharge, if any, is regulated under sections 301 and 402 or section 307 of the Clean Water Act.

(27) Hazardous secondary material that is generated and then transferred to another person for the purpose of remanufacturing is not a solid waste, provided that:

(i) The hazardous secondary material consists of one or more of the following spent solvents: Toluene, xylenes, ethylbenzene, 1,2,4-trimethylbenzene, chlorobenzene, n-hexane, cyclohexane, methyl tert-butyl ether, acetonitrile, chloroform, chloromethane, dichloromethane, methyl isobutyl ketone, NN-dimethylformamide, tetrahydrofuran, n-butyl alcohol, ethanol, and/or methanol;

(ii) The hazardous secondary material originated from using one or more of the solvents listed in paragraph (a)(27)(i) of this section in a commercial grade for reacting, extracting, purifying, or blending chemicals (or for rinsing out the process lines associated with these functions) in the pharmaceutical manufacturing (NAICS 325412), basic organic chemical manufacturing (NAICS 325199), plastics and resins manufacturing (NAICS 325211), and/or the paints and coatings manufacturing sectors (NAICS 325510).

(iii) The hazardous secondary material generator sends the hazardous secondary material spent solvents listed in paragraph (a)(27)(i) of this section to a remanufacturer in the pharmaceutical manufacturing (NAICS 325412), basic organic chemical manufacturing (NAICS 325199), plastics and resins manufacturing (NAICS 325211), and/or the paints and coatings manufacturing sectors (NAICS 325510).

(iv) After remanufacturing one or more of the solvents listed in paragraph (a)(27)(i) of this section, the use of the remanufactured solvent shall be limited to reacting, extracting, purifying, or blending chemicals (or for rinsing out the process lines associated

with these functions) in the pharmaceutical manufacturing (NAICS 325412), basic organic chemical manufacturing (NAICS 325199), plastics and resins manufacturing (NAICS 325211), and the paints and coatings manufacturing sectors (NAICS 325510) or to using them as ingredients in a product. These allowed uses correspond to chemical functional uses enumerated under the Chemical Data Reporting Rule of the Toxic Substances Control Act (40 CFR parts 704, 710–711), including Industrial Function Codes U015 (solvents consumed in a reaction to produce other chemicals) and U030 (solvents become part of the mixture);

(v) After remanufacturing one or more of the solvents listed in paragraph (a)(27)(i) of this section, the use of the remanufactured solvent does not involve cleaning or degreasing oil, grease, or similar material from textiles, glassware, metal surfaces, or other articles. (These disallowed continuing uses correspond to chemical functional uses in Industrial Function Code U029 under the Chemical Data Reporting Rule of the Toxics Substances Control Act.); and

(vi) Both the hazardous secondary material generator and the remanufacturer must:

(A) Notify EPA or the State Director, if the state is authorized for the program, and update the notification every two years per 40 CFR 260.42;

(B) Develop and maintain an up-to-date remanufacturing plan which identifies:

(1) The name, address and EPA ID number of the generator(s) and the remanufacturer(s),

(2) The types and estimated annual volumes of spent solvents to be remanufactured,

(3) The processes and industry sectors that generate the spent solvents,

(4) The specific uses and industry sectors for the remanufactured solvents, and

(5) A certification from the remanufacturer stating “on behalf of [insert remanufacturer facility name], I certify that this facility is a remanufacturer under pharmaceutical manufacturing (NAICS 325412), basic organic chemical manufacturing (NAICS 325199), plastics and resins manufac-

turing (NAICS 325211), and/or the paints and coatings manufacturing sectors (NAICS 325510), and will accept the spent solvent(s) for the sole purpose of remanufacturing into commercial-grade solvent(s) that will be used for reacting, extracting, purifying, or blending chemicals (or for rinsing out the process lines associated with these functions) or for use as product ingredient(s). I also certify that the remanufacturing equipment, vents, and tanks are equipped with and are operating air emission controls in compliance with the appropriate Clean Air Act regulations under 40 CFR part 60, part 61 or part 63, or, absent such Clean Air Act standards for the particular operation or piece of equipment covered by the remanufacturing exclusion, are in compliance with the appropriate standards in 40 CFR part 261, subparts AA (vents), BB (equipment) and CC (tank storage).”;

(C) Maintain records of shipments and confirmations of receipts for a period of three years from the dates of the shipments;

(D) Prior to remanufacturing, store the hazardous spent solvents in tanks or containers that meet technical standards found in subparts I and J of 40 CFR part 261, with the tanks and containers being labeled or otherwise having an immediately available record of the material being stored;

(E) During remanufacturing, and during storage of the hazardous secondary materials prior to remanufacturing, the remanufacturer certifies that the remanufacturing equipment, vents, and tanks are equipped with and are operating air emission controls in compliance with the appropriate Clean Air Act regulations under 40 CFR part 60, part 61 or part 63; or, absent such Clean Air Act standards for the particular operation or piece of equipment covered by the remanufacturing exclusion, are in compliance with the appropriate standards in 40 CFR part 261 subparts AA (vents), BB (equipment) and CC (tank storage); and

(F) Meet the requirements prohibiting speculative accumulation per 40 CFR 261.1(c)(8).

(b) *Solid wastes which are not hazardous wastes.* The following solid wastes are not hazardous wastes:

§261.4

40 CFR Ch. I (7-1-18 Edition)

(1) Household waste, including household waste that has been collected, transported, stored, treated, disposed, recovered (e.g., refuse-derived fuel) or reused. "Household waste" means any material (including garbage, trash and sanitary wastes in septic tanks) derived from households (including single and multiple residences, hotels and motels, bunkhouses, ranger stations, crew quarters, campgrounds, picnic grounds and day-use recreation areas). A resource recovery facility managing municipal solid waste shall not be deemed to be treating, storing, disposing of, or otherwise managing hazardous wastes for the purposes of regulation under this subtitle, if such facility:

(i) Receives and burns only

(A) Household waste (from single and multiple dwellings, hotels, motels, and other residential sources) and

(B) Solid waste from commercial or industrial sources that does not contain hazardous waste; and

(ii) Such facility does not accept hazardous wastes and the owner or operator of such facility has established contractual requirements or other appropriate notification or inspection procedures to assure that hazardous wastes are not received at or burned in such facility.

(2) Solid wastes generated by any of the following and which are returned to the soils as fertilizers:

(i) The growing and harvesting of agricultural crops.

(ii) The raising of animals, including animal manures.

(3) Mining overburden returned to the mine site.

(4)(i) Fly ash waste, bottom ash waste, slag waste, and flue gas emission control waste generated primarily from the combustion of coal or other fossil fuels, except as provided by §266.112 of this chapter for facilities that burn or process hazardous waste.

(ii) The following wastes generated primarily from processes that support the combustion of coal or other fossil fuels that are co-disposed with the wastes in paragraph (b)(4)(i) of this section, except as provided by §266.112 of this chapter for facilities that burn or process hazardous waste:

(A) *Coal pile run-off.* For purposes of paragraph (b)(4) of this section, coal pile run-off means any precipitation that drains off coal piles.

(B) *Boiler cleaning solutions.* For purposes of paragraph (b)(4) of this section, boiler cleaning solutions means water solutions and chemical solutions used to clean the fire-side and water-side of the boiler.

(C) *Boiler blowdown.* For purposes of paragraph (b)(4) of this section, boiler blowdown means water purged from boilers used to generate steam.

(D) *Process water treatment and demineralizer regeneration wastes.* For purposes of paragraph (b)(4) of this section, process water treatment and demineralizer regeneration wastes means sludges, rinses, and spent resins generated from processes to remove dissolved gases, suspended solids, and dissolved chemical salts from combustion system process water.

(E) *Cooling tower blowdown.* For purposes of paragraph (b)(4) of this section, cooling tower blowdown means water purged from a closed cycle cooling system. Closed cycle cooling systems include cooling towers, cooling ponds, or spray canals.

(F) *Air heater and precipitator washes.* For purposes of paragraph (b)(4) of this section, air heater and precipitator washes means wastes from cleaning air preheaters and electrostatic precipitators.

(G) *Effluents from floor and yard drains and sumps.* For purposes of paragraph (b)(4) of this section, effluents from floor and yard drains and sumps means wastewaters, such as wash water, collected by or from floor drains, equipment drains, and sumps located inside the power plant building; and wastewaters, such as rain runoff, collected by yard drains and sumps located outside the power plant building.

(H) *Wastewater treatment sludges.* For purposes of paragraph (b)(4) of this section, wastewater treatment sludges refers to sludges generated from the treatment of wastewaters specified in paragraphs (b)(4)(ii)(A) through (F) of this section.

(5) Drilling fluids, produced waters, and other wastes associated with the

Environmental Protection Agency

§ 261.4

exploration, development, or production of crude oil, natural gas or geothermal energy.

(6)(i) Wastes which fail the test for the Toxicity Characteristic because chromium is present or are listed in subpart D due to the presence of chromium, which do not fail the test for the Toxicity Characteristic for any other constituent or are not listed due to the presence of any other constituent, and which do not fail the test for any other characteristic, if it is shown by a waste generator or by waste generators that:

(A) The chromium in the waste is exclusively (or nearly exclusively) trivalent chromium; and

(B) The waste is generated from an industrial process which uses trivalent chromium exclusively (or nearly exclusively) and the process does not generate hexavalent chromium; and

(C) The waste is typically and frequently managed in non-oxidizing environments.

(ii) Specific wastes which meet the standard in paragraphs (b)(6)(i) (A), (B), and (C) (so long as they do not fail the test for the toxicity characteristic for any other constituent, and do not exhibit any other characteristic) are:

(A) Chrome (blue) trimmings generated by the following subcategories of the leather tanning and finishing industry: hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearling.

(B) Chrome (blue) shavings generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearling.

(C) Buffing dust generated by the following subcategories of the leather tanning and finishing industry: hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue.

(D) Sewer screenings generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish;

retan/wet finish; no beamhouse; through-the-blue; and shearling.

(E) Wastewater treatment sludges generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearling.

(F) Wastewater treatment sludges generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; and through-the-blue.

(G) Waste scrap leather from the leather tanning industry, the shoe manufacturing industry, and other leather product manufacturing industries.

(H) Wastewater treatment sludges from the production of TiO_2 pigment using chromium-bearing ores by the chloride process.

(7) Solid waste from the extraction, beneficiation, and processing of ores and minerals (including coal, phosphate rock, and overburden from the mining of uranium ore), except as provided by § 266.112 of this chapter for facilities that burn or process hazardous waste.

(i) For purposes of § 261.4(b)(7) beneficiation of ores and minerals is restricted to the following activities: crushing; grinding; washing; dissolution; crystallization; filtration; sorting; sizing; drying; sintering; pelletizing; briquetting; calcining to remove water and/or carbon dioxide; roasting, autoclaving, and/or chlorination in preparation for leaching (except where the roasting (and/or autoclaving and/or chlorination)/leaching sequence produces a final or intermediate product that does not undergo further beneficiation or processing); gravity concentration; magnetic separation; electrostatic separation; flotation; ion exchange; solvent extraction; electrowinning; precipitation; amalgamation; and heap, dump, vat, tank, and in situ leaching.

(ii) For the purposes of § 261.4(b)(7), solid waste from the processing of ores and minerals includes only the following wastes as generated:

§ 261.4

40 CFR Ch. I (7-1-18 Edition)

(A) Slag from primary copper processing;

(B) Slag from primary lead processing;

(C) Red and brown muds from bauxite refining;

(D) Phosphogypsum from phosphoric acid production;

(E) Slag from elemental phosphorus production;

(F) Gasifier ash from coal gasification;

(G) Process wastewater from coal gasification;

(H) Calcium sulfate wastewater treatment plant sludge from primary copper processing;

(I) Slag tailings from primary copper processing;

(J) Fluorogypsum from hydrofluoric acid production;

(K) Process wastewater from hydrofluoric acid production;

(L) Air pollution control dust/sludge from iron blast furnaces;

(M) Iron blast furnace slag;

(N) Treated residue from roasting/leaching of chrome ore;

(O) Process wastewater from primary magnesium processing by the anhydrous process;

(P) Process wastewater from phosphoric acid production;

(Q) Basic oxygen furnace and open hearth furnace air pollution control dust/sludge from carbon steel production;

(R) Basic oxygen furnace and open hearth furnace slag from carbon steel production;

(S) Chloride process waste solids from titanium tetrachloride production;

(T) Slag from primary zinc processing.

(iii) A residue derived from co-processing mineral processing secondary materials with normal beneficiation raw materials or with normal mineral processing raw materials remains excluded under paragraph (b) of this section if the owner or operator:

(A) Processes at least 50 percent by weight normal beneficiation raw materials or normal mineral processing raw materials; and,

(B) Legitimately reclaims the secondary mineral processing materials.

(8) Cement kiln dust waste, except as provided by § 266.112 of this chapter for facilities that burn or process hazardous waste.

(9) Solid waste which consists of discarded arsenical-treated wood or wood products which fails the test for the Toxicity Characteristic for Hazardous Waste Codes D004 through D017 and which is not a hazardous waste for any other reason if the waste is generated by persons who utilize the arsenical-treated wood and wood products for these materials' intended end use.

(10) Petroleum-contaminated media and debris that fail the test for the Toxicity Characteristic of § 261.24 (Hazardous Waste Codes D018 through D043 only) and are subject to the corrective action regulations under part 280 of this chapter.

(11) Injected groundwater that is hazardous only because it exhibits the Toxicity Characteristic (Hazardous Waste Codes D018 through D043 only) in § 261.24 of this part that is reinjected through an underground injection well pursuant to free phase hydrocarbon recovery operations undertaken at petroleum refineries, petroleum marketing terminals, petroleum bulk plants, petroleum pipelines, and petroleum transportation spill sites until January 25, 1993. This extension applies to recovery operations in existence, or for which contracts have been issued, on or before March 25, 1991. For groundwater returned through infiltration galleries from such operations at petroleum refineries, marketing terminals, and bulk plants, until [insert date six months after publication]. New operations involving injection wells (beginning after March 25, 1991) will qualify for this compliance date extension (until January 25, 1993) only if:

(i) Operations are performed pursuant to a written state agreement that includes a provision to assess the groundwater and the need for further remediation once the free phase recovery is completed; and

(ii) A copy of the written agreement has been submitted to: Waste Identification Branch (5304), U.S. Environmental Protection Agency, 1200 Pennsylvania Ave., NW., Washington, DC 20460.

Environmental Protection Agency

§ 261.4

(12) Used chlorofluorocarbon refrigerants from totally enclosed heat transfer equipment, including mobile air conditioning systems, mobile refrigeration, and commercial and industrial air conditioning and refrigeration systems that use chlorofluorocarbons as the heat transfer fluid in a refrigeration cycle, provided the refrigerant is reclaimed for further use.

(13) Non-terne plated used oil filters that are not mixed with wastes listed in subpart D of this part if these oil filters have been gravity hot-drained using one of the following methods:

(i) Puncturing the filter anti-drain back valve or the filter dome end and hot-draining;

(ii) Hot-draining and crushing;

(iii) Dismantling and hot-draining; or

(iv) Any other equivalent hot-draining method that will remove used oil.

(14) Used oil re-refining distillation bottoms that are used as feedstock to manufacture asphalt products.

(15) Leachate or gas condensate collected from landfills where certain solid wastes have been disposed, provided that:

(i) The solid wastes disposed would meet one or more of the listing descriptions for Hazardous Waste Codes K169, K170, K171, K172, K174, K175, K176, K177, K178 and K181 if these wastes had been generated after the effective date of the listing;

(ii) The solid wastes described in paragraph (b)(15)(i) of this section were disposed prior to the effective date of the listing;

(iii) The leachate or gas condensate do not exhibit any characteristic of hazardous waste nor are derived from any other listed hazardous waste;

(iv) Discharge of the leachate or gas condensate, including leachate or gas condensate transferred from the landfill to a POTW by truck, rail, or dedicated pipe, is subject to regulation under sections 307(b) or 402 of the Clean Water Act.

(v) As of February 13, 2001, leachate or gas condensate derived from K169–K172 is no longer exempt if it is stored or managed in a surface impoundment prior to discharge. As of November 21, 2003, leachate or gas condensate derived from K176, K177, and K178 is no longer exempt if it is stored or man-

aged in a surface impoundment prior to discharge. After February 26, 2007, leachate or gas condensate derived from K181 will no longer be exempt if it is stored or managed in a surface impoundment prior to discharge. There is one exception: if the surface impoundment is used to temporarily store leachate or gas condensate in response to an emergency situation (e.g., shutdown of wastewater treatment system), provided the impoundment has a double liner, and provided the leachate or gas condensate is removed from the impoundment and continues to be managed in compliance with the conditions of this paragraph (b)(15)(v) after the emergency ends.

(16) [Reserved]

(17) Solid waste that would otherwise meet the definition of low-level mixed wastes (LLMW) pursuant to § 266.210 of this chapter that is generated at the Ortho-McNeil Pharmaceutical, Inc. (OMP Spring House) research and development facility in Spring House, Pennsylvania and treated on-site using a bench-scale high temperature catalytic oxidation unit is not a hazardous waste provided that:

(i) The total volume of LLMW generated and treated is no greater than 50 liters/year, (ii) OMP Spring House submits a written report to the EPA Region III office once every six months beginning six months after June 27, 2005, that must contain the following:

(A) Analysis demonstrating the destruction and removal efficiency of the treatment technology for all organic components of the wastestream,

(B) Analysis demonstrating the capture efficiencies of the treatment technology for all radioactive components of the wastestream and an estimate of the amount of radioactivity released during the reporting period,

(C) Analysis (including concentrations of constituents, including inorganic constituents, present and radioactivity) of the wastestream prior to and after treatment,

(D) Volume of the wastestream being treated per batch, as well as a total for the duration of the reporting period, and

(E) Final disposition of the radioactive residuals from the treatment of the wastestream.

§ 261.4

40 CFR Ch. I (7-1-18 Edition)

(iii) OMP Spring House makes no significant changes to the design or operation of the high temperature catalytic oxidation unit or the wastestream.

(iv) This exclusion will remain in effect for 5 years from June 27, 2005.

(18) Solvent-contaminated wipes, except for wipes that are hazardous waste due to the presence of trichloroethylene, that are sent for disposal are not hazardous wastes from the point of generation provided that

(i) The solvent-contaminated wipes, when accumulated, stored, and transported, are contained in non-leaking, closed containers that are labeled "Excluded Solvent-Contaminated Wipes." The containers must be able to contain free liquids, should free liquids occur. During accumulation, a container is considered closed when there is complete contact between the fitted lid and the rim, except when it is necessary to add or remove solvent-contaminated wipes. When the container is full, or when the solvent-contaminated wipes are no longer being accumulated, or when the container is being transported, the container must be sealed with all lids properly and securely affixed to the container and all openings tightly bound or closed sufficiently to prevent leaks and emissions;

(ii) The solvent-contaminated wipes may be accumulated by the generator for up to 180 days from the start date of accumulation for each container prior to being sent for disposal;

(iii) At the point of being transported for disposal, the solvent-contaminated wipes must contain no free liquids as defined in § 260.10 of this chapter.

(iv) Free liquids removed from the solvent-contaminated wipes or from the container holding the wipes must be managed according to the applicable regulations found in 40 CFR parts 260 through 273;

(v) Generators must maintain at their site the following documentation:

(A) Name and address of the landfill or combustor that is receiving the solvent-contaminated wipes;

(B) Documentation that the 180 day accumulation time limit in 40 CFR 261.4(b)(18)(ii) is being met;

(C) Description of the process the generator is using to ensure solvent-contaminated wipes contain no free

liquids at the point of being transported for disposal;

(vi) The solvent-contaminated wipes are sent for disposal

(A) To a municipal solid waste landfill regulated under 40 CFR part 258, including 40 CFR 258.40, or to a hazardous waste landfill regulated under 40 CFR parts 264 or 265; or

(B) To a municipal waste combustor or other combustion facility regulated under section 129 of the Clean Air Act or to a hazardous waste combustor, boiler, or industrial furnace regulated under 40 CFR parts 264, 265, or 266 subpart H.

(c) Hazardous wastes which are exempted from certain regulations. A hazardous waste which is generated in a product or raw material storage tank, a product or raw material transport vehicle or vessel, a product or raw material pipeline, or in a manufacturing process unit or an associated non-waste-treatment-manufacturing unit, is not subject to regulation under parts 262 through 265, 268, 270, 271 and 124 of this chapter or to the notification requirements of section 3010 of RCRA until it exits the unit in which it was generated, unless the unit is a surface impoundment, or unless the hazardous waste remains in the unit more than 90 days after the unit ceases to be operated for manufacturing, or for storage or transportation of product or raw materials.

(d) *Samples.* (1) Except as provided in paragraphs (d)(2) and (4) of this section, a sample of solid waste or a sample of water, soil, or air, which is collected for the sole purpose of testing to determine its characteristics or composition, is not subject to any requirements of this part or parts 262 through 268 or part 270 or part 124 of this chapter or to the notification requirements of section 3010 of RCRA, when:

(i) The sample is being transported to a laboratory for the purpose of testing; or

(ii) The sample is being transported back to the sample collector after testing; or

(iii) The sample is being stored by the sample collector before transport to a laboratory for testing; or

(iv) The sample is being stored in a laboratory before testing; or

Environmental Protection Agency

§ 261.4

(v) The sample is being stored in a laboratory after testing but before it is returned to the sample collector; or

(vi) The sample is being stored temporarily in the laboratory after testing for a specific purpose (for example, until conclusion of a court case or enforcement action where further testing of the sample may be necessary).

(2) In order to qualify for the exemption in paragraphs (d)(1) (i) and (ii) of this section, a sample collector shipping samples to a laboratory and a laboratory returning samples to a sample collector must:

(i) Comply with U.S. Department of Transportation (DOT), U.S. Postal Service (USPS), or any other applicable shipping requirements; or

(ii) Comply with the following requirements if the sample collector determines that DOT, USPS, or other shipping requirements do not apply to the shipment of the sample:

(A) Assure that the following information accompanies the sample:

(1) The sample collector's name, mailing address, and telephone number;

(2) The laboratory's name, mailing address, and telephone number;

(3) The quantity of the sample;

(4) The date of shipment; and

(5) A description of the sample.

(B) Package the sample so that it does not leak, spill, or vaporize from its packaging.

(3) This exemption does not apply if the laboratory determines that the waste is hazardous but the laboratory is no longer meeting any of the conditions stated in paragraph (d)(1) of this section.

(4) In order to qualify for the exemption in paragraphs (d)(1)(i) and (ii) of this section, the mass of a sample that will be exported to a foreign laboratory or that will be imported to a U.S. laboratory from a foreign source must additionally not exceed 25 kg.

(e) *Treatability Study Samples.* (1) Except as provided in paragraphs (e)(2) and (4) of this section, persons who generate or collect samples for the purpose of conducting treatability studies as defined in 40 CFR 260.10, are not subject to any requirement of 40 CFR parts 261 through 263 or to the notification requirements of Section 3010 of

RCRA, nor are such samples included in the quantity determinations of 40 CFR 261.5 and 262.34(d) when:

(i) The sample is being collected and prepared for transportation by the generator or sample collector; or

(ii) The sample is being accumulated or stored by the generator or sample collector prior to transportation to a laboratory or testing facility; or

(iii) The sample is being transported to the laboratory or testing facility for the purpose of conducting a treatability study.

(2) The exemption in paragraph (e)(1) of this section is applicable to samples of hazardous waste being collected and shipped for the purpose of conducting treatability studies provided that:

(i) The generator or sample collector uses (in "treatability studies") no more than 10,000 kg of media contaminated with non-acute hazardous waste, 1000 kg of non-acute hazardous waste other than contaminated media, 1 kg of acute hazardous waste, 2500 kg of media contaminated with acute hazardous waste for each process being evaluated for each generated waste stream; and

(ii) The mass of each sample shipment does not exceed 10,000 kg; the 10,000 kg quantity may be all media contaminated with non-acute hazardous waste, or may include 2500 kg of media contaminated with acute hazardous waste, 1000 kg of hazardous waste, and 1 kg of acute hazardous waste; and

(iii) The sample must be packaged so that it will not leak, spill, or vaporize from its packaging during shipment and the requirements of paragraph A or B of this subparagraph are met.

(A) The transportation of each sample shipment complies with U.S. Department of Transportation (DOT), U.S. Postal Service (USPS), or any other applicable shipping requirements; or

(B) If the DOT, USPS, or other shipping requirements do not apply to the shipment of the sample, the following information must accompany the sample:

(1) The name, mailing address, and telephone number of the originator of the sample;

§ 261.4

40 CFR Ch. I (7-1-18 Edition)

(2) The name, address, and telephone number of the facility that will perform the treatability study;

(3) The quantity of the sample;

(4) The date of shipment; and

(5) A description of the sample, including its EPA Hazardous Waste Number.

(iv) The sample is shipped to a laboratory or testing facility which is exempt under §261.4(f) or has an appropriate RCRA permit or interim status.

(v) The generator or sample collector maintains the following records for a period ending 3 years after completion of the treatability study:

(A) Copies of the shipping documents;

(B) A copy of the contract with the facility conducting the treatability study;

(C) Documentation showing:

(1) The amount of waste shipped under this exemption;

(2) The name, address, and EPA identification number of the laboratory or testing facility that received the waste;

(3) The date the shipment was made; and

(4) Whether or not unused samples and residues were returned to the generator.

(vi) The generator reports the information required under paragraph (e)(2)(v)(C) of this section in its biennial report.

(3) The Regional Administrator may grant requests on a case-by-case basis for up to an additional two years for treatability studies involving bioremediation. The Regional Administrator may grant requests on a case-by-case basis for quantity limits in excess of those specified in paragraphs (e)(2) (i) and (ii) and (f)(4) of this section, for up to an additional 5000 kg of media contaminated with non-acute hazardous waste, 500 kg of non-acute hazardous waste, 2500 kg of media contaminated with acute hazardous waste and 1 kg of acute hazardous waste:

(i) In response to requests for authorization to ship, store and conduct treatability studies on additional quantities in advance of commencing treatability studies. Factors to be considered in reviewing such requests include the nature of the technology, the type of process (e.g., batch versus contin-

uous), size of the unit undergoing testing (particularly in relation to scale-up considerations), the time/quantity of material required to reach steady state operating conditions, or test design considerations such as mass balance calculations.

(ii) In response to requests for authorization to ship, store and conduct treatability studies on additional quantities after initiation or completion of initial treatability studies, when: There has been an equipment or mechanical failure during the conduct of a treatability study; there is a need to verify the results of a previously conducted treatability study; there is a need to study and analyze alternative techniques within a previously evaluated treatment process; or there is a need to do further evaluation of an ongoing treatability study to determine final specifications for treatment.

(iii) The additional quantities and timeframes allowed in paragraph (e)(3) (i) and (ii) of this section are subject to all the provisions in paragraphs (e) (1) and (e)(2) (iii) through (vi) of this section. The generator or sample collector must apply to the Regional Administrator in the Region where the sample is collected and provide in writing the following information:

(A) The reason why the generator or sample collector requires additional time or quantity of sample for treatability study evaluation and the additional time or quantity needed;

(B) Documentation accounting for all samples of hazardous waste from the waste stream which have been sent for or undergone treatability studies including the date each previous sample from the waste stream was shipped, the quantity of each previous shipment, the laboratory or testing facility to which it was shipped, what treatability study processes were conducted on each sample shipped, and the available results on each treatability study;

(C) A description of the technical modifications or change in specifications which will be evaluated and the expected results;

(D) If such further study is being required due to equipment or mechanical failure, the applicant must include information regarding the reason for the failure or breakdown and also include

Environmental Protection Agency

§ 261.4

what procedures or equipment improvements have been made to protect against further breakdowns; and

(E) Such other information that the Regional Administrator considers necessary.

(4) In order to qualify for the exemption in paragraph (e)(1)(i) of this section, the mass of a sample that will be exported to a foreign laboratory or testing facility, or that will be imported to a U.S. laboratory or testing facility from a foreign source must additionally not exceed 25 kg.

(f) *Samples Undergoing Treatability Studies at Laboratories and Testing Facilities.* Samples undergoing treatability studies and the laboratory or testing facility conducting such treatability studies (to the extent such facilities are not otherwise subject to RCRA requirements) are not subject to any requirement of this part, part 124, parts 262-266, 268, and 270, or to the notification requirements of Section 3010 of RCRA provided that the conditions of paragraphs (f) (1) through (11) of this section are met. A mobile treatment unit (MTU) may qualify as a testing facility subject to paragraphs (f) (1) through (11) of this section. Where a group of MTUs are located at the same site, the limitations specified in (f) (1) through (11) of this section apply to the entire group of MTUs collectively as if the group were one MTU.

(1) No less than 45 days before conducting treatability studies, the facility notifies the Regional Administrator, or State Director (if located in an authorized State), in writing that it intends to conduct treatability studies under this paragraph.

(2) The laboratory or testing facility conducting the treatability study has an EPA identification number.

(3) No more than a total of 10,000 kg of "as received" media contaminated with non-acute hazardous waste, 2500 kg of media contaminated with acute hazardous waste or 250 kg of other "as received" hazardous waste is subject to initiation of treatment in all treatability studies in any single day. "As received" waste refers to the waste as received in the shipment from the generator or sample collector.

(4) The quantity of "as received" hazardous waste stored at the facility for

the purpose of evaluation in treatability studies does not exceed 10,000 kg, the total of which can include 10,000 kg of media contaminated with non-acute hazardous waste, 2500 kg of media contaminated with acute hazardous waste, 1000 kg of non-acute hazardous wastes other than contaminated media, and 1 kg of acute hazardous waste. This quantity limitation does not include treatment materials (including nonhazardous solid waste) added to "as received" hazardous waste.

(5) No more than 90 days have elapsed since the treatability study for the sample was completed, or no more than one year (two years for treatability studies involving bioremediation) have elapsed since the generator or sample collector shipped the sample to the laboratory or testing facility, whichever date first occurs. Up to 500 kg of treated material from a particular waste stream from treatability studies may be archived for future evaluation up to five years from the date of initial receipt. Quantities of materials archived are counted against the total storage limit for the facility.

(6) The treatability study does not involve the placement of hazardous waste on the land or open burning of hazardous waste.

(7) The facility maintains records for 3 years following completion of each study that show compliance with the treatment rate limits and the storage time and quantity limits. The following specific information must be included for each treatability study conducted:

(i) The name, address, and EPA identification number of the generator or sample collector of each waste sample;

(ii) The date the shipment was received;

(iii) The quantity of waste accepted;

(iv) The quantity of "as received" waste in storage each day;

(v) The date the treatment study was initiated and the amount of "as received" waste introduced to treatment each day;

(vi) The date the treatability study was concluded;

§261.4

40 CFR Ch. I (7-1-18 Edition)

(vii) The date any unused sample or residues generated from the treatability study were returned to the generator or sample collector or, if sent to a designated facility, the name of the facility and the EPA identification number.

(8) The facility keeps, on-site, a copy of the treatability study contract and all shipping papers associated with the transport of treatability study samples to and from the facility for a period ending 3 years from the completion date of each treatability study.

(9) The facility prepares and submits a report to the Regional Administrator, or state Director (if located in an authorized state), by March 15 of each year, that includes the following information for the previous calendar year:

(i) The name, address, and EPA identification number of the facility conducting the treatability studies;

(ii) The types (by process) of treatability studies conducted;

(iii) The names and addresses of persons for whom studies have been conducted (including their EPA identification numbers);

(iv) The total quantity of waste in storage each day;

(v) The quantity and types of waste subjected to treatability studies;

(vi) When each treatability study was conducted;

(vii) The final disposition of residues and unused sample from each treatability study.

(10) The facility determines whether any unused sample or residues generated by the treatability study are hazardous waste under §261.3 and, if so, are subject to parts 261 through 268, and part 270 of this chapter, unless the residues and unused samples are returned to the sample originator under the §261.4(e) exemption.

(11) The facility notifies the Regional Administrator, or State Director (if located in an authorized State), by letter when the facility is no longer planning to conduct any treatability studies at the site.

(g) *Dredged material that is not a hazardous waste.* Dredged material that is subject to the requirements of a permit that has been issued under 404 of the Federal Water Pollution Control Act

(33 U.S.C.1344) or section 103 of the Marine Protection, Research, and Sanctuaries Act of 1972 (33 U.S.C. 1413) is not a hazardous waste. For this paragraph (g), the following definitions apply:

(1) The term *dredged material* has the same meaning as defined in 40 CFR 232.2;

(2) The term *permit* means:

(i) A permit issued by the U.S. Army Corps of Engineers (Corps) or an approved State under section 404 of the Federal Water Pollution Control Act (33 U.S.C. 1344);

(ii) A permit issued by the Corps under section 103 of the Marine Protection, Research, and Sanctuaries Act of 1972 (33 U.S.C. 1413); or

(iii) In the case of Corps civil works projects, the administrative equivalent of the permits referred to in paragraphs (g)(2)(i) and (ii) of this section, as provided for in Corps regulations (for example, see 33 CFR 336.1, 336.2, and 337.6).

(h) *Carbon dioxide stream injected for geologic sequestration.* Carbon dioxide streams that are captured and transported for purposes of injection into an underground injection well subject to the requirements for Class VI Underground Injection Control wells, including the requirements in 40 CFR Parts 144 and 146 of the Underground Injection Control Program of the Safe Drinking Water Act, are not a hazardous waste, provided the following conditions are met:

(1) Transportation of the carbon dioxide stream must be in compliance with U.S. Department of Transportation requirements, including the pipeline safety laws (49 U.S.C. 60101 et seq.) and regulations (49 CFR Parts 190-199) of the U.S. Department of Transportation, and pipeline safety regulations adopted and administered by a state authority pursuant to a certification under 49 U.S.C. 60105, as applicable.

(2) Injection of the carbon dioxide stream must be in compliance with the applicable requirements for Class VI Underground Injection Control wells, including the applicable requirements in 40 CFR Parts 144 and 146;

(3) No hazardous wastes shall be mixed with, or otherwise co-injected with, the carbon dioxide stream; and

Environmental Protection Agency

§ 261.6

(4)(i) Any generator of a carbon dioxide stream, who claims that a carbon dioxide stream is excluded under this paragraph (h), must have an authorized representative (as defined in 40 CFR 260.10) sign a certification statement worded as follows:

I certify under penalty of law that the carbon dioxide stream that I am claiming to be excluded under 40 CFR 261.4(h) has not been mixed with hazardous wastes, and I have transported the carbon dioxide stream in compliance with (or have contracted with a pipeline operator or transporter to transport the carbon dioxide stream in compliance with) Department of Transportation requirements, including the pipeline safety laws (49 U.S.C. 60101 et seq.) and regulations (49 CFR Parts 190–199) of the U.S. Department of Transportation, and the pipeline safety regulations adopted and administered by a state authority pursuant to a certification under 49 U.S.C. 60105, as applicable, for injection into a well subject to the requirements for the Class VI Underground Injection Control Program of the Safe Drinking Water Act.

(ii) Any Class VI Underground Injection Control well owner or operator, who claims that a carbon dioxide stream is excluded under paragraph (h) of this section, must have an authorized representative (as defined in 40 CFR 260.10) sign a certification statement worded as follows:

I certify under penalty of law that the carbon dioxide stream that I am claiming to be excluded under 40 CFR 261.4(h) has not been mixed with, or otherwise co-injected with, hazardous waste at the Underground Injection Control (UIC) Class VI permitted facility, and that injection of the carbon dioxide stream is in compliance with the applicable requirements for UIC Class VI wells, including the applicable requirements in 40 CFR Parts 144 and 146.

(iii) The signed certification statement must be kept on-site for no less than three years, and must be made available within 72 hours of a written request from the Administrator, Regional Administrator, or state Director (if located in an authorized state), or their designee. The signed certification statement must be renewed every year that the exclusion is claimed, by having an authorized representative (as defined in 40 CFR 260.10) annually prepare and sign a new copy of the certification statement within one year of the date of the previous statement. The signed certification statement must also be

readily accessible on the facility's publicly-available Web site (if such Web site exists) as a public notification with the title of "Carbon Dioxide Stream Certification" at the time the exclusion is claimed.

[45 FR 33119, May 19, 1980]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting § 261.4, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and at www.fdsys.gov.

§ 261.5 [Reserved]

§ 261.6 Requirements for recyclable materials.

(a)(1) Hazardous wastes that are recycled are subject to the requirements for generators, transporters, and storage facilities of paragraphs (b) and (c) of this section, except for the materials listed in paragraphs (a)(2) and (a)(3) of this section. Hazardous wastes that are recycled will be known as "recyclable materials."

(2) The following recyclable materials are not subject to the requirements of this section but are regulated under subparts C through N of part 266 of this chapter and all applicable provisions in parts 268, 270, and 124 of this chapter.

(i) Recyclable materials used in a manner constituting disposal (40 CFR part 266, subpart C);

(ii) Hazardous wastes burned (as defined in section 266.100(a)) in boilers and industrial furnaces that are not regulated under subpart O of part 264 or 265 of this chapter (40 CFR part 266, subpart H);

(iii) Recyclable materials from which precious metals are reclaimed (40 CFR part 266, subpart F);

(iv) Spent lead-acid batteries that are being reclaimed (40 CFR part 266, subpart G).

(3) The following recyclable materials are not subject to regulation under parts 262 through parts 268, 270 or 124 of this chapter, and are not subject to the notification requirements of section 3010 of RCRA:

(i) Industrial ethyl alcohol that is reclaimed except that exports and imports of such recyclable materials must comply with the requirements of 40 CFR part 262, subpart H.