

Environmental Protection Agency

§ 761.62

recordkeeping is required in accordance with § 761.125(c)(5).

(b) *Performance-based disposal.* (1) Any person disposing of liquid PCB remediation waste shall do so according to § 761.60(a) or (e), or decontaminate it in accordance with § 761.79.

(2) Any person disposing of non-liquid PCB remediation waste shall do so by one of the following methods:

(i) Dispose of it in a high temperature incinerator approved under § 761.70(b), an alternate disposal method approved under § 761.60(e), a chemical waste landfill approved under § 761.75, or in a facility with a coordinated approval issued under § 761.77.

(ii) Decontaminate it in accordance with § 761.79.

(3) Any person may manage or dispose of material containing <50 ppm PCBs that has been dredged or excavated from waters of the United States:

(i) In accordance with a permit that has been issued under section 404 of the Clean Water Act, or the equivalent of such a permit as provided for in regulations of the U.S. Army Corps of Engineers at 33 CFR part 320.

(ii) In accordance with a permit issued by the U.S. Army Corps of Engineers under section 103 of the Marine Protection, Research, and Sanctuaries Act, or the equivalent of such a permit as provided for in regulations of the U.S. Army Corps of Engineers at 33 CFR part 320.

(c) *Risk-based disposal approval.* (1) Any person wishing to sample, cleanup, or dispose of PCB remediation waste in a manner other than prescribed in paragraphs (a) or (b) of this section, or store PCB remediation waste in a manner other than prescribed in § 761.65, must apply in writing to the Regional Administrator in the Region where the sampling, cleanup, disposal, or storage site is located, for sampling, cleanup, disposal, or storage occurring in a single EPA Region; or to the Director, Office of Resource Conservation and Recovery, for sampling, cleanup, disposal, or storage occurring in more than one EPA Region. Each application must include information described in the notification required by paragraph (a)(3) of this section. EPA may request other information that it believes necessary to evaluate the application. No person

may conduct cleanup activities under this paragraph prior to obtaining written approval by EPA.

(2) EPA will issue a written decision on each application for a risk-based method for PCB remediation wastes. EPA will approve such an application if it finds that the method will not pose an unreasonable risk of injury to health or the environment.

[63 FR 35448, June 29, 1998, as amended at 64 FR 33761, June 24, 1999; 72 FR 57239, Oct. 9, 2007; 74 FR 30232, June 25, 2009]

§ 761.62 Disposal of PCB bulk product waste.

PCB bulk product waste shall be disposed of in accordance with paragraph (a), (b), or (c) of this section. Under some of these provisions, it may not be necessary to determine the PCB concentration or leaching characteristics of the PCB bulk product waste. When it is necessary to analyze the waste to make either of these determinations, use the applicable procedures in subpart R of this part to sample the waste for analysis, unless EPA approves another sampling plan under paragraph (c) of this section.

(a) *Performance-based disposal.* Any person disposing of PCB bulk product waste may do so as follows:

(1) In an incinerator approved under § 761.70.

(2) In a chemical waste landfill approved under § 761.75.

(3) In a hazardous waste landfill permitted by EPA under section 3004 of RCRA, or by a State authorized under section 3006 of RCRA.

(4) Under an alternate disposal approval under § 761.60(e).

(5) In accordance with the decontamination provisions of § 761.79.

(6) For metal surfaces in contact with PCBs, in accordance with the thermal decontamination provisions of § 761.79(c)(6).

(7) In accordance with a TSCA PCB Coordinated Approval issued under § 761.77.

(b) *Disposal in solid waste landfills.* (1) Any person may dispose of the following PCB bulk product waste in a facility permitted, licensed, or registered by a State as a municipal or non-municipal non-hazardous waste landfill:

(i) Plastics (such as plastic insulation from wire or cable; radio, television and computer casings; vehicle parts; or furniture laminates); preformed or molded rubber parts and components; applied dried paints, varnishes, waxes or other similar coatings or sealants; caulking; Galbestos; non-liquid building demolition debris; or non-liquid PCB bulk product waste from the shredding of automobiles or household appliances from which PCB small capacitors have been removed (shredder fluff).

(ii) Other PCB bulk product waste, sampled in accordance with the protocols set out in subpart R of this part, that leaches PCBs at <10 µg/L of water measured using a procedure used to simulate leachate generation.

(2) Any person may dispose of PCB bulk product waste other than those materials meeting the conditions of paragraph (b)(1) of this section, (e.g., paper or felt gaskets contaminated by liquid PCBs in a facility that is permitted, licensed, or registered by a State to manage municipal solid waste subject to part 258 of this chapter or non-municipal non-hazardous waste subject to §§ 257.5 through 257.30 of this chapter, as applicable, if:

(i) The PCB bulk product waste is segregated from organic liquids disposed of in the landfill unit.

(ii) Leachate is collected from the landfill unit and monitored for PCBs.

(3) Any release of PCBs (including but not limited to leachate) from the landfill unit shall be cleaned up in accordance with §761.61.

(4)(i) Any person disposing off-site of PCB bulk product waste regulated under paragraph (b)(1) of this section at a waste management facility not having a commercial PCB storage or disposal approval must provide written notice to the facility a minimum of 15 days in advance of the first shipment from the same disposal waste stream. The notice shall state that the PCB bulk product waste may include components containing PCBs at ≥50 ppm based on analysis of the waste in the shipment or application of a general knowledge of the waste stream (or similar material) which is known to contain PCBs at those levels, and that

the PCB bulk product waste is known or presumed to leach <10 µg/L PCBs.

(ii) Any person disposing off-site of PCB bulk product waste regulated under paragraph (b)(2) of this section at a waste management facility not having a commercial PCB storage or disposal approval must provide written notice to the facility a minimum of 15 days in advance of the first shipment from the same disposal waste stream and with each shipment thereafter. The notice shall state that the PCB bulk product waste may include components containing PCBs at ≥50 ppm based on analysis of the waste in the shipment or application of a general knowledge of the waste stream (or similar material) which is known to contain PCBs at those levels, and that the PCB bulk product waste is known or presumed to leach ≥10 µg/L PCBs.

(5) Any person disposing of PCB bulk product waste must maintain a written record of all sampling and analysis of PCBs or notifications made under this paragraph for 3 years from the date of the waste's generation. The records must be made available to EPA upon request.

(6) Requirements in subparts C, J, and K of this part do not apply to waste disposed of under paragraph (b) of this section.

(c) *Risk-based disposal approval.* (1) Any person wishing to sample or dispose of PCB bulk product waste in a manner other than prescribed in paragraphs (a) or (b) of this section, or store PCB bulk product waste in a manner other than prescribed in §761.65, must apply in writing to the Regional Administrator in the Region where the sampling, disposal, or storage site is located, for sampling, disposal, or storage occurring in a single EPA Region; or to the Director, Office of Resource Conservation and Recovery, for sampling, disposal, or storage occurring in more than one EPA Region. Each application must contain information indicating that, based on technical, environmental, or waste-specific characteristics or considerations, the proposed sampling, disposal, or storage methods or locations will not pose an unreasonable risk or injury to health or the environment. EPA may

Environmental Protection Agency

§ 761.65

request other information that it believes necessary to evaluate the application. No person may conduct sampling, disposal, or storage activities under this paragraph prior to obtaining written approval by EPA.

(2) EPA will issue a written decision on each application for a risk-based sampling, disposal, or storage method for PCB bulk product wastes. EPA will approve such an application if it finds that the method will not pose an unreasonable risk of injury to health or the environment.

(d) *Disposal as daily landfill cover or roadbed.* Bulk product waste described in paragraph (b)(1) of this section may be disposed of:

(1) As daily landfill cover as long as the daily cover remains in the landfill and is not released or dispersed by wind or other action; or

(2) Under asphalt as part of a road bed.

[63 FR 35451, June 29, 1998, as amended at 64 FR 33761, June 24, 1999; 72 FR 57239, Oct. 9, 2007; 74 FR 30232, June 25, 2009]

§ 761.63 PCB household waste storage and disposal.

PCB household waste, as defined at § 761.3, managed in a facility permitted, licensed, or registered by a State to manage municipal or industrial solid waste, or in a facility with an approval to dispose of PCB bulk product waste under § 761.62(c), is not subject to any other requirements of part 761 of this chapter. PCB household waste stored in a unit regulated for storage of PCB waste must not be commingled with PCB waste.

[63 FR 35452, June 29, 1998]

§ 761.64 Disposal of wastes generated as a result of research and development activities authorized under § 761.30(j) and chemical analysis of PCBs.

This section provides disposal requirements for wastes generated during and as a result of research and development authorized under § 761.30(j). This section also provides disposal requirements for wastes generated during the chemical analysis of samples containing PCBs under part 761, including §§ 761.30, 761.60, 761.61, 761.62, and 761.79. For determining the presence of PCBs

in samples, chemical analysis includes: sample preparation, sample extraction, extract cleanup, extract concentration, addition of PCB standards, and instrumental analysis.

(a) Portions of samples of a size designated in a chemical extraction and analysis method for PCBs and extracted for purposes of determining the presence of PCBs or concentration of PCBs are unregulated for PCB disposal under this part.

(b) All other wastes generated during these activities are regulated for disposal based on their concentration at the time of disposal as follows:

(1) Liquid wastes, including rinse solvents, must be disposed of according to § 761.61(a)(5)(iv).

(2) Non-liquid wastes must be disposed of in the same manner as non-liquid cleaning materials and personal protective equipment waste according to § 761.61(a)(5)(v)(A).

[63 FR 35452, June 29, 1998]

§ 761.65 Storage for disposal.

This section applies to the storage for disposal of PCBs at concentrations of 50 ppm or greater and PCB Items with PCB concentrations of 50 ppm or greater.

(a)(1) *Storage limitations.* Any PCB waste shall be disposed of as required by subpart D of this part within 1-year from the date it was determined to be PCB waste and the decision was made to dispose of it. This date is the date of removal from service for disposal and the point at which the 1-year time frame for disposal begins. PCB/radioactive waste removed from service for disposal is exempt from the 1-year time limit provided that the provisions at paragraphs (a)(2)(ii) and (a)(2)(iii) of this section are followed and the waste is managed in accordance with all other applicable Federal, State, and local laws and regulations for the management of radioactive material.

(2) *One-year extension.* Any person storing PCB waste that is subject to the 1-year time limit for storage and disposal in paragraph (a)(1) of this section may provide written notification to the EPA Regional Administrator for the Region in which the PCB waste is stored that their continuing attempts to dispose of or secure disposal for