TABLE 1—LAW ENFORCEMENT PLANS (MHz)

	LE VHF plan		LE UHF plan			
			'			
Identifier	Mobile transmit	Mobile receive	Identifier	Mobile transmit	Mobile receive	
LEA	167.0875 (S)	167.0875	LEB	414.0375 (S)	414.0375	
LE1	162.0875	167.0875	LE10	418.9875	409.9875	
LE2	162.2625	167.2500	LE11	419.1875	410.1875	
LE3	162.8375	167.7500	LE12	419.6125	410.6125	
LE4	163.2875	168.1125	LE13	414.0625 (S)	414.0625	
LE5	163.4250	168.4625	LE14	414.3125 (S)	414.3125	
LE6	167.2500 (S)	167.2500	LE15	414.3375 (S)	414.3375	
LE7	167.7500 (S)	167.7500	LE16	409.9875 (S)	409.9875	
LE8	168.1125 (S)	168.1125	LE17	410.1875 (S)	410.1875	
LE9	168.4625 (S)	168.4625	LE18	410.6125 (S)	410.6125	

⁽S)—Simplex.

TABLE 2—INCIDENT RESPONSE PLANS (MHZ)

	LE VHF Plan		LE UHF Plan			
Identifier Mobile transmit		Mobile receive	Identifier	Mobile transmit	Mobile receive	
NC1 Calling	164.7125	169.5375 170.0125 170.4125 170.6875 173.0375 169.5375 170.0125 170.4125 170.6875	NC2 Calling	419.2375	410.2375 410.4375 410.6375 410.8375 413.1875 413.2125 410.2375 410.4375 410.8375	

⁽S)—Simplex.

[83 FR 19980, May 7, 2018]

EFFECTIVE DATE NOTE: At 83 FR 19980, May 7, 2018, §90.25 was added. This text contains information collection and recordkeeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

Subpart C—Industrial/Business Radio Pool

Source: 62 FR 18874, Apr. 17, 1997, unless otherwise noted.

§ 90.31 Scope.

The Industrial/Business Radio Pool covers the licensing of the radio communications of entities engaged in commercial activities, engaged in clergy activities, operating educational, philanthropic, or ecclesiastical institutions, or operating hospitals, clinics, or medical associations. Rules as to eligibility for licensing, frequencies available, permissible communications and classes and number of stations, and

any special requirements are set forth in the following sections.

§ 90.33 General eligibility.

- (a) In addition to the eligibility shown in the Industrial/Business Pool, eligibility is also provided for any corporation proposing to furnish nonprofit radiocommunication service to its parent corporation, to another subsidiary of the same parent, or to its own subsidiary. This corporate eligibility is not subject to the cooperative use provision of §90.179.
- (b) Eligibility is also provided for a nonprofit corporation or association that is organized for the purpose of furnishing a radiocommunications service to persons who meet the eligibility requirements of the Industrial/Business Pool. Such use is subject to the cooperative use provisions of §90.179.

§ 90.35 Industrial/Business Pool.

(a) Eligibility. Persons primarily engaged in any of the following activities are eligible to hold authorizations in

the Industrial/Business Pool to provide commercial mobile radio service as defined in part 20 of this chapter or to operate stations for transmission of communications necessary to such activities of the licensee:

- (1) The operation of a commercial activity;
- (2) The operation of educational, philanthropic, or ecclesiastical institu-
 - (3) Clergy activities: or
- (4) The operation of hospitals, clinics, or medical associations.
- (5) Public Safety Pool eligibles are eligible for Industrial/Business Pool spectrum only to The extent that they are engaged in activities listed in paragraphs (a)(1) through (4) of this section. Industrial/Business Pool spectrum many not be utilized for the purposes set forth in § 90.20(a).
- (b) Industrial/Business Pool frequencies. (1) The following table indicates frequencies available for assignment to Industrial/Business Pool stations, together with the class of station(s) to which they are normally assigned, the specific assignment limitations which are explained in paragraph (b) of this section, and the certified frequency coordinator for each frequency:
- (2) Unless otherwise specified, coordination of frequencies in the Industrial/ Business pool must be done in accordance with the following:
- (i) Unless specified elsewhere in this part, frequencies without any coordinator specified in the Coordinator column of paragraph (b)(3) of this section may be coordinated by any frequency coordinator certified in the Industrial/ Business Pool.
- (ii) A letter symbol in the Coordinator column of the frequency table in paragraph (b)(3) of this section designates the mandatory certified frequency coordinator for the associated frequency in the table. However, any coordinator certified in the Industrial/ Business Pool may coordinate applications on such frequencies provided the prior written consent of the designated coordinator is obtained. Frequencies for which two coordinators are listed may be coordinated by either of the listed coordinators.
- (iii) For frequencies above 150 MHz, applications for new or modified facili-

ties on frequencies shared prior to radio service consolidation by the former Manufacturers Radio Service, the Forest Products Radio Service, the Power Radio Service, the Petroleum Radio Service, the Motor Carrier Radio Service, the Railroad Radio Service, the Telephone Maintenance Radio Service and the Automobile Emergency Radio Service may be coordinated by any certified Industrial/Business Pool coordinator. However, in the event that the interference contour of a proposed station would overlap the service contour of an existing station licensed on one of these previously shared frequencies, the written concurrence of the coordinator associated with the industry for which the existing station license was issued, or the written concurrence of the licensee of the existing station, shall be obtained. For the purposes of this §90.35, the service contour for UHF stations is the 39 dBu contour; and the interference contour for UHF stations is the 21 dBu contour: the service contour for VHF stations is the 37 dBu contour; and the interference contour for VHF stations is the 19 dBu contour.

(iv) The letter symbols listed in the Coordinator column of the frequency table in paragraph (b)(3) of this section refer to specific frequency coordinators as follows:

IP—Petroleum Coordinator IW—Power Coordinator LR-Railroad Coordinator

LA—Automobile Emergency Coordinator

(3) Frequencies.

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	
	Kilohertz			
2000 to 25,000	Fixed, base or mobile.	1, 90		
2292	Base or mobile	4, 5, 7.		
2398	do	5, 7.		
4637.5	do	5, 7.		
	Megahertz	2		
25.02	do	3, 4	IP	
25.04	do	8	IP	
25.06	do	3, 4	IP	
25.08	do	8, 9	IP	
25.10	do	3, 4, 9	IP	
25.10 25.12	do	3, 4, 9	IP IP	
		1 ' '	l	

47 CFR Ch. I (10-1-20 Edition)

§ 90.35

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
05.10	do	2 4 0	IP	21.00	do		
25.18	do	3, 4, 9	IP	31.80	do.		
25.20	do	9	IP	31.84	do.		
25.22 25.24	dodo	4, 7	IP	31.88	do.		
		4 7	IP	31.92	do.		
25.26	do	4, 7		31.96	do.		
25.28	do		IP	33.12	Mobile	11	
25.30	do	4, 7	IP.	33.14	Mobile	11, 12.	
25.32	do		IP	33.16	Base or mobile		
27.43	do.			33.18	do		IP
27.45	do.			33.20	do		IP
27.47	do.			33.22	do		IP
27.49	do	10.		33.24	do		IP
27.51	Mobile	11.		33.26	do		IP
27.53	do	11.		33.28	do		IP
27.555	Base or mobile	89		33.30	do		IP
27.615	do	89		33.32	do		ΪΡ
27.635	do	89		33.34	do		IP
27.655	do	89		33.36	do		IP
27.000	do	89		22.20	do		IP
27.765	do			33.38	do	10.14	ار
27.86	Base or mobile	89		33.40	Mobile	12, 14.	
29.71	do			35.02	do	11, 12, 13.	
29.73	do.			35.04	Base or Mobile	10.	
29.75	do.			35.06	do.		
29.77	do.			35.08	do.		
29.79	do.		1	35.10	do.		
30.58	do.			35.12	do.		
30.60	do.			35.14	do.		
30.62	do.			35.16	do.		
30.64	do.			35.18	do.		
30.66	do	4 7		35.28			
00.00		4, 7.		05.20	do.		
30.68	do.			35.32	do.		
30.70	do	4, 7	IP	35.36	do.		
30.72	do.			35.40	do.		
30.74	do	4, 7.		35.44	do		
30.76	do.			35.48	do		
30.78	do	4, 7	IP	35.52	do		
30.80	do.			35.70	do.		
30.82	do	4, 7.		35.72	do.		
30.84	Mobile	11, 12.		35.74	do.		
30.86	Base or mobile	13		35.76	do.		
30.88	do.	10		35.78	do.		
30.90	do	13.		35.80	do.		
	do.	10.		25.00			
30.92		40		35.82	do.		
30.94	do	13.		35.84	do.		
30.96	do.			35.86	do.		
30.98	do	13.		35.88	do.		
31.00	do.			35.90	do.		
31.02	do	13.		35.92	do.		
31.04	do.			35.94	do.		
31.06	do	13.		35.96	do.		
31.08	do.			35.98	do.		
31.10	do	13.		36.25	do	15	IP
31.12	do.		1	37.44	do.		l .
31.14	do	13.		37.46	do		ıw
		10.	1				IW
31.16	do.		1	37.48	do		
31.20	do.			37.50	do		IW
31.24	do.			37.52	do		IW
31.28	do.			37.54	do		IW
31.32	do.			37.56	do		IW
31.36	do.			37.58	do		IW
31.40	do.			37.60	Base, mobile,	16	IW
31.44	do.				or operational		
31.48	do.		1		fixed.		
31.52	do.			37.62	Base or mobile		IW
			1				
31.56	do.			37.64	do		IW
31.60	do.			37.66	do		IW
31.64	do.			37.68	do		IW
31.68	do.			37.70	do		IW
31.72	do.			37.72	do		IW
31.76	do.			37.74	do		ıw

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
37.76	do		IW	44.52	do.		
37.78	do		lw	44.54	do.		
37.80	do		IW	44.56	do.		
37.82	do		IW	44.58	do.		
37.84	Base, mobile,	16	IW	44.60	do.		
	or operational			47.44	do.		
07.00	fixed.			47.48	do.		
37.86	Base or mobile		IW	47.52	do. do.		
37.88 41.71	do. do	15	IP	47.56 47.60	do.		
42.96	do.	13	"	47.64	do.		
42.98	Mobile	11, 12.		47.68	do.		
43.00	Base or mobile	,		47.70	do		lw
43.02	do.			47.72	do		IW
43.04	do	17.		47.74	do		IW
43.06	do.			47.76	do		IW
43.08	do.			47.78	do		IW
43.10	do.			47.80	do		IW
43.12	do.			47.82	do		IW
43.14	do.			47.84	do		IW
43.16	Mobile.			47.86	do		IW
43.18	Base or mobile.			47.88	do		IW
43.28	do.			47.90	dodo		IW IW
43.32	do.			47.92	do		IW
43.36 43.40	do.			47.94 47.96	do		IW
43.44	do.			47.98	do		iw
43.48	do.			48.00	do		iw
43.52	do.			48.02	do		iw
43.70	do.			48.04	do		ıw
43.72	do	18.		48.06	do		IW
43.74	do	18.		48.08	do		IW
43.76	do.			48.10	do		IW
43.78	do.			48.12	do		IW
43.80	do.			48.14	do		IW
43.82	do	18.		48.16	do		IW IW
43.84	do	18.		48.18	do		IW
43.86	dodo	19. 19.		48.20 48.22	dodo		IW
43.88 43.90	do	19.		48.24	do		iw
43.92	do	18, 19.		48.26	do		iw
43.94	do	19.		48.28	do		iw
43.96	do	18.		48.30	do		IW
43.98	do.			48.32	do		IW
44.00	do.			48.34	do		IW
44.02	do.			48.36	do		IW
44.04	do.			48.38	do		IW
44.06	do.			48.40	do		IW
44.08	do.			48.42	do		IW
44.10	do	20.		48.44	do		IW
44.12	do	18.		48.46	do		IW
44.14	do.	18.	1	48.48	do		IW IW
44.16 44.18	dodo	18. 18.		48.50 48.52	dodo		IW
44.20	do	18, 21.		48.54	do		IW
44.22	do.	10, 21.		48.56	do.		'**
44.24	do.			48.58	do.		
44.26	do.			48.60	do.		
44.28	do.			48.62	do.		
44.30	do.			48.64	do.		
44.32	do	18.		48.66	do.		
44.34	do.			48.68	do.		
44.36	do	18, 19.		48.70	do.		
44.38	do	19.		48.72	do.		
44.40	do	18, 19.		48.74	do.	1.0	
44.42	do	19.		48.76	do	18.	
44.44	do	19.		48.78	do.		
44.46	do	18.		48.80	do.		
44.48	do	18.		48.82	do.	10	
44.50	ldo.		I	48.84	ldo	18.	I

47 CFR Ch. I (10-1-20 Edition)

§ 90.35

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

							_
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
48.86	do	18.		74.73	do	26, 77.	
48.88	do.			74.75	do	26, 77.	
48.90	do.			74.77	do	26, 77.	
48.92	do	18.		74.79	do	26, 77.	
48.94	do.			75.21	do	26, 77.	
48.96	do.			75.23	do	26, 77.	
48.98	do.			75.25	do	26, 77.	
49.00	do.			75.27	do	26, 77.	
49.02	do	18.		75.29	do	26, 77.	
49.04	do.			75.31	do	26, 77.	
49.06 49.08	do.	18.		75.33 75.35	dodo	26, 77. 26, 77.	
49.10	do	18.		75.37	do	26, 77.	
49.12	do.	10.		75.39	do	26, 77.	
49.14	do.			75.44	do	13, 24, 77.	
49.16	do	18.		75.48	do	13, 24, 77.	
49.18	do.			75.52	do	13, 24, 77.	
49.20	do	18.		75.56	do	13, 24, 77.	
49.22	do.			75.60	do	13, 24, 77.	
49.24	do	18.		150 to 170	Base or mobile	27.	
49.26	do	18.		150.815	do		LA
49.28	do	18.		150.830	do	28, 29	LA
49.30	do.			150.845	do		LA
49.32	do.			150.8525	do	30	LA
49.34	do.			150.860	do		LA
49.36	do	18.		150.8675	do	30	LA
49.38	do.			150.875	do		LA
49.40	do	18.		150.8825	do	30	LA
49.42	do.			150.890	do		LA
49.44	do.	10		150.8975 150.905	do	30	LA LA
49.46	do	18.		150.920	do	20 20	LA
49.48 49.50	do.	18.		150.935	dodo	28, 29	LA
49.52	do.	10.		150.9425	do	30	LA
49.54	do.			150.950	do		LA
49.56	do.			150.9575	do	30	LA
49.58	do.			150.965	do		LA
72 to 76	Operational	22.		150.9725	do	30	LA
	fixed.			150.980	do	8	IP
72.02	Mobile	23, 24.		150.9875	do	8, 30	IP
72.04	do	23, 24.		150.995	do	31.	
72.06				151.0025			
72.08	do	23, 24.			do	30, 31	
	do	23, 24, 25.		151.010	do	31.	
72.10	dodo	23, 24, 25. 23, 24.		151.010 151.0175	dodo	31. 30, 31	
72.10 72.12	dododododo	23, 24, 25. 23, 24. 23, 24.		151.010 151.0175 151.025	dododododo	31. 30, 31 31.	
72.10 72.12 72.14	dododododododo	23, 24, 25. 23, 24. 23, 24. 23, 24.		151.010 151.0175 151.025 151.0325	do	31. 30, 31 31. 30, 31	
72.10 72.12 72.14 72.16	do	23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24, 25.		151.010 151.0175 151.025 151.0325 151.040	do .	31. 30, 31 31. 30, 31 31.	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24, 25. 23, 24.		151.010 151.0175 151.025 151.0325 151.040 151.0475	do	31. 30, 31 31. 30, 31 31. 3031	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24, 25. 23, 24. 23, 24.		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31.	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24, 25. 23, 24. 23, 24. 23, 24.		151.010	dodododododododododododododododdo	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31.	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24, 25. 23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24.		151.010	dodododododododododododododb	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31.	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24, 25. 23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24.		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24, 25. 23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24, 25. 23, 24. 23, 24, 25.		151.010	do .	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24. 25, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24.		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31 31. 30, 31	
72.10	do	23, 24, 25. 23, 24. 23, 24.		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31 31. 30, 31 31.	
72.10	do	23, 24, 25. 23, 24. 23, 24.		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31 31. 30, 31 31.	
72.10	do	23, 24, 25. 23, 24. 23, 24.		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31 31. 30, 31 31. 30, 31 31.	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 25. 23, 24. 25. 23, 24. 25. 25. 26. 26. 26. 26. 26. 26. 26. 26. 26. 26		151.010	do	31, 30, 31 31, 30, 31 31, 3031 31, 28, 29, 31, 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31	
72.10	do	23, 24, 25. 23, 24. 23, 24.		151.010	do	31, 30, 31 31, 30, 31 31, 3031 31, 28, 29, 31, 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 31, 31, 31, 31, 31, 31, 31, 31, 31, 31,	
72.10	do	23, 24, 25. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 23, 24. 25. 23, 24. 25. 23, 24. 25. 25. 26. 26. 26. 26. 26. 26. 26. 26. 26. 26		151.010	do	31, 30, 31 31, 30, 31 31, 3031 31, 28, 29, 31, 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31	
72.10	do	23, 24, 25. 23, 24. 23, 24.		151.010	do .	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31.	
72.10	do	23, 24, 25. 23, 24. 23, 24. 25. 36. 37. 37. 37. 37. 37. 37. 37. 37. 37. 37		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 30, 31 31. 31. 30, 31 31. 31. 31. 31. 30, 31 31. 31. 31. 31. 31. 31. 31. 31. 31. 3	
72.10	do	23, 24, 25. 23, 24. 23, 24. 24. 27. 27. 27. 27. 27. 27. 27. 27. 27. 27		151.010	do	31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31	
72.10	do	23, 24, 25. 23, 24. 23, 24. 27, 27. 28, 27. 28		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31. 30, 31 31.	
72.10 72.11 72.12 72.14 72.16 72.18 72.20 72.22 72.24 72.28 72.30 72.32 72.34 72.36 72.38 72.40 72.44 72.55 72.48 72.50 72.48 72.50 72.48 72.50 72.60 72.60 72.60	do	23, 24, 25. 23, 24. 24. 25. 25. 26. 27. 28. 28. 28. 28. 28. 28. 28. 28. 28. 28		151.010	do	31. 30, 31 31. 30, 31 31. 3031 31. 28, 29, 31. 31. 30, 31 31. 30, 31 31. 31. 30, 31 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 30, 31 30, 31 31. 30, 31 30, 30 30, 3	
72.10	do	23, 24, 25. 23, 24. 25. 31, 24, 77. 13, 24, 77. 13, 24, 77. 26, 77. 26, 77. 26, 77.		151.010	do	31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 31, 32, 28, 29, 31, 31, 31, 31, 31, 31, 31, 31, 31, 31	
72.10 72.12 72.14 72.16 72.18 72.20 72.22 72.24 72.26 72.28 72.30 72.32 72.34 72.36 72.38 72.40 72.44 72.52 72.56 72.48 72.57 72.60 72.41 72.41 72.41 72.42 72.52 72.56 72.48 72.52 72.56 72.60 74.61 74.63 74.65	do	23, 24, 25. 23, 24. 27. 13, 24, 77. 13, 24, 77. 13, 24, 77. 13, 24, 77. 26, 77. 26, 77. 26, 77. 26, 77. 26, 77. 26, 77. 26, 77. 26, 77.		151.010	do	31, 30, 31 31, 30, 31 31, 28, 29, 31, 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 30, 31 31, 31, 30, 31 31, 31, 30, 31 31, 31, 30, 31	
72.10	do	23, 24, 25. 23, 24. 25. 31, 24, 77. 13, 24, 77. 13, 24, 77. 26, 77. 26, 77. 26, 77.		151.010	do	31. 30, 31 31. 30, 31 31. 30, 31 31. 28, 29, 31. 31. 30, 31 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 31. 30, 31 31. 31. 31. 31. 31. 31. 31. 31. 31. 3	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
151 250	do	21		151 965	do.		
151.250	do	31.		151.865	1		
151.2575	do	30, 31		151.895 151.9025	do do	30	
151.265	do	31.				30	
151.2725	do	30, 31		151.910	do		
151.280	do	31.		151.9175	do	30	
151.2875	do	30, 31		151.925	do.		
151.295	do	31.		151.955	do	00	
151.310	Base	28, 29, 31.		151.9625	do	30	
151.325	Base or mobile	31.		151.970	do	30	
151.3325	do	30, 31		151.9775	do	30	
151.340	do	31.		151.985	do.		
151.3475	do	30, 31		152.2625	do	33.	
151.355	do	31.		152.270	do	6.	
151.3625	do	30, 31		152.2775	do	6, 30	
151.370	do	31.		152.285	do	6.	
151.3775	do	30, 31		152.2925	do	6, 30	
151.385	do	31.		152.300	do	6.	
151.3925	do	30, 31		152.3075	do	6, 30	
151.400	do	31.		152.315	do	6.	
151.4075	do	30, 31		152.3225	do	6, 30	
151.415	do	31.		152.330	do	6.	
151.4225	do	30, 31		152.3375	do	6, 30	
151.430	do	31.		152.345	do	6.	
151.4375	do	30, 31		152.3525	do	6, 30	
151.445	do	31.		152.360	do	6.	
151.4525	do	30, 31		152.3675	do	6, 30	
151.460	do	31.		152.375	do	6.	
151.4675	do	30, 31		152.3825	do	6, 30	
151.475	do	31.		152.390	do	6.	
151.4825	do	30, 31		152.3975	do	6, 30	
151.490	do	13, 32.		152.405	do	6.	
151.4975	do	30, 32		152.4125	do	6, 30	
151.505	do	17.		152.420	do	6.	
151.5125	do	30, 17		152.4275	do	6, 30	
151.520	do.			152.435	do	6.	
151.5275	do	30		152.4425	do	6, 30	
151.535	do.			152.450	do	6.	
151.5425	do	30		152.4575	do	6, 30	
151.550	do.			152.465	do	79.	
151.5575	do	30		152.480	do	29, 36, 37,	
151.565	do.			450.0005		38.	
151.5725	do	30		152.8625	do	33.	
151.580	do.			152.870	do		
151.5875	do	30		152.8775	do	30	
151.595	do.			152.885	do.		
151.6025	do	30		152.8925	do	30	
151.625	do	10.		152.900	do.		
151.640	do	10, 33.		152.9075	do	30	
151.6475	do	30		152.915	do.	1	
151.655	do.			152.9225	do	30	
151.6625	do	30		152.930	do.		
151.670	do	30		152.9375	do	30	
151.6775	do	30		152.945	do.		
151.685	do.			152.9525	do	30	
151.700	do	10, 30, 34.		152.960	do.		
151.715	do.			152.9675	do	30	
151.7225	do	30		152.975	do.		
151.730	do	30		152.9825	do	30	
151.7375	do	30		152.990	do.		
151.745	do.			152.9975	do	30	
151.760	do	10, 30, 34.		153.005	do.		
151.775	do.			153.0125	do	30	
151.7825	do	30		153.020	do.		
151.790	do	30		153.0275	do	30	
151.7975	do	30		153.035	do		IP.
151.805	do.			153.0425	do	30	IP.
151.835	Base or mobile.			153.050	do	4, 7	IP.
151.8425	do	30		153.0575	do	4, 7, 30	IP.
151.850	do	30		153.065	do		IP.
151.8575		30		153.0725		30	IP.

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

	TABLE COIN	iiiucu			TABLE COIN	iiiucu	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
153.080	do	4, 7	IP.	153.605	do	80	IP, IW
153.0875	do	4, 7, 30	IP.	153.6125	do	30, 80	IP, IW
153.095	do	4, 7, 00	IP.	153.620	do	80	IP. IW
153.1025	do	30, 80	IP.	153.6275	do	30, 80	IP, IW
153.110	do	4, 7	IP.	153.635	do	80	IP. IW
153.1175	do	4, 7, 30	IP.	153.6425	do	30, 80	IP, IW
153.125	do		IP.	153.650	do		IW IW
153.1325	do		IP.	153.6575	do	30	iw
153.140	do	4, 7	IP.		do	80	IP, IW
153.1475	do	4, 7, 30	IP.	153.665 153.6725	do	30, 80	IP, IW
153.155			IP.	153.680	do	80	IP, IW
		30	IP.	153.6875			IP, IW
153.1625			IP.		do	30, 80	IW IW
153.170	do	4, 7		153.695	do		
153.1775	do	4, 7, 30	IP.	153.7025	do	30	IW
153.185	do		IP.	153.710	do		IW
153.1925	do	30	IP.	153.7175	do	30	IW
153.200	do	4, 7	IP.	153.725	do		IW
153.2075	do	4, 7, 30	IP.	153.7325	do	30	IW
153.215	do		IP.	154.45625	Fixed or mobile	39, 40, 41,	
153.2225	do	30	IP.			42.	
153.230	do	4, 7	IP.	154.46375	do	39, 40, 43.	
153.2375	do	4, 7, 30	IP.	154.47125	do	39, 40, 41,	
153.245	do		IP.			44.	
153.2525	do	30	IP.	154.47875	do	39, 40, 41,	
153.260	do	4, 7	IP.			42.	
153.2675	do	4, 7, 30	IP.	154.4825	Base or mobile	30	
153.275	do		IP.	154.490	do.		
153.2825	do	30	IP.	154.4975	do	30	
153.290	do	4, 7	IP.	154.505	do	30	
153.2975	do	4, 7, 30	IP.	154.515	do.		
153.305	do		IP.	154.5275	Mobile	10, 30, 34	
153.3125	do	30	IP.	154.540	Base or mo-	-,, -	
153.320	do	4, 7	IP.		bile.		
153.3275	do	4, 7, 30	IP.	154.5475	do	30	
153.335	do		IP.	154.555	do	33.	
153.3425	do	30	iP.	154.585	Mobile	8, 46	IP
153.350	do	4, 7	IP.	154.610	Base or mobile	33.	"
153.3575	do	4, 7, 30	iP.	154.625	do	36, 37, 48.	
153.365	do		IP.	154.640	Base	36, 37, 48.	
153.3725	do	30	IP.	157.470	Base or mobile	12	LA
153.380	do		IP.	157.4775	do	12, 30	LA
153.3875	do	30	IP.	157.485	do		LA
153.395	do		IP.	157.4925	do	12	I A
			IP.		do		- `
153.4025	do	30		157.500	do	12	LA
153.410	do		IW. IW	157.5075	do	12, 30	LA LA
153.4175	do	30		157.515	do	12	
153.425	do	80	IP, IW	157.5225	do	12, 30	LA
153.4325	do	30, 80	IP, IW	157.530	Mobile	6.	
153.440	do	80	IP, IW	157.5375	do	6, 30	
153.4475	do	30, 80	IP, IW	157.545	do	6.	
153.455	do	80	IP, IW	157.5525	do	6, 30	
153.4625	do	30, 80	IP, IW	157.560	Base or mobile	6.	
153.470	do		IW	157.5675	do	6, 30	
153.4775	do	30	IW	157.575	Mobile	6.	
153.485	do	80	IP, IW	157.5825	do	6, 30	
153.4925	do	30, 80	IP, IW	157.590	do	6.	
153.500	do	80	IP, IW	157.5975	do	6, 30	
153.5075	do	30, 80	IP, IW	157.605	do	6.	
153.515	do	80	IP, IW	157.6125	do	6, 30	
153.5225	do	30, 80	IP, IW	157.620	Base or mobile	6.	
153.530	do	,,	iw	157.6275	do	6, 30	
153.5375	do	30	iw	157.635	Mobile	6.	
153.545	do	80	IP, IW	157.6425	do	6, 30	
		30, 80	IP, IW	157.650		6.	
153.5525	do				do		
153.560		30, 80	IP, IW	157.6575	do	6, 30	
153.5675	do	30, 80	IP, IW	157.665	do	6.	
153.575	do	80	IP, IW	157.6725	do	6, 30	
153.5825	do	30, 80	IP, IW	157.680	do	6.	
153.590	do		IW	157.6875	do	6, 30	
	do	30	IW	157.695		6, 30	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
157.7025	do	6, 30		159.615	do.		
157.710	do	6.		159.6225	do	30	
157.7175	do	6, 30		159.630	do.	**	
157.725	Base or mobile	79.		159.6375	do	30	
157.740	do	29, 36, 37,		159.645	do.		
		38.		159.6525	do	30	
158.1225	do	33	lw	159.660	do.		
158.130	do		iw	159.6675	do	30	
158.1375	do	6, 30	iw	159.675	do.		
158.145	do		IP, IW	159.6825	do	30	
158.1525	do	6, 30	IP, IW	159.690	do.		
158.160	do	0, 00	IP, IW	159.6975	do	30	
158.1675	do	6, 30	IP, IW	159.705	do.	00	
158.175	do	81	IP, IW	159.7125	do	30	
158.1825	do	30, 81	IP, IW	159.720	do.		
158.190	do		iw iw	159.7275	do	30	
158.1975	do	30	iw	159.735	do.	30	
						20	
158.205	do	81	IP, IW	159.7425	do	30	
158.2125	do	30, 81	IP, IW	159.750	do.	20	
158.220	do	81	IP, IW	159.7575	do	30	
158.2275	do	30, 81	IP, IW	159.765	do.	00	
158.235	do	81	IP, IW	159.7725	do	30	
158.2425	do	30, 81	IP, IW	159.780	do.		
158.250	do		IW	159.7875	do	30	
158.2575	do	30	IW	159.795	do.	00	
158.265	do	81	IP, IW	159.8025	do	30	
158.2725	do	30, 81	IP, IW	159.810	do.		
158.280	do		IP	159.8175	do	30	
158.2875	do	30	IP	159.825	do.		
158.295	do		IP	159.8325	do	30	
158.3025	do	30	IP	159.840	do.		
158.310	do	4, 7	IP	159.8475	do	30	
158.3175	do	4, 7, 30	IP	159.855	do.		
158.325	do		IP	159.8625	do	30	
158.3325	do	30	IP	159.870	do.		
158.340	Mobile.			159.8775	do	30	
158.3475	do	30		159.885	do.		
158.355	Base or mobile		IP	159.8925	do	30	
158.3625	do	30	IP	159.900	do.		
158.370	do	4, 7	IP	159.9075	do	30	
158.3775	do	4, 7, 30	IP	159.915	do.		
158.385	do.	, ,		159.9225	do	30	
158.3925	do	30		159.930	do.		
158.400	do	17.		159.9375	do	30	
158.4075	do	17, 30		159.945	do.		
158.415	do		IP	159.9525	do	30	
158.4225	do	30	IP	159.960	do.	30	
158.430	do	4, 7	IP	159.9675	do	30	
158.4375	do	4, 7, 30	IP	159.975	dodo.	30	
	Mobile	9 40	IP IP	159.9825	do.	30	
158.445	Mobile Base or mobile	8, 49	115		dodo.	30	
158.460	Dase of Mobile	29, 36, 37,		159.990		20	
150 400	da.	38, 48.	l _{ID}	159.9975	do	30	
159.480	do	8, 82	IP	160.005	do.	00	
159.4875	do	8, 30	IP	160.0125	do	30	
159.495	do.	l		160.020	do.		
159.5025	do	30		160.0275	do	30	
159.510	do.			160.035	do.		
159.5175	do	30		160.0425	do	30	
159.525	do.			160.050	do.		
159.5325	do	30		160.0575	do	30	
159.540	do.			160.065	do.		
159.5475	do	30		160.0725	do	30	
159.555	do.			160.080	do.		
159.5625	do	30		160.0875	do	30	
159.570	do.			160.095	do.		
159.5775	do	30	1	160.1025	do	30	
	do.			160.110	do.	"	
			1			l	
159.585		30		160 1175	l do	30	
159.5925	do	30		160.1175	do	30	
		30		160.1175 160.125 160.1325	do.	30	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
160.140	do.			160.665	do	50	LR
160.1475	do	30		160.6725	do	30, 50	LR
160.155	do.	**		160.680	do	50	LR
160.1625	do	30		160.6875	do	30, 50	LR
160.170	do.			160.695	do	50	LR
160.1775	do	30		160.7025	do	30, 50	LR
160.185	do.			160.710	do	50	LR
160.1925	do	30		160.7175	do	30, 50	LR
160.200	do.			160.725	do	50	LR
160.2075	do	30		160.7325	do	30, 50	LR
160.215	do	50	LR	160.740	do	50	LR
160.2225	do	30, 50	LR	160.7475	do	30, 50	LR
160.230 160.2375	dodo	30, 50	LR LR	160.755 160.7625	dodo	50 30, 50	LR LR
160.245	do	50	LR	160.770	do	50, 30	LR
160.2525	do	30, 50	LR	160.7775	do	30, 50	LR
160.260	do	50	LR	160.785	do	50	LR
160.2675	do	30, 50	LR	160.7925	do	30, 50	LR
160.275	do	50	LR	160.800	do	50	LR
160.2825	do	30, 50	LR	160.8075	do	30, 50	LR
160.290	do	50	LR	160.815	do	50	LR
160.2975	do	30, 50	LR	160.8225	do	30, 50	LR
160.305	do	50	LR	160.830	do	50	LR
160.3125	do	30, 50	LR	160.8375	do	30, 50	LR
160.320	do	50	LR	160.845	do	50	LR
160.3275	do	30, 50	LR	160.8525	do	30, 50	LR
160.335	do	50	LR	160.860	do	50, 51	LR
160.3425	do	30, 50	LR LR	160.8675	do	30, 50, 51 50, 51	LR LR
160.350 160.3575	dodo	30, 50	LR	160.875 160.8825	dodo	30, 50, 51	LR
160.365	do	50	LR	160.890	do	50, 51	LR
160.3725	do	30, 50	LR	160.8975	do	30, 50, 51	LR
160.380	do	50	LR	160.905	do	50, 51	LR
160.3875	do	30, 50	LR	160.9125	do	30, 50, 51	LR
160.395	do	50	LR	160.920	do	50, 51	LR
160.4025	do	30, 50	LR	160.9275	do	30, 50, 51	LR
160.410	do	50, 52	LR	160.935	do	50, 51	LR
160.4175	do	30, 50, 52	LR	160.9425	do	30, 50, 51	LR
160.425	do	50, 52	LR	160.950	do	50, 51	LR
160.4325	do	30, 50, 52	LR	160.9575	do	30, 50, 51	LR
160.440	do	50, 52	LR LR	160.965	do	50, 51	LR LR
160.4475 160.455	do	30, 50, 52 50, 52	LR	160.9725 160.980	do	30, 50, 51 50, 51	LR
160.4625	dodo	30, 52	LR	160.9875	dodo	30, 50, 51	LR
160.470	do	50, 52	LR	160.995	do	50, 51	LR
160.4775	do	30, 50, 52	LR	161.0025	do	30, 50, 51	LR
160.485	do	50, 52	LR	161.010	do	50, 51	LR
160.4925	do	30, 50, 52	LR	161.0175	do	30, 50, 51	LR
160.500	do	50, 52	LR	161.025	do	50, 51	LR
160.5075	do	30, 50, 52	LR	161.0325	do	30, 50, 51	LR
160.515	do	50, 52	LR	161.040	do	50, 51	LR
160.5225	do	30, 50, 52	LR	161.0475	do	30, 50, 51	LR
160.530	do	50, 52	LR	161.055	do	50, 51	LR
160.5375	do	30, 50, 52	LR	161.0625	do	30, 50, 51	LR
160.545	do	50, 52	LR	161.070	do	50, 51	LR
160.5525	do	30, 50, 52	LR LR	161.0775	do	30, 50, 51	LR LR
160.560 160.5675	do	50, 52 30, 50, 52	LR	161.085 161.0925	do	50, 51 30, 50, 51	LR
160.575	dodo	50, 52	LR	161.100	dodo	50, 51	LR
160.5825	do	30, 50, 52	LR	161.1075	do	30, 50, 51	LR
160.590	do	50, 52	LR	161.115	do	50, 51	LR
160.5975	do	30, 50, 52	LR	161.1225	do	30, 50, 51	LR
160.605	do	50, 52	LR	161.130	do	50, 51	LR
160.6125	do	30, 50, 52	LR	161.1375	do	30, 50, 51	LR
160.620	do	50	LR	161.145	do	50, 51	LR
160.6275	do	30, 50	LR	161.1525	do	30, 50, 51	LR
160.635	do	50	LR	161.160	do	50, 51	LR
160.6425	do	30, 50	LR	161.1675	do	30, 50, 51	LR
160.650	do	50	LR	161.175	do	50, 51	LR
160.6575	ldo	30, 50	l LR	161.1825	ldo	30, 50, 51	l LR

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

	TABLE COIN	iiiucu			TABLE COIN	iiiucu	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
161.190	do	50, 51	LR	173.325	Base or mobile.		
	do	30, 50, 51	LR	173.3375	Fixed or mobile	92, 93, 94,	
161.1975	dodo	50, 50, 51	LR	173.3373	Fixed of Hilobile		
161.205 161.2125	do	30, 50, 51	LR	173.350	Base or mobile	95.	
161.220		l	LR		Fixed or mobile	00 00 04	
161.2275	dodo	30, 50, 51 30, 50, 51	LR	173.3625	Fixed of mobile	92, 93, 94,	
				170.075	Daga ay mahila	95.	
161.235 161.2425	dodo	50, 51 30, 50, 51	LR LR	173.375	Base or mobile.	40 41 44	
161.250	do	50, 50, 51	LR	173.390	Fixed or mobile	40, 41, 44, 54.	
161.2575	do	30, 50, 51	LR	173.39625	مام		
161.265	do	50, 51	LR	173.39023	do	39, 40, 41, 44.	
161.2725	do	30, 50, 51	LR	216 to 217	Base or mobile	55	
161.280	do	50, 50, 51	LR	217 to 220		55	
161.2875	do	30, 50, 51	LR	217 10 220	Base, mobile,	55	
	do	50, 51	LR		or operational		
161.295 161.3025	do	30, 50, 51	LR	000 +- 000	fixed.		
				220 to 222	Base or mobile		
161.310	do		LR	406 to 416	Operational	53.	
161.3175	do	30, 50, 51	LR	450 to 470	fixed.	07 57	
161.325	do	50, 51	LR	450 to 470	Fixed, base, or	27, 57.	
161.3325	dodo	30, 50, 51	LR	451 00005	mobile.	00	
161.340		50, 51	LR	451.00625	Base or mobile	33.	
161.3475 161.355	dodo	30, 50, 51	LR LR	451.0125	do	33.	l naz
161.3625	do	50, 51 30, 50, 51	LR	451.01875	do	33	IW.
161.370	do		LR	451.025	do		IW
161.3775	do	50, 51 30, 50, 51	LR	451.03125	do	33	IW
161.385	do	50, 52	LR	451.0375	do	30	IW
161.3925	do	30, 52	LR	451.04375	do	33	IW
161.400	do	50, 50, 52	LR	451.050	do		IW
161.4075	do	30, 50, 52	LR	451.05625	do	33	IW
161.415	do	50, 50, 52	LR	451.0625	do	30	IW
	do	30, 52	LR	451.06875	do	33	IW
161.4225 161.430	do	50, 50, 52	LR	451.075	do		IW
161.4375	do	30, 50, 52	LR	451.08125	do	33	IW
161.445	do	50, 50, 52	LR	451.0875	do	30	IW
161.4525	do	30, 50, 52	LR	451.09375	do	33	IW
161.460	do	50, 50, 52	LR	451.100	do		IW
161.4675	do	30, 50, 52	LR	451.10625	dodo	33	IW
161.475	do	50, 50, 52	LR	451.1125		30	IW
161.4825	do	30, 50, 52	LR	451.11875	do	33	IW
161.490	do	50, 52	LR	451.125	dodo		IW IW
161.4975	do	30, 50, 52	LR	451.13125		33	iw
161.505	do	50, 52	LR	451.1375	do	30	IW
161.5125	do	30, 50, 52	LR	451.14375	do	33	
161.520	do	50, 50, 52	LR	451.150 451.15625	dodo		IW IW
			LR			33	iw
161.5275 161.535	dodo	30, 50, 52 50, 52	LR	451.1625 451.16875	dodo	30	IW
161.5425	do	30, 50, 52	LR	451.175	do	33	IP, IW
161.550	do	50, 50, 52	LR	451.18125	do	33, 84.	,
161.5575	do	30, 52	LR	451.1875	do	30, 84.	
161.565	do	50, 50, 52	LR	451.19375	do	30, 84.	
161.610	do		LR	451.200	do		ıw
169 to 172		78	LIT	451.20625			iW
109 10 1/2	Mobile, oper-	53.			dodo	33	IW
173.20375	ational fixed. Fixed or mobile	20 40 44		451.2125	do	30	IW
173.20375	Fixed of mobile	39, 40, 41,		451.21875		33	1
170.010	al a	44.		451.225	do		IP, IW
173.210	do	40, 41, 44,		451.23125	do	33, 84.	
170.005	Daga au	54.		451.2375	do	30, 84.	
173.225	Base or mobile.	02 02 04		451.24375	do	33, 84.	INA/
173.2375	Fixed or mobile	92, 93, 94,		451.250	do		IW
170.050	Daga au	95.	ID IW	451.25625	do	33	IW
173.250	Base or mobile	00 00 04	IP, IW	451.2625	do	30	IW
173.2625	Fixed or mobile	92, 93, 94,		451.26875	do	33	IW IW
470.075	D	95.		451.275	do		IP, IW
173.275	Base or mobile.	00 00 01		451.28125	do	33, 84.	
173.2875	Fixed or mobile	92, 93, 94,		451.2875	do	30, 84.	
170.000		95.		451.29375	do	33, 84.	
173.300	Base or mobile		IP, IW	451.300	do.		
173.3125	Fixed or mobile	92, 93, 94,		451.30625	do	33, 84.	
	I	95.	I	451.3125	ldo	30, 84.	I

47 CFR Ch. I (10-1-20 Edition)

§ 90.35

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

TABLE GOTTINGE			TABLE CONTINUES				
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
451.31875	do	22 04		451.700	do	4, 7	IP
451.325	dodo.	33, 84.		451.70625	dodo	4, 7, 33,	"
451.33125	do	33, 84.		431.70023		84.	
451.3375	do	30, 84.		451.7125	do	4, 7, 30,	
451.34375	do	33, 84.		.0		84.	
451.350	do.	,		451.71875	do	4, 7, 33,	
451.35625	do	33, 84.				84.	
451.3625	do	30, 84.		451.725	do.		
451.36875	do	33, 84.		451.73125	do	33, 84.	
451.375	do		IP, IW	451.7375	do	30, 84.	
451.38125	do	33, 84.		451.74375	do	33, 84.	
451.3875	do	30, 84.		451.750	do	4, 7	IP
451.39375	do	33, 84.		451.75625	do	4, 7, 33,	
451.400	do.					84.	
451.40625	do	33, 84.		451.7625	do	4, 7, 30,	
451.4125	do	30, 84.				84.	
451.41875	do	33, 84.	ID IW	451.76875	do	4, 7, 33,	
451.425	do	22 04	IP, IW	454 775		84.	
451.43125 451.4375	dodo	33, 84. 30, 84.		451.775 451.78125	do. do	22	
451.44375	do	30, 84.		451.7875	do	33.	
451.450	do.	30, 04.		451.7875	do	30.	
451.45625	do	33, 84.		451.800	Base, mobile,	17, 58.	
451.4625	do	30, 84.		431.000	or operational	17, 30.	
451.46875	do	33, 84.			fixed.		
451.475	do		IP, IW	451.80625	do	17, 33, 58.	
451.48125	do	33, 84.		451.8125	do	17, 30, 58.	
451.4875	do	30, 84.		451.81875	do	17, 33, 58.	
451.49375	do	33, 84.		451.825	Base or mobile.	' '	
451.500	do.			451.83125	do	33.	
451.50625	do	33, 84.		451.8375	do	30.	
451.5125	do	30, 84.		451.84375	do	33.	
451.51875	do	33, 84.		451.850	do.		
451.525	do		IP, IW	451.85625	do	33.	
451.53125	do	33, 84. 30, 84.		451.8625	do	30.	
451.5375	dodo	30, 84.		451.86875	do	33.	
451.54375 451.550	do		IP	451.875	do.	00	
451.55625	do	4, 7 4, 7, 33,	"	451.88125 451.8875	dodo	33.	
401.00020		84.		451.89375	do	33.	
451.5625	do	4, 7, 30,		451.900	do.	00.	
10110020		84.		451.90625	do	33.	
451.56875	do	4, 7, 33,		451.9125	do	30.	
		84.		451.91875	do	33.	
451.575	do		IP, IW	451.925	do.		
451.58125	do	33, 84.		451.93125	do	33.	
451.5875	do	30, 84.		451.9375	do	30.	
451.59375	do	33, 84.		451.94375	do	33.	
451.600	do	4, 7	IP	451.950	do.		
451.60625	do	4, 7, 33,		451.95625	do	33.	
454 0405		84.		451.9625	do	30.	
451.6125	do	4, 7, 30,		451.96875	do	33.	
4E1 C107E	40	84.		451.975	do.	22	
451.61875	do	4, 7, 33,		451.98125	do	33.	
451.625	do	84.	IP, IW	451.9875 451.99375	dodo	30.	
451.63125	do	33, 84.	115, 144	452.000	do	33.	
451.6375	do	30, 84.		452.00625	do	33.	
451.64375	do	33, 84.		452.0125	do	30.	
451.650	do	4, 7	IP	452.01875	do	33.	
451.65625	do	4, 7, 33,		452.025	do.	50.	
		84.		452.03125	do	33, 84.	
451.6625	do	4, 7, 30,		452.0375	do	30, 84.	
		84.		452.04375	do	33, 84.	
451.66875	do	4, 7, 33,		452.050	do.	"/ "	
		84.		452.05625	do	33, 84.	
451.675	do		IP, IW	452.0625	do	30, 84.	
451.68125	do	33, 84.		452.06875	do	33, 84.	
451.6875	do	30, 84.		452.075	do.		
451.69375	do	33, 84.	l	452.08125	do	33, 84.	l

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

	TABLE—CON	iriueu			I ABLE—CON	inueu	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
452.0875	do	30, 84.		452.525	do		LA
452.09375	do	33, 84.		452.53125	do	33, 84	LA
452.100	do.	00, 0		452.5375	do	30, 84	LA
452.10625	do	33, 84.		452.54375	do	33, 84	LA
452.1125	do	30, 84.		452.550	do		LA
452.11875	do	33, 84.		452.55625	do	33	LA
452.125	do.			452.5625	do	30	LA
452.13125	do	33, 84.		452.56875	do	33	LA
452.1375	do	30, 84.		452.575	do		LA
452.14375	do	33, 84.		452.58125	do	33	LA
452.150	do.			452.5875	do	30	LA
452.15625	do	33, 84.		452.59375	do	33	LA
452.1625	do	30, 84.		452.600	do		LA
452.16875	do	33, 84.		452.60625	do	33	LA
452.175	do.			452.6125	do	30	LA
452.18125	do	33, 84.		452.61875	do	33	LA
452.1875	do	30, 84.		452.625	do.		
452.19375	do	33, 84.		452.63125	do	33, 84.	
452.200	do.			452.6375	do	30, 84.	
452.20625	do	33.		452.64375	do	33, 84.	
452.2125	do	30.		452.650	do.		
452.21875	do	33.		452.65625	do	33, 84.	
452.225	do			452.6625	do	30, 84.	
452.23125	do	33.		452.66875	do	33, 84.	
452.2375	do	30.		452.675	do.		
452.24375	do	33.		452.68125	do	33, 84.	
452.250	do.			452.6875	do	30, 84.	
452.25625	do	33.		452.69375	do	33, 84.	
452.2625	do	30.		452.700	do.		
452.26875	do	33.		452.70625	do	33, 84.	
452.275	do.			452.7125	do	30, 84.	
452.28125	do	33, 84.		452.71875	do	33, 84.	
452.2875	do	30, 84.		452.725	do.		
452.29375	do	33, 84.		452.73125	do	33.	
452.300	do.	00 04		452.7375	do	30.	
452.30625	do	33, 84.		452.74375	dodo.	33.	
452.3125 452.31875	dodo	30, 84. 33, 84.		452.750 452.75625	do	33, 84.	
452.325	do	33, 64.	LR	452.7625	do	30, 84.	
452.33125	do	33.	Ln	452.76875	do	33, 84.	
452.3375	do	30.		452.775	do	33, 64.	LR
452.34375	do	33.		452.78125	do	33, 84.	Ln
452.350	do.	00.		452.7875	do	30, 84.	
452.35625	do	33.		452.79375	do	33, 84.	
452.3625	do	30.		452.800	do.	00, 04.	
452.36875	do	33.		452.80625	do	33, 84.	
452.375	do	00.	LR	452.8125	do	30. 84.	
452.38125	do	33.		452.81875	do	33, 84.	
452.3875	do	30.		452.825	do		LR
452.39375	do	33.		452.83125	do	33, 84.	
452.400	do.	-		452.8375	do	30, 84.	
452.40625	do	33, 84.		452.84375	do	33, 84.	
452.4125	do	30, 84.		452.850	do.	'	
452.41875	do	33, 84.		452.85625	do	33, 84.	
452.425	do		LR	452.8625	do	30, 84.	
452.43125	do	33.		452.86875	do	33, 84.	
452.4375	do	30.		452.875	do		LR
452.44375	do	33.		452.88125	do	33, 84.	
452.450	do.			452.8875	do	30, 84.	
452.45625	do	33.		452.89375	do	33, 84.	
452.4625	do	30.		452.900	do		LR
452.46875	do	33.		452.90625	do	33	LR
452.475	do		LR	452.9125	do	30	LR
452.48125	do	33, 84.		452.91875	do	33	LR
452.4875	do	30, 84.		452.925	do	59	LR
452.49375	do	33, 84.		452.93125	do	33, 59	LR
		l '	1	452.9375	do	30, 59	LR
452.500	do.						
452.500 452.50625	do.	33, 84.		452.94375		33, 59	LR
		33, 84. 30, 84.			dodo	33, 59 59	LR LR

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

	TABLE COIN	iiiucu			TABLE CON	iiiucu	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
452.9625	do	30, 59	LR	456.375	do		IP, IW
452.96875	dodo	33, 59	LR	456.38125	do	33, 84.	IF , IVV
452.975	do.	00, 00		456.3875	do	30, 84.	
452.98125	do	33, 84.		456.39375	do	33, 84.	
452.9875	do	30, 84.		456.400	do.	00, 0	
452.99375	do	33, 84.		456.40625	do	33, 84.	
453.000	do.	00, 0		456.4125	do	30, 84.	
453.00625	do	33.		456.41875	do	33, 84.	
453.0125	do	30.		456.425	do		IP, IW
453.01875	do	33.		456.43125	do	33, 84.	
454.000	do	8	IP.	456.4375	do	30, 84.	
456.00625	do	33.		456.44375	do	33, 84.	
456.0125	do	33.		456.450 456.45625	do.	33, 84.	
456.01875	do	33	IW.	456.4625	do	30, 84.	
456.025	Mobile		IW IW	456.46875	do	33, 84.	
456.03125 456.0375	dodo	33	IW	456.475	do		IP, IW
456.04375	do	33	iw	456.48125	do	33, 84.	'
456.050	do		iw	456.4875	do	30, 84.	
456.05625	do	33	iW	456.49375	do	33, 84.	
456.0625	do	30	IW	456.500	do.		
456.06875	do	33	IW	456.50625	do	33, 84.	
456.075	do		IW	456.5125	do	30, 84.	
456.08125	do	33	IW	456.51875 456.525	dodo	33, 84.	IP, IW
456.0875	do	30	IW	456.53125	do	33, 84.	11, 100
456.09375	do	33	IW	456.5375	do	30, 84.	
456.100	do		IW IW	456.54375	do	33, 84.	
456.10625 456.1125	dodo	33	IW	456.550	do		IP
456.11875	do	33	iw	456.55625	do	33, 84.	
456.125	do		iw	456.5625	do	30, 84.	
456.13125	do	33	iw	456.56875	do	33, 84.	
456.1375	do	30	IW	456.575	do		IP, IW
456.14375	do	33	IW	456.58125 456.5875	dodo	33, 84.	
456.150	do		IW	456.59375	do	30, 84. 33, 84.	
456.15625	do	33	IW	456.600	do		IP.
456.1625	do	30	IW	456.60625	do	33, 84.	
456.16875 456.175	dodo	33	IW IP, IW	456.6125	do	30, 84.	
456.18125	do	33, 84.	IF, IVV	456.61875	do	33, 84.	
456.1875	do	30, 84.		456.625	do		IP, IW
456.19375	do	33, 84.		456.63125	do	33, 84.	
456.200	do		IW	456.6375 456.64375	dodo	30, 84. 33, 84.	
456.20625	do	33	IW	456.650	do	33, 64.	IP
456.2125	do	30	IW	456.65625	do	33, 84.	"
456.21875	do	33	IW	456.6625	do	30, 84.	
456.225	do		IP, IW	456.66875	do	33, 84.	
456.23125	do	33, 84.		456.675	do		IP, IW
456.2375	do	30, 84.		456.68125	do	33, 84.	
456.24375 456.250	dodo	33, 84.	ıw	456.6875	do	30, 84.	
456.25625	do	33	iw	456.69375	do	33, 84.	I.D
456.2625	do	30	iw	456.700 456.70625	do	33, 84.	IP
456.26875	do	33	iw	456.7125	do	30, 84.	
456.275	do		IP, IW	456.71875	do	33, 84.	
456.28125	do	33, 84.		456.725	do.	,	
456.2875	do	30, 84.		456.73125	do	33, 84.	
456.29375	do	33, 84.		456.7375	do	30, 84.	
456.300	do.			456.74375	do	33, 84.	
456.30625	do	33, 84.		456.750	do		IP
456.3125	do	30, 84.		456.75625	do	33, 84.	
456.31875 456.325	dodo.	33, 84.		456.7625	do	30, 84.	
456.33125	do.	33, 84.		456.76875 456.775	dodo.	33, 84.	
456.3375	do	30, 84.		456.78125	do	33.	
456.34375	do	33, 84.		456.7875	do	30.	
456.350	do.	,		456.79375	do	33.	
456.35625	do	33, 84.		456.800	Base, mobile,	17, 58.	
456.3625	do	30, 84.			or operational		
456.36875	do	33, 84.	l		fixed.	l	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

	TABLE—Cont	inued			TABLE—Conf	inued	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
456.80625	do	17, 33, 58.		457.24375	do	33.	
456.8125	do	17, 30, 58.		457.250	do.		
456.81875	do	17, 33, 58.		457.25625	do	33.	
456.825	Mobile.			457.2625	do	30.	
456.83125	do	33.		457.26875	do	33.	
456.8375	do	30.		457.275	do.	l	
456.84375	do	33.		457.28125	do	33, 84.	
456.850	do.	33.		457.2875 457.29375	dodo	30, 84. 33, 84.	
456.85625 456.8625	dodo	30.		457.300	do.	33, 64.	
456.86875	do	33.		457.30625	do	33, 84.	
456.875	do.	55.		457.3125	do	30, 84.	
456.88125	do	33.		457.31875	do	33, 84.	
456.8875	do	30.		457.325	do		LR
456.89375	do	33.		457.33125	do	33.	
456.900	do.			457.3375	do	30.	
456.90625	do	33.		457.34375	do	33.	
456.9125	do	30.		457.350 457.35625	do. do	33.	
456.91875	do	33.		457.3625	do	30.	
456.925	do.			457.36875	do	33.	
456.93125 456.9375	dodo	33. 30.		457.375	do		LR
456.94375	do	33.		457.38125	do	33.	
456.950	do.	00.		457.3875	do	30.	
456.95625	do	33.		457.39375	do	33.	
456.9625	do	30.		457.400	do.		
456.96875	do	33.		457.40625	do	33, 84.	
456.975	do.			457.4125 457.41875	dodo	30, 84.	
456.98125	do	33.		457.425	do	33, 84.	LR
456.9875	do	30.		457.43125	do	33.	
456.99375 457.000	dodo.	33.		457.4375	do	30.	
457.00625	do	33.		457.44375	do	33.	
457.0125	do	30.		457.450	do.		
457.01875	do	33.		457.45625 457.4625	do	33. 30.	
457.025	do.			457.46875	dodo	33.	
457.03125	do	33, 84.		457.475	do		LR
457.0375	do	30, 84.		457.48125	do	33, 84.	
457.04375 457.050	dodo.	33, 84.		457.4875	do	30, 84.	
457.05625	do	33, 84.		457.49375	do	33, 84.	
457.0625	do	30, 84.		457.500 457.50625	do.	33, 84.	
457.06875	do	33, 84.		457.5125	dodo	30, 84.	
457.075	do.	'		457.51875	do	33, 84.	
457.08125	do	33, 84.		457.525	do	12, 47, 60.	
457.0875	do	30, 84.		457.53125	do	11, 12, 33,	
457.09375	do	33, 84.				47, 60.	
457.100	do.	00.04		457.5375	do	11, 12, 30,	
457.10625 457.1125	do	33, 84. 30, 84.		457.54075		47, 60.	
457.11875	do	33, 84.		457.54375	do	11, 12, 33, 47, 60.	
457.125	do.			457.550	do	12, 47, 60.	
457.13125	do	33, 84.		457.55625	do	11, 12, 33,	
457.1375	do	30, 84.				47, 60.	
457.14375	do	33, 84.		457.5625	do	12, 30, 47,	
457.150	do.					60.	
457.15625 457.1625	do	33, 84. 30, 84.		457.56875	do	11, 12, 33,	
457.16875	do	33, 84.		457.575	do	47, 60. 12, 47, 60.	
457.175	do.	35, 64.		457.58125	do	11, 12, 33,	
457.18125	do	33, 84.		.07.00720		47, 60.	
457.1875	do	30, 84.		457.5875	do	12, 30, 47,	
457.19375	do	33, 84.				60.	
457.200	do.			457.59375	do	11, 12, 33,	
457.20625	do	33.		457.000		47, 60.	
457.2125 457.21875	dodo	30. 33.		457.600 457.60625	dodo	12, 47, 60. 11, 12, 33,	
457.225	do.	55.		701.00020		47, 60.	
457.23125	do	33.		457.6125	do	12, 30, 47,	
457.2375	do	30.				60.	

47 CFR Ch. I (10-1-20 Edition)

§ 90.35

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
457.61875	do	11, 12, 33, 47, 60.		460.66875 460.675	do	33, 61, 62. 61, 62.	
4E7 COE	do.	47, 00.		460.68125			
457.625		00.04			do	33, 61, 62.	
457.63125	do	33, 84.		460.6875	do	30, 61, 62,	
457.6375	do	30, 84.				69.	
457.64375	do	33, 84.		460.69375	do	33, 61, 62.	
457.650	do.			460.700	do	61, 62.	
457.65625	do	33, 84.		460.70625	do	33, 61, 62.	
457.6625	do	30, 84.		460.7125	do	30, 61, 62,	
457.66875	do	33, 84.		10017 120 111111111		69.	
457.675	do.	,		460.71875	do	33, 61, 62.	
457.68125	do	33, 84.			uo		
457.6875	do	30, 84.		460.725	do	61, 62.	
				460.73125	do	33, 61, 62.	
457.69375	do	33, 84.		460.7375	do	30, 61, 62,	
457.700	do.					69.	
457.70625	do	33, 84.		460.74375	do	33, 61, 62.	
457.7125	do	30, 84.		460.750	do	61, 62.	
457.71875	do	33, 84.		460.75625	do	33, 61, 62.	
457.725	do.	· ·	1	460.7625	do		
457.73125	do	33.	1	400./025	uu	30, 61, 62,	
457.7375	do	30.	1		l .	69.	
				460.76875	do	33, 61, 62.	
457.74375	do	33.	1	460.775	do	61, 62.	
457.750	do.			460.78125	do	33, 61, 62.	
457.75625	do	33.		460.7875	do	30, 61, 62,	
457.7625	do	30.		100.7070		69.	
457.76875	do	33.		460.79375	do		
457.775	do		LR			33, 61, 62.	
457.78125	do	33, 84.		460.800	do	61, 62.	
457.7875	do	30, 84.		460.80625	do	33, 61, 62.	
457.79375	do	33, 84.		460.8125	do	30, 61, 62,	
		33, 64.				69.	
457.800	do.			460.81875	do	33, 61, 62.	
457.80625	do	33, 84.		460.825	do	61, 62.	
457.8125	do	30, 84.		460.83125	do	33, 61, 62.	
457.81875	do	33, 84.					
457.825	do		LR	460.8375	do	30, 61, 62,	
457.83125	do	33, 84.				69.	
457.8375	do	30, 84.		460.84375	do	33, 61, 62.	
457.84375	do	33, 84.		460.850	do	61, 62.	
457.850	do.	00, 04.		460.85625	do	33, 61, 62.	
457.85625		33, 84.		460.8625	do	30, 61, 62,	
	do					69.	
457.8625	do	30, 84.		460.86875	do	33, 61, 62.	
457.86875	do	33, 84.					
457.875	do		LR	460.875	do	61, 62.	
457.88125	do	33, 84.		460.88125	do	33, 61, 62.	
457.8875	do	30, 84.		460.8875	do	30, 61, 62,	
457.89375	do	33, 84.				69.	
457.900	do	00, 04.	LR	460.89375	do	33, 61, 62.	
				460.900	do	63, 64, 65.	
457.90625	do	33	LR	460.90625	do	33, 63, 65,	
457.9125	do	30	LR	.00.00020			
457.91875	do	33	LR	100 0105		87.	
457.925	do	59	LR	460.9125	do	63, 65, 83	
457.93125	do	33, 59	LR			87.	
457.9375	do	30, 59	LR	460.91875	do	33, 63, 65,	
457.94375	do	33, 59	LR			87.	
457.950		59	LR	460.925	do	63, 64, 65.	
				460.93125	do	33, 63, 65,	
457.95625	do	33, 59	LR	400.93123	uo		
457.9625	do	30, 59	LR			87.	
457.96875	do	33, 59	LR	460.9375	do	63, 65, 83,	
457.975	do.					87.	
457.98125	do	33, 84.		460.94375	do	33, 63, 65,	
457.9875	do	30, 84.	1			87.	
457.99375	do	33, 84.		460.950	do	63, 64, 65.	
		JJ, 04.	1				
458.000	do.			460.95625	do	33, 63, 65,	
458.00625	do	33.			l .	87.	
458.0125	do	30.		460.9625	do	63, 65, 83,	
458.01875	do	33.				87.	
459.000	Base or mobile	8	IP	460.96875	do	33, 63, 65,	
460.650	do	61, 62.				87.	
460.65625	do	33, 61, 62.		460.975	do	64, 65, 66	
460.6625	do	30, 61, 62,	1	460.98125	do	33, 65, 66,	
		69.	I .		i .	l 87. l	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

	I ABLE—Cont	inued			I ABLE—Cont	inued	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
460.9875	do	65, 66, 83, 87.		461.39375 461.400	do	33, 62. 62.	
460.99375	do	33, 65, 66, 87.		461.40625 461.4125	do	33, 62. 30, 62.	
461.000	do	64, 65, 66.		461.41875	do	33, 62.	
461.00625	do	33, 65, 66,		461.425	do	62.	
461.0125	do	87. 65, 66, 83,		461.43125 461.4375	do	33, 62. 30, 62.	
		87.		461.44375	do	33, 62.	
461.01875	do	33, 65, 66, 87.		461.450 461.45625	dodo	62. 33, 62.	
461.025	do	62.		461.4625	do	30, 62.	
461.03125	do	33, 86.		461.46875	do	33, 62.	
461.0375 461.04375	dodo	83, 86. 33, 86.		461.475 461.48125	dodo	62. 33, 62.	
461.050	do	62.		461.4875	do	30, 62.	
461.05625	do	33, 86.		461.49375 461.500	dodo	33, 62.	
461.0625 461.06875	dodo	83, 86. 33, 86.		461.50625	do	62. 33, 62.	
461.075	do	62.		461.5125	do	30, 62.	
461.08125	do	33, 86.		461.51875	do	33, 62.	
461.0875 461.09375	dodo	83, 86. 33, 86.		461.525 461.53125	dodo	62. 33, 62.	
461.100	do	62.		461.5375	do	30, 62.	
461.10625	do	33, 86.		461.54375	do	33, 62.	
461.1125 461.11875	dodo	83, 86. 33, 86.		461.550 461.55625	dodo	62. 33, 62.	
461.125	do	62.		461.5625	do	30, 62.	
461.13125	do	33, 86.		461.56875	do	33, 62.	
461.1375 461.14375	dodo	83, 86. 33, 86.		461.575 461.58125	dodo	62. 33, 62.	
461.150	do	62.		461.5875	do	30, 62.	
461.15625	do	33, .		461.59375	do	33, 62.	
461.1625 461.16875	dodo	83, 86. 33, 86.		461.600 461.60625	dodo	62. 33, 62.	
461.175	do	62.		461.6125	do	30, 62.	
461.18125	do	33, 86.		461.61875	do	33, 62.	
461.1875 461.19375	dodo	83, 86. 33, 86.		461.625 461.63125	dodo	62. 33, 62.	
461.200	do	62.		461.6375	do	30, 62.	
461.20625	do	33, 86.		461.64375	do	33, 62.	
461.2125 461.21875	dodo	83, 86. 33, 86.		461.650 461.65625	dodo	62. 33, 62.	
461.225	do	62.		461.6625	do	30, 62.	
461.23125	do	33, 86.		461.66875	do	33, 62.	
461.2375 461.24375	dodo	83, 86. 33, 86.		461.675 461.68125	dodo	62. 33, 62.	
461.250	do	62.		461.6875	do	30, 62.	
461.25625	do	33, 86.		461.69375	do	33, 62.	
461.2625 461.26875	dodo	83, 86. 33, 86.		461.700 461.70625	dodo	62. 33, 62.	
461.275	do	62.		461.7125	do	30, 62.	
461.28125	do	33, 86.		461.71875	do	33, 62.	
461.2875 461.29375	dodo	83, 86. 33, 86.		461.725 461.73125	do	62.	
461.300	do	62.		461.7375	dodo	33, 62. 30, 62.	
461.30625	do	33, 86.		461.74375	do	33, 62.	
461.3125	do	83, 86.		461.750	do	62.	
461.31875 461.325	dodo	33, 86. 62.		461.75625 461.7625	do	33, 62. 30, 62.	
461.33125	do	33, 86.		461.76875	do	33, 62.	
461.3375	do	83, 86.		461.775	do	62.	
461.34375 461.350	dodo	33, 86. 62.		461.78125 461.7875	dodo	33, 62. 30, 62.	
461.35625	do	33, 86.		461.79375	do	33, 62.	
461.3625	do	83, 86.		461.800	do	62.	
461.36875 461.375	dodo	33, 86. 62.		461.80625 461.8125	dodo	33, 62. 30, 62.	
461.38125	do	33, 62.		461.81875	do	33, 62.	
461.3875	do	30, 62.		461.825	do	62.	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

	TABLE COIN	iiiucu			TABLE CON	iiiucu	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
461.83125	do	33, 62.		462.26875	do	33, 85.	
461.8375	do	30, 62.		462.275	do.	00.05	
461.84375	do	33, 62.		462.28125	do	33, 85.	
461.850	do	62.		462.2875	do	83, 85.	
461.85625	do	33, 62.		462.29375	do	33, 85.	
461.8625	do	30, 62.		462.300	do.		
461.86875	do	33, 62.		462.30625	do	33, 85.	
461.875	do	62.		462.3125	do	83, 85.	
461.88125	do	33, 62.		462.31875	do	33, 85.	
461.8875	do	30, 62.		462.325	do.		
461.89375	do	33, 62.		462.33125	do	33, 85.	
461.900	do	62.		462.3375	do	83, 85.	
461.90625	do	33, 62.		462.34375	do	33, 85.	
461.9125	do	30, 62.		462.350	do.	,	
461.91875	do	33, 62.		462.35625	do	33, 85.	
461.925	do	62.		462.3625	do	83, 85.	
461.93125	do	33, 62.		462.36875	do	33, 85.	
461.9375	do	30, 62.		462.375	do.	00, 00.	
461.94375	do	33, 62.		462.38125	do	33, 85.	
461.950	do	62.		462.3875	do	83, 85.	
461.95625	do	33, 62.		462.39375	do		
461.9625	do	30, 62.		462.400	do.	33, 85.	
461.96875	do	33, 62.		462.40625	do	33, 85.	
461.975	do	62.		462.4125	do	83, 85.	
461.98125	do	33, 62.		462.41875	do	33, 85.	
461.9875	do	30, 62.		462.425	do.	00, 00.	
461.99375	do	33, 62.		462.43125	do	33, 85.	
462.000	do	62.		462.4375	do	83, 85.	
462.00625	do	33, 62.		462.44375	do	33, 85.	
462.0125	do	30, 62.		462.450	do.	,	
462.01875	do	33, 62.		462.45625	do	33, 84.	
462.025	do	62.		462.4625	do	83, 84.	
462.03125	do	33, 62.		462.46875	do	33, 84.	
462.0375	do	30, 62.		462.475	do		IP, IW
462.04375	do	33, 62.		462.48125	do	33, 84.	,
462.050	do	62.		462.4875	do	83, 84.	
462.05625	do	33, 62.		462.49375	do	84.	
462.0625	do	30, 62.		462.500	do.		
462.06875	do	33, 62.		462.50625	do	33, 84.	
462.075	do	62.		462.5125	do	83, 84.	
462.08125	do	33, 62.		462.51875	do	33, 84.	
462.0875	do	30, 62.		462.525	do		IP, IW
462.09375	do	33, 62.		462.53125	do	33.	
462.100	do	62.		462.5375	do	2.	
462.10625	do	33, 62.		462.7375	do	2.	
462.1125	do	30, 62.		462.750	Base	29, 36.	
462.11875	do	33, 62.		462.7625	Mobile	67, 86.	
462.125	do	62.		462.775	Base	29, 36.	
462.13125	do	33, 62.		462.7875	Mobile	67, 86.	
462.1375	do	30, 62.		462.800	Base	29, 36.	
462.14375	do	33, 62.		462.8125	Mobile	67, 86.	
462.150	do	62.		462.825	Base	29, 36.	
462.15625	do	33, 62.		462.8375	Mobile	67, 86.	
462.1625	do	30, 62.		462.850	Base	29, 36.	
462.16875	do	33, 62.		462.8625	Mobile	67, 86.	
462.175	do	62.		462.875	Base	29, 36.	
462.18125	do	33, 84.		462.8875	Mobile	67, 86.	
462.1875	do	83, 84.		462.900	Base	29, 36.	
462.19375	do	33, 84.		462.9125	Mobile	67, 86.	
462.200	do.			462.925	Base	29, 36.	
462.20625	do	33, 85.		462.9375	Mobile	88	
462.2125	do	83, 85.		462.94375	Base or mobile	33.	
462.21875	do	33, 85.		463.200	do	62.	
462.225	do.			463.20625	do	33, 62.	
462.23125	do	33, 85.		463.2125	do	30, 62.	
462.2375	do	83, 85.		463.21875	do	33, 62.	
462.24375	do	33, 85.		463.225	do	62.	
462.250	do.	00.05		463.23125	do	33, 62.	
462.25625	do	33, 85.		463.2375	do	30, 62.	
402.2025	do	83, 85.		463.24375	ıao	33, 62.	ı

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
463.250	do	62.		463.6875	do	30, 62.	
463.25625	do	33, 62.		463.69375	do	33, 62.	
463.2625	do	30, 62.		463.700	do	62.	
463.26875	do	33, 62.		463.70625	do	33, 62.	
463.275	do	62.		463.7125	do	30, 62.	
463.28125	do	33, 62.		463.71875	do	33, 62.	
463.2875	do	30, 62.		463.725	do	62.	
463.29375	do	33, 62.		463.73125	do	33, 62.	
463.300	do	62.		463.7375	do	30, 62.	
463.30625	do	33, 62.		463.74375	do	33, 62.	
463.3125	do	30, 62.		463.750	do	62.	
463.31875	do	33, 62.		463.75625	do	33, 62.	
463.325	do	62.		463.7625	do	30, 62.	
463.33125	do	33, 62.		463.76875	do	33, 62.	
463.3375	do	30, 62.		463.775	do	62.	
463.34375	do	33, 62.		463.78125	do	33, 62.	
463.350	do	62.		463.7875	do	30, 62.	
463.35625	do	33, 62.		463.79375	do	33, 62.	
463.3625	do	30, 62.		463.800	do	62.	
463.36875	do	33, 62.		463.80625	do	33, 62.	
463.375	do	62.		463.8125	do	30, 62.	
463.38125	do	33, 62.		463.81875	do	33, 62.	
463.3875	do	30, 62.		463.825	do	62.	
463.39375	do	33, 62.		463.83125	do	33, 62.	
463.400	do	62.		463.8375	do	30, 62.	
463.40625	do	33, 62.		463.84375	do	33, 62.	
463.4125	do	30, 62.		463.850	do	62.	
463.41875 463.425	do	33, 62. 62.		463.85625	do	33, 62. 30, 62.	
463.43125	dodo			463.8625 463.86875	dodo		
463.4375	do	33, 62. 30, 62.		463.875	do	33, 62. 62.	
463.44375	do	33, 62.		463.88125	do		
463.450	do	62.		463.8875	do	33, 62. 30, 62.	
463.45625	do	33, 62.		463.89375	do	33, 62.	
463.4625	do	30, 62.		463.900	do	62.	
463.46875	do	33, 62.		463.90625	do	33, 62.	
463.475	do	62.		463.9125	do	30, 62.	
463.48125	do	33, 62.		463.91875	do	33, 62.	
463.4875	do	30, 62.		463.925	do	62.	
463.49375	do	33, 62.		463.93125	do	33, 62.	
463.500	do	62.		463.9375	do	30, 62.	
463.50625	do	33, 62.		463.94375	do	33, 62.	
463.5125	do	30, 62.		463.950	do	62.	
463.51875	do	33, 62.		463.95625	do	33, 62.	
463.525	do	62.		463.9625	do	30, 62.	
463.53125	do	33, 62.		463.96875	do	33, 62.	
463.5375	do	30, 62.		463.975	do	62.	
463.54375	do	33, 62.		463.98125	do	33, 62.	
463.550	do	62.		463.9875	do	30, 62.	
463.55625	do	33, 62.		463.99375	do	33, 62.	
463.5625	do	30, 62.		464.000	do	62.	
463.56875	do	33, 62.		464.00625	do	33, 62.	
463.575	do	62.		464.0125	do	30, 62.	
463.58125	do	33, 62.		464.01875	do	33, 62.	
463.5875	do	30, 62.		464.025	do	62.	
463.59375	do	33, 62.		464.03125	do	33, 62.	
463.600	do	62.		464.0375	do	30, 62.	
463.60625	do	33, 62.		464.04375	do	33, 62.	
463.6125	do	30, 62.		464.050	do	62.	
463.61875	do	33, 62.		464.05625	do	33, 62.	
463.625	do	62.		464.0625	do	30, 62.	
463.63125	do	33, 62.		464.06875	do	33, 62.	
463.6375	do	30, 62.		464.075	do	62.	
463.64375	do	33, 62.		464.08125	do	33, 62.	
463.650	do	62.		464.0875	do	30, 62.	
463.65625	do	33, 62.		464.09375	do	33, 62.	
463.6625	do	30, 62.		464.100	do	62.	
463.66875	do	33, 62.		464.10625	do	33, 62.	
463.675	do	62.		464.1125	do	30, 62.	
463.68125	ldo	33, 62.		464.11875	ldo	33, 62.	

47 CFR Ch. I (10-1-20 Edition)

§ 90.35

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
464.125	do	62.		464.5875	do	30, 62.	
464.13125	do	33, 62.		464.59375	do	33, 62.	
464.1375	do	30, 62.		464.600	do	62.	
464.14375	do	33, 62.		464.60625	do	33, 62.	
464.150	do	62.		464.6125	do	30, 62.	
464.15625	do	33, 62.		464.61875	do	33, 62.	
464.1625	do	30, 62.		464.625	do	62.	
464.16875	do	33, 62.		464.63125	do	33, 62.	
464.175	do	62.		464.6375	do	30, 62.	
464.18125	do	33, 62.		464.64375	do	33, 62.	
464.1875	do	30, 62.		464.650	do	62.	
464.19375	do	33, 62.		464.65625	do	33, 62.	
464.200	do	62.		464.6625	do	30, 62.	
464.20625	do	33, 62.		464.66875	do	33, 62.	
464.2125	do	30, 62.		464.675	do	62.	
464.21875	do	33, 62.		464.68125	do	33, 62.	
464.225	do	62.		464.6875	do	30, 62.	
464.23125	do	33, 62.		464.69375	do	33, 62.	
464.2375	do	30, 62.		464.700	do	62.	
464.24375	do	33, 62.		464.70625	do	33, 62.	
464.250	do	62.		464.7125	do	30, 62.	
464.25625	do	33, 62.		464.71875	do	33, 62.	
464.2625	do	30, 62.		464.725	do	62.	
464.26875	do	33, 62.		464.73125	do	33, 62.	
464.275	do	62.		464.7375	do	30, 62.	
464.28125	do	33, 62.		464.74375	do	33, 62.	
464.2875	do	30, 62.		464.750	do	62.	
464.29375	do	33, 62.		464.75625	do	33, 62.	
464.300	do	62.		464.7625	do	30, 62.	
464.30625	do	33, 62.		464.76875	do	33, 62.	
464.3125	do	30, 62.		464.775	do	62.	
464.31875	do	33, 62.		464.78125	do	33, 62.	
464.325	do	62.		464.7875	do	30, 62.	
464.33125	do	33, 62.		464.79375	do	33, 62.	
464.3375	do	30, 62.		464.800	do	62.	
464.34375	do	33, 62.		464.80625	do	33, 62.	
464.350	do	62.		464.8125	do	30, 62.	
464.35625	do	33, 62.		464.81875	do	33, 62.	
464.3625	do	30, 62.		464.825	do	62.	
464.36875	do	33, 62.		464.83125	do	33, 62.	
464.375	do	62.		464.8375	do	30, 62.	
464.38125	do	33, 62.		464.84375	do	33, 62.	
464.3875	do	30, 62.		464.850	do	62.	
464.39375	do	33, 62.		464.85625	do	33, 62.	
464.400	do	62.		464.8625	do	30, 62.	
464.40625	do	33, 62.		464.86875	do	33, 62.	
464.4125	do	30, 62.		464.875	do	62.	
464.41875	do	33, 62.		464.88125	do	33, 62.	
464.425	do	62.		464.8875	do	30, 62.	
464.43125 464.4375	do	33, 62. 30, 62.		464.89375	do	33, 62. 62.	
404.4373	do	30, 62.		464.900	do		
464.44375	do			464.90625	do	33, 62.	
464.450 464.45625	do	62. 33, 62.		464.9125 464.91875	do	30, 62. 33, 62.	
464 4625	do				do	62.	
464.4625	do	30, 62.		464.925	do		
464.46875 464.475	do	33, 62. 62.		464.93125 464.9375	do	33, 62. 30, 62.	
464.48125	do			464.94375	do	30, 62.	
464.4875	do	33, 86. 83, 86.		464.950	do		
464.500	dodo	10, 34.		464.95625	do	62. 33, 62.	
464.5125	do	83, 86.		464.9625	do	30, 62.	
464.51875	do	33, 86.		464.96875	do	33, 62.	
464.525	do	62.		464.975	do	62.	
464.53125	do	33, 86.		464.98125	do	33, 62.	
464.5375	do	83, 86.		464.9875	Mobile	67.	
				465.000	Base	29, 34, 36.	
		10.34					
464.550	do	10, 34. 83, 86					
464.550 464.5625	dodo	83, 86.		465.0125	Mobile	88.	
464.550 464.5625 464.56875	dododododo	83, 86. 33, .		465.0125 465.01875	Mobiledo	88. 33, 34.	
464.550 464.5625	dodo	83, 86. 33, . 62.		465.0125	Mobile	88.	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

§ 90.35

	TABLE—CON	inueu			TABLE—COM	illueu	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
465.6625	do	30, 62, 68,		466.03125	do	33, 86.	
		69.		466.0375	do	83, 86.	
465.66875	do	33, 62, 68.		466.04375	do	33, 86.	
465.675	do	62, 68.		466.050	do	62.	
465.68125	do	33, 62, 68.		466.05625	do	33, 86.	
465.6875	do	30, 62, 68,		466.0625	do	83, 86.	
		69.		466.06875	do	33, 86.	
465.69375	do	33, 62, 68.		466.075	do	62.	
465.700	do	62, 68.		466.08125	do	33, 86.	
465.70625	do	33, 62, 68.		466.0875	do	83, 86.	
465.7125	do	30, 62, 68,		466.09375	do	33, 86.	
		69.		466.100	do	62.	
465.71875	do	33, 62, 68.		466.10625	do	33, 86.	
465.725	do	62, 68.		466.1125	do	83, 86.	
465.73125	do	33, 62, 68.		466.11875	do	33, 86.	
465.7375	do	30, 62, 68,		466.125	do	62.	
		69.		466.13125	do	33, 86.	
465.74375	do	33, 62, 68.		466.1375	do	83, 86.	
465.750	do	62, 68.		466.14375	do	33, 86.	
465.75625	do	33, 62, 68.		466.150	do	62.	
465.7625	do	30, 62, 68,		466.15625	do	33, 86.	
-JJJ.1 UZJ	do	69.		466.1625	do	83, 86.	
465.76875	do	33, 62, 68.		466.16875	do	33, 86.	
465.775	do	62, 68.		466.175	do	62.	
465.78125	do	33, 62, 68.		466.18125	do	33, 84.	
465.7875	do			466.1875	do	83, 84.	
405./8/5	do	30, 62, 68,		466.19375	do	33, 84.	
40E 7007E	ala.	69.		466.200	do	62.	
465.79375	do	33, 62, 68.		466.20625	do	33, 85.	
465.800	do	62, 68.		466.2125	do		
465.80625	do	33, 62, 68.		400.2125		83, 85.	
465.8125	do	30, 62, 68,		466.21875	do	33, 85.	
105.01075		69.		466.225	do	62.	
465.81875	do	33, 62, 68.		466.23125	do	33, 85.	
465.825	do	62, 68.		466.2375	do	83, 85.	
465.83125	do	33, 62, 68.		466.24375	do	33, 85.	
465.8375	do	30, 62, 68,		466.250	do	62.	
		69.		466.25625	do	33, 85.	
465.84375	do	33, 62, 68.		466.2625	do	83, 85.	
465.850	do	62, 68.		466.26875	do	33, 85.	
465.85625	do	33, 62, 68.		466.275	do	62.	
465.8625	do	30, 62, 68,		466.28125	do	33, 85.	
		69.		466.2875	do	83, 85.	
465.86875	do	33, 62, 68.		466.29375	do	33, 85.	
465.875	do	62, 68.		466.300	do	62.	
465.88125	do	33, 62, 68.		466.30625	do	33, 85.	
465.8875	do	30, 62, 68,		466.3125	do	83, 85.	
		69.		466.31875	do	33, 85.	
465.89375	do	33, 62, 68.		466.325	do	62.	
465.900	do	63, 64.		466.33125	do	33, 85.	
465.90625	do	33, 63, 87.		466.3375	do	83, 85.	
465.9125	do	63, 83, 87.		466.34375	do	33, 85.	
465.91875	do	33, 63, 87.		466.350	do	62.	
465.925	do	63, 64.		466.35625	do	33, 85.	
465.93125	do	33, 63, 87.		466.3625	do	83, 85.	
465.9375	do	63, 83, 87.		466.36875	do	33, 85.	
465.94375	do	33, 63, 87.		466.375	do	62.	
465.950	do	63, 64.		466.38125	do	33, 85.	
465.95625	do	33, 63, 87.		466.3875	do	83, 85.	
465.9625	do	63, 83, 87.		466.39375	do	33, 85.	
465.96875	do	33, 63, 64.		466.400	do	62.	
465.975	do	64, 66.		466.40625	do	33, 85.	
465.98125	do			466.4125	do		
		33, 66, 87.				83, 85.	
465.9875	do	66, 83, 87.		466.41875	do	33, 85.	
465.99375	do	33, 66, 87.		466.425	do	62.	
466.000	do	64, 66.		466.43125	do	33, 85.	
466.00625	do	33, 66, 87.		466.4375	do	83, 85.	
466.0125	do	66, 69, 83,		466.44375	do	33, 85.	
		87.		466.450	do	62.	
					i ala	100 04	
466.01875	dodo	33, 66, 87. 62.		466.45625 466.4625	dodo	33, 84. 83, 84.	

47 CFR Ch. I (10-1-20 Edition)

§ 90.35

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
466.46875	do	33, 84.		466.90625	do	33, 62.	
466.475	do	62.		466.9125	do	67, 86.	
466.48125	do	33, 84.		466.91875	do	33, 62.	
466.4875	do	83, 84.		466.925	do	62.	
466.49375	do	33, 84.		466.93125	do	33, 62.	
466.500	do	62.		466.9375	do	88.	
466.50625 466.5125	dodo	33, 84. 83, 84.		466.94375 466.950	do	33, 62. 62.	
466.51875	do	33, 84.		466.95625	dodo	33, 62.	
466.525	do	62.		466.9625	do	30, 62.	
466.53125	do	33, 62.		466.96875	do	33, 62.	
466.5375	do	30, 62.		466.975	do	62.	
466.54375	do	33, 62.		466.98125	do	33, 62.	
466.550	do	62.		466.9875	do	30, 62.	
466.55625	do	33, 62.		466.99375	do	33, 62.	
466.5625	do	30, 62.		467.000	do	62.	
466.56875	do	33, 62.		467.00625	do	33, 62.	
466.575	do	62.		467.0125	do	30, 62.	
466.58125	do	33, 62.		467.01875	do	33, 62.	
466.5875	do	30, 62.		467.025	do	62.	
466.59375	do	33, 62.		467.03125	do	33, 62.	
466.600	do	62.		467.0375	do	30, 62.	
466.60625	do	33, 62.		467.04375	do	33, 62.	
466.6125	do	30, 62.		467.050	do	62.	
466.61875	do	33, 62.		467.05625	do	33, 62.	
466.625	do	62.		467.0625	do	30, 62.	
466.63125	do	33, 62.		467.06875	do	33, 62. 62.	
466.6375 466.64375	dodo	30, 62. 33, 62.		467.075 467.08125	dodo	33, 62.	
466.650	do	62.		467.0875	do	30, 62.	
466.65625	do	33, 62.		467.09375	do	33, 62.	
466.6625	do	30, 62.		467.100	do	62.	
466.66875	do	33, 62.		467.10625	do	33, 62.	
466.675	do	62.		467.1125	do	30, 62.	
466.68125	do	33, 62.		467.11875	do	33, 62.	
466.6875	do	30, 62.		467.125	do	62.	
466.69375	do	33, 62.		467.13125	do	33, 62.	
466.700	do	62.		467.1375	do	30, 62.	
466.70625	do	33, 62.		467.14375	do	33, 62.	
466.7125	do	30, 62.		467.150	do	62.	
466.71875	do	33, 62.		467.15625	do	33, 62.	
466.725	do	62.		467.1625	do	30, 62.	
466.73125	do	33, 62.		467.16875	do	33, 62.	
466.7375	do	30, 62.		467.175	do	62.	
466.74375	do	33, 62.		467.18125	do	33, 62.	
466.750	do	62.		467.1875	do	30, 62.	
466.75625	do	33, 62.		467.19375	do	33, 62.	
466.7625	do	30, 62.		467.200	do.	,,	
466.76875 466.775	dodo	33, 62. 62.		467.20625 467.2125	dodo	33.	
466.78125	do	33, 62.		467.21875	do	33.	
466.7875	do	30, 62.		467.225	do.	55.	
466.79375	do	33, 62.		467.23125	do	33.	
466.800	do	62.		467.2375	do	30.	
466.80625	do	33, 62.		467.24375	do	33.	
466.8125	do	30, 62.		467.250	do.	55.	
466.81875	do	33, 62.		467.25625	do	33.	
466.825	do	62.		467.2625	do	30.	
466.83125	do	33, 62.		467.26875	do	33.	
466.8375	do	30, 62.		467.275	do.		
466.84375	do	33, 62.		467.28125	do	33.	
466.850	do	62.		467.2875	do	30.	
466.85625	do	33, 62.		467.29375	do	33.	
466.8625	do	67, 86.		467.300	do.		
466.86875	do	33, 62.		467.30625	do	33.	
466.875	do	62.		467.3125	do	30.	
466.88125	do	33, 62.		467.31875	do	33.	
466.8875	do	67, 86.		467.325	do.		
.00.00.0		1		407 00105	ا مام	100	
466.89375 466.900	dodo	33, 62.		467.33125 467.3375	dodo	33.	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
467.34375 467.350	do	33.		467.925 467.93125	do	11, 12, 35. 33.	
407.330		33.					
467.35625				467.9375	do	30, 67.	
467.3625	do	30.		467.94375	do	33.	
467.36875	do	33.		468.200	do	62.	
467.375	do.			468.20625	do	33, 62.	
467.38125	do	33.		468.2125	do	30, 62.	
467.3875	do	30.		468.21875	do	33, 62.	
467.39375	do	33.		468.225	do	62.	
467.400	do.			468.23125	do	33, 62.	
467.40625	do	33.		468.2375	do	30, 62.	
467.4125	do	30.		468.24375	do	33, 62.	
467.41875	do	33.		468.250	do	62.	
467.425	do.			468.25625	do	33, 62.	
467.43125	do	33.		468.2625	do	30, 62.	
467.4375	do	30.		468.26875	do	33, 62.	
467.44375	do	33.		468.275	do	62.	
467.450	do.			468.28125	do	33, 62.	
467.45625	do	33.		468.2875	do	30, 62.	
467.4625	do	30.		468.29375	do	33, 62.	
467.46875	do	33.		468.300	do	62.	
467.475	do		IP, IW	468.30625	do	33, 62.	
467.48125	do	33.	'	468.3125	do	30, 62.	
467.4875	do	30.		468.31875	do	33, 62.	
467.49375	do	33.		468.325	do	62.	
467.500	do.			468.33125	do	33, 62.	
467.50625	do	33.		468.3375	do	30, 62.	
467.5125	do	30.		468.34375	do	33, 62.	
467.51875	do	33.		468.350	do	62.	
467.525	do	00.	IP, IW	468.35625	do	33, 62.	
467.53125	do	33.	" , "**	468.3625	do	30, 62.	
467.5375	do	2.		468.36875	do	33, 62.	
467.7375	do	2.		468.375	do	62.	
467.74375	do	33, 62.		468.38125	do	33, 62.	
467.750	do	11, 12, 35,		468.3875	do	30, 62.	
407.730	uo	60.		468.39375	do	33, 62.	
467.75625	do	11, 12, 33,		468.400	do	62.	
407.73023	uo			468.40625	do	33, 62.	
467.7625	do	35, 60. 11, 12, 30,		468.4125	do	30, 62.	
407.7023	uo			468.41875	do	33, 62.	
407 70075	ala.	35, 60.					
467.76875	do	11, 12, 33,		468.425	do	62.	
407 775		35, 60.		468.43125	do	33, 62.	
467.775	do	11, 12, 35,		468.4375	do	30, 62.	
107 70105		60.		468.44375	do	33, 62.	
467.78125	do	11, 12, 33,		468.450	do	62.	
		35, 60.		468.45625	do	33, 62.	
467.7875	do	11, 12, 30,		468.4625	do	30, 62.	
407 700	l .	35, 60.		468.46875	do	33, 62.	
467.79375	do	11, 12, 33,		468.475	do	62.	
407.000		35, 60.		468.48125	do	33, 62.	
467.800	do	11, 12, 35,		468.4875	do	30, 62.	
407.000	l .	60.		468.49375	do	33, 62.	
467.80625	do	11, 12, 33,		468.500	do	62.	
	l .	35, 60.		468.50625	do	33, 62.	
467.8125	do	11, 12, 30,		468.5125	do	30, 62.	
		35, 60.		468.51875	do	33, 62.	
467.81875	do	11, 12, 33,		468.525	do	62.	
		35, 60.		468.53125	do	33, 62.	
467.825	do	11, 12, 35,		468.5375	do	30, 62.	
		60.		468.54375	do	33, 62.	
467.83125	do	11, 12, 33,		468.550	do	62.	
		35, 60.		468.55625	do	33, 62.	
467.8375	do	11, 12, 30,		468.5625	do	30, 62.	
		35, 60.		468.56875	do	33, 62.	
467.850	do	11, 12, 35.		468.575	do	62.	
467.8625	do	67.	1	468.58125	do	33, 62.	
467.875	do	11, 12, 35.		468.5875	do	30, 62.	
467.8875	do	67.		468.59375	do	33, 62.	
467.900	do	11, 12, 35.		468.600	do	62.	
	do	67.	1	468.60625	do	33, 62.	
-07.0120	uo	. 07.	•	-50.00025	uo	1 00, 02.	

INDUSTRIAL/BUSINESS POOL FREQUENCY TABLE—Continued

	TABLE COIN	iiiucu			TABLE COIN	illucu	
Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator	Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
468.6125	do	30, 62.	<u> </u>	469.050	do	62.	
468.61875	do	33, 62.		469.05625	do	33, 62.	
468.625	do	62.		469.0625	do	30, 62.	
468.63125	do	33, 62.		469.06875	do	33, 62.	
468.6375	do	30, 62.		469.075	do	62.	
468.64375	do	33, 62.		469.08125	do	33, 62.	
468.650	do	62.		469.0875	do	30, 62.	
468.65625	do	33, 62.		469.09375	do	33, 62.	
468.6625	do	30, 62.		469.100	do	62.	
468.66875	do	33, 62.		469.10625	do	33, 62.	
468.675	do	62.		469.1125	do	30, 62.	
468.68125	do	33, 62.		469.11875	do	33, 62.	
468.6875	do	30, 62.		469.125	do	62.	
468.69375	do	33, 62.		469.13125	do	33, 62.	
468.700	do	62.		469.1375	do	30, 62.	
468.70625	do	33, 62.		469.14375	do	33, 62.	
468.7125	do	30, 62.		469.150	do	62.	
468.71875	do	33, 62.		469.15625	do	33, 62.	
468.725	do	62.		469.1625	do	30, 62.	
468.73125	dodo	33, 62.		469.16875 469.175	dodo	33, 62.	
468.7375 468.74375	do	30, 62. 33, 62.		469.18125	do	62. 33, 62.	
468.750	do	62.		469.1875	do	30, 62.	
468.75625	do	33, 62.		469.19375	do	33, 62.	
468.7625	do	30, 62.		469.200	do	62.	
468.76875	do	33, 62.		469.20625	do	33, 62.	
468.775	do	62.		469.2125	do	30, 62.	
468.78125	do	33, 62.		469.21875	do	33, 62.	
468.7875	do	30, 62.		469.225	do	62.	
468.79375	do	33, 62.		469.23125	do	33, 62.	
468.800	do	62.		469.2375	do	30, 62.	
468.80625	do	33, 62.		469.24375	do	33, 62.	
468.8125	do	30, 62.		469.250	do	62.	
468.81875	do	33, 62.		469.25625	do	33, 62.	
468.825	do	62.		469.2625	do	30, 62.	
468.83125	do	33, 62.		469.26875	do	33, 62.	
468.8375	do	30, 62.		469.275	do	62.	
468.84375	do	33, 62.		469.28125	do	33, 62.	
468.850	do	62.		469.2875	do	30, 62.	
468.85625	do	33, 62.		469.29375	do	33, 62.	
468.8625	do	30, 62.		469.300	do	62.	
468.86875	do	33, 62.		469.30625	do	33, 62.	
468.875	do	62.		469.3125	do	30, 62.	
468.88125	do	33, 62.		469.31875	do	33, 62.	
468.8875	do	30, 62.		469.325	do	62.	
468.89375	do	33, 62.		469.33125	do	33, 62.	
468.900	do	62.		469.3375	do	30, 62.	
468.90625	do	33, 62.		469.34375	do	33, 62.	
468.9125	do	30, 62.		469.350	do	62.	
468.91875	do	33, 62.		469.35625	do	33, 62.	
468.925	do	62.		469.3625	do	30, 62.	
468.93125	do	33, 62.		469.36875	do	33, 62.	
468.9375	do	30, 62.		469.375	do	62.	
468.94375 468.950	do	33, 62. 62.		469.38125 469.3875	do	33, 62. 30, 62.	
					do		
468.95625	do	33, 62. 30, 62.		469.39375	do	33, 62. 62.	
468.9625 468.96875	dodo	33, 62.		469.400 469.40625	dodo	33, 62.	
		62.					
468.975 468.98125	do	33, 62.		469.4125 469.41875	dodo	30, 62. 33, 62.	
468.9875	do	30, 62.		469.425	do	62.	
468.99375	do	33, 62.		469.43125	do	33, 62.	
469.000	do	62.		469.4375	do	30, 62.	
469.00625	do	33, 62.		469.44375	do	33, 62.	
469.0125	do	30, 62.		469.450	do	62.	
469.01875	do	33, 62.		469.45625	do	33, 62.	
469.025	do	62.		469.4625	do	30, 62.	
469.03125	do	33, 62.		469.46875	do	33, 62.	
469.0375	do	30, 62.		469.475	do	62.	
	do	33, 62.		469.48125	do	33, 86.	
		,				,	

INDUSTRIAL/BUSINESS POOL FREQUENCY
TABLE—Continued

Coordi-

	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Frequency or band	Class tion	Limitations
469.4875	do .	 83, 86.
469.500	do .	 10, 34.
469.5125	do .	 83, 86.
469.51875	do .	 33, 86.
469.525		 62.
469.53125		 33, 86.
469.5375		 83, 86.
469.550		 10, 34.
469.5625 469.56875		 83, 86.
469.575		 33, 86. 62.
469.58125		 33, 62.
469.5875		 30, 62.
469.59375		 33, 62.
469.600		 62.
469.60625	do .	 33, 62.
469.6125		 30, 62.
469.61875		 33, 62.
469.625		 62.
469.63125	do .	 33, 62.
469.6375		 30, 62.
469.64375	do .	 33, 62.
469.650 469.65625		 62. 33, 62.
469.6625		 30, 62.
469.66875		 33, 62.
469.675	do .	 62.
469.68125		 33, 62.
469.6875		 30, 62.
469.69375	do .	 33, 62.
469.700		 62.
469.70625		 33, 62.
469.7125		 30, 62.
469.71875		 33, 62.
469.725 469.73125		 62. 33, 62.
469.7375		 30, 62.
469.74375		 33, 62.
469.750	do .	 62.
469.75625		 33, 62.
469.7625		 30, 62.
469.76875		 33, 62.
469.775 469.78125	do .	 62.
469.7875		 33, 62. 30, 62.
469.79375		 33, 62.
469.800		 62.
469.80625		 33, 62.
469.8125	do .	 30, 62.
469.81875		 33, 62.
469.825		 62.
469.83125		 33, 62.
469.8375		 30, 62.
469.84375		 33, 62.
469.850		 62.
469.85625 469.8625		 33, 62. 30, 62.
469.86875		 33, 62.
469.875		 62.
469.88125		 33, 62.
469.8875		 30, 62.
469.89375	do .	 33, 62.
469.900	do .	 62.
469.90625	do .	 33, 62.
469.9125		 30, 62.
469.91875	do .	 33, 62.
469.925	do .	 62.
469.93125 469.9375	do .	 33, 62. 30, 62
469.94375	do .	 30, 62. 33, 62.
	uo .	

Frequency or band	Class of sta- tion(s)	Limitations	Coordi- nator
469.950	do	62.	
469.95625	do	33, 62.	
469.9625	do	30, 62.	
469.96875	do	33, 62.	
469.975	do	62.	
469.98125	do	33, 62.	
470 to 512	Base or mobile	70.	
809 to 824	Mobile	71	
854 to 869	Base or mobile	71	
896 to 901	Mobile	71.	
928 and above	Operational fixed.	72.	
929 to 930	Base only	73.	
935 to 940	Base or mobile	71.	
1427 to 1432	Base, mobile or operational fixed	55	
2,450 to 2,500	Base or mobile	74.	
5850–5925	do	90, 91	Not appli- cable.
10,550 to 10, 680.	do	76.	

- (c) Explanation of assignment limitations appearing in the frequency table of paragraph (b)(3) of this section:
- (1) Use of this frequency is permitted as follows:
- (i) Only entities engaged in the following activities are eligible to use this spectrum, and then only in accordance with §90.266:
- (A) Prospecting for petroleum, natural gas or petroleum products;
- (B) Distribution of electric power or the distribution by pipeline of fuels or water;
- (C) Exploration, its support services, and the repair of pipelines; or
- (D) The repair of telecommunications circuits.
- (ii) Except as provided in this part, licensees may not use these frequencies in the place of other operational circuits permitted by the Commission's rules. Circuits operating on these frequencies may be used only for the following purposes:
- (A) Providing standby backup communications for circuits which have been disrupted and which directly affect the safety of life, property, or the national interest or are used for coordinating inter-utility, intra-utility, and power pool distribution of electric power;
- (B) Providing operational circuits during exploration;

- (C) Coordinating the repair of interutility, intra-utility, and power pool electric power distribution networks, or the repair of pipelines;
- (D) Exploratory efforts in mining for solid fuels, minerals, and metals important to the national interest;
- (E) Repair of pipelines used for the transmission of fuel or water;
- (F) Services supporting the exploration for energy or mineral resources important to the national interest, without which such exploration cannot be conducted; or
- (G) Coordinating the repair of wireline or point-to-point microwave circuits.
- (2) This frequency will be assigned with an authorized bandwidth not to exceed 4 kHz.
- (3) This frequency is available for assignment only to stations utilized for geophysical purposes.
- (4) Geophysical operations may use tone or impulse signaling for purposes other than indicating failure of equipment or abnormal conditions on this frequency. All such tone or impulse signaling shall be on a secondary basis and subject to the following limitations:
- (i) Maximum duration of a single non-voice transmission may not exceed 3 minutes;
- (ii) The bandwidth utilized for secondary tone or impulse signaling shall not exceed that authorized to the licensee for voice emission on the frequency concerned:
- (iii) Frequency loading resulting from the use of secondary tone or impulse signaling will not be considered in whole or in part, as a justification for authorizing additional frequencies in the licensee's mobile service system;
- (iv) The maximum transmitter output power for tone or impulse transmissions shall not exceed 50 watts.
- (5) Frequencies below 25 MHz will be assigned to base or mobile stations only upon a satisfactory showing that, from a safety of life standpoint, frequencies above 25 MHz will not meet the operational requirements of the applicant.
- (6) Frequencies may be assigned in pairs with the separation between base and mobile transmit frequencies being

- 5.26 MHz. A mobile station may be assigned the frequency which would normally be assigned to a base station for single frequency operation. However, this single-frequency operation may be subject to interference that would not occur to a two-frequency system. Base or mobile stations operating wholly within Standard Metropolitan Areas having 50,000 or more population (1950 Census) must be operated in the half-duplex mode.
- (7) This frequency is available for assignment to geophysical stations on a secondary basis to other licensees. Geophysical stations must cease operations on this frequency immediately upon receiving notice that interference is being caused to mobile service stations
- (8) This frequency is primarily available for oil spill containment and cleanup operations and for training and drills essential in the preparations for the containment and cleanup of oil spills. It is secondarily available for general base-mobile operations on a noninterference basis. Secondary users of this frequency are required to forego its use should oil spill containment and cleanup activities be present in their area of operation or upon notice by the Commission or a primary user that harmful interference is being caused to oil spill containment or cleanup activities in other areas.
- (9) Operation on this frequency is secondary to stations in the maritime mobile service operating in accordance with the International table of frequency allocations.
- (10) This frequency will be assigned only to stations used in itinerant operations, except within 56 km (35 miles) of Detroit, Mich., where it may be assigned for either itinerant or permanent area operations (i.e., general use).
- (11) Operation on this frequency is limited to a maximum output power of 2 watts; and each station authorized will be classified and licensed as a mobile station. Any units of such a station, however, may provide the operational functions of a base or fixed station on a secondary basis to mobile service operations, Provided, that the separation between the control point and the center of the radiating portion

of the antenna of any units so used does not exceed 8 m (25 ft.).

- (12) This frequency may not be used aboard aircraft in flight.
- (13) This frequency is shared with the Public Safety Pool.
- (14) Operation on this frequency is limited to a maximum output power of 1 watt and each station authorized will be classified and licensed as a mobile station. Any units of such a station, however, may provide the operational functions of a base or fixed station on a secondary basis to mobile service operations, provided that the separation between the control point and the center of the radiating portion of the antenna of any units so used does not exceed 8m (25 ft.).
- (15) This Government frequency is available for shared Government/non-Government use by stations engaged in oil spill containment and cleanup operations and for training and drills essential in the preparation for containment and cleanup of oil spills. Such use will be confined to inland and coastal waterways.
- (16) This frequency may be assigned only to stations operating in an interconnected or coordinated utility system in accordance with an operational communications plan which sets forth all points of communications. Authorizations at variance with an established operational communications plan will be made only on a secondary basis.
- (17) This frequency will be assigned only to stations used in itinerant operations.
- (18) This frequency is also used on a secondary basis for cordless telephones under part 15 of this chapter.
- (19) In addition to single frequency operation, this frequency is available to base and mobile stations for the paired frequency mode of operation. For two frequency systems, the separation between base and mobile transmit frequencies is 500 kHz with the base stations transmitting on the higher of the two frequencies.
- (20) In the State of Alaska only, the frequency 44.10 MHz is available for assignment on a primary basis to stations in the Common Carrier Rural Radio Service utilizing meteor burst communications. The frequency may

be used by private radio stations for meteor burst communications on a secondary, non-interference basis. Usage shall be in accordance with parts 22 and 90 of this chapter. Stations utilizing meteor burst communications shall not cause harmful interference to stations of other radio services operating in accordance with the allocation table.

- (21) In the State of Alaska only, the frequency 44.20 MHz is available for assignment on a primary basis to private land mobile radio stations utilizing meteor burst communications. The frequency may be used by common carrier stations for meteor burst communications on a secondary, non-interference basis. Usage shall be in accordance with parts 22 and 90 of this chapter. Stations utilizing meteor burst communications shall not cause harmful interference to stations of other radio services operating in accordance with the allocation table.
- (22) The frequencies available for use at operational fixed stations in the 72 - 76MHz are band listed $\S 90.257(a)(1)$. These frequencies are shared with other services and are available only in accordance with the provisions of §90.257. Seismic telemetry transmitters certificated with 1 watt or less power and a frequency tolerance not exceeding ±0.005% may be used as temporary operational fixed stations.
- (23) This frequency is shared with fixed stations in other services and is subject to no protection from interference.
- (24) All operations on this frequency are subject to the provisions of §90.257(b).
- (25) This frequency is shared with the Radio Control (R/C) Service, of the part 95 Personal Radio Services, where it is used solely for the radio control of models.
- (26) Pulsed modulations will not be authorized on this frequency.
- (27) Assignment of frequencies in this band are subject to the provisions of §90.173. In the 150–170 MHz band, licensees as of August 18, 1995 who operate systems that are 2.5 kHz removed from regularly assignable frequencies may continue to operate on a secondary, non-interference basis after August 1, 2003.

- (28) In Puerto Rico and the Virgin Islands this frequency is subject to the following:
- (i) This frequency is assigned only for one-way paging communications to mobile receivers. Only A1D, A2D, A3E, F1D, F2D, F3E, or G3E emissions may be authorized. Licensees may provide one-way paging communications on this frequency to individuals, persons eligible for licensing under subparts B or C of this part, to representatives of Federal Government agencies, and foreign governments and their representatives; and
- (ii) This frequency will not be assigned to stations for use at temporary locations.
- (29) This frequency will be authorized a channel bandwidth of 25 kHz. Except when limited elsewhere, one-way paging transmitters on this frequency may operate with an output power of 350 watts.
- (30) This frequency will be assigned with an authorized bandwidth not to exceed 11.25 kHz. In the 450-470 MHz band, secondary telemetry operations pursuant to \$90.238(e) will be authorized on this frequency.
- (31) Use of this frequency is limited to stations located in Puerto Rico and the Virgin Islands.
- (32) This frequency is not available to stations located in Puerto Rico and the Virgin Islands.
- (33) This frequency will be assigned with an authorized bandwidth not to exceed 6 kHz.
- (34) Operation on this frequency is limited to a maximum output power of 35 watts.
- (35) This frequency may be used for mobile operation for radio remote control and telemetering functions. A1D, A2D, F1D, or F2D emission may be authorized and mobile stations used to control remote objects or devices may be operated on the continuous carrier transmit mode.
- (36) This frequency is assigned only for one-way paging communications to mobile receivers. Only A1D, A2D, A3E, F1D, F2D, F3E, or G3E emissions may be authorized. Licensees may provide one-way paging communications on this frequency to individuals, persons eligible for licensing under subparts B or C of this part, to representatives of

Federal Government agencies, and foreign governments and their representatives.

- (37) This frequency is available on a secondary basis to one-way paging communications.
- (38) This frequency will not be assigned to stations for use at temporary locations.
- (39) For FM transmitters the sum of the highest modulating frequency and the amount of frequency deviation may not exceed 2.8 kHz and the maximum frequency deviation may not exceed 2.5 kHz. For AM transmitters the highest modulating frequency may not exceed 2.0 kHz. The carrier frequency must be maintained within 0.0005 percent, and the authorized bandwidth may not exceed 6 kHz.
- (40) This frequency is shared with the Public Safety Pool for remote control and telemetry operations.
- (41) Operational fixed stations must employ directional antennas having a front-to-back ratio of at least 20 dB. Omnidirectional antennas having unity gain may be employed for stations communicating with at least three receiving locations separated by 160 deg. of azimuth.
- (42) The maximum effective radiated power (ERP) may not exceed 20 watts for fixed stations and 2 watts for mobile stations. The height of the antenna system may not exceed 15.24 meters (50 ft.) above the ground. All such operation is on a secondary basis to adjacent channel land mobile operations.
- (43) This frequency is available for the following:
- (i) Assignment to multiple address stations employing directional antennas used for power utility peak load shaving and shedding and to mobile stations used for the remote control of objects and devices. The maximum power that may be authorized to fixed stations is 300 watts output, and the maximum power that may be authorized for mobile stations is 1 watt output. This frequency may also be assigned to operational fixed stations employing directional antenna systems (front-to-back ratio of 20 dB) when such stations are located at least 120 km. (75 mi.) from the boundaries of any urbanized area of 200,000 or more population. (U.S. Census of Population,

- 1960). The maximum power output of the transmitter for such fixed stations may not exceed 50 watts. A1A, A1D, A2B, A2D, F1B, F1D, F2B, F2D, G1B, G1D, G2B, or G2D emission may be authorized; or
- (ii) On a secondary basis for remote control and telemetry operations, subject to paragraphs (c)(41), (42), (43), (46), and (47) of this section.
- (44) The maximum output power of the transmitter may not exceed 50 watts for fixed stations and 1 watt for mobile stations. A1A, A1D, A2B, A2D, F1B, F1D, F2B, F2D, G1B, G1D, G2B, or G2D emission may be authorized, and mobile stations used to control remote objects and devices may be operated in the continuous transmit mode.
 - (45) [Reserved]
- (46) This frequency is limited to a maximum power of 20 watts.
- (47) This frequency may be used for mobile operation for remote control and telemetering functions. A1D, A2D, F1D, or F2D emission may be authorized. The use of the continuous carrier transmit mode for these purposes is permitted only for stations authorized and continuously licensed since before May 21, 1971.
- (48) Operation on this frequency is limited to a maximum output power of 20 watts.
- (49) Operation on this frequency is limited to a maximum output power of 75 watts.
- (50) This frequency may also be used for the transmission of tone or voice communications, including such communications when prerecorded, for purposes of automatically indicating abnormal conditions of trackage and railroad rolling stock when in motion, on a secondary basis to other stations on this frequency. All such operations shall be subject to the following:
- (i) The output power shall not exceed 30 watts;
- (ii) The bandwidth used shall not exceed that authorized to the licensee for voice transmissions on the frequency concerned:
- (iii) The station shall be so designed and installed that it can normally be activated only by its associated automatic control equipment and, in addition, it shall be equipped with a time delay or clock device which will deacti-

- vate the station within three (3) minutes following activation by the last car in the train; and
- (iv) Stations authorized pursuant to the provisions of this paragraph are exempt from the station identification requirements of §90.425.
- (51) In Puerto Rico and the Virgin Islands only, this frequency is available on a shared basis with remote pickup broadcast stations.
- (52) In Puerto Rico and the Virgin Islands only, this frequency is available to all stations operating in the Industrial/Business Pool and may be coordinated by any frequency coordinator certified in the Industrial/Business Pool.
- (53) Frequencies in this band will be assigned only for transmitting hydrological or meteorological data or for low power wireless microphones in accordance with the provisions of §90.265.
- (54) For FM transmitters the sum of the highest modulating frequency and the amount of frequency deviation may not exceed 1.7 kHz and the maximum deviation may not exceed 1.2 kHz. For AM transmitters the highest modulating frequency may not exceed 1.2 kHz. The carrier frequency must be maintained within 0.0005 percent and the authorized bandwidth may not exceed 3 kHz.
- (55) This band is available to stations operating in this service subject to the provisions of §90.259.
- (56) Subpart T of this part contains rules for assignment of frequencies in the 220-222 MHz band.
- (57) The requirements for secondary fixed use of frequencies in this band are set forth in §90.261.
- (58) Operational fixed assignments on this frequency will only be made to an itinerant fixed control or relay station on a secondary basis to land-mobile stations in the Industrial/Business Pool, provided that the fixed relay or control station is to be associated with base and mobile facilities authorized to use other frequencies available for itinerant operation in the Industrial/Business Pool. All such use of these frequencies for fixed systems is limited to locations 161 or more km. (100 mi.) from the center of any urbanized area of 200,000 or more population, except

that the distance may be 120 km. (75 mi.) if the output power does not exceed 20 watts. All such fixed systems are limited to a maximum of two frequencies and must employ directional antennas with a front-to-back ratio of at least 15 dB. The centers of urbanized areas of 200,000 or more population are determined from the appendix, page 226, of the U.S. Commerce publication, "Air Line Distance Between Cities in the United States." Urbanized areas of 200,000 or more population are defined in the U.S. Census of Population, 1960, volume 1, table 23, page 1–50.

(59) This frequency may be assigned primarily for stations used for the purpose of controlling slave locomotives that are placed within a train to assist the lead locomotive by providing, among other functions, auxiliary starting, pulling, and braking actions. Additionally, on a secondary basis this frequency may be assigned for remote control of all types of locomotives and, within a railroad yard or terminal area, for remote control of cab indicator devices placed with a locomotive to give visual signals to the operator of the locomotive. (A1, A2, F1 or F2 emissions may be authorized.)

(60)(i) This frequency is available for voice or non-voice communications concerned with cargo handling from a dock or cargo handling facility, a vessel alongside the dock, or cargo handling facility. The effective radiated power (ERP) shall not exceed 2 watts. Mobile relay stations may be temporarily installed on vessels located at or in the vicinity of a dock or cargo handling facility. The center of the radiating system of the mobile relay shall be located no more than 3 meters (10 feet) above the vessel's highest working dock.

(ii) This frequency is also available for low power non-cargo handling operations, both voice and non-voice, on a secondary basis to cargo handling communications. Such operations are not subject to the power limitations in paragraph (c)(60)(i) of this section on the following frequencies: 457.525 MHz, 457.550 MHz, 457.5625 MHz, 457.575 MHz, 457.5875 MHz, 457.600 MHz, and 457.6125 MHz. This frequency will not be assigned for non-cargo handling operations at temporary locations.

(iii) For mobile relay operations under paragraph (c)(60)(i) of this section, frequency pairing is as follows:

Mobile relay (MHz) ¹	Mobile (MHz)
457.525	467.750
457.53125	467.75625
457.5375	467.7625
457.54375	467.76875
457.550	467.775
457.55625	467.78125
457.5625	467.7875
457.56875	467.79375
457.575	467.800
457.58125	467.80625
457.5875	467.8125
457.59375	467.81875
457.600	467.825
457.60625	467.83125
457.6125	
457.61875	

¹The mobile relay frequencies may also be used for single frequency simplex.

(61) This frequency is available for assignment as follows:

(i) To persons furnishing commercial air transportation service or, pursuant to §90.179, to an entity furnishing radio communications service to persons so engaged, for stations located on or near the airports listed in paragraph (c)(61)(iv) of this section. Stations will be authorized on a primary basis and may be used only in connection with servicing and supplying of aircraft. Operation on this frequency is limited to a maximum effective radiated power (ERP) of 100 watts at locations within 16 km (10 miles) of the coordinates of the listed airports.

(ii) To stations in the Industrial/Business Pool for secondary use at locations 80 km (approximately 50 miles) or more from the coordinates of the listed airports. Operation will be limited to a maximum ERP of 300 watts.

(iii) To stations in the Industrial/Business Pool for secondary use at locations greater than 16 km (approximately 10 miles) but less than 80 km (approximately 50 miles) from the coordinates of the listed airports. Operation will be limited to a maximum ERP of 10 watts. Use of this frequency is restricted to the confines of an industrial complex or manufacturing yard area. Stations licensed prior to April 25, 2005, may continue to operate with facilities authorized as of that date.

(iv) The airports and their respective reference coordinates are (coordinates

are referenced to North American Datum 1983 (NAD83)):

City and airport	Reference	Reference coordinates	
ony and airport	N latitude	W longitude	
Aberdeen, SD: Aberdeen Regional (ABR)	45°26′56.6″	98°25′18.6″	
Aguana, GU: Guam International (GUM)		144°47′45.5″ E	
Akron, OH: Akron-Canton Regional (CAK)		81°26′32.9″	
Alamosa, CO: San Luis Valley Regional/Bergman Field (ALS)		105°51′59.6″	
Albany, NY: Albany Int'l (ALB)		73°48′10.7″	
Nbuquerque, NM: Albuquerque International Sunport (ABQ)		106°36′33.1″	
Illentown-Bethlehem, PA: Lehigh Valley Int'l (ABE)		75°26′25.5″	
marillo, TX: Amarillo International (AMA)		101°42′21.3″	
Anchorage, AK: Ted Stevens Anchorage International (ANC)		149°59′46.3″	
Appleton, WI: Appleton Int'l (ATW)		88°31′10.1″	
Aspen, CO: Aspen-Pitkin County/Sardy Field (ASE)	39°13′23.4″	106°52′07.9″	
Atlanta International (ATL)	33°38′25.6″	84°25′37.0″	
Dekalb-Peachtree (PDK)	33°52′32.2″	84°18′07.1″	
Dekalb-Peachtree (PDK)Fulton County/Brown Field (FTY)	33°46′44.9″	84°31′16.9″	
Austin, TX: Austin Bergstrom International (AUS)	30°11′40.3″	97°40′11.5″	
Bakersfield, CA: Meadows Field (BFL)		119°03′24.4″	
Baltimore, MD: Baltimore-Washington International Thurgood Marshall (BWI)		74°40′05.5″	
Baton Rouge, LA: Baton Rouge Metropolitan (BTR)		91°08′58.7″	
Billings, MT: Billings Logan International (BIL)		108°32′34.3″	
Birmings, WT. Billings Logari International (BIL) Birmingham, AL: Birmingham-Shuttlesworth Int'l (BHM)		86°45′12.8″	
Bismarck, ND: Bismarck Municipal (BIS)		100°44′44.7″	
Boise, ID: Boise Air Terminal/Gowen Field (BOI)	43°33′52.0″	116°13′22.0″	
Boston, MA: Logan International (BOS)	42°21′51.7″	17°00′18.7″	
Bozeman, MT: Bozeman Yellowstone Int'l (BZN)	45°46′36.8″	111°09′10.8″	
Bridgeport, CT: Sikorsky Memorial (BDR)	41°09′48.5″	73°07′34.2″	
Buffalo, NY: Buffalo Niagara Int'l (BUF)		78°43′55.8″	
Burlington, VT: Burlington Int'l (BTV)	44°28′18.7″	73°09′11.8″	
Cedar Rapids, IA: The Eastern Iowa (CID)	41°53′04.5″	91°42′39.1″	
Charleston, SC: Charleston AFB/International (CHS)	32°53′55.1″	80°02′25.8″	
Charlotte, NC: Charlotte-Douglas Int'l (CLT)	35°12′50.4″	80°56′35.3″	
Chattanooga, TN: Lovell (CHA)	35°02′06.9″	85°12′13.6″	
Chicago, IL-Northwest IN:			
Chicago Executive (PWK)	42°06′51.1″	87°54′05.3″	
South Bend Int'l (SBN)		86°19'06.5"	
Midway (MDW)		87°45′08.7″	
O'Hare International (ORD)		87°54′16.1″	
DuPage (DPA)		88°14′54.3″	
Cincinnati, OH: Cincinnati Municipal/Lunken Field (LUK)		84°25′07.0″	
Cleveland. OH:	39 00 12.0	04 23 07.0	
Burke Lakefront (BKL)	41°31′03.0″	81°41′00.0″	
Cuyahoga County (CGF)		81°29′10.9″	
Hopkins International (CLE)		81°50′57.8″	
Columbia CC: Columbia Metropolitan (CAE)	41 24 39.2 33°56′19.8″		
Columbia, SC: Columbia Metropolitan (CAE) Columbus, GA: Columbus (CSG)	33°56 19.8″ 32°30′58.8″	81°07′10.3″ 84°56′19.9″	
Columbus, GA: Columbus (CSG)	32 30 36.8	04 30 19.9	
John Glenn Columbus Int'l (CMH)	39°59′52.8″	82°53′30.8″	
Distantia Columbus IIII (CMII)	09-09 02.8		
Rickenbacker International (LCK)	39°48′49.5″	82°55′40.3″	
Corpus Christi, TX Corpus Christi International (CRP)	27°46′13.3″	97°30′04.4″	
Covington/Cincinnati, KY: Cincinnati/Northern Kentucky Int'l (CVG)		84°39′43.8″	
Crescent City, CA: JackMcNamara Field (CEC)	41°46′48.6″	124°14′11.5″	
Dallas, TX:			
Addison (ADS)		96°50′11.2″	
Dallas-Ft. Worth Int'l (DFW)	32°53′45.4″	97°02′13.9″	
Dallas-Love Field (DAL)	32°50′49.6″	96°51′06.4″	
Dallas Executive (RBD)	32°40′51.1″	96°52′05.5″	
Davenport, IA:			
Davenport Municipal (DVN)	41°36′37.0″	90°35′18.0″	
Quad City Int'l (MLI)		90°30′27.1″	
		84°13′09.8″	
Dayton, OH: James M. Cox Int'l (DAY)	55 5 . 55.5	35 00.0	
		104°50′57.5″	
Denver, CO:	30°3//12 5"		
Denver, CO: Centennial (APA)			
Denver, CO: Centennial (APA) Colorado Springs Municipal (COS)	38°48′20.9″	104°42′00.9″	
Denver, CO: Centennial (APA) Colorado Springs Municipal (COS) Rocky Mountain Metropolitan (BJC)	38°48′20.9″ 39°54′31.6″	104°42′00.9″ 105°07′01.9″	
Denver, CO: Centennial (APA) Colorado Springs Municipal (COS) Rocky Mountain Metropolitan (BJC) Denver International (DEN)	38°48′20.9″ 39°54′31.6″ 39°51′30.3″	104°42′00.9″ 105°07′01.9″ 104°40′01.2″	
Denver, CO: Centennial (APA) Colorado Springs Municipal (COS) Rocky Mountain Metropolitan (BJC) Denver International (DEN) Des Moines, IA: Des Moines Int'l (DSM)	38°48′20.9″ 39°54′31.6″ 39°51′30.3″	104°42′00.9″ 105°07′01.9″	
Denver, CO: Centennial (APA) Colorado Springs Municipal (COS) Rocky Mountain Metropolitan (BJC) Denver International (DEN) Des Moines, IA: Des Moines Int'l (DSM)	38°48′20.9″ 39°54′31.6″ 39°51′30.3″ 41°32′05.8″	104°42′00.9″ 105°07′01.9″ 104°40′01.2″ 93°39′38.5″	
Colorado Springs Municipal (COS)	38°48′20.9″ 39°54′31.6″ 39°51′30.3″ 41°32′05.8″ 42°24′33.1″	104°42′00.9″ 105°07′01.9″ 104°40′01.2″	

Olbo and the state of	Reference	Reference coordinates	
City and airport	N latitude	W longitude	
Oakland County Int'l (PTK)	42°39′54.7″	83°25′07.4″	
Willow Run (YIP)		83°31′49.5″	
Duluth, MN: Duluth International (DLH)	46°50′31.5″	92°11′37.1″	
Durango, CO: Durango-La Plata County (DRO)	37°09′05.5″	107°45′13.6″	
Eagle, CO: Eagle County Regional (EGE)	39°38′33.2″	106°55′03.7″	
El Paso, TX: El Paso International (ELP)	31°48′24.0″	106°22′40.1″	
Eugene, OR: Mahlon Sweet Field (EUG)	44°07′23.7″	123°13′07.3″	
Eureka, CA: Samoa Field (O33)	40°46′51.4″	124°12′44.2″	
Fargo, ND: Hector International (FAR)	46°55′09.7″	96°48′53.9″	
Flint, MI: Bishop Int'l (FNT)	42°57′55.8″	83°44′36.4″	
Ft. Lauderdale Executive (FXE)	26°11′50.2″	80°10′14.6″	
Ft. Lauderdale-Hollywood Int'l (FLL)	26°04′21.3″	80°09′09.9″	
Ft. Myers, FL: Page Field (FMY)	26°35′11.8″	81°51′47.7″	
Southwest Florida Int'l (RSW)	26°32′10.2″	81°45′18.6″	
Ft. Wayne, IN: Fort Wayne International (FWA)	40°58′42.5″	85°11′42.5″	
Ft. Worth, TX: Fort Worth Alliance (AFW)	32°59′12.5″	97°19′07.7″	
Meacham Int'l (FTW)	32°49′11.2″	97°21′44.8″	
Fresno, CA:			
Fresno Chandler Executive (FCH)	36°43′56.5″	119°49′11.6″	
Fresno Yosemite Int'l (FAT)	36°46′34.3″	119°43′05.3″	
Gainesville, FL: Gainesville Regional (GNV)	29°41′24.2″	82°16′18.4″	
Grand Forks, ND: Grand Forks International (GFK)	47°56′57.3″	97°10′34.0″	
Grand Rapids, MI: Gerald R. Ford Int'l (GRR)		85°31′22.1″	
Great Falls, MT: Great Falls International (GTF)		111°22′14.5″	
Green Bay, WI: Austin Straubel Int'l (GRB)	44°29′06.3″	88°07′46.5″	
Greensboro, NC: Piedmont Tirad International (GSO)	36°05′51.9″	79°56′14.3″	
Greer, SC: Greenville-Spartanburg Int'l (GSP)	34°53′44.4″	82°13′07.9″	
Gunnison, CO: Gunnison-Crested Butte Regional (GUC)	38°32′02.2″	106°55′58.9″	
Hana, HI: Hana (HNM)	20°47′44.3″	156°00′52.0″	
Harlingen, TX: Valley International (HRL)	26°13′42.6″	97°39′15.8″	
Capital City (CXY)	40°13′01.7″	76°51′05.3″	
Harrisburg Int'l (MDT)	40°11′36.6″	76°45′48.3″	
Hartford, CT (Windsor Locks):			
Bradley Int'l (BDL)	41°56′20.0″	72°40′59.6″	
Hartford-Brainard (HFD)	41°44′10.6″	72°39′00.8″	
Hayden, CO: Yampa Valley (HDN)	40°28′52.2″	107°13′03.6″	
Hilo, HI: Hilo Int'l (ITO)	19°43′12.9″	155°02′54.5″	
Honolulu, HI: Daniel K. Inouye Int'l (HNL)	21°19′07.3″	157°55′20.7″	
Houston, TX:			
W.P. Hobby (HOU)	29°38′43.5″	95°16′44.0″	
D.W. Hooks Memorial (DWH)		95°33′10.0″	
George Bush Intercontinental (IAH)	29°58′49.7″	95°20′23.0″	
Indianapolis, IN: Indianapolis Int'l (IND)	39°43′02.4″	86°17′39.8″	
Jackson Hole, WY: Jackson Hole (JAC)	43°36′26.4″	110°44′15.9″	
Jacksonville, FL:			
Jacksonville Executive at Craig (CRG)	30°20′10.8″	81°30′52.0″	
Jacksonville Int'l (JAX)		81°41′16.3″	
Kahului. HI: Kahului (OGG)	20°53′55.4″	156°25′48.9″	
Kailula-Kona, HI: Kona Int'l at Ke-Ahole (KOA)	19°44′19.7″	156°02′44.2″	
Kalamazoo, MI: Kalamazoo/Battle Creek International (AZO)	42°14′05.5″	85°33′07.4″	
Kalispell, MT: Glacier Park International (FCA)	48°18′41.1″	114°15′18.2″	
Kansas City, MO-K5: Kansas City Int'l (MCI)	39°17′51.4″	94°42′50.1″	
Charles B. Wheeler Downtown (MKC)	39°07′23.7″	94°35′33.9″	
Kauna Kakai, HI: Molokai (MKK)		157°05′46.5″	
Knoxville, TN: McGhee Tyson (TYS)	35°48′44.9″	83°59′34.3″	
LaCrosse, WI: LaCrosse Regional (LSE)	43°52′46.5″	91°15′24.6″	
Lansing, MI: Capital Region Int'l (LAN)		84°35′14.5″	
Las Vegas, NV: McCarran Int'l (LAS)		115°09′08.4″	
Lihue, HI: Lihue (LIH)	21°58′33.5″	159°20′20.3″	
Linde, HI: Linde (LIH)			
Little Rock, AR: Bill and Hillary Clinton National/Adams Field (LIT)	40°51′03.5″	96°45′33.3″ 92°13′27.3″	
Los Angeles, CA:	34°43′48.8″		
Bob Hope (BUR)	34°12′02.2″	118°21′30.6″	
Catalina (AVX)	33°24′17.8″	118°24′57.1″	
Long Beach-Daugherty Field (LGB)	33°49′03.8″	118°09′05.8″	
Long Beach-Daugherty Field (LGB)	33°56′33.1″	118°09'05.8" 118°24'29.1"	

City and airport	Reference coordinates	
Oity and airport	N latitude	W longitud
John Wayne-Orange County (SNA)	33°40′32.4″	117°52′05.6″
ouisville, KY: Louisville Int'l-Standiford Field (SDF)	38°10′27.8″	85°44′09.6″
ubbock, TX: Lubbock Preston Smith Int'l (LBB)	33°39′49.1″	101°49′22.0″
/nchburg, VA: Lynchburg Regional-Preston Glen Field (LYH)	37°19′36.1″	79°12′01.6″
adison, WI: Dane County Regional-Truax Field (MSN)	43°08′23.5″	89°20′15.1″
anchester, NH: Manchester (MHT)	42°56′04.3″	71°26′13.4″
emphis, TN: Memphis Int'l (MEM)	35°02′32.7″	89°58′36.0″
ami, FL:		69 36 30.0
Miami Int'l (MIA) Opa-Locka Executive (OPF)		80°17′26.0″
Miami Executive (TMB)	25°54′25.2″	80°16′42.2″
	25°38′52.4″	80°25′58.0″
Iwaukee, WI: General Mitchell Int'l (MKE)	42°56′50.0″	87°53′47.7″
nneapolis-St. Paul, MN: Minneapolis-St. Paul Int'l (MSP)	44°52′49.9″	93°13′00.9″
not, ND: Minot International (MOT)	48°15′33.8″	101°16′49.2″
ssoula, MT: Missoula International (MSO)		114°05′26.0″
obile, AL: Mobile Regional (MOB)	30°41′29.1″	88°14′34.2″
odesto, CA: Modesto City-County (MOD)	37°37′32.9″	120°57′15.9″
onterey, CA: Monterey Regional (MRY)	36°35′13.1″	121°50′34.6″
ontrose, CO: Montrose Regional (MTJ)	38°30′31.9″	107°53′37.8″
shville, TN: Nashville Int'l (BNA)	36°07′28.1″	86°40′41.5″
ew Haven, CT: Tweed-New Haven (HVN)		72°53′13.6″
ew Orleans, LA:		1 - 1 - 1 - 1 - 1 - 1
Lakefront (NEW)	30°02′32.7″	90°01′41.7″
Louis Armstrong New Orleans Int'l (MSY)	29°59′36.2″	90°15′28.9″
ewburgh, NY: Stewart International (SWF)	41°30′14.7″	74°06′17.4″
ewport News-Hampton,VA: Newport News/Williamsburg (PHF)	37°07′54.8″	76°29′34.8″
Republic (FRG)	40°43′43.6″	73°24′48.3″
JFK International (JFK)	40°38′23.1″	73°46′44.1″
LaGuardia (LGA)	40°46′38.1″	73°52′21.4″
Long Island-McArthur (ISP)	40°47′42.8″	73°06′00.8″
Morristown Municipal (NJ) (MMU)	40°47′57.7″	74°24′53.5″
Newark Int'l (EWR)		74°10′07.2″
Teterboro (NJ) (TEB)	40°51′00.4″	74°03′39.0″
orfolk, VA: Norfolk Int'l (ORF)dahoma City, OK:	36°53′40.6″	76°12′04.4″
Wiley Post (PWA)	35°32′04.4″	97°38′49.9″
Will Rogers World (OKC)	35°23′35.1″	97°36′02.6″
maha, NE: Eppley Airfield (OMA)		
rlando, FL:	41 10 09.1	95°53′39.0″
Orlando Executive (ORL)	28°32′43.7″	81°19′58.6″
Orlando Int'l (MCO)	28°25′44.0″	81°18′57.7″
alm Springs, CA: Palm Springs International (PSP)	33°49′46.8″	116°30′24.1″
eoria, IL: General Wayne A. Downing Peoria Int'l (PIA)	40°39′51.3″	89°41′35.9″
	40 39 31.3	09 41 33.9
hiladelphia, PA-NJ:	40004/55 0#	75:00/00 4//
Northeast Philadelphia (PNE)	40°04′55.0″	75°00′38.1″
Philadelphia Int'l (PHL)	39°52′19.0″	75°14′28.1″
hoenix, AZ:		
Phoenix-Sky Harbor Int'l (PHX)	33°26′03.0″	112°00′29.0″
Scottsdale (SDL)	33°37′22.3″	111°54′37.9″
ttsburgh, PA:		
Allegheny County (AGC)	40°21′15.9″	79°55′48.9″
Pittsburgh Int'l (PIT)	40°29′29.3″	80°13′58.3″
ortland, ME: Portland International Jetport (PWM)	43°38′46.2″	70°18′31.5″
ortland, OR:		
Portland-Hillsboro (HIO)	45°32′25.4″	122°56′59.4″
		122°35′51.0″
Portland International (PDX)		
	45°32′57.7″	122°24′04.5″
ovidence-Pawtucket, RI-MA:	44055/44 7"	74000'00 0"
North Central State (SFZ)	41°55′14.7″	71°29′29.0″
T.F. Green State (PVD)	41°43′26.4″	71°25′41.6″
leblo, CO: Pueblo Memorial (PUB)		104°29′47.7″
aleigh/Durham, NC: Raleigh-Durham International (RDU)	35°52′39.5″	78°47′14.9″
	44°02′43.2″	103°03′26.5″
apid City, SD: Rapid City Regional (RAP)	39°29′54.8″	119°46′05.0″
	37°30′18.6″	77°19′10.8″
eno, NV: Reno/Tahoe International (RNO)	0. 00 10.0	79°58′31.5″
ono, NV: Reno/Tahoe International (RNO)	37010/31 7"	1 / 3 30 31.3
eno, NV: Reno/Tahoe International (RNO)	37°19′31.7″	
eno, NV: Reno/Tahoe International (RNO) chmond, VA: Richmond International (RIC) anoke, VA: Roanoke-Blacksburg Regional/Woodrum Field (ROA) cohester, MN: Rochester International (RST)	43°54′26.0″	92°29′56.4″
eno, NV: Reno/Tahoe International (RNO) chmond, VA: Richmond International (RIC) canoke, VA: Roanoke-Blacksburg Regional/Woodrum Field (ROA) cohester, MN: Rochester International (RST) cohester, NY: Greater Rochester Int'l (ROC)		
apid City, SD: Rapid City Regional (RAP) eno, NV: Reno/Tahoe International (RNO) cichmond, VA: Richmond International (RIC) canoke, VA: Roanoke-Blacksburg Regional/Woodrum Field (ROA) cochester, MN: Rochester International (RST) cochester, NY: Greater Rochester Int'l (ROC) acramento, CA: Sacramento Executive (SAC)	43°54′26.0″	92°29′56.4″

City and airport	Reference coordinates	
City and airport	N latitude	W longitude
Saginaw, MI: MBS International (MBS)	43°31′58.5″	84°04′46.7″
Saipan Isl., CQ: Francisco C. Ada/Saipan Int'l (GSN)		145°43′45.7″ E
St. Louis, MO:	10 07 00.1	
Spirit of St. Louis (SUS)	38°39′42.7″	90°39′04.4″
Lambert-St. Louis Int'l (STL)		90°21′35.9″
St. Petersburg, FL:		
Albert Whitted Municipal (SPG)	27°45′54.4″	82°37′37.1″
St. Petersburg Clearwater Int'l (PIE)		82°41′14.9″
Salt Lake City, UT: Salt Lake City Int'l (SLC)		111°58′39.9″
San Antonio, TX: San Antonio Int'l (SAT)		29°32′01.3″
San Diego, CA: San Diego Int'l (SAN)		117°11′22.8″
San Francisco-Oakland, CA:		
Metropolitan Oakland Int'l (OAK)	37°43′16.7″	122°13′14.6″
San Francisco Int'l (SFO)		122°22′29.4″
an Jose, CA: Norman Y. Mineta San Jose Int'l (SJC)		121°55′44.4″
an Juan, PR: Luis Munoz (SJU)		66°00′06.6″
ianta Barbara, CA: Santa Barbara Municipal (SBA)		119°50′25.3″
Santa Fe, NM: Santa Fe Municipal (SAF)		106°05′17.3″
Sarasota, FL: Sarasota/Bradenton International (SRQ)		82°33′14.8″
Savanna, GA: Savanah/Hilton Head Int'l (SAV)		81°12′7.7″
Scranton, PA: Wilkes Barre/Scranton Int'l (AVP)		75°43′27.4″
Seattle, WA:	11 20 17.0	70 102711
Boeing/King County Int'l (BFI)	47°31′48.4″	122°18′07.4″
Seattle-Tacoma Int'l (SEA)		122°18′33.5″
Shreveport, LA:	20 00.0	122 10 00.0
Shreveport Downtown (DTN)	32°32′24.8″	93°44′42.1″
Shreveport Regional (SHV)		93°49′32.2″
Sioux City, IA: Sioux Gateway/Colonel Bud Day Field (SUX)		96°23′03.7″
Sioux Falls, SD: Joe Foss Field (FSD)		96°44′30.1″
South Bend, IN: South Bend Regional (SBN)		86°19′06.5″
Spokane, WA:		00 10 00.0
Grant County Int'l (MWH)	47°12′27.5″	119°19′12.7″
Spokane Int'l (GEG)		117°32′01.8″
Springfield, MA:		02 0 0
Westfield-Barnes Regional (BAF)	42°09′27.8″	72°42′56.2″
Westover ARB/Metropolitan (CEF)		72°32′03.3″
Springfield, MO: Springfield-Branson National (SGF)		93°23′12.7″
Syracuse, NY: Syracuse-Hancock Int'l (SYR)		76°06′22.7″
Facoma, WA: Tacoma Narrows (TIW)		122°34′41.2″
allahasee, FL: Tallahasee Int'l (TLH)		84°21′01.2″
Tampa, FL: Tampa Int'l (TPA)		82°31′59.7″
Felluride, CO: Telluride Regional (TEX)		107°54′30.5″
olidio, OH: Toledo Express (TOL)		83°48′28.2″
renton, NJ-PA: Trenton Mercer (TTN)		74°48′48.5″
Tucson, AZ: Tucson Int'l (TUS)		110°56′27.7″
ucson, Az. Tucson intr (103)	SE 00 37.3	110 30 27.7
R.L. Jones, Jr. (RVS)	36°02′22.7″	95°59′04.7″
Tulsa Int'l (TUL)		95°53′17.7″
Vashington, DC:	00 11 34.1	33 33 17.7
Dulles International (IAD)	38°56′40.3″	77°27′20.9″
Ronald Reagan National (DCA)		77°02′15.8″
Vaterloo, IA: Waterloo Regional (ALO)		92°24′01.2″
Vest Palm Beach, FL: Palm Beach International (PBI)		80°05′44.1″
White Plains, NY: Westchester County (HPN)		73°42′27.3″
Vichita, KS: Wichita Dwight D. Eisenhower National (ICT)	37°38′59.9″	97°25′58.9″
Vilmington, DE: New Castle (ILG)		75°36′23.5″
	1 03 40 40.4	10 00 20.0
Vorcester, MA: Worcester Regional (ORH)	42°16′02.4″	71°52′32.6″

Coordinates followed by an "E" are east longitude.

(62) This frequency may be assigned to fixed stations in the Industrial/Business Pool in accordance with the provisions of §90.261.

(63) Unless concurrence is obtained in accordance with §90.175(b) of this chapter from the Commission-certified fre-

quency coordinator for frequencies designated for central station alarm operations (central station alarm frequency coordinator), this frequency may be used within the boundaries of urbanized areas of 200,000 or more population, defined in the United States

Census of Population, 1960, vol. 1, table 23, page 1-50, only by persons rendering a central station commercial protection service within the service area of the radio station using the frequency and may be used only for communications pertaining to safety of life and property, and for maintenance or testing of the protection facilities. Central station commercial protection service is defined as an electrical protection and supervisory service rendered to the public from and by a central station accepted and certified by one or more of the recognized rating agencies, or the Underwriters Laboratories' (UL), or Factory Mutual System. Other stations in the Industrial/Business Pool may be licensed on this frequency without the central station alarm frequency coordinator's concurrence only when all base, mobile relay and control stations are located at least 120 km (75 miles) from the city center or centers of the specified urban areas of 200,000 or more population. With respect to combination urbanized areas containing more than one city, 120 km (75 mile) separation shall be maintained from each city center which is included in the urbanized area. The locations of centers of cities are determined from appendix, page 226, of the U.S. Commerce publication "Air Line Distance Between Cities in the United States.'

- (64) Persons who render a central station commercial protection service are authorized to operate fixed stations on this frequency for the transmission of tone or impulse signals on a co-primary basis to base/mobile operations. Fixed stations may be licensed as mobiles. Fixed stations used for central station alarm operations may use antennas mounted not more than 6.1 meters (20 feet) above a man-made supporting structure, including antenna structure.
- (i) The output power shall not exceed 30 watts (at the remote site).
- (ii) A1D, A2D, F1D, or F2D emission may be authorized.
- (iii) Operational fixed stations authorized under this paragraph are exempt from the requirements of §§ 90.137(b), 90.429(d), 90.425 and 90.433.
- (65) Licensees providing a central station commercial protection service may communicate with police or fire

stations, or vehicles, on this frequency, and may install licensed transmitting units which operate on this frequency at police or fire stations, or in police or fire vehicles, if the frequency's primary use is in a base/mobile system for a central station commercial protection service

- (66) Unless concurrence is obtained in accordance with section 90.175(b) of this chapter from the Commission-certified frequency coordinator for frequencies designated for central station alarm operations, this frequency may be assigned only to persons rendering a central station commercial protection service, which is defined in paragraph (c)(63) of this section, within the service area of the radio station using the frequency.
- (67) Medical telemetry operations are authorized on this frequency on a secondary basis. Medical telemetry operations are subject to the provisions of §90.267(h)(2).
- (68) Each station authorized on this frequency will be classified and licensed as a mobile station. Any units of such a station, however, may provide the operational functions of a base station on a secondary basis to mobile service operations provided that the vertical separation between control point or ground level and the center of the radiating portion of the antenna of any units so used does not exceed 8 meters (approximately 25 feet). This frequency is available for assignment as follows:
- (i) To persons furnishing commercial air transportation service or, pursuant to §90.179, to an entity furnishing radio communications service to persons so engaged, for stations located on or near the airports listed in paragraph (c)(61)(iv) of this section. Stations will be authorized on a primary basis and may be used only in connection with servicing and supplying of aircraft. Operation on this frequency is limited to a maximum effective radiated power (ERP) of 40 watts at locations within 16 km (approximately 10 miles) of the coordinates of the listed airports.
- (ii) To stations in the Industrial/Business Pool for secondary use at locations 80 km (approximately 50 miles) or more from the coordinates of the

listed airports. Operation will be limited to a maximum ERP of 120 watts. Wide area operation will not be permitted. The area of normal, day-to-day operations will be described in the application.

- (iii) To stations in the Industrial/Business Pool for secondary use at locations greater than 16 km (approximately 10 miles) but less than 80 km (approximately 50 miles) from the coordinates of the listed airports. Operation will be limited to a maximum ERP of 6 watts. Use of this frequency is restricted to the confines of an industrial complex or manufacturing yard area. Stations licensed prior to April 25, 2005, may continue to operate with facilities authorized as of that date.
- (69) This frequency may be used on a secondary, non-interference basis by a hospital or health care institution holding a license to operate a radio station under this part to operate a medical radio telemetry device with an output power not to exceed 20 milliwatts without specific authorization from the Commission.
- (70) Subpart L of this part contains rules for assignment of frequencies in the 470-512 MHz band.
- (71) Subpart S of this part contains rules for assignment of frequencies in the 806–824/851–869 MHz band and for narrowband operations in the 896–901/935–940 MHz band.
- (72) Assignment of frequencies above 928 MHz for operational-fixed stations is governed by part 101 of this chapter.
- (73) Frequencies in this band are available only for one-way paging operations in accordance with § 90.494.
- (74) Available only on a shared basis with stations in other services, and subject to no protection from interference due to the operation of industrial, scientific, or medical (ISM) devices. In the band 2483.5-2500 MHz, no applications for new stations or modification to existing stations to increase the number of transmitters will be accepted. Existing licensees as of July 25, 1985, and licensees whose initial applications were filed on or before July 25, 1985, are grandfathered and their operations are on a co-primary basis with the mobile-satellite and radiodetermination-satellite services, and in the segment 2495-2500 MHz, their operations

are also on a co-primary basis with part 27 fixed and mobile except aeronautical mobile service operations.

- (75) [Reserved]
- (76) The frequencies in the band 10.55–10.68 GHz are available for Digital Termination Systems and for associated intermodal links in the Point-to-Point Microwave Service. No new licenses will be issued under this subpart but current licenses will be renewed.
- (77) All communications on this frequency must be conducted within the boundaries or confines of the licensee's business premises.
- (78) Base and mobile stations authorized as of April 1, 1968, may continue to be authorized for such operation on a secondary basis to the Maritime Mobile Service. The licensees of such stations may renew, modify, reinstate, or assign their licenses in those cases where such assignment accompanies a change of ownership of the licensee's business to the assignee, and may expand existing systems when using that frequency; however, they will not be authorized to establish any new systems.
- (79) Frequencies may be assigned in pairs with the separation between base and mobile transmit frequencies being 5.26 MHz. A mobile station may be assigned the frequency which would normally be assigned to a base station for single frequency operation. However, this single-frequency operation may be subject to interference that would not occur to a two-frequency system. Base or mobile stations located 80.5 km (50 miles) or less from the center or any urbanized area of 600,000 or more population (U.S. Census of Population, 1970) must be operated in the half-duplex mode.
- (80) Concurrence from the Petroleum Coordinator is required only for applications for this frequency that request authorization for transmitters in Arkansas, Louisiana, Oklahoma, or Texas.
- (81) Concurrence from the Petroleum Coordinator is required only for applications for this frequency that request authorization for transmitters in Arkansas, Louisiana, Oklahoma, Oregon, Texas, or Washington.

- (82) After December 7, 2000 new stations will only be licensed with an authorized bandwidth not to exceed 11.25 kHz. Licensees authorized prior to December 7, 2000 may continue to use bandwidths wider than 11.25 kHz on a co-primary basis until January 1, 2005. After January 1, 2005, all stations operating with an authorized bandwidth greater than 11.25 kHz will be secondary to adjacent channel public safety interoperability operations. (See § 90.20(c)(3)).
- (83) Telemetry operations on this frequency will be authorized pursuant to §90.267.
- (84) Operation on this frequency is subject to the low power provisions of §90.267. This frequency is assigned to Group A in the low power pool.
- (85) Operation on this frequency is subject to the low power provisions of §90.267. This frequency is assigned to Group B in the low power pool.
- (86) Operation on this frequency is subject to the low power provisions of §90.267. This frequency is assigned to Group C in the low power pool.
- (87) Operation on this frequency is subject to the low power provisions of §90.267. This frequency is assigned to Group D in the low power pool.
- (88) Use of this frequency is on a secondary basis limited to 2 watts output power and subject to the provisions of $\S 90.267(h)(1)$, (h)(2), (h)(3) and (h)(4).
- (89) The frequency may be assigned only to entities meeting the definition of a forest product licensee (see §90.7). Operations are on a secondary basis to Federal Government operations including experimental stations, will not exceed 150 watts output power, and are limited to the states of Washington, Oregon, Maine, North Carolina, South Carolina, Tennessee, Georgia, Florida, Alabama, Mississippi, Louisiana, and Texas (eastern portion).
- (90) As of March 25, 2007, the FCC will cease to issue licenses for new stations in the fixed and mobile services in the following bands: 5900–5950 kHz, 7300–7350 kHz, 9400–9500 kHz, 11600–11650 kHz, 12050–12100 kHz, 13800–13870 kHz, and 15600–15800 kHz. As of March 29, 2009, the FCC will cease to issue licenses for new stations in the fixed and mobile services in the band 7350–7400 kHz and, in the U.S. Pacific insular areas in Re-

- gion 3, the band 7400–7450 kHz. Stations licensed as of March 25, 2007 in the bands 5900–5950 kHz, 7300–7350 kHz, 9400–9500 kHz, 11600–11650 kHz, 12050–12100 kHz, 13800–13870 kHz, and 15600–15800 kHz and as of March 29, 2009 for the band 7350–7400 kHz in Region 2 and the band 7350–7450 kHz in Region 3 shall:
- (1) Be limited to communications only within the United States and its insular areas;
- (2) Not cause harmful interference to the broadcasting service;
- (3) Be limited to the minimum power needed to achieve communications; and
- (4) Take account of the seasonal use of frequencies by the broadcasting service published in accordance with Article 12 of the ITU Radio Regulations.
- (91) Subpart M of this part contains rules for assignment of frequencies in the 5850-5925 MHz band.
- (92) This frequency is available on a shared basis both for remote control and telemetry operations and for mobile repeater operations. The authorized bandwidth may not exceed $11.25 \, \mathrm{kHz}$
- (93) This frequency is available on a shared basis with the Public Safety Pool for remote control and telemetry operations. In cases where §90.35(c)(95) applies to this frequency, licensees seeking primary status for the use of this frequency for mobile repeater stations and hand-carried transmitters that communicate directly with mobile repeater stations must describe the area of normal day-to-day operations either in terms of operation in a specific county or in the terms of maximum distance from a geographic center (latitude and longitude) and shall be subject to the frequency coordination requirements of §90.175.
- (94) Mobile repeaters operating on this frequency are subject to a channel loading requirement of 50 transmitter-receivers. Loading standards will be applied in terms of the number of units actually in use or to be placed in use within 8 months following authorization. A licensee will be required to show that an assigned frequency pair is at full capacity before it may be assigned a second or additional frequency. Channel capacity may be reached either by the requirements of a single licensee or by several users sharing a channel. Until a channel is loaded

to capacity it will be available for assignment to other users in the same area.

(95) The maximum effective radiated power (ERP) may not exceed 2 watts for mobile stations, and 5 watts for mobile repeater stations and hand-carried transmitters that communicate directly with mobile repeater stations.

(d) Additional frequencies available. In addition to the frequencies shown in the frequency table of this section, the following frequencies are available in this service. (See also §90.253.)

(1) Frequencies may be substituted for those available below 25 MHz in accordance with the provisions of §90.263.

(2) Frequencies in the band 73.0–74.6 MHz may be assigned to stations authorized on or before December 1, 1961, but no new stations will be authorized in this band, nor will expansion of existing systems be permitted. (See also § 90.257).

(3) Frequencies in the 421–430 MHz band are available in the Detroit, Cleveland, and Buffalo areas in accordance with the rules in §§ 90.273 through 90.281.

(4) The following frequencies are available only in Puerto Rico and the Virgin Islands. These "Base and Mobile" and "Mobile only" frequencies are available on a shared basis with the Public Safety Pool. These "Mobile only" frequencies may be assigned to a control station associated with a mobile relay system if it is also assigned to the associated mobile station.

Base and mobile	Mobile only
159.240	160.410
159.2475	160.4175
159.255	160.425
159.2625	160.4325
159.270	160.440
159.2775	160.4475
159.285	160.455
159.2925	160.4625
159.300	160.470
159.3075	160.4775
159.315	160.485
159.3225	160.4925
159.330	160.500
159.3375	160.5075
159.345	160.515
159.3525	160.5225
159.360	160.530
159.3675	160.5375
159.375	160.545
159.3825	160.5525
159.390	160.560
159.3975	160.5675

Base and mobile	Mobile only
159.405	160.575
159.4125	160.5825
159.420	160.590
159.4275	160.5975
159.435	160.605
159.4425	160.6125

(5) Low power mobile stations of 100 mw or less output power used for one-way, non-voice medical telemetry operations in hospitals or in medical convalescent centers are subject to the provisions of §90.238.

(6) [Reserved]

(7) A railroad licensee, i.e., a licensee eligible for frequencies listed in §90.35(b)(3) of this section that are coordinated by the railroad coordinator (LR), may operate radio units at fixed locations and in moving railroad locomotives/cars that transmit on the frequency 24.10 GHz, both unmodulated continuous wave radio signals and modulated FM digital signals for the purpose of alerting motorists to the presence of an approaching train. Unattended and continuous operation of such transmitters will be permitted without additional authorization from the Commission, provided type accepted equipment or equipment authorized pursuant to §§ 90.203(b)(4) and (b)(5) of this part is used, and all other rule provisions are satisfied.

(e) Limitation on number of frequencies assignable. Normally only one frequency, or pair of frequencies in the paired frequency mode of operation, will be assigned for mobile service operations by a single applicant in a given area. The assignment of an additional frequency or pair of frequencies will be made only upon a satisfactory showing of need, except that:

(1) Additional frequencies above 25 MHz may be assigned in connection with operation of mobile repeaters in accordance with §90.247 notwithstanding this limitation.

(2) [Reserved]

(3) Frequencies in the 25–50 MHz, 150–170 MHz, 450–512 MHz and 902–928 MHz bands may be assigned for the operation of Location and Monitoring Service (LMS) systems in accordance with the provisions of subpart M of this part, notwithstanding this limitation.

- (4) Authorizations for multiple frequencies for geophysical operations will be granted on the frequencies governed by the limitations in paragraphs (c)(3) and (c)(4) of this section. However, each geophysical exploration party may use a maximum of four frequencies at any one time.
- (5) Authorization for more than one mobile frequency in the band 72–76 MHz will be issued notwithstanding this limitation.
- (6) This limitation shall not apply to paragraph (c)(1) of this section.
- (7) Frequencies in the 457 and 467 MHz bands may be assigned collectively as provided by paragraph (c)(60) of this section notwithstanding this limitation.
- (f) Limitation on itinerant operation. Base or mobile stations being utilized in itinerant operation will be authorized only on base or mobile frequencies designated for itinerant operation under paragraphs (c)(10) or (c)(17) of this section, or on other frequencies not designated for permanent use.
- (g) The frequencies 9-490 kHz are used to operate electric utility Power Line Carrier (PLC) systems on power transmission lines for communications essential to the reliability and security of electric service to the public, in accordance with part 15 of this chapter. Any electric utility that generates, transmits, or distributes electrical energy for use by the general public or by the members of a cooperative organization may operate PLC systems and shall supply to a Federal Communica-Commission/National communications and Information Administration recognized industry-operated entity, information on all existing, changes to existing, and proposed systems for inclusion in a data base. Such information shall include the frequency, power, location of transmitter(s), location of receivers and other technical and operational parameters, which would characterize the system's potential both to interfere with authorized radio users, and to receive harmful interference from these users. In an agreed upon format, the industry-operated entity shall inform the FCC and the NTIA of these system characteristics prior to implementation of any proposed PLC system and

shall provide monthly or periodic lists with supplements of PLC systems. The FCC and NTIA will supply appropriate application and licensing information to the notification activity regarding authorized radio stations operating in the band. PLC systems in this band operate on a non-interference basis to radio systems assigned frequencies by the NTIA or licensed by the FCC and are not protected from interference due to these radio operations.

[62 FR 18874, Apr. 17, 1997]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting \$90.35, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and at www.govinfo.gov.

EFFECTIVE DATE NOTE: At 64 FR 36262, July 6, 1999, $\S90.35$ was amended by revising entries in the table in paragraph (b)(3) and by adding paragraphs (c)(80) and (c)(81), effective Aug. 5, 1999. At 64 FR 50467, Sept. 17, 1999, paragraphs (c)(80), (c)(81), and the following entries in the table in paragraph (b)(3) were stayed:

153.035 MHz through 153.4025 MHz, 153.4025 MHz through 153.4625 MHz, 153.485 MHz through 153.5225 MHz, 153.545 MHz through 153.5825 MHz, 153.605 MHz through 153.6425 MHz, 153.665 MHz through 153.6675 MHz, 158.145 MHz through 158.1825 MHz, 158.205 MHz through 158.2425 MHz, 158.265 MHz through 158.3325 MHz, 158.355 MHz through 158.3775 MHz, 158.415 MHz through 158.4375 MHz, 173.250 MHz, 173.300 MHz, 173.350 MHz, 451.175 MHz, 451.225 MHz, 451.275 MHz, 451.375 MHz, 451.425 MHz, 451.475 MHz, 451.525 MHz, 451.550 MHz, 451.575 MHz, 451.600 MHz, 451.625 MHz, 451.650 MHz, 451.675 MHz, 451.700 MHz, 451.750 MHz, 452.325 MHz, 452.375 MHz, 452.425 MHz, 452.475 MHz, 452.775 MHz, 452.825 MHz, 452.875 MHz, 456.175 MHz, 456.225 MHz, 456.275 MHz, 456.375 MHz, 456.425 MHz, 456.475 MHz, 456.525 MHz, 456.550 MHz, 456.575 MHz, 456.600 MHz, 456.625 MHz, 456.650 MHz, 456.675 MHz, 456.700 MHz, 456.750 MHz, 457.325 MHz, 457.375 MHz, 457.425 MHz, 457.475 MHz, 457.775 MHz, 457.825 MHz, 457.875 MHz, 462.475 MHz, 462.525 MHz, 467.475 MHz, and 467.525 MHz

Subparts D-E [Reserved]

Subpart F—Radiolocation Service

§ 90.101 Scope.

The Radiolocation Service accommodates the use of radio methods for determination of direction, distance, speed, or position for purposes other than navigation. Rules as to eligibility