

## Environmental Protection Agency

## § 262.14

(2) Hazardous waste generated by on-site treatment (including reclamation) of the generator's hazardous waste, so long as the hazardous waste that is treated was previously counted once; and

(3) Hazardous waste spent materials that are generated, reclaimed, and subsequently reused on site, so long as such spent materials have been previously counted once.

(e) Based on the generator category as determined under this section, the generator must meet the applicable independent requirements listed in § 262.10. A generator's category also determines which of the provisions of §§ 262.14, 262.15, 262.16 or 262.17 must be met to obtain an exemption from the storage facility permit, interim status, and operating requirements when accumulating hazardous waste.

(f) *Mixing hazardous wastes with solid wastes*—(1) *Very small quantity generator wastes*. (i) Hazardous wastes generated by a very small quantity generator may be mixed with solid wastes. Very small quantity generators may mix a portion or all of its hazardous waste with solid waste and remain subject to § 262.14 even though the resultant mixture exceeds the quantity limits identified in the definition of very small quantity generator at § 260.10 of this chapter, unless the mixture exhibits one or more of the characteristics of hazardous waste identified in part 261 subpart C of this chapter.

(ii) If the resulting mixture exhibits a characteristic of hazardous waste, this resultant mixture is a newly-generated hazardous waste. The very small quantity generator must count both the resultant mixture amount plus the other hazardous waste generated in the calendar month to determine whether the total quantity exceeds the very small quantity generator calendar month quantity limits identified in the definition of generator categories found in § 260.10 of this chapter. If so, to remain exempt from the permitting, interim status, and operating standards, the very small quantity generator must meet the conditions for exemption applicable to either a small quantity generator or a large quantity generator. The very small quantity generator must also comply with the appli-

cable independent requirements for either a small quantity generator or a large quantity generator.

(iii) If a very small quantity generator's wastes are mixed with used oil, the mixture is subject to 40 CFR part 279. Any material produced from such a mixture by processing, blending, or other treatment is also regulated under 40 CFR part 279.

(2) *Small quantity generator and large quantity generator wastes*. (i) Hazardous wastes generated by a small quantity generator or large quantity generator may be mixed with solid waste. These mixtures are subject to the following: the mixture rule in §§ 261.3(a)(2)(iv), (b)(2) and (3), and (g)(2)(i); the prohibition of dilution rule at § 268.3(a); the land disposal restriction requirements of § 268.40 if a characteristic hazardous waste is mixed with a solid waste so that it no longer exhibits the hazardous characteristic; and the hazardous waste determination requirement at § 262.11.

(ii) If the resulting mixture is found to be a hazardous waste, this resultant mixture is a newly-generated hazardous waste. A small quantity generator must count both the resultant mixture amount plus the other hazardous waste generated in the calendar month to determine whether the total quantity exceeds the small quantity generator calendar monthly quantity limits identified in the definition of generator categories found in § 260.10 of this chapter. If so, to remain exempt from the permitting, interim status, and operating standards, the small quantity generator must meet the conditions for exemption applicable to a large quantity generator. The small quantity generator must also comply with the applicable independent requirements for a large quantity generator.

[81 FR 85808, Nov. 28, 2016, as amended at 84 FR 5939, Feb. 22, 2019]

### **§ 262.14 Conditions for exemption for a very small quantity generator.**

(a) Provided that the very small quantity generator meets all the conditions for exemption listed in this section, hazardous waste generated by the very small quantity generator is not subject to the requirements of parts

**§262.14**

**40 CFR Ch. I (7-1-21 Edition)**

124, 262 (except §§262.10 through 262.14) through 268, and 270 of this chapter, and the notification requirements of section 3010 of RCRA and the very small quantity generator may accumulate hazardous waste on site without complying with such requirements. The conditions for exemption are as follows:

(1) In a calendar month the very small quantity generator generates less than or equal to the amounts specified in the definition of “very small quantity generator” in §260.10 of this chapter;

(2) The very small quantity generator complies with §262.11(a) through (d);

(3) If the very small quantity generator accumulates at any time greater than 1 kilogram (2.2 lbs) of acute hazardous waste or 100 kilograms (220 lbs) of any residue or contaminated soil, water, or other debris resulting from the cleanup of a spill, into or on any land or water, of any acute hazardous waste listed in §§261.31 or 261.33(e) of this chapter, all quantities of that acute hazardous waste are subject to the following additional conditions for exemption:

(i) Such waste is held on site for no more than 90 days beginning on the date when the accumulated wastes exceed the amounts provided above; and

(ii) The conditions for exemption in §262.17(a) through (g).

(4) If the very small quantity generator accumulates at any time 1,000 kilograms (2,200 lbs) or greater of non-acute hazardous waste, all quantities of that hazardous waste are subject to the following additional conditions for exemption:

(i) Such waste is held on site for no more than 180 days, or 270 days, if applicable, beginning on the date when the accumulated waste exceed the amounts provided above;

(ii) The quantity of waste accumulated on site never exceeds 6,000 kilograms (13,200 lbs); and

(iii) The conditions for exemption in §262.16(b)(2) through (f).

(5) A very small quantity generator that accumulates hazardous waste in amounts less than or equal to the limits in paragraphs (a)(3) and (4) of this section must either treat or dispose of its hazardous waste in an on-site facil-

ity or ensure delivery to an off-site treatment, storage, or disposal facility, either of which, if located in the U.S., is:

(i) Permitted under part 270 of this chapter;

(ii) In interim status under parts 265 and 270 of this chapter;

(iii) Authorized to manage hazardous waste by a state with a hazardous waste management program approved under part 271 of this chapter;

(iv) Permitted, licensed, or registered by a state to manage municipal solid waste and, if managed in a municipal solid waste landfill is subject to part 258 of this chapter;

(v) Permitted, licensed, or registered by a state to manage non-municipal non-hazardous waste and, if managed in a non-municipal non-hazardous waste disposal unit, is subject to the requirements in §§257.5 through 257.30 of this chapter;

(vi) A facility which:

(A) Beneficially uses or reuses, or legitimately recycles or reclaims its waste; or

(B) Treats its waste prior to beneficial use or reuse, or legitimate recycling or reclamation;

(vii) For universal waste managed under part 273 of this chapter, a universal waste handler or destination facility subject to the requirements of part 273 of this chapter;

(viii) A large quantity generator under the control of the same person as the very small quantity generator, provided the following conditions are met:

(A) The very small quantity generator and the large quantity generator are under the control of the same person as defined in §260.10 of this chapter. “Control,” for the purposes of this section, means the power to direct the policies of the generator, whether by the ownership of stock, voting rights, or otherwise, except that contractors who operate generator facilities on behalf of a different person as defined in §260.10 of this chapter shall not be deemed to “control” such generators.

(B) The very small quantity generator marks its container(s) of hazardous waste with:

(1) The words “Hazardous Waste”; and

(2) An indication of the hazards of the contents (examples include, but are not limited to, the applicable hazardous waste characteristic(s) (*i.e.*, ignitable, corrosive, reactive, toxic); hazard communication consistent with the Department of Transportation requirements at 49 CFR part 172 subpart E (labeling) or subpart F (placarding); a hazard statement or pictogram consistent with the Occupational Safety and Health Administration Hazard Communication Standard at 29 CFR 1910.1200; or a chemical hazard label consistent with the National Fire Protection Association code 704);

(ix) A reverse distributor (as defined in §266.500), if the hazardous waste pharmaceutical is a potentially creditable hazardous waste pharmaceutical generated by a healthcare facility (as defined in §266.500).

(x) A healthcare facility (as defined in §266.500) that meets the conditions in §§266.502(1) and 266.503(b), as applicable, to accept non-creditable hazardous waste pharmaceuticals and potentially creditable hazardous waste pharmaceuticals from an off-site healthcare facility that is a very small quantity generator.

(xi) For airbag waste, an airbag waste collection facility or a designated facility subject to the requirements of §261.4(j) of this chapter.

(b) The placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited.

(c) A very small quantity generator experiencing an episodic event may generate and accumulate hazardous waste in accordance with subpart L of this part in lieu of §§262.15, 262.16, and 262.17.

[81 FR 85808, Nov. 28, 2016, as amended at 83 FR 61563, Nov. 30, 2018; 84 FR 5940, Feb. 22, 2019]

**§262.15 Satellite accumulation area regulations for small and large quantity generators.**

(a) A generator may accumulate as much as 55 gallons of non-acute hazardous waste and/or either one quart of liquid acute hazardous waste listed in §261.31 or §261.33(e) of this chapter or 1 kg (2.2 lbs) of solid acute hazardous

waste listed in §261.31 or §261.33(e) of this chapter in containers at or near any point of generation where wastes initially accumulate which is under the control of the operator of the process generating the waste, without a permit or interim status and without complying with the requirements of parts 124, 264 through 267, and 270 of this chapter, provided that all of the conditions for exemption in this section are met. A generator may comply with the conditions for exemption in this section instead of complying with the conditions for exemption in §262.16(b) or §262.17(a), except as required in §262.15(a)(7) and (8). The conditions for exemption for satellite accumulation are:

(1) If a container holding hazardous waste is not in good condition, or if it begins to leak, the generator must immediately transfer the hazardous waste from this container to a container that is in good condition and does not leak, or immediately transfer and manage the waste in a central accumulation area operated in compliance with §262.16(b) or §262.17(a).

(2) The generator must use a container made of or lined with materials that will not react with, and are otherwise compatible with, the hazardous waste to be accumulated, so that the ability of the container to contain the waste is not impaired.

(3) Special standards for incompatible wastes.

(i) Incompatible wastes, or incompatible wastes and materials, (see appendix V of part 265 for examples) must not be placed in the same container, unless §265.17(b) of this chapter is complied with.

(ii) Hazardous waste must not be placed in an unwashed container that previously held an incompatible waste or material (see appendix V of part 265 for examples), unless §265.17(b) of this chapter is complied with.

(iii) A container holding a hazardous waste that is incompatible with any waste or other materials accumulated nearby in other containers must be separated from the other materials or protected from them by any practical means.